

Panel PC 900

User's Manual

Version: **1.00 (December 2013)**
Model no.: **MAPPC900-ENG**

All information contained in this manual is current as of its creation/publication. B&R reserves the right to change the contents of this manual without notice. The information contained herein is believed to be accurate as of the date of publication; however, Bernecker + Rainer Industrie-Elektronik Ges.m.b.H. makes no warranty, expressed or implied, with regard to the products or documentation contained within this manual. In addition, Bernecker + Rainer Industrie-Elektronik Ges.m.b.H. shall not be liable for any incidental or consequential damages in connection with or arising from the furnishing, performance or use of the product(s) in this documentation. Software names, hardware names and trademarks are registered by their respective companies.

Chapter 1: General information

Chapter 2: Technical data

Chapter 3: Installation

Chapter 4: Software

Chapter 5: Standards and certifications

Chapter 6: Accessories

Chapter 7: Maintenance and service

Appendix A

Chapter 1 General information.....	9
1 Manual history.....	9
2 Safety guidelines.....	10
2.1 Intended use.....	10
2.2 Protection against electrostatic discharge.....	10
2.2.1 Packaging.....	10
2.2.2 Guidelines for proper ESD handling.....	10
2.3 Policies and procedures.....	10
2.4 Transport and storage.....	11
2.5 Installation.....	11
2.6 Operation.....	11
2.6.1 Protection against touching electrical parts.....	11
2.6.2 Environmental conditions - Dust, humidity, aggressive gases.....	11
2.6.3 Viruses and dangerous programs.....	11
2.7 Environmentally friendly disposal.....	12
2.7.1 Separation of materials.....	12
3 Organization of safety notices.....	13
4 Guidelines.....	13
5 Overview.....	14

Chapter 2 Technical data..... 16

1 Introduction.....	16
1.1 About this user's manual.....	16
1.2 Description of individual modules.....	16
1.2.1 Display units.....	16
1.2.2 CPU board and system unit.....	17
1.3 Structure/Configuration.....	18
1.3.1 Configuration.....	18
2 Complete system.....	21
2.1 Mechanical characteristics.....	21
2.1.1 Dimensions.....	21
2.1.2 Installation diagrams.....	22
2.1.3 Spacing for air circulation.....	23
2.1.4 Mounting orientations.....	24
2.1.5 Weight specifications.....	25
2.2 Environmental characteristics.....	26
2.2.1 Temperature specifications.....	26
2.2.2 Humidity.....	31
2.2.3 Vibration.....	32
2.2.4 Shock.....	32
2.2.5 Protection.....	32
2.3 Electrical characteristics.....	33
2.3.1 +24 VDC power supply.....	33
2.3.2 Optional Supply voltage VAC.....	33
2.3.3 Power calculation.....	34
2.3.4 Block diagram.....	36
2.4 Device interfaces and slots.....	37
2.4.1 Overview of device interfaces.....	37
2.4.2 Supply voltage.....	39
2.4.3 COM1 serial interface.....	41
2.4.4 COM2 serial interface.....	41
2.4.5 Monitor/Panel interface.....	42
2.4.6 Ethernet 1 (ETH1).....	44
2.4.7 Ethernet 2 (ETH2).....	44
2.4.8 USB interfaces.....	45
2.4.9 CFast slot.....	46
2.4.10 Audio.....	46

Table of contents

2.4.11 Status LEDs.....	47
2.4.12 Power button.....	48
2.4.13 Reset button.....	48
2.4.14 Battery.....	49
2.4.15 Slide-in compact slot.....	50
2.4.16 Slide-in slot.....	50
2.4.17 Main memory.....	51
2.4.18 IF option 1 slot.....	52
2.4.19 IF option 2 slot.....	52
2.4.20 Card slot (PCI / PCIe).....	53
3 Individual components.....	54
3.1 Display units.....	54
3.1.1 5AP923.1215-00.....	54
3.1.2 5AP923.1505-00.....	56
3.1.3 5AP923.1906-00.....	58
3.1.4 5AP933.156B-00.....	60
3.1.5 5AP933.185B-00.....	62
3.1.6 5AP933.215C-00.....	64
3.1.7 5AP933.240C-00.....	66
3.2 QM77 CPU boards.....	68
3.2.1 5PC901.TS77-0x.....	68
3.3 HM76 CPU boards.....	71
3.3.1 5PC901.TS77-0x.....	71
3.4 System units.....	74
3.4.1 5PC911.SX00-00.....	74
3.4.2 5PC911.SX00-01.....	75
3.5 Main memory.....	76
3.5.1 5MMDDR.xxxx-03.....	76
3.6 Bus units.....	77
3.6.1 5AC902.BX0x-xx.....	77
3.7 Fan kit.....	79
3.7.1 5AC902.FA00-00.....	79
3.7.2 5AC902.FA0X-00.....	80
3.8 Drives.....	81
3.8.1 5AC901.CHDD-01.....	81
3.8.2 5AC901.CSSD-03.....	83
3.8.3 5AC901.CSSD-04.....	85
3.8.4 5AC901.CSSD-05.....	88
3.8.5 5MMSSD.0060-01.....	90
3.8.6 5MMSSD.0128-01.....	92
3.8.7 5MMSSD.0256-00.....	95
3.8.8 5AC901.CCFA-00.....	97
3.8.9 5AC901.SDVW-00.....	98
3.8.10 5AC901.SSCA-00.....	100
3.9 Interface options.....	101
3.9.1 5AC901.I485-00.....	101
3.9.2 5AC901.ICAN-00.....	105
3.9.3 5AC901.ISRM-00.....	107
3.9.4 5AC901.IHDA-00.....	109
3.10 Uninterruptible power supply (UPS).....	111
3.10.1 Requirements.....	111
3.10.2 5AC901.IUPS-00.....	112
3.10.3 5AC901.IUPS-01.....	114
3.10.4 5AC901.BUPS-00.....	116
3.10.5 5AC901.BUPS-01.....	119
3.10.6 5CAUPS.xxxx-01.....	122
3.11 Power supply.....	124

3.11.1 5AC902.PS00-00.....	124
Chapter 3 Installation.....	125
1 Installation.....	125
1.1 Installation Panel PC 900.....	125
1.2 Replacing the CPU board and system unit.....	128
1.3 Installing or replacing the AC power supply.....	130
1.4 Replacing the main memory modules.....	132
1.5 Installing the interface option.....	134
1.6 Installing and replacing the slide-in compact drive.....	137
1.7 Replacing the fan kit.....	139
1.8 Replacing the fan filter.....	140
1.9 Installing the bus unit.....	141
1.10 Installing PCI / PCIe cards.....	143
1.11 Installing a slide-in drive.....	145
1.12 Installing and connecting the UPS battery unit.....	147
2 Connecting to the power mains.....	148
2.1 Installing the DC mains cable.....	148
2.1.1 Wiring.....	148
2.2 Installing the AC mains cable.....	149
2.2.1 Wiring.....	149
2.3 Connecting the power supply to a B&R device.....	150
2.4 Grounding concept functional ground.....	151
3 Cable connections.....	152
4 Switching on for the first time.....	153
4.1 General information before switching on.....	153
4.2 Switching on the Panel PC.....	153
5 Touch screen calibration.....	154
5.1 Single-touch (analog resistive).....	154
5.1.1 Windows 7 Professional / Ultimate.....	154
5.1.2 Windows Embedded Standard 7 Embedded / Premium.....	154
5.1.3 Windows XP Professional.....	154
5.1.4 Windows Embedded Standard 2009.....	154
5.2 Multi-touch (PCT - Projected capacitive).....	154
5.2.1 Windows 7 Professional / Ultimate.....	154
5.2.2 Windows Embedded Standard 7 Premium.....	154
6 Adjusting the display brightness.....	155
7 Configuring a SATA RAID set using the internal RAID controller.....	156
7.1 Create RAID volume.....	157
7.2 Delete RAID volume.....	158
7.3 Reset disks to non-RAID.....	159
7.4 Recovery volume options.....	160
Chapter 4 Software.....	161
1 BIOS options.....	161
1.1 General information.....	161
1.2 BIOS Setup and boot procedure.....	161
1.2.1 BIOS Setup keys.....	162
1.3 Main.....	163
1.3.1 Platform information.....	164
1.4 Advanced.....	165
1.4.1 Graphics configuration.....	166
1.4.2 OEM features.....	168
1.4.3 PCI configuration.....	187
1.4.4 PCI Express configuration.....	189
1.4.5 ACPI settings.....	195
1.4.6 RTC wake settings.....	196

Table of contents

1.4.7 CPU configuration.....	197
1.4.8 Chipset configuration.....	200
1.4.9 SATA configuration.....	201
1.4.10 Memory configuration.....	204
1.4.11 USB configuration.....	207
1.4.12 Serial port console redirection.....	211
1.5 Boot.....	213
1.5.1 Boot device priority.....	213
1.5.2 Boot configuration.....	214
1.6 Security.....	215
1.6.1 HDD user password.....	216
1.7 Save & Exit.....	216
1.8 BIOS default settings.....	218
1.8.1 Advanced.....	218
1.8.2 Boot.....	222
1.9 Allocation of resources.....	224
1.9.1 RAM address assignment.....	224
1.9.2 I/O address assignment.....	224
1.9.3 Interrupt assignments in PIC mode.....	224
1.9.4 Interrupt assignments in APIC mode.....	225
2 Upgrade information.....	227
2.1 BIOS upgrade.....	227
2.1.1 Important information.....	227
2.1.2 Procedure with MS-DOS.....	228
2.2 Firmware upgrade.....	229
2.2.1 Procedure.....	229
2.3 Creating an MS-DOS boot diskette in Windows XP.....	230
2.4 Creating a bootable USB flash drive for B&R upgrade files.....	232
2.4.1 Requirements.....	232
2.4.2 Procedure.....	232
2.4.3 How to access MS-DOS.....	232
2.5 Creating a bootable mass storage device for B&R upgrade files.....	233
2.5.1 Requirements.....	233
2.5.2 Procedure.....	233
2.5.3 How to access MS-DOS.....	233
3 Windows 7.....	234
3.1 General information.....	234
3.2 Order data.....	234
3.3 Overview.....	234
3.4 Installation.....	235
3.5 Drivers.....	235
3.6 Special considerations, limitations.....	235
4 Windows Embedded Standard 7.....	236
4.1 General information.....	236
4.2 Order data.....	236
4.3 Overview.....	236
4.4 Features with WES7 (Windows Embedded Standard 7).....	236
4.5 Installation.....	237
4.6 Drivers.....	237
4.6.1 Touch screen driver.....	237
5 Windows XP Professional.....	238
5.1 General information.....	238
5.2 Order data.....	238
5.3 Overview.....	238
5.4 Installation.....	238
5.5 Drivers.....	238
6 Windows Embedded Standard 2009.....	240

6.1 General information.....	240
6.2 Order data.....	240
6.3 Overview.....	240
6.4 Features with WES2009 (Windows Embedded Standard 2009).....	240
6.5 Installation.....	241
6.6 Drivers.....	241

Chapter 5 Standards and certifications..... **242**

1 Standards and guidelines.....	242
1.1 CE mark.....	242
1.2 EMC directive.....	242
1.3 Low voltage directive.....	242
2 Certifications.....	243
2.1 UL certification.....	243
2.2 UL Haz. Loc. Certifications.....	243
2.3 GOST-R.....	243

Chapter 6 Accessories..... **244**

1 Power connectors.....	244
1.1 0TB103.9x.....	244
1.1.1 General information.....	244
1.1.2 Order data.....	244
1.1.3 Technical data.....	244
1.2 0TB3103.8000.....	245
1.2.1 General information.....	245
1.2.2 Order data.....	245
1.2.3 Technical data.....	245
2 Replacement CMOS batteries.....	246
2.1 0AC201.91 / 4A0006.00-000.....	246
2.1.1 General information.....	246
2.1.2 Order data.....	246
2.1.3 Technical data.....	246
3 CFast cards.....	247
3.1 5CFAST.xxxx-00.....	247
3.1.1 General information.....	247
3.1.2 Order data.....	247
3.1.3 Technical data.....	247
3.1.4 Dimensions.....	248
3.1.5 Temperature humidity diagram.....	249
4 USB flash drives.....	250
4.1 5MMUSB.xxxx-01.....	250
4.1.1 General information.....	250
4.1.2 Order data.....	250
4.1.3 Technical data.....	250
4.1.4 Temperature humidity diagram.....	251
5 Cables.....	252
5.1 DVI cables.....	252
5.1.1 5CADVI.0xxx-00.....	252
5.2 SDL cables.....	255
5.2.1 5CASDL.0xxx-00.....	255
5.3 SDL cables with 45° male connector.....	258
5.3.1 5CASDL.0xxx-01.....	258
5.4 SDL flex cables.....	261
5.4.1 5CASDL.0xxx-03.....	261
5.5 SDL flex cables with extender.....	264
5.5.1 5CASDL.0xx0-13.....	264
5.6 USB cables.....	268

Table of contents

5.6.1 5CAUSB.00xx-00.....	268
5.7 RS232 cables.....	269
5.7.1 9A0014.xx.....	269
Chapter 7 Maintenance and service.....	271
1 Changing the battery.....	271
1.1 Procedure.....	271
2 Replacing a CFast card.....	273
3 Cleaning.....	274
4 Tips for extending the service life of the display.....	275
4.1 Backlight.....	275
4.1.1 How can the service life of the backlight be extended?.....	275
4.2 Screen burn-in.....	275
4.2.1 What causes screen burn-in?.....	275
4.2.2 How can screen burn-in be avoided?.....	275
5 Pixel errors.....	275
Appendix A	276
1 Abbreviations.....	276
2 Viewing angles.....	276

Chapter 1 • General information

1 Manual history

Version	Date	Change
1.00	19-Dec-13	<ul style="list-style-type: none">• First version

Table 1: Manual history

2 Safety guidelines

2.1 Intended use

Programmable logic controllers (PLCs), operating/monitoring devices (industrial PCs, Power Panels, Mobile Panels, etc.), and B&R uninterruptible power supplies have been designed, developed and manufactured for conventional use in industrial environments. They were not designed, developed and manufactured for any use involving serious risks or hazards that could lead to death, injury, serious physical damage or loss of any kind without the implementation of exceptionally stringent safety precautions. In particular, such risks and hazards include the use of these devices to monitor nuclear reactions in nuclear power plants, their use in flight control or flight safety systems as well as in the control of mass transportation systems, medical life support systems or weapons systems.

2.2 Protection against electrostatic discharge

Electrical components that can be damaged by electrostatic discharge (ESD) must be handled accordingly.

2.2.1 Packaging

- **Electrical components with a housing**
...Do not require special ESD packaging but must be handled properly (see "Electrical components with a housing").
- **Electrical components without a housing**
...Must be protected by ESD-suitable packaging.

2.2.2 Guidelines for proper ESD handling

Electrical components with a housing

- Do not touch the connector contacts on connected cables.
- Do not touch the contact tips on circuit boards.

Electrical components without a housing

The following applies in addition to the points listed under "Electrical components with a housing":

- Any persons handling electrical components or devices with installed electrical components must be grounded.
- Components may only be touched on their narrow sides or front plate.
- Components should always be stored in a suitable medium (ESD packaging, conductive foam, etc.). Metallic surfaces are not suitable storage surfaces!
- Components should not be subjected to electrostatic discharge (e.g. through the use of charged plastics).
- Ensure a minimum distance of 10 cm from monitors and TV sets.
- Measurement devices and equipment must be grounded.
- Measurement probes on potential-free measurement devices must be discharged on sufficiently grounded surfaces before taking measurements.

Individual components

- ESD protective measures for individual components are thoroughly integrated at B&R (conductive floors, footwear, arm bands, etc.).
- These increased ESD protective measures for individual components are not necessary for customers handling B&R products.

2.3 Policies and procedures

Electronic devices are never completely fail-safe. If the programmable control system, operating/monitoring device or uninterruptible power supply fails, the user is responsible for ensuring that other connected devices, e.g. motors, are brought to a secure state.

When using programmable logic controllers or operating/monitoring devices as control systems together with a Soft PLC (e.g. B&R Automation Runtime or comparable product) or Slot PLC (e.g. B&R LS251 or comparable product), safety precautions relevant to industrial control systems (e.g. the provision of safety devices such as emergency stop circuits, etc.) must be observed in accordance with applicable national and international regulations. The same applies for all other devices connected to the system, such as drives.

All tasks such as the installation, commissioning and servicing of devices are only permitted to be carried out by qualified personnel. Qualified personnel are those familiar with the transport, mounting, installation, commissioning and operation of devices who also have the appropriate qualifications (e.g. IEC 60364). National accident prevention regulations must be observed.

The safety notices, connection descriptions (nameplate and documentation) and limit values listed in the technical data are to be read carefully before installation and commissioning and must be observed.

2.4 Transport and storage

During transport and storage, devices must be protected against undue stress (mechanical loads, temperature, humidity, aggressive atmospheres, etc.).

2.5 Installation

- Installation must be performed according to this documentation using suitable equipment and tools.
- Devices may only be installed by qualified personnel without voltage applied. Before installation, voltage to the control cabinet must be switched off and prevented from being switched on again.
- General safety guidelines and national accident prevention regulations must be observed.
- Electrical installation must be carried out according to applicable guidelines (e.g. line cross sections, fuses, protective ground connections).

2.6 Operation

2.6.1 Protection against touching electrical parts

To operate programmable logic controllers, operating/monitoring devices or uninterruptible power supplies, it is necessary for certain parts to carry dangerous voltage levels over 42 VDC. Touching one of these parts can result in a life-threatening electric shock. This could lead to death, severe injury or damage to equipment.

Before turning on the programmable logic controller, operating/monitoring devices or the uninterruptible power supply, the housing must be properly grounded (PE rail). Ground connections must be established even when testing or operating operating/monitoring devices or the uninterruptible power supply for a short time!

Before turning the device on, all parts that carry voltage must be securely covered. During operation, all covers must remain closed.

2.6.2 Environmental conditions - Dust, humidity, aggressive gases

The use of operating/monitoring devices (e.g. industrial PCs, Power Panels, Mobile Panels, etc.) and uninterruptible power supplies in very dusty environments should be avoided. Dust collection on the devices can affect functionality and may prevent sufficient cooling, especially in systems with active cooling systems (fans).

The presence of aggressive gases can also lead to malfunctions. When combined with high temperature and humidity, aggressive gases – e.g. with sulfur, nitrogen and chlorine components – can induce chemical reactions that can damage electronic components very quickly. Signs of the presence of aggressive gases are blackened copper surfaces and cable ends on existing equipment.

For operation in dusty or humid conditions, correctly installed (e.g. cutout installations) operating/monitoring devices like the Automation Panel or Power Panel are protected on the front. The back of all devices must be protected from dust and humidity and cleaned at suitable intervals.

2.6.3 Viruses and dangerous programs

This system is subject to potential risk each time data is exchanged or software is installed from a data medium (e.g. diskette, CD-ROM, USB flash drive, etc.), a network connection or the Internet. The user is responsible for assessing these dangers, implementing preventive measures such as virus protection programs, firewalls, etc. and making sure that software is only obtained from trusted sources.

2.7 Environmentally friendly disposal

All B&R programmable controllers, operating/monitoring devices and uninterruptible power supplies are designed to inflict as little harm as possible on the environment.

2.7.1 Separation of materials

It is necessary to separate different materials so the device can undergo an environmentally friendly recycling process.

Component	Disposal
Programmable logic controllers Operating/monitoring devices Uninterruptible power supply Batteries and rechargeable batteries Cables	Electronics recycling
Cardboard box / paper packaging	Paper / cardboard recycling
Plastic packaging	Plastic recycling

Table 2: Environmentally friendly separation of materials

Disposal must comply with applicable legal regulations.

3 Organization of safety notices


Safety notices in this manual are organized as follows:

Safety notice	Description
Danger!	Disregarding these safety guidelines and notices can be life-threatening.
Warning!	Disregarding these safety guidelines and notices can result in severe injury or substantial damage to equipment.
Caution!	Disregarding these safety guidelines and notices can result in injury or damage to equipment.
Information:	This information is important for preventing errors.

Table 3: Description of the safety notices used in this documentation

4 Guidelines

European dimension standards apply to all dimension diagrams in this document.



All dimensions are specified in mm.

Range of nominal sizes	General tolerance according to DIN ISO 2768 (medium)
Up to 6 mm	± 0.1 mm
For 6 to 30 mm	± 0.2 mm
For 30 to 120 mm	± 0.3 mm
For 120 to 400 mm	± 0.5 mm
For 400 to 1000 mm	± 0.8 mm

Table 4: Range of nominal sizes

5 Overview

Product ID	Short description	on page
Batteries		
0AC201.91	Lithium batteries 4 pcs., 3 V / 950 mAh button cell We hereby state that the lithium cells contained in this shipment qualify as "partly regulated". Handle with care. If the package is damaged, inspect the cells, repack intact cells and protect the cells against short circuit. For emergency information, call RENATA SA at + 41 61 319 28 27	246
Bus units		
5AC902.BX01-00	PPC900 bus unit, 1-slot - 1 PCI - 1 slide-in	78
5AC902.BX01-01	PPC900 bus unit, 1-slot - 1 PCI Express x8 - 1 slide-in	78
5AC902.BX02-00	PPC900 bus unit, 2-slot - 2 PCI - 1 slide-in	78
5AC902.BX02-01	PPC900 2-slot bus unit - 1 PCI - 1 PCI Express x8 - 1 slide-in	78
CFast cards		
5CFAST.016G-00	CFast card, 16 GB	247
5CFAST.032G-00	CFast card, 32 GB	247
5CFAST.2048-00	CFast card, 2 GB	247
5CFAST.4096-00	CFast card, 4 GB	247
5CFAST.8192-00	CFast card, 8 GB	247
CPU boards		
5PC901.TS77-00	CPU board Intel Core i7 3615QE 2.3 GHz - Quad core - QM77 chipset	68
5PC901.TS77-01	CPU board Intel Core i7 3612QE 2.1 GHz - Quad core - QM77 chipset	68
5PC901.TS77-02	CPU board Intel Core i7 3555LE 2.5 GHZ - Dual core - QM77 chipset	68
5PC901.TS77-03	CPU board Intel Core i7 3517UE 1.7 GHz - Dual core - QM77 chipset	68
5PC901.TS77-04	CPU board Intel Core i5 3610ME 2.7 GHz - Dual core - QM77 chipset	68
5PC901.TS77-05	CPU board Intel Core i3 3120ME 2.4 GHz - Dual core - QM77 chipset	68
5PC901.TS77-06	CPU board Intel Core i3 3217UE 1.6 GHz - Dual core - QM77 chipset	68
5PC901.TS77-07	CPU board Intel Celeron 847E 1.1 GHz - Dual core - HM76 chipset	71
5PC901.TS77-08	CPU board Intel Celeron 827E 1.4 GHz - Single core - HM76 chipset	71
5PC901.TS77-09	CPU board Intel Celeron 1020E 2.2 GHz - Dual core - HM76 chipset	71
5PC901.TS77-10	CPU board Intel Celeron 1047UE 1.4 GHz - Dual core - HM76 chipset	71
DVI cable		
5CADVI.0018-00	DVI-D cable, 1.8 m	252
5CADVI.0050-00	DVI-D cable, 5 m	252
5CADVI.0100-00	DVI-D cable, 10 m	252
Display units		
5AP923.1215-00	Automation Panel 12.1" XGA TFT - 1024 x 768 pixels (4:3) - Single-touch (analog resistive) - IP65 protection (front)	54
5AP923.1505-00	Automation Panel 15.0" XGA TFT - 1024 x 768 pixels (4:3) - Single-touch (analog resistive) - IP65 protection (front)	56
5AP923.1906-00	Automation Panel 19.0" SXGA TFT - 1280 x 1024 pixels (4:3) - Single-touch (analog resistive) - IP65 protection (front)	58
5AP933.156B-00	Automation Panel 15.6" HD TFT - 1366 x 768 pixels (16:9) - Multi-touch (projected capacitive) - IP65 protection (front)	60
5AP933.185B-00	Automation Panel 18.5" HD TFT - 1366 x 768 pixels (16:9) - Multi-touch (projected capacitive) - IP65 protection (front)	62
5AP933.215C-00	Automation Panel 21.5" Full HD TFT - 1920 x 1080 pixels (16:9) - Multi-touch (projected capacitive) - IP65 protection (front)	64
5AP933.240C-00	Automation Panel 24.0" Full HD TFT - 1920 x 1080 pixels (16:9) - Multi-touch (projected capacitive) - IP65 protection (front)	66
Drives		
5AC901.CCFA-00	CFast adapter for operating a CFast card in a slide-in compact slot	97
5AC901.CHDD-01	500 GB SATA hard disk, slide-in compact, 24/7 operation Note: please see the manual for information about using this hard disk	81
5AC901.CSSD-03	60 GB SATA slide-in compact SSD (MLC)	83
5AC901.CSSD-04	128 GB SATA SSD (MLC), slide-in compact	85
5AC901.CSSD-05	256 GB SSD MLC - Slide-in compact - Toshiba - SATA	88
5AC901.SDVW-00	DVD-R/RW DVD+R/RW SATA slide-in drive	98
5AC901.SSCA-00	Slide-in compact adapter for operating a slide-in compact drive in a slide-in slot.	100
5MMSSD.0060-01	60 GB SATA SSD (MLC); replacement for 5AC801.SSDI-03 and 5AC901.CSSD-03; SSD for 5PP5IO.GMAC-00; note: please see the manual for information about using this SSD	90
5MMSSD.0128-01	128 GB SATA SSD (MLC); replacement for 5AC801.SSDI-04 and 5AC901.CSSD-04; SSD for 5PP5IO.GMAC-00; note: please see the manual for information about using this SSD	92
5MMSSD.0256-00	256 GB SSD MLC - Slide-in compact - Toshiba - SATA	95
Fan kits		
5AC902.FA00-00	PPC900 fan kit - For 5PC911.SX00-00	79
5AC902.FA0X-00	PPC900 fan kit - For PPC900 bus unit	80
Interface options		
5AC901.I485-00	RS232/422/485 interface option; for installation in an APC910 or PPC900	101
5AC901.ICAN-00	CAN interface option; for installation in an APC910 or PPC900	105
5AC901.IHDA-00	Audio interface option; connection for 1x MIC, 1x Line IN, 1x Line OUT; for installation in an APC910	109
5AC901.ISRM-00	SRAM interface option, 2 MB; for installation in an APC910 or PPC900	107
Main memory		
5MMDDR.1024-03	SO-DIMM DDR3, 1024 MB	76
5MMDDR.2048-03	SO-DIMM DDR3, 2048 MB	76
5MMDDR.4096-03	SO-DIMM DDR3, 4096 MB	76
5MMDDR.8192-03	SO-DIMM DDR3, 8192 MB	76

Product ID	Short description	on page
	Power supply	
5AC902.PS00-00	PPC900 power supply 85-264 VAC	124
	RS232 cable	
9A0014.02	RS232 extension cable for remote operation of a display unit with touch screen, 1.8 m	269
9A0014.05	RS232 extension cable for remote operation of a display unit with touch screen, 5 m	269
9A0014.10	RS232 extension cable for remote operation of a display unit with touch screen, 10 m	269
	SDL cable - 45° connector	
5CASDL.0018-01	SDL cable with 45° male connector, 1.8 m	258
5CASDL.0050-01	SDL cable with 45° male connector, 5 m	258
5CASDL.0100-01	SDL cable with 45° male connector, 10 m	258
5CASDL.0150-01	SDL cable with 45° male connector, 15 m	258
	SDL cables	
5CASDL.0018-00	SDL cable, 1.8 m	255
5CASDL.0050-00	SDL cable, 5 m	255
5CASDL.0100-00	SDL cable, 10 m	255
5CASDL.0150-00	SDL cable, 15 m	255
5CASDL.0200-00	SDL cable, 20 m	255
5CASDL.0250-00	SDL cable, 25 m	255
5CASDL.0300-00	SDL cable, 30 m	255
	SDL flex cable	
5CASDL.0018-03	SDL flex cable, 1.8 m	261
5CASDL.0050-03	SDL flex cable, 5 m	261
5CASDL.0100-03	SDL flex cable, 10 m	261
5CASDL.0150-03	SDL flex cable, 15 m	261
5CASDL.0200-03	SDL flex cable, 20 m	261
5CASDL.0250-03	SDL flex cable, 25 m	261
5CASDL.0300-03	SDL flex cable, 30 m	261
5CASDL.0300-13	SDL flex cable with extender, 30 m	264
5CASDL.0400-13	SDL flex cable with extender, 40 m	264
5CASDL.0430-13	SDL flex cable with extender, 43 m	264
	System units	
5PC911.SX00-00	PPC900 active system unit	74
5PC911.SX00-01	PPC900 passive system unit	75
	Terminal blocks	
0TB103.9	Connector, 24 VDC, 3-pin female, 3.31 mm ² screw clamp, protected against vibration by the screw flange	244
0TB103.91	Connector, 24 VDC, 3-pin female, 3.31 mm ² cage clamp, protected against vibration by the screw flange	244
0TB3103.8000	Connector, 230 VAC, 3-pin female, 4 mm ² screw clamp, protected against vibration by the screw flange	245
	USB accessories	
5MMUSB.2048-01	USB 2.0 flash drive, 2048 MB, B&R	250
5MMUSB.4096-01	USB 2.0 flash drive, 4096 MB, B&R	250
	USB cable	
5CAUSB.0018-00	USB 2.0 connection cable type A - type B, 1.8 m	268
5CAUSB.0050-00	USB 2.0 connection cable type A - type B, 5 m	268
	Uninterruptible power supplies	
5AC901.BUPS-00	Battery unit 4.5 Ah; for UPS 5AC901.IUPS-00	116
5AC901.BUPS-01	Battery unit 2.2 Ah; for UPS 5AC901.IUPS-01	119
5AC901.IUPS-00	UPS interface option; for installation in an APC910 or PPC900; for 4.5 Ah battery	112
5AC901.IUPS-01	UPS interface option; for installation in an APC910 or PPC900; for 2.2 Ah battery	114
5CAUPS.0005-01	UPS cable 0.5 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	122
5CAUPS.0010-01	UPS cable 1 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	122
5CAUPS.0030-01	UPS cable 3 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	122
	Windows 7 Professional/Ultimate	
5SWWI7.1100-ENG	Microsoft OEM Windows 7 Professional 32-bit, Service Pack 1, DVD, English. Only available with a new device.	234
5SWWI7.1100-GER	Microsoft OEM Windows 7 Professional 32-bit, Service Pack 1, DVD, German. Only available with a new device.	234
5SWWI7.1200-ENG	Microsoft OEM Windows 7 Professional 64-bit, Service Pack 1, DVD, English. Only available with a new device.	234
5SWWI7.1200-GER	Microsoft OEM Windows 7 Professional 64-bit, Service Pack 1, DVD, German. Only available with a new device.	234
5SWWI7.1300-MUL	Microsoft OEM Windows 7 Ultimate 32-bit, Service Pack 1, DVD, multilingual. Only available with a new device.	234
5SWWI7.1400-MUL	Microsoft OEM Windows 7 Ultimate 64-bit, Service Pack 1, DVD, multilingual. Only available with a new device.	234
	Windows Embedded Standard 2009	
5SWWXP.0741-ENG	Windows Embedded Standard 2009 - English - For PPC900 with QM77/HM76 chipset	240
	Windows Embedded Standard 7	
5SWWI7.1541-ENG	Windows Embedded Standard 7 SP1 - 32-bit - English - For PPC900 with QM77/HM76 chipset - License	236
5SWWI7.1641-ENG	Windows Embedded Standard 7 SP1 - 64-bit - English - For PPC900 with QM77/HM76 chipset - License	236
5SWWI7.1741-MUL	Windows Embedded Standard 7 Premium SP1 - 32-bit - Multilingual - For PPC900 with QM77/HM76 chipset - License	236
5SWWI7.1841-MUL	Windows Embedded Standard 7 Premium SP1 - 64-bit - Multilingual - For PPC900 with QM77/HM76 chipset - License	236
	Windows XP Professional	
5SWWXP.0600-ENG	Microsoft OEM Windows XP Professional Service Pack 3, CD, English. Only available with a new device.	238
5SWWXP.0600-GER	Microsoft OEM Windows XP Professional Service Pack 3, CD, German. Only available with a new device.	238
5SWWXP.0600-MUL	Microsoft OEM Windows XP Professional Service Pack 3, CD, multilingual. Only available with a new device.	238

Chapter 2 • Technical data

1 Introduction

1.1 About this user's manual

This user's manual contains all relevant information about a functioning Panel PC 900.

1.2 Description of individual modules

1.2.1 Display units

Display units consists of a display and touch screen and form the basis for each Automation Panel 9x3 and Panel PC 900 System. Different display sizes and touch screen technologies are available. These display units can be operated exclusively as a complete system together with a link module (Automation Panel 9x3) or CPU board and system unit (Panel PC 900).

Model numbers for display units with single-touch technology begin with 5AP923.xxxx-xx; those for display units with multi-touch technology begin with 5AP933.xxxx-xx.



1.2.2 CPU board and system unit

The CPU board integrates all of the PPC900's interfaces and also allows interface options, slide-in compact drives and CFast cards to be inserted.

A system unit consists of an anthracite gray housing and a heat sink. There are both passive variants (without a fan kit) and active variants (with a fan kit) available.

A functioning Panel PC 900 is put together by installing a system unit, main memory and mass storage device in a display unit. Panel PC 900 systems are mounted using retaining clips.

A CPU board and system unit cannot function without a display unit.



1.3 Structure/Configuration

Automation Panel 9x3 and Panel PC900 systems can be assembled to meet individual requirements and operating conditions. Automation Panel 9x3 and Panel PC 900 systems are so flexible that an Automation Panel can be rebuilt into a Panel PC and a Panel PC into an Automation Panel.


1.3.1 Configuration

The following components are absolutely essential for operation as a Panel PC 900:

- Display unit
- CPU board
- System unit
- Main memory
- Fan kit¹⁾
- Drive (mass storage device such as CFast card or hard disk) for the operating system
- Software

Panel PC 900 system can be operated with or without a fan kit. This choice plays a role in determining the various types of housing to be used.

Using a fan kit allows for operation at higher ambient temperatures. More information can be found under "Maximum ambient temperature during operation" on page 27.

Configuration - Base system	
Display unit	Select 1
	5AP923.1215-00 12.1" XGA single-touch 5AP923.1505-00 15.0" XGA single-touch 5AP923.1906-00 19.0" SXGA single-touch 5AP933.156B-00 15.6" HD multi-touch 5AP933.185B-00 18.5" HD multi-touch 5AP933.215C-00 21.5" FHD multi-touch 5AP933.240C-00 24.0" FHD multi-touch
CPU board - System unit - Fan kit - Main memory	
CPU board	Select 1
	QM77 CPU boards 5PC901.TS77-00 ¹⁾ 5PC901.TS77-04 5PC901.TS77-01 5PC901.TS77-05 5PC901.TS77-02 5PC901.TS77-06 5PC901.TS77-03
System unit	Select 1
	5PC911.SX00-00 Active system
	5PC911.SX00-01 System, passive
Fan kit	Select 1
	5AC902.FA00-00
Main memory	Select one or two
	5MMDDR.1024-03 5MMDDR.4096-03 5MMDDR.2048-03 5MMDDR.8192-03

1) The 5PC901.TS77-00 CPU board can only be used with system unit 5PC911.SX00-00.

Figure 1: Panel PC 900 - Base system configuration

¹⁾ It may be necessary to use a fan kit under certain conditions. Detailed information can be found in the section "Maximum ambient temperature during operation" on page 27.

Accessory and software configuration						
Power supply	Select 1					
	5AC902.PS00-00					
Slide-in compact drives	Select 1					
	5AC901.CHDD-01 5AC901.CSSD-03 5AC901.CSSD-04					
IF options	Select max. 2 ¹⁾					
	5AC901.I485-00 5AC901.ICAN-00					
UPS	Select 1 each					
	UPS module²⁾ + Battery unit + UPS cable 5AC901.IUPS-00 + 5AC901.BUPS-00 5AC901.IUPS-01 + 5AC901.BUPS-01					
5CAUPS.0005-01 5CAUPS.0010-01 5CAUPS.0030-01						
Bus unit - Slide-in drive - Fan kit						
Bus units	Select 1					
	5AC902.BX01-00 Bus 1PCI 1SI 5AC902.BX01-01 Bus 1PCIe.x8 1SI 5AC902.BX02-00 Bus 2PCI 1SI 5AC902.BX02-01 Bus 1PCI 1PCIe.x8 1SI					
Slide-in drives	Select max. 1					
	5AC901.SDVW-00 5AC901.SSCA-00					
Fan kit ³⁾	Select max. 1					
	5AC902.FA0X-00					
CFast cards	Select 1					
	5CFAST.2048-00 5CFAST.4096-00 5CFAST.8192-00					
USB accessories	Select 1					
	5MMUSB.2048-01 5MMUSB.4096-01					
Terminal blocks	Select 1					
	DC power connector 0TB103.9 0TB103.91		AC power connector 0TB3103.8000			

1) Certain limitations must be taken into account when using IF options. For more information, please refer to the section "Device interfaces" in Chapter 2 "Technical data".

2) The UPS module can only be operated in the IF option 1 slot.

3) If an active system unit is being used, then a fan kit must be selected for the bus unit.

Figure 2: Panel PC 900 - Accessory configuration

Configuration options




Figure 3: Panel PC 900 without bus unit




Figure 4: Panel PC 900 with 1-slot bus unit




Figure 5: Panel PC 900 with 2-slot bus unit

2 Complete system

2.1 Mechanical characteristics

2.1.1 Dimensions




Figure 6: Panel PC 900 + power supply + bus units - Dimensions

All dimensions are specified in mm.

Display type	Model number	A	B	C	D	E	F	G
12" single-touch	5AP923.1215-00	315	239	302	0	9	226	13.5
15" single-touch	5AP923.1505-00	370	288	357	36.5	9	275	14.5
19" single-touch	5AP923.1906-00	440	358	427	101	9	345	23
15" widescreen multi-touch	5AP933.156B-00	414	258.5	401	57.5	9	245.5	20
18" widescreen multi-touch	5AP933.185B-00	475	295	462	118.5	9	282	18
21" widescreen multi-touch	5AP933.215C-00	541.5	333	528.5	151.75	9	320	18
24" widescreen multi-touch	5AP933.240C-00	598.5	364	585.5	180.25	9	351	18

Table 5: Display unit - Dimensions

Component	Model number	H	I	J	K	L	M	N
CPU board and System unit	5PC901.TS77-xx & 5PC911.SX00-xx	54	226	225	-	-	-	-
1-slot bus unit	5AC902.BX01-xx	-	-	-	-	54.7	218	164
2-slot bus unit	5AC902.BX02-xx	-	-	-	-	75	218	164
Power supply	5AC902.PS00-00	53.5	225.5	-	74.5	-	-	-

Table 6: CPU boards, system units, bus units and power supply - Dimensions

Information:

3D diagrams are available upon request or can be downloaded from the B&R website www.br-automation.com.

2.1.2 Installation diagrams

Information:

When installing the Panel PC 900, spacing for air circulation as well as additional clearance for device operation and maintenance must be taken into consideration.




Figure 7: Panel PC 900 + power supply + bus units - Installation diagram

All dimensions are specified in mm.

Display type	Model number	X	Y	Z min	Z max	Number of retaining clips
12" single-touch	5AP923.1215-00	304	228	1	6	10 pcs.
15" single-touch	5AP923.1505-00	359	277	1	6	10 pcs.
19" single-touch	5AP923.1906-00	429	347	1	6	12 pcs.
15" widescreen multi-touch	5AP933.156B-00	403	247.5	1	6	10 pcs.
18" widescreen multi-touch	5AP933.185B-00	464	284	1	6	10 pcs.
21" widescreen multi-touch	5AP933.215C-00	530.5	322	1	6	14 pcs.
24" widescreen multi-touch	5AP933.240C-00	587.5	353	1	6	14 pcs.

Table 7: Display units - Installation diagrams

The "Z" dimension indicates the thickness of the wall or control cabinet panel.

A hex-head screwdriver is needed to tighten and loosen the screws on the retaining clips. The maximum torque for the retaining clips is 1 Nm.

2.1.3 Spacing for air circulation

In order to guarantee sufficient air circulation, the specified amount of space above, below, to the side and behind the device must be provided. The minimum specified spacing is indicated in the following diagram. This applies to all variants.

Information:

The following image and table provides a thermal examination of the complete system. If additional space is needed to operate or maintain the device, this must be taken into consideration during installation.

Air intake and exhaust is indicated in the following image for active Panel PCs (with fan kit). The air intake on passive Panel PCs (without fan kit) is located on the bottom to accommodate the rising warm air.




Figure 8: Panel PC 900 - Spacing for air circulation

S1: ≥20 mm

S2: ≥20 mm

S3: ≥50 mm

S4: ≥100 mm

S5: ≥50 mm

Caution!

The spacing specifications for air circulation are based on the worst-case scenario for operation at the maximum specified ambient temperature. The maximum specified ambient temperature must not be exceeded!

If the spacing specifications for air circulation cannot be adhered to, then the maximum specified temperatures for the temperature sensors (see "Temperature sensor locations" on page 30) must be monitored by the user and appropriate measures taken if they are exceeded.

2.1.4 Mounting orientations

The following diagrams show the approved mounting orientations for the Panel PC 900. The PPC900 must be mounted as described in the following sections.




Figure 9: Panel PC 900 - Mounting orientation

Mounting orientation	Ambient temperature limitation ¹⁾
0°	0°
A	-90° (counterclockwise)
B	+90° (clockwise)
C, D	±180° (interfaces on top)
C	-45°
D	+90° (display downwards)

Table 8: Mounting orientations with and without a fan kit

1) The maximum ambient temperature must be reduced by

Mounting orientation	Mounting orientation limitation with individual components ¹⁾	
	5AC901.SDVW-00	
0°	0°	
A	-30°	
B	+30°	
C	-5°	
D	+30°	

Table 9: Mounting orientation when operated with individual components with limitations

1) The mounting orientation may only be max.

In order to facilitate natural air circulation, devices must be mounted according to the spacing indicated in the section "Spacing for air circulation" on page 23.

2.1.5 Weight specifications

All weights are specified in g (grams).

Display type	Model number	Weight
12" single-touch	5AP923.1215-00	2200
15" single-touch	5AP923.1505-00	3700
19" single-touch	5AP923.1906-00	5800
15" widescreen multi-touch	5AP933.156B-00	3850
18" widescreen multi-touch	5AP933.185B-00	4850
21" widescreen multi-touch	5AP933.215C-00	5400
24" widescreen multi-touch	5AP933.240C-00	7800

Table 10: Display units - Weight

Component	Model number	Weight
CPU boards	5PC901.TS77-xx	450
System units	5PC911.SX00-00	3020
	5PC911.SX00-01	3020
1-slot bus units	5AC902.BX01-00	1020
	5AC902.BX01-01	1020
2-slot bus units	5AC902.BX02-00	1220
	5AC902.BX02-01	1220
Power supply	5AC902.PS00-00	580
Fan kit	5AC902.FA00-00	70
	5AC902.FA0X-00	36
Slide-in compact drives	5AC901.CHDD-01	134
	5AC901.CSSD-03	118
	5AC901.CSSD-04	118
	5AC901.CSSD-05	118
Slide-in drives	5AC901.SDVW-00	400
Interface options	5AC901.I485-00	34
	5AC901.ICAN-00	33
	5AC901.ISRM-00	20
	5AC901.IHDA-00	21
Uninterruptible power supply	5AC901.IUPS-00	28
	5AC901.IUPS-01	28
	5AC901.BUPS-00	4600
	5AC901.BUPS-01	2550

Table 11: CPU boards, system units, bus units and power supply - Weight

2.2 Environmental characteristics

2.2.1 Temperature specifications

CPU boards can be combined with various other components such as drives, main memory, additional plug-in cards, etc. depending on the display unit and system unit. The many different configurations possible result in varying maximum ambient temperatures, which can be seen in the following tables in this section.

Information:

The maximum specified ambient temperatures for operation with and without a fan kit have been determined under worst-case conditions. Experience has shown that higher ambient temperatures can be reached in typical applications, e.g. those in Microsoft Windows. Testing and evaluation must be performed on-site by the user (temperatures can be read in BIOS or with the B&R Control Center).

Information regarding worst-case conditions

- Thermal Analysis Tool (TAT V7.1) from Intel for simulating a 100% processor load
- BurnInTest tool (BurnInTest V4.0 Pro from Passmark Software) for simulating a 100% load on the interface via loop back adapters (serial interfaces, slide-in drives, USB ports, audio outputs)
- Maximum system expansion and power consumption

2.2.1.1 Maximum ambient temperature during operation

Operation with a fan kit

Information:

The 5PC911.SX00-00 system unit must be used when operating the Panel PC 900 with a fan kit.

Operation with a fan kit and 5PC911.SX00-00 system unit											
	i7 3615QE	i7 3612QE	i7 3555LE	i7 3517UE	i5 3610ME	i3 3120ME	i3 3217UE	C 847E	C 827E	C 1020E	C 1047UE
All temperature values in degrees Celsius (°C) at 500 m above sea level.											
The maximum ambient temperature is typically derated by 1°C per 1000 meters (starting at 500 meters above sea level).											
Maximum ambient temperature	50	55	55	55	55	55	55	55	55	55	55
What else can also be operated at the max. ambient temperature, or are there any limits?											
Display units	5AP923.1215-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	5AP923.1505-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	5AP923.1906-00	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	5AP933.156B-00	✓	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	5AP933.185B-00	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	5AP933.215C-00	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
	5AP933.240C-00	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
Main memory	1x 5MMDDR.xxxx-03 inserted ¹⁾	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	2x 5MMDDR.xxxx-03 inserted	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Slide-in compact drives	5AC901.CHDD-01	✓	50	50	50	50	50	50	50	50	-
	5AC901.CSSD-03	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.CSSD-04	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.CSSD-05	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.CCFA-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Slide-in drives	5AC901.SDVW-00	40	40	40	40	40	40	40	40	40	-
	5AC901.SSCA-00 ²⁾	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Interface options	5AC901.I485-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.ICAN-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.IHDA-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.ISRM-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.IUPS-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.IUPS-01	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Bus units	5AC902.BX01-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC902.BX01-01	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC902.BX02-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC902.BX02-01	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Power supply	5AC902.PS00-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
CFast cards	5CFAST.2048-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5CFAST.4096-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5CFAST.8192-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5CFAST.016G-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5CFAST.032G-00	✓	✓	✓	✓	✓	✓	✓	✓	✓	-

1) Main memory must be inserted in RAM slot 2.

2) The max. ambient temperature depends on the slide-in compact drive being used.

Table 12: Ambient temperature with a fan kit

Operation without a fan kit**Information:**

The 5PC901.TS77-00 CPU board cannot be operated without a fan kit.

The 5PC911.SX00-01 system unit must be used when operating the Panel PC 900 without a fan kit.

Operation without a fan kit and 5PC911.SX00-01 system unit													
	5PC901.TS77-00 i7 3615QE	5PC901.TS77-01 i7 3612QE	5PC901.TS77-02 i7 3555LE	5PC901.TS77-03 i7 3517UE	5PC901.TS77-04 i5 3610ME	5PC901.TS77-05 i3 3120ME	5PC901.TS77-06 i3 3217UE	C 847E	C 827E	C 1020E	C 1047UE	Temperature limits	Location of sensor(s)
	Maximum ambient temperature	-	35	40	50	35	35	50	50	50	35	50	
	What else can also be operated at the max. ambient temperature, or are there any limits?												
Display units	5AP923.1215-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AP923.1505-00	-	✓	TBD	✓	TBD	TBD	TBD	TBD	TBD	TBD	TBD	-
	5AP923.1906-00	-	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	-
	5AP933.156B-00	-	TBD	TBD	45	TBD	TBD	TBD	TBD	TBD	TBD	TBD	-
	5AP933.185B-00	-	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	-
	5AP933.215C-00	-	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	-
	5AP933.240C-00	-	TBD	TBD	35	TBD	TBD	TBD	TBD	TBD	TBD	TBD	-
Main memory	1x 5MMDR.xxxx-03 inserted ¹⁾	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	2x 5MMDR.xxxx-03 inserted	-	30	35	45	30	30	45	45	45	30	45	-
Slide-in compact drives	5AC901.CHDD-01	-	30 ³⁾	30 ³⁾	35 ³⁾	30 ³⁾	30 ³⁾	35 ³⁾	35 ³⁾	35 ³⁾	30 ³⁾	35 ³⁾	-
	5AC901.CSSD-03	-	✓	✓	40 ³⁾	✓	✓	40 ³⁾	40 ³⁾	40 ³⁾	✓	40 ³⁾	-
	5AC901.CSSD-04	-	✓	✓	40 ³⁾	✓	✓	40 ³⁾	40 ³⁾	40 ³⁾	✓	40 ³⁾	-
	5AC901.CSSD-05	-	✓	✓	40 ³⁾	✓	✓	40 ³⁾	40 ³⁾	40 ³⁾	✓	40 ³⁾	-
	5AC901.CCFA-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Slide-in drives	5AC901.SDVW-00	-	✓	✓	40	✓	✓	40	40	40	✓	40	-
	5AC901.SSCA-00 ²⁾	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Interface options	5AC901.I485-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.ICAN-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.IHDA-00	-	✓	✓	40	✓	✓	40	40	40	✓	40	-
	5AC901.ISRM-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.IUPS-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC901.IUPS-01	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Bus units	5AC902.BX01-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC902.BX01-01	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC902.BX02-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5AC902.BX02-01	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Power supply	5AC902.PS00-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
CFast cards	5CFAST.2048-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5CFAST.4096-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5CFAST.8192-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5CFAST.016G-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
	5CFAST.032G-00	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-

1) Main memory must be inserted in RAM slot 2.

2) The max. ambient temperature depends on the slide-in compact drive being used.

3) For systems with a total system load >90 W, the max. ambient temperature must be reduced by 5°C.

Table 13: Ambient temperature without a fan kit

2.2.1.1 How is the maximum ambient temperature for the Panel PC 900 determined?

1. System unit selection (with or without a fan kit)
2. CPU type selection
3. The "Maximum ambient temperature" row shows the maximum ambient temperature for the complete system, including the respective CPU board.

Information:

Maximum temperature data is for operation at 500 meters. The maximum ambient temperature is typically derated by 1°C per 1000 meters (starting at 500 meters above sea level).

4. Incorporating additional drives, interface options, etc. can change the temperature limits of a PPC900 system.

5. The mounting orientation of the Panel PC 900 may result in limitations. For more information, see "Mounting orientations" on page 24.

If there is a "✓" next to the component, it can be used at the maximum ambient temperature of the complete system without problems.

If there is a specific temperature, for example "45", next to the component, then the ambient temperature of the complete PPC900 system cannot exceed this temperature.

2.2.1.2 Minimum ambient temperature during operation

For systems containing the following components, the minimum ambient temperature during operation is +5°C: 5AC901.SDVW-00.

If none of these components are used, then the minimum ambient temperature during operation is 0°C.

2.2.1.3 Ambient temperature for storage and transport

The following table provides an overview of the minimum and maximum ambient temperature for storing and transporting the complete system. The use of individual components may result in limitations.

Storage	Transport
-20 to 60°C With 5AC901.BUPS-01: -15 to 40°C	-20 to 60°C With 5AC901.BUPS-01: -15 to 40°C

Table 14: Ambient temperature in storage / transport

2.2.1.4 Temperature monitoring

Sensors monitor temperature values at many different locations in the PPC900. The location of these temperature sensors is illustrated in Figure 10 "Panel PC 900 - Temperature sensor positions" on page 30. The values listed in Table 15 "Temperature sensor locations" on page 30 represent the defined maximum temperature for this measurement point. An alarm is not triggered if this temperature is exceeded. These temperatures can be read in BIOS or approved Microsoft Windows operating systems via the B&R Control Center.

In addition, the hard disks for PPC900 systems available from B&R are equipped with S.M.A.R.T., or Self-Monitoring, Analysis, and Reporting Technology. This makes it possible to read various parameters, e.g. temperature, using software (such as HDD Thermometer, a freeware program) on approved Microsoft operating systems.

2.2.1.5 Temperature sensor locations

Sensors indicate temperature values at many different locations in the PPC900. The temperatures²⁾ can be read in BIOS (Advanced - OEM features - System board features / CPU board features - Temperature values) or in Microsoft Windows operating systems via the B&R Control Center³⁾.

For applications that don't use Windows, the temperatures can be evaluated using the B&R implementation guide. In addition to the implementation guide, there are also programs available in MS-DOS.



Figure 10: Panel PC 900 - Temperature sensor positions

ADI sensors	Position	Measurement point for	Measurement	Max. specified
Panel	A	Display	Temperature of the display (sensor integrated in display unit)	5AP923.1215-00: 80°C
CPU board	B	CPU	Ambient temperature of the processor (sensor integrated in the processor)	95°C
System unit 1	C	Board	Board temperature (sensor integrated on the CPU board)	95°C
System unit 2	D	Chipset	Chipset area temperature (sensor integrated on the CPU board)	85°C
System unit 3	E	Board power supply	Board power supply area temperature (sensor integrated on the CPU board)	95°C
System unit 4	F	CFast	CFast area temperature (sensor integrated on the CPU board)	85°C
Slide-in drive	G	Slide-in drive	Temperature of slide-in drive 1 (sensor integrated on the slide-in drive)	Depends on the drive
	H	Interface option ¹⁾	Interface option temperature (sensor integrated on the interface option)	Depends on the IF option

Table 15: Temperature sensor locations

1) A temperature sensor is currently not integrated in the interface options.

2.2.1.6 Fan control

The MTCX constantly monitors the temperature using temperature sensors, which directly determines how the fans are controlled. The speed depends on the measured temperature. Limit values may depend on the MTCX firmware version being used.

Position	Measurement point for	Startup temperature	Max. fan speed at:
A	Display	5AP923.1215-00: 70°C	5AP923.1215-00: 86°C
B	CPU	65°C	81°C
C	Board controller	70°C	86°C
D	Chipset	70°C	86°C
E	Board power supply	70°C	86°C
F	CFast	60°C	76°C
G	Slide-in drive 1	5AC901.SDVW-00: 44°C, 5AC901.SSCA-00: 55°C	5AC901.SDVW-00: 60°C, 5AC901.SSCA-00: 71°C
H	Interface option ¹⁾	-	-

Table 16: Temperature sensor locations

1) A temperature sensor is currently not integrated in the interface options.

Once the startup temperature is reached, the device is started at the minimum fan speed. The maximum fan speed is reached at a startup temperature of 16°C. The fan speed in this area is controlled depending on the temperature.

Example with slide-in drive 5AC901.SDVW-00: 44°C + 16°C = 60°C --> maximum fan speed

The fans will only be shut off again if the evaluation temperature is more than 6°C below the switch-on temperature for a period of 4 hours (=overshoot time).

²⁾ The temperature measured approximates the immediate ambient temperature but may also be influenced by neighboring components.

³⁾ The ADI driver that includes the B&R Control Center is available in the Downloads section of the B&R website (www.br-automation.com).

2.2.2 Humidity

The following table lists the minimum and maximum relative humidity values for the individual components that are relevant for the humidity limitations of a complete system. The lowest and highest common values are always used when establishing these limits.

Display type	Model number	Operation	Storage / Transport
12" single-touch	5AP923.1215-00	5 to 90%	5 to 90%
15" single-touch	5AP923.1505-00	8 to 90%	8 to 90%
19" single-touch	5AP923.1906-00	5 to 90%	5 to 90%
15" widescreen multi-touch	5AP933.156B-00	5 to 90%	5 to 90%
18" widescreen multi-touch	5AP933.185B-00	5 to 90%	5 to 90%
21" widescreen multi-touch	5AP933.215C-00	10 to 90%	10 to 90%
24" widescreen multi-touch	5AP933.240C-00	5 to 90%	5 to 90%

Table 17: Display units - Humidity

Component	Model number	Operation	Storage / Transport
CPU board	5PC901.TS77-xx	10 to 90%	5 to 95%
System unit	5PC911.SX00-xx	5 to 95%	5 to 95%
1-slot bus unit	5AC902.BX01-xx	5 to 95%	5 to 95%
2-slot bus unit	5AC902.BX02-xx	5 to 95%	5 to 95%
Power supply	5AC902.PS00-00	7 to 90%	7 to 90%
Slide-in compact drives	5AC901.CHDD-01	5 to 95%	5 to 95%
	5AC901.CSSD-03	8 to 95%	8 to 95%
	5AC901.CSSD-04	8 to 95%	8 to 95%
	5AC901.CSSD-05	8 to 95%	8 to 95%
	5AC901.CCFA-00	5 to 95%	5 to 95%
Slide-in drives	5AC901.SDVW-00	8 to 80%	5 to 95%
Interface options	5AC901.I485-00	5 to 90%	5 to 95%
	5AC901.ICAN-00	5 to 90%	5 to 95%
	5AC901.IHDA-00	5 to 90%	5 to 95%
	5AC901.ISRM-00	5 to 90%	5 to 95%
Uninterruptible power supply	5AC901.IUPS-00	5 to 90%	5 to 95%
	5AC901.IUPS-01	5 to 90%	5 to 95%
	5AC901.BUPS-00	5 to 95%	5 to 95%
	5AC901.BUPS-01	25 to 85%	25 to 85%

Table 18: CPU boards, system units, bus units and power supply - Humidity

The specifications listed correspond to the relative humidity at an ambient temperature of 30°C. More detailed information about specific temperature-dependent humidity values can be found in the technical data for the individual components.

2.2.3 Vibration

The following table provides an overview of the maximum vibration specifications of the complete system. The use of individual components may result in limitations.

Panel PC	Operation		Storage	Transport
	Continuous	Periodic		
With SSD drives and CFast cards	9 to 200 Hz: 1 g	9 to 200 Hz: 1 g	TBD	TBD
With hard disk drives	5 to 500 Hz: 0.25 g	5 to 500 Hz: 0.5 g	TBD	TBD
With DVD-R/RW drives	-	5 to 500 Hz: 0.2 g	TBD	TBD

Table 19: Vibration

2.2.4 Shock

The following table provides an overview of the maximum shock specifications of the complete system. The use of individual components may result in limitations.

Panel PC	Operation	Storage		Transport
		Shock	Vibration	
With SSD drives and CFast cards	15 g, 11 ms	TBD	TBD	TBD
With hard disk drives	400 g, 2 ms	TBD	TBD	TBD
With DVD-R/RW drives	5 g, 11 ms	TBD	TBD	TBD

Table 20: Shock

2.2.5 Protection

The Panel PC 900 is rated IP65 on the front and IP20 on the back under the following conditions:

- Panel PC 900 correctly installed (see "Installation Panel PC 900" on page 125)
- All covers and components installed on the interfaces and slots
- All environmental conditions observed

2.3 Electrical characteristics

2.3.1 +24 VDC power supply

The 3-pin male connector required for the supply voltage connection is not included in delivery. It can be ordered from B&R using model number 0TB103.9 (screw clamp) or 0TB103.91 (cage clamp).

The pinout is listed in the following table. The supply voltage is protected internally by a soldered fuse (15 A, fast-acting) to prevent damage to the device in the event of an overload (fuse replacement necessary) or if the voltage supply is connected incorrectly (reverse polarity protection - fuse replacement not necessary). The device must be returned to B&R for repairs if the fuse is blown in the event of an error.

+24 VDC power supply	
Protected against reverse polarity	
Pin	Description
1	+
2	Functional ground
3	-
Model number	Short description
Terminal blocks	
0TB103.9	Connector 24 V 5.08 3-pin screw clamp
0TB103.91	Connector 24 V 5.08 3-pin cage clamp




Table 21: +24 VDC supply voltage connection

Electrical characteristics	
Nominal voltage	24 VDC ±25%
Nominal current	5.5 A
Starting current	Max. 60 A for <300 µs
Electrical isolation	Yes
Uninterruptible power supply	Optional, with 5AC901.IUPS-00 or 5AC901.IUPS-01

2.3.2 Optional Supply voltage VAC

In order to operate the Panel PC with AC power, the optional 5AC902.PS00-00 power supply must be installed on the Panel PC.

The 3-pin male connector required for the supply voltage connection is not included in delivery. This can be ordered from B&R using model number 0TB3103.8000.

The pinout is listed in the following table and printed on the housing. The supply voltage is protected internally by a soldered fuse to prevent damage to the device in the event of an overload (fuse replacement necessary) or if the voltage supply is connected incorrectly (reverse polarity protection - fuse replacement not necessary). The device must be returned to B&R for repairs if the fuse is blown in the event of an error.

VAC power supply	
Protected against reverse polarity	
Pin	Description
1	Protective ground
2	L
3	N
Model number	Short description
Terminal blocks	
0TB3103.8000	Connector, 230 VAC, 3-pin female, 4 mm² screw clamp, protected against vibration by the screw flange




Table 22: Supply voltage connection - VAC power supply

Electrical characteristics	
Nominal voltage	100 to 240 VAC
Frequency	45 to 65 Hz
Nominal current	1.25 to 2.5 A
Starting current	< 20 A (cold restart, 100% load and 100 VAC)
Internal fuse	Yes
Uninterruptible power supply	Optional with external UPS

2.3.3 Power calculation

In order to calculate the total power of the Panel PC, the power specifications of the display being used (see "Display units - Power calculation") must be entered in the "Display unit, permanent consumer" row of the "CPU board - Power calculation" table.

Information:

The power supply's maximum total power of 130 watts must not be exceeded.

Information:		CPU board												Current system	
		i7 3615QE 45 W CPU	i7 3612QE 35 W CPU	i7 3555LE 25 W CPU	i7 3517UE 17 W CPU	i5 3610ME 35 W CPU	i3 3120ME 35 W CPU	i3 3217UE 17 W CPU	C 84E 17 W CPU	C 827E 17 W CPU	C 1020E 35 W CPU	C 1047UE 17 W CPU			
	All values in watts The values for the suppliers are maximum values. The values for the consumers are average maximum values, but not peak values.	5PC901.TS77-00	5PC901.TS77-01	5PC901.TS77-02	5PC901.TS77-03	5PC901.TS77-04	5PC901.TS77-05	5PC901.TS77-06	5PC901.TS77-07	5PC901.TS77-08	5PC901.TS77-09	5PC901.TS77-10	Enter values in this column		
		Total power supply power (maximum)												130	
		Maximum possible												130	
+12 V	Display unit, permanent consumer ¹⁾														
	CPU board, permanent consumer	50	40	30	22	40	40	22	22	22	40	22			
	1024 MB RAM, each 2 W, max. 2 pcs.														
	2048 MB RAM, each 2.5 W, max. 2 pcs.														
	4096 MB RAM, each 3 W, max. 2 pcs.														
	8192 MB RAM, each 3.5 W, max. 2 pcs.														
	Fan kit, optional	3	3	3	3	3	3	3	3	3	3	3			
	UPS IF option 5AC901.IUPS-00 during operation, optional	30	30	30	30	30	30	30	30	30	30	30			
	UPS IF option 5AC901.IUPS-01 during operation, optional	25	25	25	25	25	25	25	25	25	25	25			
	PCI card limit, optional (max. 3 W without fan kit, max. 6 W with fan kit) ²⁾														
Total power supply +12 V	PCIe x8 card limit, optional (max. 3 W without fan kit, max. 20 W with fan kit) ²⁾														
	Consumers Σ												Maximum possible at +5V		50
	Display unit, permanent consumer ¹⁾														
	CPU board, permanent consumer	2	2	2	2	2	2	2	2	2	2	2			
	Slide-in compact drive (HDD / SSD)	4	4	4	4	4	4	4	4	4	4	4			
	Slide-in drive (DVD / ...)	4	4	4	4	4	4	4	4	4	4	4			
	4x USB peripherals, each max. 5 W														
	Interface option, optional ³⁾ , max. 2 connections														
	PCI card limit, optional (max. 3 W without fan kit, max. 20 W with fan kit) ²⁾														
	Maximum possible at -12V												1.2		
+5 V	PCI card limit, optional (max. 1.2 W with or without fan kit) ²⁾												Consumers -12 V Σ		
	Consumers +5 V Σ														
	Maximum possible at 3V3												33		
	Display unit, permanent consumer ¹⁾														
	CPU board, permanent consumer	5	5	5	5	5	5	5	5	5	5	5			
	CFast card	1	1	1	1	1	1	1	1	1	1	1			
	Interface option, optional ³⁾														
	PCI card limit, optional (max. 3 W without fan kit, max. 15 W with fan kit) ²⁾														
	PCIe x8 card limit, optional (max. 3 W without fan kit, max. 10 W with fan kit) ²⁾														
	Consumers 3V3 Σ														
Total power supply, consumers Σ															

1) Power ratings for the display units can be found in the table below.

2) The total performance of one PCI/PCIe card per PCI slot (= sum of the power consumption for each voltage range) may not exceed the limits stated for operation with or without a fan kit.

3) Power ratings for the interface options are listed in the table below.

Table 23: CPU board - Power calculation

In order to accurately determine the total power of the complete system, the values in this table must be entered in the power calculation table depending on the display unit being used.

Display type	Model number	+5 V	3V3	+12 V
12" single-touch	5AP923.1215-00	-	4.20 W	7.20 W
15" single-touch	5AP923.1505-00	-	3.55 W	6.00 W
19" single-touch	5AP923.1906-00	8.00 W	-	22.40 W
15" widescreen multi-touch	5AP933.156B-00	3.35 W	-	10.50 W
18" widescreen multi-touch	5AP933.185B-00	6.10 W	-	10.80 W
21" widescreen multi-touch	5AP933.215C-00	7.40 W	-	18.30 W
24" widescreen multi-touch	5AP933.240C-00	6.35 W	-	24.00 W

Table 24: Display units - Power calculation

In order to accurately determine the total power of the complete system, the values in this table must be entered in the power calculation table if one or more of these options are connected to the system unit.

Component	Model number	+5 V	3V3	+12 V
Interface option				
RS232/422/485 IF option	5AC901.I485-00	1 W	-	-
CAN IF option	5AC901.ICAN-00	1 W	-	-
Audio IF option	5AC901.IHDA-00	0.2 W	0.2 W	-
SRAM IF option	5AC901.ISRM-00	-	2 W	-
UPS IF option	5AC901.IUPS-00 in standby	-	-	0.1 W
UPS IF option	5AC901.IUPS-01 in standby	-	-	0.1 W

Table 25: Interface options - Power calculation

2.3.4 Block diagram

The following block diagram shows the simplified structure of the Panel PC 900 complete system without a display unit.




Figure 11: Block diagram - Panel PC 900

2.4 Device interfaces and slots

2.4.1 Overview of device interfaces

Interfaces are located on the bottom of the Panel PC 900.

The following indicates the position of interfaces on a Panel PC 900 with installed bus unit and AC power supply.




Figure 12: Device interfaces - Overview (bottom)

No.	Type of interface	No.	Type of interface
1	"+24 VDC power supply"	12	"USB interfaces"
2	"Optional Supply voltage VAC "	13	"USB interfaces"
3	"On/Off switch"	14	"USB interfaces"
4	"Grounding"	15	Retaining clips
5	"IF option 1 slot"	16	"Ethernet 1 (ETH1)"
6	"IF option 2 slot"	17	"Ethernet 2 (ETH2)"
7	"COM1 serial interface"	18	"Card slot (PCI / PCIe)"
8	"COM2 serial interface"	19	"Card slot (PCI / PCIe)"
9	"Audio"	20	Optional bus unit
10	"Monitor/Panel"	21	"Battery"
11	"USB interfaces"	22	Optional AC power supply




Figure 13: Device interfaces - Overview (side)

No.	Type of interface	No.	Type of interface
21	"CFast slot"	27	"LINK LED"
22	"Main memory" Slide-in compact slot	28	"RUN LED"
23	"Power button"	29	Fan kit for system unit
24	"Reset button"	30	Fan kit for bus unit
25	"Status LEDs"	31	Slide-in drive on bus unit
26	"HDD LED"		"Slide-in slot"

2.4.2 Supply voltage

The Panel PC can be operated with 24 VDC or optionally with 100~240 VAC. The 5AC902.PS00-00 power supply is needed for AC power.

Information on installing or exchanging the power supply can be found under "Installing or replacing the AC power supply" on page 130.

Danger!

- All supply voltage must be disconnected before removing device covers or components or removing/installing accessories, hardware or cables.**
- The power cable must be disconnected from the device and from the voltage supply.**
- Before the device can be connected to the power supply and turned on, all covers, components, accessories, hardware and cables must be installed or attached.**

2.4.2.1 +24 VDC power supply

The 3-pin male connector required for the supply voltage connection is not included in delivery. It can be ordered from B&R using model number 0TB103.9 (screw clamp) or 0TB103.91 (cage clamp).

The pinout is listed in the following table. The supply voltage is protected internally by a soldered fuse (15 A, fast-acting) to prevent damage to the device in the event of an overload (fuse replacement necessary) or if the voltage supply is connected incorrectly (reverse polarity protection - fuse replacement not necessary). The device must be returned to B&R for repairs if the fuse is blown in the event of an error.

+24 VDC power supply	
Protected against reverse polarity	
Pin	Description
1	+
2	Functional ground
3	-
Model number	Short description
	Terminal blocks
0TB103.9	Connector 24 V 5.08 3-pin screw clamp
0TB103.91	Connector 24 V 5.08 3-pin cage clamp




Table 26: +24 VDC supply voltage connection

Electrical characteristics	
Nominal voltage	24 VDC ±25%
Nominal current	5.5 A
Starting current	Max. 60 A for <300 µs
Electrical isolation	Yes
Uninterruptible power supply	Optional, with 5AC901.IUPS-00 or 5AC901.IUPS-01

2.4.2.1.1 Grounding

Caution!

The functional ground (pin 2) must be connected to ground (e.g. control cabinet) using the shortest possible path. Using the largest possible conductor cross section on the supply connector is recommended.

The ground connection is located on the bottom of the Panel PC system.



Figure 14: Ground connection

The ground connection can be used, for example, to fasten a copper strip to a central grounding point in the control cabinet or system where the device is installed. The largest possible conductor cross section should be used.

2.4.2.2 Optional Supply voltage VAC

In order to operate the Panel PC with AC power, the optional 5AC902.PS00-00 power supply must be installed on the Panel PC.

The 3-pin male connector required for the supply voltage connection is not included in delivery. This can be ordered from B&R using model number 0TB3103.8000.

The pinout is listed in the following table and printed on the housing. The supply voltage is protected internally by a soldered fuse to prevent damage to the device in the event of an overload (fuse replacement necessary) or if the voltage supply is connected incorrectly (reverse polarity protection - fuse replacement not necessary). The device must be returned to B&R for repairs if the fuse is blown in the event of an error.

VAC power supply	
Protected against reverse polarity	
Pin	Description
1	Protective ground
2	L
3	N
Model number	Short description
Terminal blocks	
0TB3103.8000	Connector, 230 VAC, 3-pin female, 4 mm ² screw clamp, protected against vibration by the screw flange

3-pin female connector

Supply voltage
100~240 VAC

1 2 3

Table 27: Supply voltage connection - VAC power supply

Electrical characteristics	
Nominal voltage	100 to 240 VAC
Frequency	45 to 65 Hz
Nominal current	1.25 to 2.5 A
Starting current	< 20 A (cold restart, 100% load and 100 VAC)
Internal fuse	Yes
Uninterruptible power supply	Optional with external UPS

2.4.2.2.1 On/Off switch

The On/Off switch can be used to turn the Panel PC on and off. It is found on the 100 ~ 240 VAC power supply.

On/Off switch	
Switch position	Description
0	The Panel PC is off.
1	The Panel PC is on.

On/Off switch

Table 28: On/Off switch

2.4.3 COM1 serial interface

COM1 serial interface ¹⁾	
RS232	
Type	RS232, modem-capable, not electrically isolated
UART	16550-compatible, 16-byte FIFO
Transfer rate	Max. 115 kbit/s
Bus length	Max. 15 m
Pin	Assignment
1	DCD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

9-pin male DSUB connector

Table 29: COM1 - Pinout

- 1) The interfaces, etc. available on the device or module have been numbered as such for easy identification. This numbering may differ from that used by the particular operating system.

2.4.4 COM2 serial interface

COM2 serial interface ¹⁾	
RS232	
Type	RS232, modem-capable, not electrically isolated
UART	16550-compatible, 16-byte FIFO
Transfer rate	Max. 115 kbit/s
Bus length	Max. 15 m
Pin	Assignment
1	DCD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

9-pin male DSUB connector

Table 30: COM2 - Pinout

- 1) The interfaces, etc. available on the device or module have been numbered as such for easy identification. This numbering may differ from that used by the particular operating system.

2.4.5 Monitor/Panel interface

Monitor/Panel interface - RGB / SDL (Smart Display Link) / DVI	
CPU board	Video signals for all system unit variants
5PC901.TS77-00	RGB, DVI, SDL
5PC901.TS77-01	RGB, DVI, SDL
5PC901.TS77-02	RGB, DVI, SDL
5PC901.TS77-03	RGB, DVI, SDL
5PC901.TS77-04	RGB, DVI, SDL
5PC901.TS77-05	RGB, DVI, SDL
5PC901.TS77-06	RGB, DVI, SDL
5PC901.TS77-07	RGB, DVI, SDL
5PC901.TS77-08	RGB, DVI, SDL
5PC901.TS77-09	RGB, DVI, SDL
5PC901.TS77-10	RGB, DVI, SDL



Table 31: Monitor/Panel interface - RGB, DVI, SDL

Information:

The hardware and graphics drivers of approved operating systems support the hot-plugging of display devices to the monitor/panel interface for service purposes. The male monitor/panel connector is specified for 100 connection cycles.

Information:

If a display device with a touch screen is connected to the monitor/panel interface and then disconnected again during operation (hot-plugging), it may be necessary to recalibrate the touch screen.

Information:

The RGB interface uses an analog signal whose line length depends on the resolution and the prevailing environmental conditions. Accordingly, this interface is only recommended for service purposes.

2.4.5.1 USB transfer rates in SDL and DVI modes

Information:

In **SDL mode**, the **USB transfer rate is limited to USB 1.1**.

In **DVI mode**, the **maximum USB transfer rate is determined by the USB interface and USB hub on the display device**.

2.4.5.2 Pinout

Pin	Assignment	Description	Pin	Assignment	Description
1	TMDS data 2-	DVI lane 2 (negative)	16	HPD	Hot plug detect
2	TMDS data 2+	DVI lane 2 (positive)	17	TMDS data 0-	DVI lane 0 (negative)
3	TMDS data 2/4 SHIELD	Shield for data pair 2 and 4	18	TMDS data 0+	DVI lane 0 (positive)
4	SDL-	SDL lane (negative)	19	TMDS Data 0/ XUSB1 SHIELD	Shield for data pair 0 and USB1
5	SDL+	SDL lane (positive)	20	XUSB1-	USB lane 1 (negative)
6	DDC clock	DDC-based control signal (clock)	21	XUSB1+	USB lane 1 (positive)
7	DDC data	DDC-based control signal (data)	22	TMDS clock shield	Shield for clock pair
8	NC	Not connected	23	TMDS clock+	DVI clock (positive)
9	TMDS data 1-	DVI lane 1 (negative)	24	TMDS clock -	DVI clock (negative)
10	TMDS DATA 1+	DVI lane 1 (negative) HDMI clock (positive)	C1	ANALOG RED	Analog red
11	TMDS DATA 1 / XUSBO SHIELD	Shield for data pair 1 and USBO	c2	ANALOG GREEN	Analog green
12	XUSBO-	USB lane 0 (negative)	C3	ANALOG BLUE	Analog blue
13	XUSBO+	USB lane 0 (positive)	C4	ANALOG HORZ SYNC	Analog horizontal synchronization




Table 32: DVI interface - Pinout

Pin	Assignment	Description	Pin	Assignment	Description	
14	+5 V power ¹⁾	+5 V power supply	C5	ANALOG GND	Analog ground (return for R, G and B signals)	
15	Ground (return for +5 V, HSync and VSync)	Ground				

Table 32: DVI interface - Pinout

1) Protected internally by a multifuse.

2.4.5.3 Cable lengths and resolutions for SDL transmission

The following table lists the relationship between segment lengths and maximum resolution depending on the SDL cable being used:

SDL cables Segment length [m]	Resolution						
	VGA 640 x 480	SVGA 800 x 600	XGA 1024 x 768	SXGA 1280 x 1024	HD 1366 x 768	UXGA 1600 x 1200	FHD 1920 x 1080
1.8	5CSDL.0018-00 5CSDL.0018-01 5CSDL.0018-03						
5	5CSDL.0050-00 5CSDL.0050-01 5CSDL.0050-03						
10	5CSDL.0100-00 5CSDL.0100-01 5CSDL.0100-03						
15	5CSDL.0150-00 5CSDL.0150-01 5CSDL.0150-03	5CSDL.0150-00 5CSDL.0150-01 5CSDL.0150-03	5CSDL.0150-00 5CSDL.0150-01 5CSDL.0150-03	5CSDL.0150-00 5CSDL.0150-01 5CSDL.0150-03	5CSDL.0150-00 5CSDL.0150-01 5CSDL.0150-03	-	-
20	5CSDL.0200-00 5CSDL.0200-03	5CSDL.0200-00 5CSDL.0200-03	5CSDL.0200-00 5CSDL.0200-03	5CSDL.0200-00 5CSDL.0200-03	5CSDL.0200-00 5CSDL.0200-03	-	-
25	5CSDL.0250-00 5CSDL.0250-03	5CSDL.0250-00 5CSDL.0250-03	5CSDL.0250-00 5CSDL.0250-03	- -	5CSDL.0250-00 5CSDL.0250-03	-	-
30	5CSDL.0300-00 5CSDL.0300-03	5CSDL.0300-00 5CSDL.0300-03	5CSDL.0300-13	5CSDL.0300-13	5CSDL.0300-13	-	5CSDL.0300-13
40	5CSDL.0400-13	5CSDL.0400-13	5CSDL.0400-13	5CSDL.0400-13	5CSDL.0400-13	-	5CSDL.0400-13

Table 33: Cable lengths and resolutions for SDL transmission

2.4.5.4 Cable lengths and resolutions for DVI transmission

The following table lists the relationship between segment lengths and maximum resolution depending on the DVI cable being used:

DVI cables Segment length [m]	Resolution						
	VGA 640 x 480	SVGA 800 x 600	XGA 1024 x 768	SXGA 1280 x 1024	HD 1366 x 768	UXGA 1600 x 1200	FHD 1920 x 1080
1.8	5CADVI.0018-00	5CADVI.0018-00	5CADVI.0018-00	5CADVI.0018-00	5CADVI.0018-00	5CADVI.0018-00	5CADVI.0018-00
5	5CADVI.0050-00	5CADVI.0050-00	5CADVI.0050-00	5CADVI.0050-00	5CADVI.0050-00	5CADVI.0050-00	5CADVI.0050-00

Table 34: Cable lengths and resolutions for DVI transmission

The maximum cable length for DVI transfer is limited to 5 m due to the USB specification.

2.4.6 Ethernet 1 (ETH1)

This Ethernet controller is integrated in the CPU board and connected to external devices via the system unit.

Ethernet 1 interface (ETH1 ¹⁾)		
Controller	Intel® 82579V	
Cabling	S/STP (Cat 5e)	
Transfer rate	10/100/1000 Mbit/s ²⁾	
Cable length	Max. 100 m (min. Cat 5e)	
Speed LED	On	Off
Green	100 Mbit/s	10 Mbit/s ³⁾
Orange	1000 Mbit/s	-
Link LED	On	Off
Green	Link (Ethernet network connection available)	Activity (blinking - data transfer in progress)

Table 35: Ethernet interface (ETH1)

- 1) The interfaces, etc. available on the device or module have been numbered as such for easy identification. This numbering may differ from that used by the particular operating system.
- 2) Switching takes place automatically.
- 3) The 10 Mbit/s transfer speed / connection only exists if the Link LED is also lit at the same time.

Driver support

A special driver is required in order to operate the Ethernet controller. Drivers for approved operating systems are available in the Downloads section of the B&R website (www.br-automation.com).

Information:

Required drivers can only be downloaded from the B&R website, not from manufacturer websites.

2.4.7 Ethernet 2 (ETH2)

This Ethernet controller is integrated in the CPU board and connected to external devices via the system unit.

Ethernet 2 interface (ETH2 ¹⁾)		
Controller	Intel® I210	
Cabling	S/STP (Cat 5e)	
Transfer rate	10/100/1000 Mbit/s ²⁾	
Cable length	Max. 100 m (min. Cat 5e)	
Speed LED	On	Off
Green	100 Mbit/s	10 Mbit/s ³⁾
Orange	1000 Mbit/s	-
Link LED	On	Off
Green	Link (Ethernet network connection available)	Activity (blinking - data transfer in progress)

Table 36: Ethernet interface (ETH2)

- 1) The interfaces, etc. available on the device or module have been numbered as such for easy identification. This numbering may differ from that used by the particular operating system.
- 2) Switching takes place automatically.
- 3) The 10 Mbit/s transfer speed / connection only exists if the Link LED is also lit at the same time.

Driver support

A special driver is required in order to operate the Ethernet controller. Drivers for approved operating systems are available in the Downloads section of the B&R website (www.br-automation.com).

Information:

Required drivers can only be downloaded from the B&R website, not from manufacturer websites.

2.4.8 USB interfaces

The Panel PC features a USB 3.0 (Universal Serial Bus) host controller with multiple USB ports, 4 of which are accessible externally for the user.

Warning!

Peripheral USB devices can be connected to the USB interfaces on this device. Due to the vast number of USB devices available on the market, B&R cannot guarantee their performance. B&R does ensure the performance of all USB devices that they provide.

Caution!

Because this interface is designed according to general PC specifications, extreme care should be exercised with regard to EMC, cable routing, etc.

USB1, USB2, USB3, USB4

4 USB 3.0 ports are provided on the bottom of the Panel PC.

Universal Serial Bus (USB1, USB2, USB3, USB4) ¹⁾	
Type	USB 3.0
Design	Type A
Transfer rate	Low speed (1.5 Mbit/s), full speed (12 Mbit/s), high speed (480 Mbit/s), super speed (5 Gbit/s) ²⁾
Current load ³⁾ USB1, USB2 USB3, USB4	Max. 1 A Max. 1 A
Cable length USB 2.0 USB 3.0	Max. 5 m (without hub) Max. 3 m (without hub)




Table 37: USB1, USB2, USB3 and USB4 interfaces

- 1) The interfaces, etc. available on the device or module have been numbered as such for easy identification. This numbering may differ from that used by the particular operating system.
- 2) Compatibility with Super Speed depends on the operating system used.
- 3) Each USB port is protected by a maintenance-free "USB current limiting circuit breaker" (max. 1 A).

2.4.9 CFast slot

The Panel PC offers an easy-to-reach CFast slot on the side, so that the CFast card can also be used as removable media for transferring data or performing upgrades.

This CFast slot is connected to the chipset internally via SATA 1 with SATA III design (SATA 6 Gbit/s).

CFast slot	
Connection	SATA 1
Model number	Short description
	CFast cards
5CFAST.2048-00	CFast card, 2 GB
5CFAST.4096-00	CFast card, 4 GB
5CFAST.8192-00	CFast card, 8 GB
5CFAST.016G-00	CFast card, 16 GB
5CFAST.032G-00	CFast card, 32 GB



Table 38: CFast slot

Warning!

Power must be turned off before inserting or removing CFast cards.

2.4.10 Audio

The MIC and Line IN ports share a connection. The Line OUT port has a separate connection. When a device is connected to an audio port, it is detected by the driver and the user can configure the connections.

MIC, Line IN, Line OUT	
Controller	Realtek RTL888
MIC	Connection of a mono microphone with a 3.5 mm jack
Line IN	Stereo Line IN signal supplied via a 3.5 mm jack
Line OUT	Connection of a stereo playback device (e.g. amplifier) via a 3.5 mm jack




Table 39: Audio


A special driver is required in order to operate the audio controller. Drivers for approved operating systems are available in the Downloads section of the B&R website (www.br-automation.com).

Information:

Required drivers can only be downloaded from the B&R website, not from manufacturer websites.

2.4.11 Status LEDs

The Status LEDs are located on the right side of the Panel PC when viewed from the front.



The following timing is used for the LED status indicators:

Block size: 250 ms

Repeat interval: 500 ms, 2 boxes thus represent one interval

LED	Color	Status	Description	LED status indicator
Power	Green	On	Supply voltage OK	
		Blinking	Device booted, battery status "BAD"	
	Information: For more information, see "Battery" on page 49.			
	Red	On	System in standby mode (S5: Soft-off mode or S4: Hibernation mode suspend-to-disk)	
		Blinking	MTCX running, battery status "BAD". System in standby mode (S5: Soft-off mode or S4: Hibernation mode suspend-to-disk).	
	Red / green	Blinking	Faulty or incomplete BIOS, MTCX or I/O FPGA update, battery status OK, supply voltage OK	
			Faulty or incomplete BIOS, MTCX or I/O FPGA update, battery status OK, standby mode (S5: Soft-off mode or S4: Hibernation mode suspend-to-disk)	
			Faulty or incomplete BIOS, MTCX or I/O FPGA update, battery status BAD, supply voltage OK	
			Faulty or incomplete BIOS, MTCX or I/O FPGA update, battery status BAD, standby mode (S5: Soft-off mode or S4: Hibernation mode suspend-to-disk)	
	Information: An update must be performed again.			
	Yellow	On	Supply voltage not OK, system operating from UPS	
HDD	Yellow	On	Indicates drive access (HDD, CFast)	
Link	Yellow	On	Indicates an active SDL connection on the male panel connector	
		Blinking	Indicates that an active SDL connection has been interrupted by a loss of power to the display unit	
	Information: Check the supply voltage / power connector of the connected display unit.			
Run	Green	Blinking	Automation Runtime booting Controlled by Automation Runtime (ARemb and ARwin)	
	Green	On	Application running Controlled by Automation Runtime (ARemb and ARwin)	
	Red	On	Application in service mode Controlled by Automation Runtime (ARemb and ARwin)	

Table 40: Data - LED status indicators

2.4.12 Power button

The power button provides a wide range of ATX power supply functions.


Power button	
<p>The power button can be pressed with a pointed object (e.g. paper clip or tip of a pen).</p> <p>The power button acts like the on/off switch on a normal desktop PC with an ATX power supply:</p> <p>Press and release ... Switches on the Panel PC or shuts down the operating system and switches off the Panel PC.</p> <p>Press and hold ... Switches off the ATX power supply without shutting down the Panel PC (data could be lost!)</p> <p>Pressing the power button does not reset the MTCX processor.</p>	

Table 41: Power button

2.4.13 Reset button


Reset button	
<p>The reset button can be pressed with a pointed object (e.g. paper clip or tip of a pen).</p> <p>Pushing the reset button triggers a hardware and PCI reset. The Panel PC is restarted (cold restart).</p> <p>Pressing the reset button does not reset the MTCX processor.</p>	

Table 42: Reset button

Warning!

A system reset can result in lost data!

2.4.14 Battery

The lithium battery (3 V, 950 mAh) buffers the internal real-time clock (RTC). It is located on the back of the Panel PC. The battery is installed in a battery holder, making it very easy to replace.

The battery's buffer lifespan is at least 4 years (at 50°C, 8.5 µA for the components being supplied and a self-discharge of 40%). If an SRAM interface option has been installed, this lifespan is reduced to 2½ years. The battery has a limited service life and should be replaced regularly (after the specified service life at the latest).

Battery	
Battery	
Type	Renata 950 mAh
Removable	Yes, accessible from the outside
Service life	4 years ¹⁾
Model number	Short description
	Batteries
OAC201.91	Lithium batteries, 4 pcs., 3 V / 950 mAh, button cell
4A0006.00-000	Lithium battery, 1 pc., 3 V / 950 mAh, button cell




Table 43: Battery

1) At 50°C, 8.5 µA of the supplied components and a self-discharge of 40%.

The status of the battery is determined immediately after the device is started and subsequently checked by the system every 24 hours. During this measurement, the battery is subjected to a brief load (approximately 1 second) and then evaluated. Once determined, the battery status is displayed in BIOS (Advanced - OEM Features - System board features - Voltage values) and in the B&R Control Center (ADI driver); it can also be read in a customer application using the ADI library.

Battery status	Description
N/A	The hardware or firmware being used is too old and does not support reading the battery status.
GOOD	Data buffering is intact.
BAD	From the point when battery capacity is recognized as insufficient (BAD), data buffering is intact for approximately another 500 hours.

Table 44: Battery status

From the point when battery capacity is recognized as insufficient, data buffering is intact for approximately another 500 hours. When replacing the battery, data is buffered for approximately 10 minutes by a gold leaf capacitor.

2.4.15 Slide-in compact slot

The slide-in compact slot is connected to the chipset internally via SATA 0 with SATA III design (SATA 6 Gbit/s).

Slide-in compact slot	
Connection	SATA 0
Model number	Short description
	Drives
5AC901.CHDD-01	500 GB SATA slide-in compact hard disk, 24/7 operation with extended temperature range, note: Please see the manual for information about using this hard disk.
5AC901.CSSD-03	60 GB SATA SSD (MLC), slide-in compact
5AC901.CSSD-04	128 GB SATA SSD (MLC), slide-in compact
5AC901.CSSD-05	256 GB SATA slide-in compact SSD (MLC)
5AC901.CCFA-00	CFast adapter for operating a CFast card in a slide-in compact slot

Table 45: Slide-in compact slot

Information:

For information about installing or replacing a slide-in compact drive, please refer to the section "Installing and replacing the slide-in compact drive" on page 137.

2.4.16 Slide-in slot

The slide-in slot is integrated in the bus unit. It is connected to the chipset internally via SATA 2 and USB with SATA II design (SATA 3 Gbit/s).

Slide-in slot	
Connection	SATA 2 and USB
Model number	Short description
	Drives
5AC901.SCFA-00	CFast adapter for operating a CFast card in a slide-in slot
5AC901.SDVW-00	DVD-R/RW DVD+R/RW SATA drive, slide-in

Table 46: Slide-in slot

Information:

For information about installing or replacing a slide-in drive, please refer to the section "Installing a slide-in drive" on page 145.

2.4.17 Main memory

The Panel PC 900 provides 2 slots for DDR3 main memory modules.

Main memory slot	
Speed	DDR3-1600 (PC3-12800)
Model number	Short description
	Main memory
5MMDDR.1024-03	SO-DIMM DDR3, 1024 MB
5MMDDR.2048-03	SO-DIMM DDR3, 2048 MB
5MMDDR.4096-03	SO-DIMM DDR3, 4096 MB
5MMDDR.8192-03	SO-DIMM DDR3, 8192 MB





Table 47: Main memory slot

Information:

For information about installing or replacing main memory, please refer to the section "Replacing the main memory modules" on page 132.

Caution!

If only one main memory module is to be used, it must be installed in RAM slot 2.



2.4.18 IF option 1 slot

The Panel PC system units include 2 slots for interface options.

The following table lists the interface options that can be used in the IF option 1 slot.

IF option 1 slot	
Model number	Short description
Interface option	
5AC901.I485-00 ¹⁾	RS232/422/485 interface option, for installation in an APC910
5AC901.ICAN-00 ^{1,2)}	CAN interface option, for installation in an APC910
5AC901.IHDA-00	Audio interface option, connection for 1x MIC, 1x Line IN, 1x Line OUT, for installation in an APC910
5AC901.IUPS-00 ³⁾	UPS interface option; for installation in an APC910; for a 4.5 Ah battery.
5AC901.IUPS-01 ⁴⁾	UPS interface option; for installation in an APC910; for a 2.2 Ah battery.




Table 48: IF option 1 slot

- 1) If IF options 5AC901.I485-00 and 5AC901.ICAN-00 are used simultaneously, 5AC901.ICAN-00 should be installed in the IF option 1 slot and 5AC901.I485-00 should be installed in the IF option 2 slot.
- 2) It is not possible to operate two 5AC901.ICAN interface options (in the IF option 1 and IF option 2 slots) at the same time.
- 3) The 5AC901.IUPS-00 UPS IF option is only permitted to be operated with the 5AC901.BUPS-00 battery unit!
- 4) The 5AC901.IUPS-01 UPS IF option is only permitted to be operated with the 5AC901.BUPS-01 battery unit!

Information:

For information about installing or replacing an interface option, please refer to the section "Installing the interface option" on page 134.

2.4.19 IF option 2 slot

The Panel PC system units include 2 slots for interface options.

The following table lists the interface options that can be used in the IF option 2 slot.

IF option 2 slot	
Model number	Short description
Interface option	
5AC901.I485-00 ¹⁾	RS232/422/485 interface option, for installation in an APC910
5AC901.ICAN-00 ^{1,2)}	CAN interface option, for installation in an APC910
5AC901.ISRM-00	SRAM interface option, 2 MB, for installation in an APC910




Table 49: IF option 2 slot

- 1) If IF options 5AC901.I485-00 and 5AC901.ICAN-00 are used simultaneously, 5AC901.ICAN-00 should be installed in the IF option 1 slot and 5AC901.I485-00 should be installed in the IF option 2 slot.
- 2) It is not possible to operate two 5AC901.ICAN interface options (in the IF option 1 and IF option 2 slots) at the same time.

Information:

For information about installing or replacing an interface option, please refer to the section "Installing the interface option" on page 134.

2.4.20 Card slot (PCI / PCIe)

If a bus unit is installed in the Panel PC 900, the bus unit variant being used will determine whether a standard PCI 2.2 half-size card or PCIe Express (PCIe) half-size card can be inserted. They cannot exceed the following dimensions.




Figure 15: Standard half-size 32-bit PCI card - Dimensions




Figure 16: Standard half-size PCIe card - Dimensions

Information:

For information about installing or replacing a PCI / PCIe card, please refer to the section "Installing PCI / PCIe cards" on page 143.

3 Individual components

3.1 Display units

3.1.1 5AP923.1215-00

3.1.1.1 General information

- Display unit for AP9x3 or PPC900
- 12" TFT XGA color display
- Single-touch (analog resistive)
- Black aluminum front
- IP65 protection (on front)

3.1.1.2 Order data


Model number	Short description	Figure
Display units		
5AP923.1215-00	Automation Panel 12.1" XGA TFT - 1024 x 768 pixels (4:3) - Single-touch (analog resistive) - IP65 protection (front)	

Table 50: 5AP923.1215-00 - Order data

3.1.1.3 Technical data

Product ID	5AP923.1215-00
General information	
Certification	
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
Display	
Type	Color TFT
Diagonal	12.1"
Colors	16.2 million
Resolution	XGA, 1024 x 768 pixels
Contrast	700:1
Viewing angles	
Horizontal	Direction R / Direction L = 80°
Vertical	Direction U / Direction D = 80°
Backlight	
Classification	LED
Brightness	500 cd/m ²
Half-brightness time ²⁾	50,000 h
Touch screen ³⁾	
Type	AMT
Technologies	Analog, resistive
Controller	B&R, serial, 12-bit
Transmittance	80% ±3%
Mechanical characteristics	
Front	
Frame	Aluminum paint
Design	Black
Gasket	3 mm built-in seal

Table 51: 5AP923.1215-00 - Technical data

Product ID	5AP923.1215-00
Dimensions	
Width	315 mm
Height	239 mm
Weight	2200 g

Table 51: 5AP923.1215-00 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) At an ambient temperature of 25°C. Reducing the brightness by 50% can result in an approximately 50% increase in the half-brightness time.
- 3) Touch screen drivers for approved operating systems are available in the Downloads section of the B&R website.

3.1.1.4 Dimensions




Figure 17: 5AP923.1215-00 - Dimensions

3.1.1.5 Temperature humidity diagram




Figure 18: 5AP923.1215-00 - Temperature humidity diagram

3.1.2 5AP923.1505-00

3.1.2.1 General information

- Display unit for AP9x3 or PPC900
- 15" TFT XGA color display
- Single-touch (analog resistive)
- Black aluminum front
- IP65 protection (on front)

3.1.2.2 Order data


Model number	Short description	Figure
Display units		
5AP923.1505-00	Automation Panel 15.0" XGA TFT - 1024 x 768 pixels (4:3) - Single-touch (analog resistive) - IP65 protection (front)	

Table 52: 5AP923.1505-00 - Order data

3.1.2.3 Technical data

Product ID	5AP923.1505-00
General information	
Certification GOST-R	Yes
Display	
Type	Color TFT
Diagonal	15"
Colors	16.2 million
Resolution	XGA, 1024 x 768 pixels
Contrast	700:1
Viewing angles Horizontal Vertical	Direction R / Direction L = 80° Direction U / Direction D = 70°
Backlight Classification Brightness Half-brightness time ¹⁾	LED 350 cd/m ² 50,000 h
Touch screen ²⁾ Type Technologies Controller Transmittance	AMT Analog, resistive B&R, serial, 12-bit 81% ±3%
Mechanical characteristics	
Front Frame Design Gasket	Aluminum paint Black 3 mm built-in seal
Dimensions Width Height	370 mm 288 mm
Weight	3700 g

Table 53: 5AP923.1505-00 - Technical data

- 1) At an ambient temperature of 25°C. Reducing the brightness by 50% can result in an approximately 50% increase in the half-brightness time.
 2) Touch screen drivers for approved operating systems are available in the Downloads section of the B&R website.

3.1.2.4 Dimensions




Figure 19: 5AP23.1505-00 - Dimensions

3.1.2.5 Temperature humidity diagram




Figure 20: 5AP923.1505-00 - Temperature humidity diagram

3.1.3 5AP923.1906-00

3.1.3.1 General information

- Display unit for AP9x3 or PPC900
- 19" TFT SXGA color display
- Single-touch (analog resistive)
- Black aluminum front
- IP65 protection (on front)

3.1.3.2 Order data


Model number	Short description	Figure
Display units		
5AP923.1906-00	Automation Panel 19.0" SXGA TFT - 1280 x 1024 pixels (4:3) - Single-touch (analog resistive) - IP65 protection (front)	

Table 54: 5AP923.1906-00 - Order data

3.1.3.3 Technical data

Product ID	5AP923.1906-00
Display	
Type	Color TFT
Diagonal	19"
Colors	16.7 million
Resolution	SXGA, 1280 x 1024 pixels
Contrast	2000:1
Viewing angles Horizontal	Direction R / Direction L = 89°
Vertical	Direction U / Direction D = 89°
Backlight Classification	LED
Brightness	300 cd/m ²
Half-brightness time ¹⁾	50,000 h
Touch screen ²⁾ Type	AMT
Technologies	Analog, resistive
Controller	B&R, serial, 12-bit
Transmittance	81% ±3%
Mechanical characteristics	
Front Frame	Aluminum paint
Design	Black
Gasket	3 mm built-in seal
Dimensions Width	440 mm
Height	358 mm
Weight	5800 g

Table 55: 5AP923.1906-00 - Technical data

- 1) At an ambient temperature of 25°C. Reducing the brightness by 50% can result in an approximately 50% increase in the half-brightness time.
 2) Touch screen drivers for approved operating systems are available in the Downloads section of the B&R website.

3.1.3.4 Dimensions




Figure 21: 5AP23.1906-00 - Dimensions

3.1.3.5 Temperature humidity diagram




Figure 22: 5AP923.1906-00 - Temperature humidity diagram

3.1.4 5AP933.156B-00

3.1.4.1 General information

- Display unit for AP9x3 or PPC900
- 15.6" TFT HD color display
- Multi-touch (PCT)
- Black aluminum front
- IP65 protection (on front)

3.1.4.2 Order data


Model number	Short description	Figure
Display units		
5AP933.156B-00	Automation Panel 15.6" HD TFT - 1366 x 768 pixels (16:9) - Multi-touch (projected capacitive) - IP65 protection (front)	

Table 56: 5AP933.156B-00 - Order data

3.1.4.3 Technical data

Product ID	5AP933.156B-00
General information	
Certification GOST-R	Yes
Display	
Type	Color TFT
Diagonal	15.6"
Colors	16.7 million
Resolution	HD, 1366 x 768 pixels
Contrast	500:1
Viewing angles Horizontal Vertical	Direction R / Direction L = 85° Direction U / Direction D = 80°
Backlight Classification Brightness Half-brightness time ¹⁾	LED 300 cd/m ² 50,000 h
Touch screen ²⁾ Type Technologies Controller Transmittance	3M Projected capacitive touch (PCT) 3M 88% ±2%
Mechanical characteristics	
Front Frame Design Gasket	Aluminum paint Black 3 mm built-in seal
Dimensions Width Height	414 mm 258.5 mm
Weight	3850 g

Table 57: 5AP933.156B-00 - Technical data

- 1) At an ambient temperature of 25°C. Reducing the brightness by 50% can result in an approximately 50% increase in the half-brightness time.
 2) Touch screen drivers for approved operating systems are available in the Downloads section of the B&R website.

3.1.4.4 Dimensions




Figure 23: 5AP933.156B-00 - Dimensions

3.1.4.5 Temperature humidity diagram




Figure 24: 5AP933.156B-00 - Temperature humidity diagram

3.1.5 5AP933.185B-00

3.1.5.1 General information

- Display unit for AP9x3 or PPC900
- 18.5" TFT HD color display
- Multi-touch (PCT)
- Black aluminum front
- IP65 protection (on front)

3.1.5.2 Order data


Model number	Short description	Figure
Display units		
5AP933.185B-00	Automation Panel 18.5" HD TFT - 1366 x 768 pixels (16:9) - Multi-touch (projected capacitive) - IP65 protection (front)	

Table 58: 5AP933.185B-00 - Order data

3.1.5.3 Technical data

Product ID	5AP933.185B-00
General information	
Certification GOST-R	Yes
Display	
Type	Color TFT
Diagonal	18.5"
Colors	16.7 million
Resolution	HD, 1366 x 768 pixels
Contrast	1000:1
Viewing angles Horizontal Vertical	Direction R / Direction L = 170° Direction U / Direction D = 160°
Backlight Classification Brightness Half-brightness time ¹⁾	LED 300 cd/m ² 50,000 h
Touch screen ²⁾ Type Technologies Controller Transmittance	3M Projected capacitive touch (PCT) 3M 88% ±2%
Mechanical characteristics	
Front Frame Design Gasket	Aluminum paint Black 3 mm built-in seal
Dimensions Width Height	475 mm 295 mm
Weight	4850 g

Table 59: 5AP933.185B-00 - Technical data

- 1) At an ambient temperature of 25°C. Reducing the brightness by 50% can result in an approximately 50% increase in the half-brightness time.
 2) Touch screen drivers for approved operating systems are available in the Downloads section of the B&R website.

3.1.5.4 Dimensions




Figure 25: 5AP933.185B-00 - Dimensions

3.1.5.5 Temperature humidity diagram




Figure 26: 5AP933.185B-00 - Temperature humidity diagram

3.1.6 5AP933.215C-00

3.1.6.1 General information

- Display unit for AP9x3 or PPC900
- 21.5" TFT FHD color display
- Multi-touch (PCT)
- Black aluminum front
- IP65 protection (on front)

3.1.6.2 Order data


Model number	Short description	Figure
Display units		
5AP933.215C-00	Automation Panel 21.5" Full HD TFT - 1920 x 1080 pixels (16:9) - Multi-touch (projected capacitive) - IP65 protection (front)	

Table 60: 5AP933.215C-00 - Order data

3.1.6.3 Technical data

Product ID	5AP933.215C-00
General information	
Certification GOST-R	Yes
Display	
Type	Color TFT
Diagonal	21.46"
Colors	16.7 million
Resolution	FHD, 1920 x 1080 pixels
Contrast	1000:1
Viewing angles Horizontal Vertical	Direction R / Direction L = 178° Direction U / Direction D = 178°
Backlight Classification Brightness Half-brightness time ¹⁾	LED 250 cd/m ² 30,000 h
Touch screen ²⁾ Type Technologies Controller Transmittance	3M Projected capacitive touch (PCT) 3M 88% ±2%
Mechanical characteristics	
Front Frame Design Gasket	Aluminum paint Black 3 mm built-in seal
Dimensions Width Height	541.5 mm 333 mm
Weight	5400 g

Table 61: 5AP933.215C-00 - Technical data

- 1) At an ambient temperature of 25°C. Reducing the brightness by 50% can result in an approximately 50% increase in the half-brightness time.
 2) Touch screen drivers for approved operating systems are available in the Downloads section of the B&R website.

3.1.6.4 Dimensions




Figure 27: 5AP933.215C-00 - Dimensions

3.1.6.5 Temperature humidity diagram




Figure 28: 5AP933.215C-00 - Temperature humidity diagram

3.1.7 5AP933.240C-00

3.1.7.1 General information

- Display unit for AP9x3 or PPC900
- 24" TFT FHD color display
- Multi-touch (PCT)
- Black aluminum front
- IP65 protection (on front)

3.1.7.2 Order data


Model number	Short description	Figure
Display units		
5AP933.240C-00	Automation Panel 24.0" Full HD TFT - 1920 x 1080 pixels (16:9) - Multi-touch (projected capacitive) - IP65 protection (front)	

Table 62: 5AP933.240C-00 - Order data

3.1.7.3 Technical data

Product ID	5AP933.240C-00
Display	
Type	Color TFT
Diagonal	24.0"
Colors	16.7 million
Resolution	FHD, 1920 x 1080 pixels
Contrast	5000:1
Viewing angles Horizontal Vertical	Direction R / Direction L = 89° Direction U / Direction D = 89°
Backlight Classification Brightness Half-brightness time ¹⁾	LED 300 cd/m ² 50,000 h
Touch screen ²⁾ Type Technologies Controller Transmittance	3M Projected capacitive touch (PCT) 3M 88% ±2%
Mechanical characteristics	
Front Frame Design Gasket	Aluminum paint Black 3 mm built-in seal
Dimensions Width Height	598.5 mm 364 mm
Weight	Approx. 7800 g

Table 63: 5AP933.240C-00 - Technical data

1) At an ambient temperature of 25°C. Reducing the brightness by 50% can result in an approximately 50% increase in the half-brightness time.

2) Touch screen drivers for approved operating systems are available in the Downloads section of the B&R website.

3.1.7.4 Dimensions




Figure 29: 5AP933.240C-00 - Dimensions

3.1.7.5 Temperature humidity diagram




Figure 30: 5AP933.240C-00 - Temperature humidity diagram

3.2 QM77 CPU boards

3.2.1 5PC901.TS77-0x

3.2.1.1 General information

- Intel® Core™ i-series processors
- Intel® QM77 chipset
- 2x DDR3 memory socket
- Intel® HD Graphics 4000
- AMI BIOS (UEFI)

Information:

Operating the 5PC901.TS77-00 CPU boards is only possible if the system unit is equipped with a fan kit (active, 5PC911.SX00-00).

3.2.1.2 Order data

Model number	Short description	Figure
	CPU boards	
5PC901.TS77-00	CPU board Intel Core i7 3615QE 2.3 GHz - Quad core - QM77 chipset	
5PC901.TS77-01	CPU board Intel Core i7 3612QE 2.1 GHz - Quad core - QM77 chipset	
5PC901.TS77-02	CPU board Intel Core i7 3555LE 2.5 GHz - Dual core - QM77 chipset	
5PC901.TS77-03	CPU board Intel Core i7 3517UE 1.7 GHz - Dual core - QM77 chipset	
5PC901.TS77-04	CPU board Intel Core i5 3610ME 2.7 GHz - Dual core - QM77 chipset	
5PC901.TS77-05	CPU board Intel Core i3 3120ME 2.4 GHz - Dual core - QM77 chipset	
5PC901.TS77-06	CPU board Intel Core i3 3217UE 1.6 GHz - Dual core - QM77 chipset	
	Required accessories	
	Main memory	
5MMDDR.1024-03	SO-DIMM DDR3, 1024 MB	
5MMDDR.2048-03	SO-DIMM DDR3, 2048 MB	
5MMDDR.4096-03	SO-DIMM DDR3, 4096 MB	
5MMDDR.8192-03	SO-DIMM DDR3, 8192 MB	

Table 64: 5PC901.TS77-00, 5PC901.TS77-01, 5PC901.TS77-02, 5PC901.TS77-03, 5PC901.TS77-04, 5PC901.TS77-05, 5PC901.TS77-06 - Order data

3.2.1.3 Technical data

Product ID	5PC901.TS77-00	5PC901.TS77-01	5PC901.TS77-02	5PC901.TS77-03	5PC901.TS77-04	5PC901.TS77-05	5PC901.TS77-06
General information							
Cooling	Passive via heat sink						
LEDs	Power, HDD, Link, Run						
B&R ID code	\$DF8A	\$DF8B	\$DF8C	\$DF8D	\$DF8E	\$DF8F	\$DF90
Battery							
Type	Renata 950 mAh						
Service life	4 years ¹⁾						
Removable	Yes, on the back side of the Panel PC						
Design	Lithium ion						
Power button	Yes						
Reset button	Yes						
Buzzer	Yes						
Certification							
CE	Yes						
cULus	Yes						
cULus HazLoc Class 1 Division 2	Yes ²⁾						
GOST-R	Yes						
Controller							
Boot loader	BIOS						

Table 65: 5PC901.TS77-00, 5PC901.TS77-01, 5PC901.TS77-02, 5PC901.TS77-03, 5PC901.TS77-04, 5PC901.TS77-05, 5PC901.TS77-06 - Technical data

Product ID	5PC901. TS77-00	5PC901. TS77-01	5PC901. TS77-02	5PC901. TS77-03	5PC901. TS77-04	5PC901. TS77-05	5PC901. TS77-06
Processor							
Type	Intel® Core™ i7 3615QE	Intel® Core™ i7 3612QE	Intel® Core™ i7 3555LE	Intel® Core™ i7 3555LE	Intel® Core™ i5 3610ME	Intel® Core™ i3 3120ME	Intel® Core™ i3 3217UE
Clock frequency	2300 MHz	2100 MHz	2500 MHz	1700 MHz	2700 MHz	2400 MHz	1600 MHz
Number of cores	4	4	2	2	2	2	2
Architectures				22 nm			
Intel® Smart Cache	6 MB	6 MB	4 MB	4 MB	3 MB	3 MB	3 MB
External bus				DMI, 5 GT/s			
Intel® 64 Architecture				Yes			
Intel® Turbo Boost Technology	2.0	2.0	2.0	2.0	2.0	No	No
Intel® Hyper-Threading Technology				Yes			
Intel® Virtualization Technology (VT-x)				Yes			
Enhanced Intel SpeedStep® Technology				Yes			
Chipset				Intel® QM77			
Real-time clock							
Accuracy				At 25°C: typ. 12 ppm (1 seconds) per day ³⁾			
Battery-buffered				Yes			
Power failure logic							
Controller				MTCX ⁴⁾			
Buffer time				10 ms			
Memory socket							
Number of memory channels				2			
Type				DDR3			
Size				Max. 16 GB			
Max. memory bandwidth				25.6 GB/s			
Graphics							
Controller				Intel® HD Graphics 4000			
Max. dynamic graphics frequency				900 MHz			
Color depth				Max. 32-bit			
Resolution					Resolution up to 1920 x 1200 (WUXGA)		
DVI					350 MHz RAMDAC, resolution up to 2048 x 1536 @ 75 Hz (QXGA)		
RGB							
Mass memory management					3x SATA		
Power management					ACPI 4.0 with battery support		
Interfaces							
COM1					RS232, modem-capable, not electrically isolated		
Type					9-pin male DSUB connector		
Design					16550-compatible, 16-byte FIFO		
UART					115 kbit/s		
Max. baud rate							
COM2					RS232, modem-capable, not electrically isolated		
Type					9-pin male DSUB connector		
Design					16550-compatible, 16-byte FIFO		
UART					115 kbit/s		
Max. baud rate							
CFast slot					1		
Quantity					SATA III (SATA 6 Gbit/s)		
Type							
USB							
Quantity					4		
Type					USB 3.0 (on bottom)		
Design					Type A		
Transfer rate					Low speed (1.5 Mbit/s), full speed (12 Mbit/s), high speed (480 Mbit/s), super speed (5 Gbit/s) ⁵⁾		
Current load					Max. 1 A per connection		
Ethernet							
Quantity					2		
Design					Shielded RJ45 port		
Transfer rate					10/100/1000 Mbit/s		
Max. baud rate					1 Gbit/s		
Monitor/Panel interface							
Design					Female DVI-I connector		
Type					SDL/DVI/Monitor		
Audio							
Type					HDA		
Controller					Realtek RTL888		
Inputs					Microphone, Line IN		
Outputs					Line OUT		
Inserts							
Slide-in compact drives					1		
Quantity					SATA III (SATA 6 Gbit/s)		
Type							
Interface option					2		

Table 65: 5PC901.TS77-00, 5PC901.TS77-01, 5PC901.TS77-02, 5PC901.TS77-03, 5PC901.TS77-04, 5PC901.TS77-05, 5PC901.TS77-06 - Technical data

Product ID	5PC901. TS77-00	5PC901. TS77-01	5PC901. TS77-02	5PC901. TS77-03	5PC901. TS77-04	5PC901. TS77-05	5PC901. TS77-06
Add-on UPS slot				Yes ⁶⁾			
Insert for fan kit				Yes			
Electrical characteristics							
Nominal voltage				24 VDC ±25%			
Nominal current				5.5 A			
Starting current				Max. 60 A for <300 µs			
Electrical isolation				Yes			
Environmental conditions							
Altitude Operation				Max. 3000 m (depends on the component) ⁷⁾			
Mechanical characteristics							
Weight				Approx. 450 g			

Table 65: 5PC901.TS77-00, 5PC901.TS77-01, 5PC901.TS77-02, 5PC901.TS77-03,
5PC901.TS77-04, 5PC901.TS77-05, 5PC901.TS77-06 - Technical data

- 1) At 50°C, 8.5 µA of the supplied components and a self-discharge of 40%. If an SRAM interface option has been installed, the service life is 2½ years.
- 2) Yes, although applies only if all components installed within the complete system have this certification
- 3) At max. specified ambient temperature: Typ. 58 ppm (5 seconds) - worst-case 220 ppm (19 seconds).
- 4) Maintenance Controller Extended.
- 5) The super speed transfer rate (5 Gbit/s) is only possible with USB 3.0.
- 6) This UPS module can only be operated in the IF option 1 slot.
- 7) The maximum ambient temperature is typically derated by 1°C per 1000 meters (starting at 500 meters above sea level).

3.3 HM76 CPU boards

3.3.1 5PC901.TS77-0x

3.3.1.1 General information

- Intel® Celeron® processors
- Intel® HM76 chipset
- 2x DDR3 memory socket
- Intel® HD graphics 2000 / 2500
- AMI BIOS (UEFI)

3.3.1.2 Order data

Model number	Short description	Figure
CPU boards		
5PC901.TS77-07	CPU board Intel Celeron 847E 1.1 GHz - Dual core - HM76 chipset	
5PC901.TS77-08	CPU board Intel Celeron 827E 1.4 GHz - Single core - HM76 chipset	
5PC901.TS77-09	CPU board Intel Celeron 1020E 2.2 GHz - Dual core - HM76 chipset	
5PC901.TS77-10	CPU board Intel Celeron 1047UE 1.4 GHz - Dual core - HM76 chipset	
Required accessories		
Main memory		
5MMDDR.1024-03	SO-DIMM DDR3, 1024 MB	
5MMDDR.2048-03	SO-DIMM DDR3, 2048 MB	
5MMDDR.4096-03	SO-DIMM DDR3, 4096 MB	
5MMDDR.8192-03	SO-DIMM DDR3, 8192 MB	

Table 66: 5PC901.TS77-07, 5PC901.TS77-08, 5PC901.TS77-09, 5PC901.TS77-10 - Order data

3.3.1.3 Technical data

Product ID	5PC901.TS77-07	5PC901.TS77-08	5PC901.TS77-09	5PC901.TS77-10
General information				
Cooling		Passive via heat sink		
LEDs		Power, HDD, Link, Run		
B&R ID code	\$DFCD	\$DFCE	\$E18E	\$E1AD
Battery				
Type		Renata 950 mAh		
Service life		4 years ¹⁾		
Removable		Yes, on the back side of the Panel PC		
Design		Lithium ion		
Power button		Yes		
Reset button		Yes		
Buzzer		Yes		
Certification				
CE		Yes		
cULus		Yes		
cULus HazLoc Class 1 Division 2		Yes ²⁾		
GOST-R		Yes		
Controller				
Boot loader		BIOS		
Processor				
Type	Intel® Celeron® 847E	Intel® Celeron® 827E	Intel® Celeron® 1020E	Intel® Celeron® 1047UE
Clock frequency	1100 MHz	1400 MHz	2200 MHz	1400 MHz
Number of cores	2	1	2	2
Architectures	32 nm	32 nm	22 nm	22 nm
Intel® Smart Cache	2 MB	1.5 MB	2 MB	2 MB
External bus		DMI, 5 GT/s		
Intel® 64 Architecture		Yes		
Intel® Turbo Boost Technology		No		
Intel® Hyper-Threading Technology		No		
Intel® Virtualization Technology (VT-x)		Yes		
Enhanced Intel SpeedStep® Technology		Yes		
Chipset		Intel® HM76		

Table 67: 5PC901.TS77-07, 5PC901.TS77-08, 5PC901.TS77-09, 5PC901.TS77-10 - Technical data

Technical data • Individual components

Product ID	5PC901.TS77-07	5PC901.TS77-08	5PC901.TS77-09	5PC901.TS77-10
Real-time clock				
Accuracy	At 25°C: typ. 12 ppm (1 seconds) per day ³⁾			
Battery-buffered	Yes			
Power failure logic				
Controller	MTCX ⁴⁾			
Buffer time	10 ms			
Memory socket				
Number of memory channels	2			
Type	DDR3			
Size	Max. 16 GB			
Max. memory bandwidth	21.3 GB/s	21.3 GB/s	25.6 GB/s	25.6 GB/s
Graphics				
Controller	Intel® HD Graphics 2000	Intel® HD Graphics 2000	Intel® HD Graphics 2500	Intel® HD Graphics 2500
Max. dynamic graphics frequency	800 MHz	800 MHz	1 GHz	900 MHz
Color depth	Max. 32-bit			
Resolution	Resolution up to 1920 x 1200 (WUXGA)			
DVI	350 MHz RAMDAC, resolution up to 2048 x 1536 @ 75 Hz (QXGA)			
RGB				
Mass memory management	3x SATA			
Power management	ACPI 4.0 with battery support			
Interfaces				
COM1				
Type	RS232, modem-capable, not electrically isolated			
Design	9-pin male DSUB connector			
UART	16550-compatible, 16-byte FIFO			
Max. baud rate	115 kbit/s			
COM2				
Type	RS232, modem-capable, not electrically isolated			
Design	9-pin male DSUB connector			
UART	16550-compatible, 16-byte FIFO			
Max. baud rate	115 kbit/s			
CFast slot				
Quantity	1			
Type	SATA III (SATA 6 Gbit/s)			
USB				
Quantity	4			
Type	USB 3.0 (on bottom)			
Design	Type A			
Transfer rate	Low speed (1.5 Mbit/s), full speed (12 Mbit/s), high speed (480 Mbit/s), super speed (5 Gbit/s) ⁵⁾			
Current load	Max. 1 A per connection			
Ethernet				
Quantity	2			
Design	Shielded RJ45 port			
Transfer rate	10/100/1000 Mbit/s			
Max. baud rate	1 Gbit/s			
Monitor/Panel interface				
Design	Female DVI-I connector			
Type	SDL/DVI/Monitor			
Audio				
Type	HDA			
Controller	Realtek RTL888			
Inputs	Microphone, Line IN			
Outputs	Line OUT			
Inserts				
Slide-in compact drives				
Quantity	1			
Type	SATA III (SATA 6 Gbit/s)			
Interface option	2			
Add-on UPS slot	Yes ⁶⁾			
Insert for fan kit	Yes			
Electrical characteristics				
Nominal voltage	24 VDC ±25%			
Nominal current	5.5 A			
Starting current	Max. 60 A for <300 µs			
Electrical isolation	Yes			
Environmental conditions				
Altitude				
Operation	Max. 3000 m (depends on the component) ⁷⁾			
Mechanical characteristics				
Weight	Approx. 450 g			

Table 67: 5PC901.TS77-07, 5PC901.TS77-08, 5PC901.TS77-09, 5PC901.TS77-10 - Technical data

- 1) At 50°C, 8.5 µA of the supplied components and a self-discharge of 40%. If an SRAM interface option has been installed, the service life is 2½ years.
- 2) Yes, although applies only if all components installed within the complete system have this certification
- 3) At max. specified ambient temperature: Typ. 58 ppm (5 seconds) - worst-case 220 ppm (19 seconds).
- 4) Maintenance Controller Extended.

- 5) The super speed transfer rate (5 Gbit/s) is only possible with USB 3.0.
- 6) This UPS module can only be operated in the IF option 1 slot.
- 7) The maximum ambient temperature is typically derated by 1°C per 1000 meters (starting at 500 meters above sea level).

3.4 System units

3.4.1 5PC911.SX00-00

3.4.1.1 General information

The active Panel PC 900 system unit consists of a housing and heat sink. A fan kit is also required for operation. A CPU board, main memory, IF options, fan kit and slide-in compact drive are installed in the system unit.

The 5AC902.FA00-00 fan kit is not included in the delivery of the system unit and must be ordered separately.

3.4.1.2 Order data

Model number	Short description	Figure
	System units	
5PC911.SX00-00	PPC900 active system unit	
	Required accessories	
	CPU boards	
5PC901.TS77-00	CPU board Intel Core i7 3615QE 2.3 GHz - Quad core - QM77 chipset	
5PC901.TS77-01	CPU board Intel Core i7 3612QE 2.1 GHz - Quad core - QM77 chipset	
5PC901.TS77-02	CPU board Intel Core i7 3555LE 2.5 GHZ - Dual core - QM77 chipset	
5PC901.TS77-03	CPU board Intel Core i7 3517UE 1.7 GHz - Dual core - QM77 chipset	
5PC901.TS77-04	CPU board Intel Core i5 3610ME 2.7 GHz - Dual core - QM77 chipset	
5PC901.TS77-05	CPU board Intel Core i3 3120ME 2.4 GHz - Dual core - QM77 chipset	
5PC901.TS77-06	CPU board Intel Core i3 3217UE 1.6 GHz - Dual core - QM77 chipset	
5PC901.TS77-07	CPU board Intel Celeron 847E 1.1 GHz - Dual core - HM76 chipset	
5PC901.TS77-08	CPU board Intel Celeron 827E 1.4 GHz - Single core - HM76 chipset	
5PC901.TS77-09	CPU board Intel Celeron 1020E 2.2 GHz - Dual core - HM76 chipset	
5PC901.TS77-10	CPU board Intel Celeron 1047UE 1.4 GHz - Dual core - HM76 chipset	
	Fan kits	
5AC902.FA00-00	PPC900 fan kit - For 5PC911.SX00-00	

Table 68: 5PC911.SX00-00 - Order data

3.4.1.3 Technical data

Product ID	5PC911.SX00-00
General information	
Cooling	Active via fan kit Passive via heat sink
Certification	
cULus	Yes
GOST-R	Yes
Mechanical characteristics	
Housing	
Material	Aluminum, Light metal die casting
Paint	Anthracite
Dimensions	
Width	225 mm
Height	226 mm
Depth	54 mm
Weight	Approx. 3020 g

Table 69: 5PC911.SX00-00 - Technical data

3.4.2 5PC911.SX00-01

3.4.2.1 General information

The passive Panel PC 900 system unit consists of a housing and heat sink. A CPU board, main memory, IF options and slide-in compact drive are installed in the system unit.

3.4.2.2 Order data

Model number	Short description	Figure
System units		
5PC911.SX00-01	PPC900 passive system unit	
Required accessories		
CPU boards		
5PC901.TS77-01	CPU board Intel Core i7 3612QE 2.1 GHz - Quad core - QM77 chipset	
5PC901.TS77-02	CPU board Intel Core i7 3555LE 2.5 GHz - Dual core - QM77 chipset	
5PC901.TS77-03	CPU board Intel Core i7 3517UE 1.7 GHz - Dual core - QM77 chipset	
5PC901.TS77-04	CPU board Intel Core i5 3610ME 2.7 GHz - Dual core - QM77 chipset	
5PC901.TS77-05	CPU board Intel Core i3 3120ME 2.4 GHz - Dual core - QM77 chipset	
5PC901.TS77-06	CPU board Intel Core i3 3217UE 1.6 GHz - Dual core - QM77 chipset	
5PC901.TS77-07	CPU board Intel Celeron 847E 1.1 GHz - Dual core - HM76 chipset	
5PC901.TS77-08	CPU board Intel Celeron 827E 1.4 GHz - Single core - HM76 chipset	
5PC901.TS77-09	CPU board Intel Celeron 1020E 2.2 GHz - Dual core - HM76 chipset	
5PC901.TS77-10	CPU board Intel Celeron 1047UE 1.4 GHz - Dual core - HM76 chipset	

Table 70: 5PC911.SX00-01 - Order data

3.4.2.3 Technical data

Product ID	5PC911.SX00-01
General information	
Cooling	Passive via heat sink
Certification	
cULus	Yes
GOST-R	Yes
Mechanical characteristics	
Housing	
Material	Aluminum, Light metal die casting
Paint	Anthracite
Dimensions	
Width	225 mm
Height	226 mm
Depth	54 mm
Weight	Approx. 3020 g

Table 71: 5PC911.SX00-01 - Technical data

3.5 Main memory

3.5.1 5MMDDR.xxxx-03

3.5.1.1 General information

These 204-pin DDR3 main memory modules operate at 1600 MHz and range in size from 1 GB to 8 GB.

If two RAM modules with the same size (e.g. 2 GB) are inserted into the CPU board, then dual-channel memory technology is supported. This technology is not supported if two RAM modules of different sizes (e.g. 2 GB and 4 GB) are inserted.

If two 2 GB modules or one 4 GB module is installed on a 32-bit operating system, only 3 GB of main memory can be used. On a 64-bit operating system, up to 16 GB of main memory can be used.

3.5.1.2 Order data

Model number	Short description	Figure
	<u>Main memory</u>	
5MMDDR.1024-03	SO-DIMM DDR3, 1024 MB	
5MMDDR.2048-03	SO-DIMM DDR3, 2048 MB	
5MMDDR.4096-03	SO-DIMM DDR3, 4096 MB	
5MMDDR.8192-03	SO-DIMM DDR3, 8192 MB	

Table 72: 5MMDDR.1024-03, 5MMDDR.2048-03, 5MMDDR.4096-03, 5MMDDR.8192-03 - Order data

3.5.1.3 Technical data

Product ID	5MMDDR.1024-03	5MMDDR.2048-03	5MMDDR.4096-03	5MMDDR.8192-03
General information				
Type	SO-DIMM DDR3 SDRAM			
Memory size	1 GB	2 GB	4 GB	8 GB
Construction			204-pin	
Organization	128M x 64-bit	256M x 64-bit	512M x 64-bit	1024M x 64 bits
Velocity	DDR3-1600 (PC3-12800)			
Certification				
CE	Yes			
cULus	Yes			
cULus HazLoc Class 1 Division 2	Yes ¹⁾			
GOST-R	Yes			
GL	Yes ¹⁾			

Table 73: 5MMDDR.1024-03, 5MMDDR.2048-03, 5MMDDR.4096-03, 5MMDDR.8192-03 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

3.6 Bus units

Information:

For information about installing or replacing a bus unit, please refer to the section "Installing the bus unit" on page 141.

When installing or replacing a bus unit, it is also necessary to load the BIOS Setup defaults (see "Save & Exit" on page 216).

3.6.1 5AC902.BX0x-xx

3.6.1.1 General information

Bus units consist of a housing and bus. They can be expanded on the Panel PC 900 system unit.

Variants with PCI and PCIe slots are available, and every bus unit has a slide-in drive slot and fan kit.

The fan kit is not included in the delivery of the bus unit and must be ordered separately. If an active system unit (5PC911.SX00-00) is being used, then a fan kit must be configured in the bus unit.

1-slot bus units




Figure 31: 1-slot bus units

2-slot bus units




Figure 32: 2-slot bus units

3.6.1.2 Order data

Model number	Short description	Figure
	Bus units	
5AC902.BX01-00	PPC900 bus unit, 1-slot - 1 PCI - 1 slide-in	
5AC902.BX01-01	PPC900 bus unit, 1-slot - 1 PCI Express x8 - 1 slide-in	
5AC902.BX02-00	PPC900 bus unit, 2-slot - 2 PCI - 1 slide-in	
5AC902.BX02-01	PPC900 2-slot bus unit - 1 PCI - 1 PCI Express x8 - 1 slide-in	
	Optional accessories	
	Fan kits	
5AC902.FA0X-00	PPC900 fan kit - For PPC900 bus unit	

Table 74: 5AC902.BX01-00, 5AC902.BX01-01, 5AC902.BX02-00, 5AC902.BX02-01 - Order data

3.6.1.3 Technical data

Product ID	5AC902.BX01-00	5AC902.BX01-01	5AC902.BX02-00	5AC902.BX02-01
General information				
Certification				
CE			Yes	
cULus			Yes	
cULus HazLoc Class 1 Division 2			Yes ¹⁾	
GOST-R			Yes	
Inserts				
PCI slots				
Quantity	1	-	2	1
Type	32-bit	-	32-bit	32-bit
Design	PCI half-size	-	PCI half-size	PCI half-size
Standard	2.2	-	2.2	2.2
Bus speed	33 MHz	-	33 MHz	33 MHz
PCIe to PCI bridge	Yes	-	Yes	Yes
PCIe slots				
Quantity	-	1	-	1
Design	-	PCIe half-size	-	PCIe half-size
Standard	-	1.0 a	-	1.0 a
Bus speed	-	x8 (2 GB/s)	-	x8 (2 GB/s)
Slide-in drives			1	
Mechanical characteristics				
Dimensions				
Width			164 mm	
Height			218 mm	
Depth	54.7 mm	54.7 mm	75 mm	75 mm
Weight	Approx. 1020 g	Approx. 1020 g	Approx. 1220 g	Approx. 1220 g

Table 75: 5AC902.BX01-00, 5AC902.BX01-01, 5AC902.BX02-00, 5AC902.BX02-01 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

Information:

By default, PCIe slots are limited to Gen1 in BIOS. However, this PCIe Gen setting can be changed in BIOS (Advanced - PCI Express configuration - PCI Express GEN 2 settings).

3.7 Fan kit

Information:

Fan kits are subject to wear and must be checked with appropriate frequency and cleaned or replaced when not functioning properly (e.g. due to dirt and grime). For information about replacing fan filters, please refer to the section "Replacing the fan filter" on page 140.

Information:

For information about installing or replacing a fan kit, please refer to the section "Replacing the fan kit" on page 139.

3.7.1 5AC902.FA00-00

3.7.1.1 General information

This fan kit includes 2 fans that are installed in order to improve heat dissipation on the active 5PC911.SX00-00 PPC900 system unit.

- 2 fans for improved heat dissipation on the system unit
- Simple mounting and removal

The 5AC902.FA00-00 fan kit is not included in the delivery of the system unit and must be ordered separately.

3.7.1.2 Order data

Model number	Short description	Figure
	Fan kits	
5AC902.FA00-00	PPC900 fan kit - For 5PC911.SX00-00	
	Optional accessories	
5AC902.FI00-00		

Table 76: 5AC902.FA00-00 - Order data

3.7.1.3 Technical data

Product ID	5AC902.FA00-00
General information	
Number of fans	2
Speed	Max. 9500 ±10% rpm
Noise level	40.2 dB(A) ¹⁾
Service life	70,000 hours at 40°C
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ²⁾
GOST-R	Yes
Mechanical characteristics	
Weight	Approx. 70 g

Table 77: 5AC902.FA00-00 - Technical data

1) At maximum fan speed

2) Yes, although applies only if all components installed within the complete system have this certification

3.7.2 5AC902.FA0X-00

3.7.2.1 General information

This fan kit includes a fan that is installed in order to improve heat dissipation on a PPC900 bus unit.

- 1 fan for improved heat dissipation on the bus unit
- Simple mounting and removal

The fan kit is not included in the delivery of the bus unit and must be ordered separately. If an active system unit (5PC911.SX00-00) is being used, then a fan kit must be configured in the bus unit.

3.7.2.2 Order data

Model number	Short description	Figure
5AC902.FA0X-00	Fan kits PPC900 fan kit - For PPC900 bus unit	Image not found for 5AC902.FA0X-00!
5AC902.FI0X-00	Optional accessories	

Table 78: 5AC902.FA0X-00 - Order data

3.7.2.3 Technical data

Product ID	5AC902.FA0X-00
General information	
Number of fans	1
Speed	Max. 9500 ±10% rpm
Noise level	40.2 dB(A) ¹⁾
Service life	70,000 hours at 40°C
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ²⁾
GOST-R	Yes
Mechanical characteristics	
Weight	Approx. 36 g

Table 79: 5AC902.FA0X-00 - Technical data

1) At maximum fan speed

2) Yes, although applies only if all components installed within the complete system have this certification

3.8 Drives

3.8.1 5AC901.CHDD-01

3.8.1.1 General information

This 500 GB slide-in compact hard disk is specified for 24-hour operation and can be used in APC910 and PPC900 system units.

- 500 GB hard disk
- Slide-in compact
- Specified for 24-hour operation
- S.M.A.R.T. support

3.8.1.2 Order data

Model number	Short description	Figure
5AC901.CHDD-01	Drives 500 GB SATA hard disk, slide-in compact, 24/7 operation Note: please see the manual for information about using this hard disk	
	Optional accessories	
	Drives	
5MMHDD.0500-00	500 GB SATA hard disk; replacement for 5AC801.HDDI-04, 5AC901.CHDD-01 and 5ACPCI.RAIC-06; note: please see the manual for information about using this hard disk	

Table 80: 5AC901.CHDD-01 - Order data

3.8.1.3 Technical data

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.CHDD-01
General information	
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Hard disk drive	
Capacity	500 GB
Number of heads	2
Number of sectors	976,773,168
Bytes per sector	512 (logical) / 4096 (physical)
Cache	16 MB
Speed	5400 rpm ±0.2%
Startup time	Typ. 3.5 s (from 0 rpm to read access)
Service life	5 years
MTBF	1,000,000 POH ²⁾
S.M.A.R.T. support	Yes
Interface	SATA
Access time	5.5 ms
Supported transfer modes	SATA II
Data transfer rate	
Internal	Max. 147 MB/s
To/From host	Max. 150 MB/s (SATA I), max. 300 MB/s (SATA II)
Positioning time	
Nominal (read only)	11 ms
Maximum (read only)	21 ms
Environmental conditions	
Temperature ³⁾	
Operation ⁴⁾	0 to 60°C
24-hour operation ⁵⁾	0 to 60°C
Storage	-40 to 70°C
Transport	-40 to 70°C

Table 81: 5AC901.CHDD-01 - Technical data

Product ID	5AC901.CHDD-01
Relative humidity ⁶⁾	
Operation	5 to 95%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Vibration	
Operation (continuous)	5 to 500 Hz: 0.25 g; no unrecoverable errors
Operation (occasional)	5 to 500 Hz: 0.5 g; no unrecoverable errors
Storage	10 to 500 Hz: 5 g; no unrecoverable errors
Transport	10 to 500 Hz: 5 g; no unrecoverable errors
Shock	
Operation	400 g and 2 ms duration; no unrecoverable errors
Storage	1000 g and 2 ms duration; no unrecoverable errors
Transport	1000 g and 2 ms duration; no unrecoverable errors
Altitude	
Operation	-305 to 3048 m
Storage	-305 to 12192 m
Mechanical characteristics	
Installation	Fixed ⁷⁾
Dimensions	
Width	10 mm
Height	75 mm
Depth	105 mm
Weight	134 g
Manufacturer information	
Manufacturer	Western Digital
Manufacturer product ID	WD5000LUCT

Table 81: 5AC901.CHDD-01 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) With 8760 POH (power-on hours) per year and 25°C surface temperature.
- 3) Temperature values at an elevation of 305 meters. The temperature specification must be reduced linearly by 1°C every 305 meters. The temperature increase and decrease can be a maximum of 20°C per hour.
- 4) Standard operation refers to 333 POH (power-on hours) per month.
- 5) 24-hour operation refers to 732 POH (power-on hours) per month.
- 6) Humidity gradient: Maximum 20% per hour.
- 7) Slide-in compact installation.

3.8.1.4 Temperature humidity diagram




Figure 33: 5AC901.CHDD-01 - Temperature humidity diagram

3.8.2 5AC901.CSSD-03

3.8.2.1 General information

This 60 GB slide-in compact SSD (solid-state drive) is based on MLC (multi-level cell) technology, SATA 3.0 compatible and The slide-in compact drive can be used in APC910 and PPC900 system units.

- 60 GB solid-state drive
- MLC flash
- S.M.A.R.T. support
- Slide-in compact
- SATA 3.0 compatible

3.8.2.2 Order data

Model number	Short description	Figure
5AC901.CSSD-03	Drives 60 GB SATA slide-in compact SSD (MLC)	
	Optional accessories Drives	
5MMSSD.0060-01	60 GB SATA SSD (MLC); replacement for 5AC801.SSDI-03 and 5AC901.CSSD-03; SSD for 5PP5IO.GMAC-00; note: please see the manual for information about using this SSD	

Table 82: 5AC901.CSSD-03 - Order data

3.8.2.3 Technical data

Caution!

A sudden loss of power may result in data loss! In very rare cases, the mass storage device may also become damaged.

To prevent damage and loss of data, the use of a UPS device is recommended.

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.CSSD-03
General information	
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Solid state drive	
Capacity	60 GB
Data reliability	< 1 unrecoverable error in 10 ¹⁵ bit read accesses
MTBF	1,500,000 hours
S.M.A.R.T. support	Yes
Interface	SATA
Maintenance	None
Continuous reading	Max. 510 MB/s
Continuous writing	Max. 430 MB/s
IOPS ²⁾	
4k read	Max. 60,000 (random)
4k write	Max. 25,000 (random)
Endurance	
Guaranteed data volume	
Guaranteed	35 TBW ³⁾
MLC flash	Yes
Compatibility	SATA 3.0 compliant ACS-2 SSD Enhanced SMART ATA feature set Native Command Queuing (NCQ)

Table 83: 5AC901.CSSD-03 - Technical data

Product ID	5AC901.CSSD-03
Environmental conditions	
Temperature	
Operation	0 to 70°C
Storage	-40 to 95°C
Transport	-40 to 95°C
Relative humidity	
Operation	8 to 95%, non-condensing
Storage	8 to 95%, non-condensing
Transport	8 to 95%, non-condensing
Vibration	
Operation	10 to 2000 Hz: 20 g
Storage	10 to 2000 Hz: 20 g
Transport	10 to 2000 Hz: 20 g
Shock	
Operation	1500 g, 0.5 ms
Storage	1500 g, 0.5 ms
Transport	1500 g, 0.5 ms
Altitude	
Operation	-300 to 12192 m
Storage	-300 to 12192 m
Transport	-300 to 12192 m
Mechanical characteristics	
Installation	Fixed ⁴⁾
Dimensions	
Width	13 mm
Height	98 mm
Depth	105 mm
Weight	118 g
Manufacturer information	
Manufacturer	Toshiba
Manufacturer product ID	THNSNH060GBST

Table 83: 5AC901.CSSD-03 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) IOPS: Random read and write input/output operations per second.
- 3) TBW: Terabyte written
- 4) Slide-in compact installation.

3.8.2.4 Temperature humidity diagram




Figure 34: 5AC901.CSSD-03 - Temperature humidity diagram

3.8.3 5AC901.CSSD-04

3.8.3.1 General information

This 128 GB slide-in compact SSD (solid-state drive) is based on MLC (multi-level cell) technology, SATA 3.0 compatible and The slide-in compact drive can be used in APC910 and PPC900 system units.

- 128 GB solid-state drive
- MLC flash
- S.M.A.R.T. support
- Slide-in compact
- SATA 3.0 compatible

3.8.3.2 Order data

Model number	Short description	Figure
	Drives	
5AC901.CSSD-04	128 GB SATA SSD (MLC), slide-in compact	
	Optional accessories	
	Drives	
5MMSSD.0128-01	128 GB SATA SSD (MLC); replacement for 5AC801.SSDI-04 and 5AC901.CSSD-04; SSD for 5PP5IO.GMAC-00; note: please see the manual for information about using this SSD	

Table 84: 5AC901.CSSD-04 - Order data

3.8.3.3 Technical data

Caution!

A sudden loss of power may result in data loss! In very rare cases, the mass storage device may also become damaged.

To prevent damage and loss of data, the use of a UPS device is recommended.

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.CSSD-04		
Revision	C0	D0	E0
General information			
Certification			
CE		Yes	
cULus		Yes	
cULus HazLoc Class 1 Division 2		Yes ¹⁾	
GOST-R		Yes	
Solid state drive			
Capacity	128 GB		
Data reliability	< 1 unrecoverable error in 10 ¹⁵ bit read accesses		
MTBF	1,500,000 hours		
S.M.A.R.T. support	Yes		
Interface	SATA		
Maintenance	None		
Continuous reading	Max. 510 MB/s		
Continuous writing	Max. 450 MB/s		
IOPS ²⁾	Max. 80,000 (random) Max. 85,000 (random) Max. 35,000 (random)		
Endurance			
Guaranteed data volume			
Guaranteed	74 TBW ³⁾		
MLC flash	Yes		

Table 85: 5AC901.CSSD-04, 5AC901.CSSD-04, 5AC901.CSSD-04 - Technical data

Product ID	5AC901.CSSD-04		
Compatibility	SATA 3.0 compliant ACS-2 SSD Enhanced SMART ATA feature set Native Command Queuing (NCQ)		
Environmental conditions			
Temperature	0 to 70°C	-30 to 85°C	
Operation		-40 to 95°C	
Storage		-40 to 95°C	
Transport			
Relative humidity		8 to 95%, non-condensing	
Operation		8 to 95%, non-condensing	
Storage		8 to 95%, non-condensing	
Transport			
Vibration		10 to 2000 Hz: 20 g	
Operation		10 to 2000 Hz: 20 g	
Storage		10 to 2000 Hz: 20 g	
Transport			
Shock		1500 g, 0.5 ms	
Operation		1500 g, 0.5 ms	
Storage		1500 g, 0.5 ms	
Transport			
Altitude		-300 to 12192 m	
Operation		-300 to 12192 m	
Storage		-300 to 12192 m	
Transport			
Mechanical characteristics			
Installation	Fixed ⁴⁾		
Dimensions			
Width	13 mm		
Height	98 mm		
Depth	105 mm		
Weight	118 g		
Manufacturer information			
Manufacturer	Toshiba		
Manufacturer product ID	THNSNH128GBST	THNSNJ128WBST	THNSNJ128WCST

Table 85: 5AC901.CSSD-04, 5AC901.CSSD-04, 5AC901.CSSD-04 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) IOPS: Random read and write input/output operations per second.
- 3) TBW: Terabyte written
- 4) Slide-in compact installation.

3.8.3.4 Temperature humidity diagram





Figure 35: 5AC901.CSSD-04 Rev. ≤ C0 - Temperature humidity diagram

Figure 36: 5AC901.CSSD-04 Rev. \geq D0 - Temperature humidity diagram

3.8.4 5AC901.CSSD-05

3.8.4.1 General information

This 256 GB slide-in compact SSD (solid-state drive) is based on MLC (multi-level cell) technology and is SATA 3.0 compatible. The slide-in compact drive can be used in APC910 and PPC900 system units.

- 256 GB solid state drive
- MLC flash
- S.M.A.R.T. support
- Slide-in compact
- SATA 3.0 compatible

3.8.4.2 Order data

Model number	Short description	Figure
5AC901.CSSD-05	Drives 256 GB SSD MLC - Slide-in compact - Toshiba - SATA	
	Optional accessories Drives 256 GB SSD MLC - Slide-in compact - Toshiba - SATA	
5MMSSD.0256-00		

Table 86: 5AC901.CSSD-05 - Order data

3.8.4.3 Technical data

Caution!

A sudden loss of power may result in data loss! In very rare cases, the mass storage device may also become damaged.

To prevent damage and loss of data, the use of a UPS device is recommended.

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.CSSD-05
General information	
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Solid state drive	
Capacity	256 GB
Data reliability	< 1 unrecoverable error in 10 ¹⁵ bit read accesses
MTBF	1,500,000 hours
S.M.A.R.T. support	Yes
Interface	SATA
Maintenance	None
Continuous reading	Max. 510 MB/s
Continuous writing	Max. 460 MB/s
IOPS ²⁾	
4k read	Max. 90,000 (random)
4k write	Max. 35,000 (random)
Endurance	
Guaranteed data volume	
Guaranteed	148 TBW ³⁾
MLC flash	Yes
Compatibility	SATA 3.0 compliant ACS-2 SSD Enhanced SMART ATA feature set Native Command Queuing (NCQ)

Table 87: 5AC901.CSSD-05 - Technical data

Product ID	5AC901.CSSD-05
Environmental conditions	
Temperature	
Operation	-30 to 85°C
Storage	-40 to 95°C
Transport	-40 to 95°C
Relative humidity	
Operation	8 to 95%, non-condensing
Storage	8 to 95%, non-condensing
Transport	8 to 95%, non-condensing
Vibration	
Operation	10 to 2000 Hz: 20 g
Storage	10 to 2000 Hz: 20 g
Transport	10 to 2000 Hz: 20 g
Shock	
Operation	1500 g, 0.5 ms
Storage	1500 g, 0.5 ms
Transport	1500 g, 0.5 ms
Altitude	
Operation	-300 to 12192 m
Storage	-300 to 12192 m
Transport	-300 to 12192 m
Mechanical characteristics	
Installation	Fixed ⁴⁾
Dimensions	
Width	13 mm
Height	98 mm
Depth	105 mm
Weight	118 g
Manufacturer information	
Manufacturer	Toshiba
Manufacturer product ID	THNSNJ256WCST

Table 87: 5AC901.CSSD-05 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) IOPS: Random read and write input/output operations per second.
- 3) TBW: Terabyte written
- 4) Slide-in compact installation.

3.8.4.4 Temperature humidity diagram




Figure 37: 5AC901.CSSD-05 - Temperature humidity diagram

3.8.5 5MMSSD.0060-01

3.8.5.1 General information

This 60 GB slide-in compact SSD (solid-state drive) is based on multi-level cell (MLC) technology and can be used as a replacement or accessory part.

- Replacement for 5AC801.SSDI-03 or 5AC901.CSSD-03 SSD drives
- Accessory for the APC510 (optional SSD for I/O board)

3.8.5.2 Order data

Model number	Short description	Figure
Drives		
5MMSSD.0060-01	60 GB SATA SSD (MLC); replacement for 5AC801.SSDI-03 and 5AC901.CSSD-03; SSD for 5PP5IO.GMAC-00; note: please see the manual for information about using this SSD	

Table 88: 5MMSSD.0060-01 - Order data

3.8.5.3 Technical data

Caution!

A sudden loss of power may result in data loss! In very rare cases, the mass storage device may also become damaged.

To prevent damage and loss of data, the use of a UPS device is recommended.

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5MMSSD.0060-01
General information	
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Solid state drive	
Capacity	60 GB
Data reliability	< 1 unrecoverable error in 10 ¹⁵ bit read accesses
MTBF	1,500,000 hours
S.M.A.R.T. support	Yes
Interface	SATA
Maintenance	None
Continuous reading	Max. 510 MB/s
Continuous writing	Max. 430 MB/s
IOPS ²⁾	
4k read	Max. 60,000 (random)
4k write	Max. 25,000 (random)
Endurance	
Guaranteed data volume	
Guaranteed	35 TBW ³⁾
MLC flash	Yes
Compatibility	SATA 3.0 compliant ACS-2 SSD Enhanced SMART ATA feature set Native Command Queuing (NCQ)
Environmental conditions	
Temperature	
Operation	0 to 70°C
Storage	-40 to 95°C
Transport	-40 to 95°C

Table 89: 5MMSSD.0060-01 - Technical data

Product ID	5MMSSD.0060-01
Relative humidity	
Operation	8 to 95%, non-condensing
Storage	8 to 95%, non-condensing
Transport	8 to 95%, non-condensing
Vibration	
Operation	10 to 2000 Hz: 20 g
Storage	10 to 2000 Hz: 20 g
Transport	10 to 2000 Hz: 20 g
Shock	
Operation	1500 g, 0.5 ms
Storage	1500 g, 0.5 ms
Transport	1500 g, 0.5 ms
Altitude	
Operation	-300 to 12192 m
Storage	-300 to 12192 m
Transport	-300 to 12192 m
Mechanical characteristics	
Dimensions	
Width	9.5 mm
Height	69 mm
Depth	100 mm
Weight	78 g
Manufacturer information	
Manufacturer	Toshiba
Manufacturer product ID	THNSNH060GBST

Table 89: 5MMSSD.0060-01 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
 2) IOPS: Random read and write input/output operations per second.
 3) TBW: Terabyte written

3.8.5.4 Temperature humidity diagram




Figure 38: 5MMSSD.0060-01 - Temperature humidity diagram

3.8.6 5MMSSD.0128-01

3.8.6.1 General information

This 128 GB slide-in compact SSD (solid-state drive) is based on multi-level cell (MLC) technology and can be used as a replacement or accessory part.

- Replacement for 5AC801.SSDI-04 or 5AC901.CSSD-04 SSD drives
- Accessory for the APC510 (optional SSD for I/O board)

3.8.6.2 Order data

Model number	Short description	Figure
5MMSSD.0128-01	128 GB SATA SSD (MLC); replacement for 5AC801.SSDI-04 and 5AC901.CSSD-04; SSD for 5PP5IO.GMAC-00; note: please see the manual for information about using this SSD	

Table 90: 5MMSSD.0128-01 - Order data

3.8.6.3 Technical data

Caution!

A sudden loss of power may result in data loss! In very rare cases, the mass storage device may also become damaged.

To prevent damage and loss of data, the use of a UPS device is recommended.

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5MMSSD.0128-01	
Revision	C0	D0
General information		
Certification		
CE	Yes	
cULus	Yes	
cULus HazLoc Class 1 Division 2	Yes ¹⁾	
GOST-R	Yes	
Solid state drive		
Capacity	128 GB	
Data reliability	< 1 unrecoverable error in 10 ¹⁵ bit read accesses	
MTBF	1,500,000 hours	
S.M.A.R.T. support	Yes	
Interface	SATA	
Maintenance	None	
Continuous reading	Max. 510 MB/s	
Continuous writing	Max. 450 MB/s	
IOPS ²⁾		
4k read	Max. 80,000 (random)	Max. 85,000 (random)
4k write	Max. 35,000 (random)	
Endurance		
Guaranteed data volume		
Guaranteed	74 TBW ³⁾	
MLC flash	Yes	
Compatibility	SATA 3.0 compliant ACS-2 SSD Enhanced SMART ATA feature set Native Command Queuing (NCQ)	

Table 91: 5MMSSD.0128-01, 5MMSSD.0128-01 - Technical data

Product ID	5MMSSD.0128-01		
Environmental conditions			
Temperature			
Operation	0 to 70°C		-30 to 85°C
Storage		-40 to 95°C	
Transport		-40 to 95°C	
Relative humidity			
Operation	8 to 95%, non-condensing		
Storage	8 to 95%, non-condensing		
Transport	8 to 95%, non-condensing		
Vibration			
Operation	10 to 2000 Hz: 20 g		
Storage	10 to 2000 Hz: 20 g		
Transport	10 to 2000 Hz: 20 g		
Shock			
Operation	1500 g, 0.5 ms		
Storage	1500 g, 0.5 ms		
Transport	1500 g, 0.5 ms		
Altitude			
Operation	-300 to 12192 m		
Storage	-300 to 12192 m		
Transport	-300 to 12192 m		
Mechanical characteristics			
Dimensions			
Width	9.5 mm		7 mm
Height		69 mm	
Depth		100 mm	
Weight	78 g		
Manufacturer information			
Manufacturer	Toshiba		
Manufacturer product ID	THNSNH128GBST		THNSNJ128WCST

Table 91: 5MMSSD.0128-01, 5MMSSD.0128-01 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) IOPS: Random read and write input/output operations per second.
- 3) TBW: Terabyte written

3.8.6.4 Temperature humidity diagram




Figure 39: 5MMSSD.0128-01 - Temperature humidity diagram Rev. ≤ C0




Figure 40: 5MMSSD.0128-01 - Temperature humidity diagram Rev. ≥ D0

3.8.7 5MMSSD.0256-00

3.8.7.1 General information

This 256 GB slide-in compact SSD (solid-state drive) is based on multi-level cell (MLC) technology and can be used as a replacement or accessory part.

- Replacement for 5AC801.SSDI-05 or 5AC901.CSSD-05 SSD drives
- Accessory for the APC510 (optional SSD for I/O board)

3.8.7.2 Order data

Model number	Short description	Figure
Drives		
5MMSSD.0256-00	256 GB SSD MLC - Slide-in compact - Toshiba - SATA	

Table 92: 5MMSSD.0256-00 - Order data

3.8.7.3 Technical data

Caution!

A sudden loss of power may result in data loss! In very rare cases, the mass storage device may also become damaged.

To prevent damage and loss of data, the use of a UPS device is recommended.

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5MMSSD.0256-00
General information	
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
Solid state drive	
Capacity	256 GB
Data reliability	< 1 unrecoverable error in 10 ¹⁵ bit read accesses
MTBF	1,500,000 hours
S.M.A.R.T. support	Yes
Interface	SATA
Maintenance	None
Continuous reading	Max. 510 MB/s
Continuous writing	Max. 460 MB/s
IOPS ²⁾	
4k read	Max. 90,000 (random)
4k write	Max. 35,000 (random)
Endurance	
Guaranteed data volume	
Guaranteed	148 TBW ³⁾
MLC flash	Yes
Compatibility	SATA 3.0 compliant ACS-2 SSD Enhanced SMART ATA feature set Native Command Queuing (NCQ)

Table 93: 5MMSSD.0256-00 - Technical data

Product ID	5MMSSD.0256-00
Environmental conditions	
Temperature	
Operation	-30 to 85°C
Storage	-40 to 95°C
Transport	-40 to 95°C
Relative humidity	
Operation	8 to 95%, non-condensing
Storage	8 to 95%, non-condensing
Transport	8 to 95%, non-condensing
Vibration	
Operation	10 to 2000 Hz: 20 g
Storage	10 to 2000 Hz: 20 g
Transport	10 to 2000 Hz: 20 g
Shock	
Operation	1500 g, 0.5 ms
Storage	1500 g, 0.5 ms
Transport	1500 g, 0.5 ms
Altitude	
Operation	-300 to 12192 m
Storage	-300 to 12192 m
Transport	-300 to 12192 m
Mechanical characteristics	
Dimensions	
Width	7 mm
Height	69 mm
Depth	100 mm
Weight	78 g
Manufacturer information	
Manufacturer	Toshiba
Manufacturer product ID	THNSNJ256WCST

Table 93: 5MMSSD.0256-00 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) IOPS: Random read and write input/output operations per second.
- 3) TBW: Terabyte written

3.8.7.4 Temperature humidity diagram




Figure 41: 5MMSSD.0256-00 - Temperature humidity diagram

3.8.8 5AC901.CCFA-00

3.8.8.1 General information

This CFast adapter is a slide-in compact adapter that allows a CFast card to be inserted and operated on a B&R Industrial PC. The CFast adapter can be used in APC910 and PPC900 system units.

- CFast slot
- Slide-in compact

3.8.8.2 Order data

Model number	Short description	Figure
	Drives	
5AC901.CCFA-00	CFast adapter for operating a CFast card in a slide-in compact slot	
	Optional accessories	
	CFast cards	
5CFAST.016G-00	CFast card, 16 GB	
5CFAST.032G-00	CFast card, 32 GB	
5CFAST.2048-00	CFast card, 2 GB	
5CFAST.4096-00	CFast card, 4 GB	
5CFAST.8192-00	CFast card, 8 GB	

Table 94: 5AC901.CCFA-00 - Order data



3.8.8.3 Technical data

Caution!

A sudden loss of power may result in data loss! In very rare cases, the mass storage device may also become damaged.

To prevent damage and loss of data, the use of a UPS device is recommended.

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.CCFA-00
General information	
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
GL	Yes ¹⁾
Interfaces	
CFast slot	
Quantity	1
Environmental conditions	
Temperature	
Operation	Depends on the CFast card being used
Storage	Depends on the CFast card being used
Transport	Depends on the CFast card being used
Relative humidity	
Operation	Depends on the CFast card being used
Storage	Depends on the CFast card being used
Transport	Depends on the CFast card being used

Table 95: 5AC901.CCFA-00 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

3.8.9 5AC901.SDVW-00

3.8.9.1 General information

The DVD-R/RW slide-in drive can be used in APC910 system units and PPC800 bus units with a slide-in drive slot.

- DVD-R/RW, DVD+R/RW drive
- Slide-in

3.8.9.2 Order data

Model number	Short description	Figure
Drives		
5AC901.SDVW-00	DVD-R/RW DVD+R/RW SATA slide-in drive	

Table 96: 5AC901.SDVW-00 - Order data

3.8.9.3 Technical data

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.SDVW-00
General information	
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
CD / DVD drive	
Data buffer capacity	2 MB
Data transfer rate	Max. 33.3 MB/s
Speed	Max. 5160 rpm ±1%
Noise level	Approx. 45 dBA in a distance of 50 cm (full read access)
Compatible formats	CD-DA, CD-ROM mode 1/mode 2 CD-ROM XA mode 2 (form 1, form 2) Photo CD (single-/multi-session), Enhanced CD, CD text DVD-ROM, DVD-R, DVD-R (dual layer), DVD-RW, DVD-Video DVD-RAM (4.7 GB, 2.6 GB) DVD+R, DVD+R (dual layer), DVD+RW
Laser class	Class 1 laser
Service life	60000 POH (power-on hours)
Interface	SATA
Startup time	
CD	Max. 14 seconds (from 0 rpm to read access)
DVD	Max. 15 seconds (from 0 rpm to read access)
Access time	
CD	On average 140 ms (24x)
DVD	On average 150 ms (8x)
Readable media	
CD	CD/CD-ROM (12 cm, 8 cm), CD-R, CD-RW
DVD	DVD-ROM, DVD-R, DVD-R (dual layer), DVD-RW, DVD-RAM, DVD+R, DVD+R (dual layer), DVD+RW, DVD-RAM
Writable media	
CD	CD-R, CD-RW
DVD	DVD-R/RW, DVD-R (dual layer), DVD-RAM (4.7 GB), DVD+R/RW, DVD+R (dual layer)
Read speed	
CD	24x
DVD	8x

Table 97: 5AC901.SDVW-00 - Technical data

Product ID	5AC901.SDVW-00
Write speed	
CD-R	24x, 16x, 10x and 4x
CD-RW	24x, 16x, 10x and 4x
DVD+R	8x, 4x and 2.4x
DVD+R (dual layer)	6x, 4x and 2.4x
DVD+RW	4x and 2x
DVD-R	8x, 4x and 2x
DVD-R (dual layer)	6x, 4x and 2x
DVD-RAM ²⁾	5x, 3x and 2x
DVD-RW	6x, 4x and 2x
Write methods	
CD	Disk at once, session at once, packet write, track at once
DVD	Disk at once, incremental, overwrite, sequential, multi-session
Environmental conditions	
Temperature ³⁾	
Operation	5 to 55°C ⁴⁾
Storage	-20 to 60°C
Transport	-40 to 65°C
Relative humidity	
Operation	8 to 80%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Vibration	
Operation	5 to 500 Hz: 0.2 g
Storage	5 to 500 Hz: 2 g
Transport	5 to 500 Hz: 2 g
Shock	
Operation	At max. 5 g and 11 ms duration
Storage	At max. 60 g and 11 ms duration
Transport	At max. 200 g and 2 ms duration
At max. 60 g and 11 ms duration	
At max. 200 g and 2 ms duration	
Mechanical characteristics	
Dimensions	
Width	22 mm
Height	172.5 mm
Depth	150 mm
Weight	400 g

Table 97: 5AC901.SDVW-00 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) RAM drivers are not provided by the manufacturer. Support of RAM function by "Nero" burning software (model number 5SWUTI.0000-00) or other burning software packages or drivers from third-party providers.
- 3) Temperature specifications refer to operation at 500 meters. The maximum ambient temperature is typically derated by 1°C per 1000 meters (starting at 500 meters above sea level).
- 4) Drive surface temperature.

3.8.9.4 Temperature humidity diagram




Figure 42: 5AC901.SDVW-00 - Temperature humidity diagram

3.8.10 5AC901.SSCA-00

3.8.10.1 General information

The slide-in compact adapter is a slide-in adapter that allows slide-in compact drives to be installed and operated on a B&R Industrial PC. The slide-in compact drive can be used in APC910 and PPC900 system units.

- Slide-in compact slot
- Slide-in

3.8.10.2 Order data

Model number	Short description	Figure
	Drives	
5AC901.SSCA-00	Slide-in compact adapter for operating a slide-in compact drive in a slide-in slot.	
	Optional accessories	
	Drives	
5AC901.CCFA-00	CFast adapter for operating a CFast card in a slide-in compact slot	
5AC901.CHDD-01	500 GB SATA hard disk, slide-in compact, 24/7 operation Note: please see the manual for information about using this hard disk	
5AC901.CSSD-00	32 GB SATA SSD (SLC), slide-in compact	
5AC901.CSSD-03	60 GB SATA slide-in compact SSD (MLC)	
5AC901.CSSD-04	128 GB SATA SSD (MLC), slide-in compact	
5AC901.CSSD-05	256 GB SSD MLC - Slide-in compact - Toshiba - SATA	

Table 98: 5AC901.SSCA-00 - Order data



3.8.10.3 Technical data

Caution!

A sudden loss of power may result in data loss! In very rare cases, the mass storage device may also become damaged.

To prevent damage and loss of data, the use of a UPS device is recommended.

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.SSCA-00
General information	
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Inserts	
Slide-in compact drives	1
Environmental conditions	
Temperature	
Operation	Depending on the slide-in compact drive being used
Storage	Depending on the slide-in compact drive being used
Transport	Depending on the slide-in compact drive being used
Relative humidity	
Operation	Depending on the slide-in compact drive being used
Storage	Depending on the slide-in compact drive being used
Transport	Depending on the slide-in compact drive being used

Table 99: 5AC901.SSCA-00 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

3.9 Interface options

Information:

Please note that not every interface option can be installed in interface slots 1 and 2. For more information, see "IF option 1 slot" on page 52 and "IF option 2 slot" on page 52.

Information:

For information about installing or replacing an interface option, please refer to the section "Installing the interface option" on page 134.

Depending on the IF option version, it may be necessary to load the setup defaults in BIOS after replacement or installation (see "Save & Exit" on page 216).

3.9.1 5AC901.I485-00

3.9.1.1 General information

The 5AC901.I485-00 interface option is equipped with an RS232/422/485 interface. The operating mode (RS232/RS422/RS485) is selected automatically depending on the electrical connection.

- 1x RS232/422/485 interface
- Can be installed in APC910 and PPC900 systems

3.9.1.2 Order data

Model number	Short description	Figure
Interface options		
5AC901.I485-00	RS232/422/485 interface option; for installation in an APC910 or PPC900	

Table 100: 5AC901.I485-00 - Order data

3.9.1.3 Technical data

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.I485-00
General information	
B&R ID code	\$D84A
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
GL	Yes ¹⁾
Interfaces	
COM1	
Type	RS232/422/485, electrically isolated
Design	9-pin male DSUB connector
UART	16550-compatible, 16-byte FIFO
Max. baud rate	115 kbit/s
Electrical characteristics	
Power consumption	1 W

Table 101: 5AC901.I485-00 - Technical data

Product ID	5AC901.I485-00	
Environmental conditions		
Temperature		
Operation	0 to 55°C ²⁾	
Storage	-20 to 60°C	
Transport	-20 to 60°C	
Relative humidity		
Operation	5 to 90%, non-condensing	
Storage	5 to 95%, non-condensing	
Transport	5 to 95%, non-condensing	
Mechanical characteristics		
Weight	Approx. 34 g	

Table 101: 5AC901.I485-00 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
 2) Detailed information can be found in the temperature tables in the user's manual.

3.9.1.3.1 COM serial interface

COM serial interface		
	RS232	RS422/485
Type	RS232; not modem-capable; electrically isolated	
UART	16550-compatible, 16-byte FIFO	
Transfer rate	Max. 115 kbit/s	
Bus length	Max. 15 m	Max. 1200 m
Pin	RS232 - Pinout	RS422 - Pinout
1	NC	TXD\
2	RXD	NC
3	TXD	NC
4	NC	TXD
5	GND	GND
6	NC	RXD\
7	RTS	NC
8	CTS	NC
9	NC	RXD




Table 102: COM - Pinout

3.9.1.3.2 RS232 - Bus length and cable type

The maximum transfer rate of 115 kbit/s depends on the type of cable being used.

Extension	Transfer rate
≤15 m	Typ. 64 kbit/s
≤10 m	Typ. 115 kbit/s
≤5 m	Typ. 115 kbit/s

Table 103: RS232 - Bus length and transfer rate

The material used for the cable should have all or most of the following properties in order to achieve an optimal transfer rate.

RS232 cables	Property
Signal lines	Cable cross section Wire insulation Conductor resistance Stranding Shield
Grounding line	4x 0.16 mm ² (26AWG), tinned Cu stranded wire PE ≤82 Ω/km Wires stranded in pairs Paired shield with aluminum foil
Outer sheathing	1x 0.34 mm ² (22AWG/19), tinned Cu stranded wire PE ≤59 Ω/km
Materials	PUR mixture
Features	Halogen-free
Cable shielding	From tinned copper wires

Table 104: RS232 - Cable requirements

3.9.1.3.3 RS422 - Bus length and cable type

The RTS line must be switched on to switch the transmitter to active.

The maximum transfer rate of 115 kbit/s depends on the type of cable being used.

Extension	Transfer rate
1200 m	Typ. 115 kbit/s

Table 105: RS422 - Bus length and transfer rate

The material used for the cable should have all or most of the following properties in order to achieve an optimal transfer rate.

RS422 cables	Property
Signal lines	Cable cross section: 4x 0.25 mm ² (24AWG/19), tinned Cu stranded wire Wire insulation: PE Conductor resistance: ≤82 Ω/km Stranding: Wires stranded in pairs Shield: Paired shield with aluminum foil
Grounding line	Cable cross section: 1x 0.34 mm ² (22AWG/19), tinned Cu stranded wire Wire insulation: PE Conductor resistance: ≤59 Ω/km
Outer sheathing	Materials: PUR mixture Features: Halogen-free Cable shielding: From tinned copper wires

Table 106: RS422 - Cable requirements

3.9.1.3.4 When operated as an RS485 interface

When operated in this mode, the pins of the RS422 default interface (1, 4, 6 and 9) must be used. Pins should be connected as shown.




Figure 43: RS232/422/485 interface - Operation in RS485 mode

The RTS line must be switched by the driver for each transmission or reception; there is no automatic switch-back mechanism. This cannot be configured in Windows.

The voltage drop resulting from long cable lengths can lead to greater potential differences between bus stations, which can hinder communication. This can be improved by running ground wire with the others.

3.9.1.3.5 RS485 - Bus length and cable type

The maximum transfer rate of 115 kbit/s depends on the type of cable being used.

Extension	Transfer rate
1200 m	Typ. 115 kbit/s

Table 107: RS485 - Bus length and transfer rate

The material used for the cable should have all or most of the following properties in order to achieve an optimal transfer rate.

RS485 cables	Property
Signal lines	Cable cross section: 4x 0.25 mm ² (24AWG/19), tinned Cu stranded wire Wire insulation: PE Conductor resistance: ≤82 Ω/km Stranding: Wires stranded in pairs Shield: Paired shield with aluminum foil

Table 108: RS485 - Cable requirements

RS485 cables	Property
Grounding line Cable cross section Wire insulation Conductor cross section	1x 0.34 mm ² (22AWG/19), tinned Cu stranded wire PE ≤59 Ω/km
Outer sheathing Materials Features Cable shielding	PUR mixture Halogen-free From tinned copper wires

Table 108: RS485 - Cable requirements

3.9.1.3.6 Terminating resistor

A terminating resistor for the serial interface is already integrated in the IF option. There is a switch to activate or deactivate the terminating resistor, but the system unit needs to be opened in order to reach it. An active terminating resistor is indicated by a yellow LED.




Figure 44: 5AC901.I485-00 - Terminating resistor

3.9.2 5AC901.ICAN-00

3.9.2.1 General information

The 5AC901.ICAN-00 interface option is equipped with a CAN master interface.

- 1x CAN master interface
- Can be installed in APC910 and PPC900 systems

It is not possible to operate two 5AC901.ICAN interface options (in the IF option 1 and IF option 2 slots) at the same time.

3.9.2.2 Order data

Model number	Short description	Figure
	Interface options	
5AC901.ICAN-00	CAN interface option; for installation in an APC910 or PPC900	

Table 109: 5AC901.ICAN-00 - Order data

3.9.2.3 Technical data

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.ICAN-00
General information	
B&R ID code	\$D84B
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Interfaces	
CAN	
Quantity	1
Design	9-pin male DSUB connector
Transfer rate	Max. 500 kbit/s
Electrical characteristics	
Power consumption	1 W
Environmental conditions	
Temperature	
Operation	0 to 55°C ²⁾
Storage	-20 to 60°C
Transport	-20 to 60°C
Relative humidity	
Operation	5 to 90%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Mechanical characteristics	
Weight	Approx. 33 g


Table 110: 5AC901.ICAN-00 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

2) Detailed information can be found in the temperature tables in the user's manual.

3.9.2.3.1 CAN interfaces

CAN bus	
Type	Electrically isolated
Transfer rate	Max. 500 kbit/s
Bus length	Max. 1000 meters
Pin	Assignment
1	NC
2	CAN low
3	GND
4	NC
5	NC
6	Reserved
7	CAN high
8	NC
9	NC



9-pin male DSUB connector

Table 111: 5AC901.ICAN-00 - CAN pinout

3.9.2.3.2 Terminating resistor

A terminating resistor for the CAN interface is already integrated in the IF option. There is a switch to activate or deactivate the terminating resistor, but the system unit needs to be opened in order to reach it. An active terminating resistor is indicated by a yellow LED.




Figure 45: 5AC901.ICAN-00 - Terminating resistor

3.9.3 5AC901.ISRM-00

3.9.3.1 General information

The 5AC901.ISRM-00 interface option has 2 MB SRAM.

- 2 MB SRAM
- Can be installed in APC910 and PPC900 systems

The SRAM interface option 5AC901.ISRM-00 can only be operated in the IF option 2 slot.

Information:

When writing, reading or accessing the SRAM, "non-aligned-accesses" are not supported by the AVLON bus (internal bus in the PCI Express core).

3.9.3.2 Order data

Model number	Short description	Figure
Interface options		
5AC901.ISRM-00	SRAM interface option, 2 MB; for installation in an APC910 or PPC900	

Table 112: 5AC901.ISRM-00 - Order data

3.9.3.3 Technical data

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.ISRM-00
General information	
Connection to system	Via PCI Express bus
B&R ID code	\$D850
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Controller	
SRAM	
Size	2 MB
Battery-buffered	Yes
Remanent variables in power failure mode	512 kB (e.g. for Automation Runtime, see the AS help documentation)
Electrical characteristics	
Power consumption	2 W
Environmental conditions	
Temperature	0 to 55°C ²⁾
Operation	-20 to 60°C
Storage	-20 to 60°C
Transport	

Table 113: 5AC901.ISRM-00 - Technical data

Product ID	5AC901.ISRM-00
Relative humidity	
Operation	5 to 90%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Mechanical characteristics	
Weight	Approx. 20 g

Table 113: 5AC901.ISRM-00 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) Detailed information can be found in the temperature tables in the user's manual.

3.9.4 5AC901.IHDA-00

3.9.4.1 General information

The 5AC901.IHDA-00 interface option has an HDA sound chip with externally accessible MIC, Line IN and Line OUT channels.

- 1x MIC
- 1x Line IN
- 1x Line OUT
- Can be installed in APC910 and PPC900 systems

The interface option 5AC901.IHDA-00 can only be operated in the IF option 1 slot.

3.9.4.2 Order data

Model number	Short description	Figure
Interface options		
5AC901.IHDA-00	Audio interface option; connection for 1x MIC, 1x Line IN, 1x Line OUT; for installation in an APC910	

Table 114: 5AC901.IHDA-00 - Order data

3.9.4.3 Technical data

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.IHDA-00
General information	
B&R ID code	\$D84E
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
GL	Yes ¹⁾
Interfaces	
Audio	
Type	HDA sound
Controller	Realtek ALC 662
Inputs	Microphone, Line IN
Outputs	Line OUT
Electrical characteristics	
Power consumption	0.4 W
Environmental conditions	
Temperature	
Operation	0 to 55°C ²⁾
Storage	-20 to 60°C
Transport	-20 to 60°C

Table 115: 5AC901.IHDA-00 - Technical data

Product ID	5AC901.IHDA-00
Relative humidity	
Operation	5 to 90%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Mechanical characteristics	
Weight	Approx. 21 g

Table 115: 5AC901.IHDA-00 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
 2) Detailed information can be found in the temperature tables in the user's manual.

3.9.4.3.1 MIC, Line IN, Line OUT

MIC, Line IN, Line OUT	
Controller	Realtek ALC 662
MIC	Connection of a mono microphone with a 3.5 mm jack
Line IN	Stereo Line IN signal supplied via a 3.5 mm jack
Line OUT	Connection of a stereo playback device (e.g. amplifier) via a 3.5 mm jack



3.5 mm jack, female

Line OUT Line IN MIC

Table 116: MIC, Line IN, Line OUT

A special driver is required in order to operate the audio controller. Drivers for approved operating systems are available in the Downloads section of the B&R website (www.br-automation.com).

Information:

Required drivers can only be downloaded from the B&R website, not from manufacturer websites.

3.10 Uninterruptible power supply (UPS)

With an optionally integrated UPS, the B&R Industrial PC makes sure that the PC system completes write operations even when a power failure occurs. When the UPS detects a power failure, it switches to battery operation immediately without interruption. This means that all running programs are shut down properly by the UPS software to prevent the possibility of inconsistent data (only functions if the UPS is already configured and the driver is enabled).

Information:

- The monitor/panel is not buffered by the UPS and will shut off when the power fails.
- More detailed information about uninterruptible power supplies can be found in the user's manual for the external UPS. This can be downloaded from the B&R website.

Because the charging circuit is integrated in the housing of the B&R Industrial PC, installation has been simplified to merely attaching the connection cable to the battery unit mounted next to the PC.

Special emphasis was placed on ease of maintenance when the battery unit was designed. Batteries are easily accessible from the front and can be replaced in just a few moments when servicing.

3.10.1 Requirements

- A suitable system unit
- UPS IF option 5AC901.IUPS-00 or 5AC901.IUPS-01
- Battery unit 5AC901.BUPS-00 or 5AC901.BUPS-01
- UPS connection cable 0.5 meters (5CAUPS.0005-01), 1 meter (5CAUPS.0010-01) or 3 meters (5CAUPS.0030-01)
- Configuration of the B&R UPS in the ADI Control Center

Warning!

The 5AC901.BUPS-00 battery unit must only be operated with the 5AC901.IUPS-00 UPS IF option!

The 5AC901.BUPS-01 battery unit must only be operated with the 5AC901.IUPS-01 UPS IF option!

Information:

For information about installation and connecting to the UPS IF option, see "Installing and connecting the UPS battery unit" on page 147.

3.10.2 5AC901.IUPS-00

3.10.2.1 General information

The 5AC901.IUPS-00 UPS IF option, together with the 5AC901.BUPS-00 battery unit, allows the B&R Industrial PC to be shut down without any loss of data during a power failure.

The 5AC901.IUPS-00 UPS interface option can only be operated in the IF option 1 slot.

Warning!

The 5AC901.IUPS-00 UPS IF option is only permitted to be operated with the 5AC901.BUPS-00 battery unit!

Information:

If the system is in standby mode (S5: Soft-off mode or S4: Hibernation mode - suspend-to-disk), then the internal UPS interface option charges the connected battery unit. The system's internal power supplies are active during this procedure. This allows various actions to be completed (e.g. opening the tray of the slide-in DVD drive).

3.10.2.2 Order data

Model number	Short description	Figure
	Uninterruptible power supplies	
5AC901.IUPS-00	UPS interface option; for installation in an APC910 or PPC900; for 4.5 Ah battery	
	Required accessories	
	Uninterruptible power supplies	
5AC901.BUPS-00	Battery unit 4.5 Ah; for UPS 5AC901.IUPS-00	
5CAUPS.0005-01	UPS cable 0.5 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0010-01	UPS cable 1 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0030-01	UPS cable 3 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	



Table 117: 5AC901.IUPS-00 - Order data

3.10.2.3 Technical data

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.IUPS-00
General information	
B&R ID code	\$D851
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Electrical characteristics	
Power consumption	Max. 30 watts at 1.0 A
Deep discharge protection	Yes
Short circuit protection	Yes ²⁾
Battery charging data	
Charging current	Typ. 1 A
Environmental conditions	
Temperature	
Operation	0 to 55°C ³⁾
Storage	-20 to 60°C
Transport	-20 to 60°C

Table 118: 5AC901.IUPS-00 - Technical data

Product ID	5AC901.IUPS-00
Relative humidity	
Operation	5 to 90%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Mechanical characteristics	
Weight	Approx. 28 g

Table 118: 5AC901.IUPS-00 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) The interface option provides protection against short circuits. This does not apply to the connected battery unit.
- 3) Detailed information can be found in the temperature tables in the user's manual.

3.10.2.3.1 UPS interface

UPS interface	
Pin	Assignment
1	Temperature sensor
2	Temperature sensor
3	-
4	+




Table 119: 5AC901.IUPS-00 / -01 - Pinout

3.10.2.4 Installation

This module is installed using the materials included in delivery. For more information regarding installation, see "Installing the interface option" on page 134.

3.10.3 5AC901.IUPS-01

3.10.3.1 General information

The 5AC901.IUPS-01 UPS IF option, together with the 5AC901.BUPS-01 battery unit, allows the B&R Industrial PC to be shut down without any loss of data during a power failure.

The 5AC901.IUPS-01 UPS interface option can only be operated in the IF option 1 slot.

Warning!

The 5AC901.IUPS-01 UPS IF option is only permitted to be operated with the 5AC901.BUPS-01 battery unit!

Information:

If the system is in standby mode (S5: Soft-off mode or S4: Hibernation mode - suspend-to-disk), then the internal UPS interface option charges the connected battery unit. The system's internal power supplies are active during this procedure. This allows various actions to be completed (e.g. opening the tray of the slide-in DVD drive).

3.10.3.2 Order data

Model number	Short description	Figure
	Uninterruptible power supplies	
5AC901.IUPS-01	UPS interface option; for installation in an APC910 or PPC900; for 2.2 Ah battery	
	Required accessories	
	Uninterruptible power supplies	
5AC901.BUPS-01	Battery unit 2.2 Ah; for UPS 5AC901.IUPS-01	
5CAUPS.0005-01	UPS cable 0.5 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0010-01	UPS cable 1 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0030-01	UPS cable 3 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	

Table 120: 5AC901.IUPS-01 - Order data

3.10.3.3 Technical data

Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

Product ID	5AC901.IUPS-01
General information	
B&R ID code	\$DF84
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Electrical characteristics	
Power consumption	Max. 25 watts at 0.9 A
Deep discharge protection	Yes
Short circuit protection	Yes ²⁾
Battery charging data	
Charging current	Typ. 0.88 A
Environmental conditions	
Temperature	
Operation	0 to 55°C ³⁾
Storage	-20 to 60°C
Transport	-20 to 60°C

Table 121: 5AC901.IUPS-01 - Technical data

Product ID	5AC901.IUPS-01
Relative humidity	
Operation	5 to 90%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Mechanical characteristics	
Weight	Approx. 28 g

Table 121: 5AC901.IUPS-01 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
- 2) The interface option provides protection against short circuits. This does not apply to the connected battery unit.
- 3) Detailed information can be found in the temperature tables in the user's manual.

3.10.3.3.1 UPS interface

UPS interface	
Pin	Assignment
1	Temperature sensor
2	Temperature sensor
3	-
4	+




Table 122: 5AC901.IUPS-00 / -01 - Pinout

3.10.3.4 Installation

This module is installed using the materials included in delivery. For more information regarding installation, see "Installing the interface option" on page 134.

3.10.4 5AC901.BUPS-00

3.10.4.1 General information

- Battery unit for UPS IF option 5AC901.IUPS-00
- Single cell rechargeable battery
- 2 Hawker Cyclon 12 V 4.5 Ah rechargeable batteries connected in series
- Rated voltage: 24 V
- Capacity: 4.5 Ah

The battery unit has a limited service life and should be replaced regularly (after the specified service life at the latest).

Warning!

The battery unit 5AC901.BUPS-00 must only be operated with the UPS IF option 5AC901.IUPS-00!

3.10.4.2 Order data

Model number	Short description	Figure
	Uninterruptible power supplies	
5AC901.BUPS-00	Battery unit 4.5 Ah; for UPS 5AC901.IUPS-00	
	Required accessories	
	Uninterruptible power supplies	
5CAUPS.0005-01	UPS cable 0.5 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0010-01	UPS cable 1 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0030-01	UPS cable 3 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	

Table 123: 5AC901.BUPS-00 - Order data

3.10.4.3 Technical data

Product ID	5AC901.BUPS-00
General information	
Battery	
Type	Hawker Cyclon 12V 4.5 Ah; two rechargeable batteries connected in series
Service life	Up to 15 years ¹⁾
Design	Single cell
Temperature sensor	NTC resistance
Maintenance interval during storage	6 month interval between charges
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ²⁾
GOST-R	Yes
Charge duration when battery low	Typ. 7 hours
Electrical characteristics	
Nominal voltage	24 V
Capacity	4.5 Ah
Fuse	Yes
Battery charging data	
Charging current ³⁾	Typ. 1 A
Environmental conditions	
Temperature	
Operation	-30 to 60°C ⁴⁾
Storage	-65 to 80°C
Transport	-65 to 80°C
Relative humidity	
Operation	5 to 95%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Altitude	
Operation	Max. 3000 m

Table 124: 5AC901.BUPS-00 - Technical data

Product ID	5AC901.BUPS-00
Mechanical characteristics	
Dimensions	
Width	223.2 mm
Height	78.2 mm
Depth	145 mm
Weight	Approx. 4600 g

Table 124: 5AC901.BUPS-00 - Technical data

- 1) Depends on the ambient temperature and charge/discharge cycles.
- 2) Yes, although applies only if all components installed within the complete system have this certification
- 3) Maximum charging current.
- 4) Battery backing is no longer provided if the temperature falls below the minimum temperature or rises above the maximum temperature. Charging also no longer takes place since this could lead to battery damage.

3.10.4.4 Dimensions




Figure 46: 5AC901.BUPS-00 - Dimensions

3.10.4.5 Drilling template




Figure 47: 5AC901.BUPS-00 - Drilling template

3.10.4.6 Installation

For information about installation and connecting to the UPS IF option, see "Installing and connecting the UPS battery unit" on page 147.

3.10.4.7 Precautions for handling and use

Spills and leaks:

Any further spillage or leakage must be prevented. Smaller spills must be bonded with dry sand, dirt and vermiculite. The use of flammable materials is prohibited. If possible, neutralize acids with sodium bicarbonate, chalk, etc. Acid-resistant clothing, shoes, gloves and face protection must be worn. The disposal of unneutralized acid in the sewage system is prohibited!

Waste disposal:

Used batteries must be disposed of in an environmentally friendly recycling process.

Neutralized mud must be stored in closed containers and stored/disposed of in accordance with applicable regulations. After neutralization and testing, larger spills diluted with water must be disposed of in accordance with applicable regulations.

Handling and storage:

- Batteries must be kept in cool, dry and well ventilated rooms with impermeable surfaces and appropriate containment conditions in case of leakage.
- Batteries must be protected from adverse weather conditions and separated from incompatible materials during storage and transport.
- A sufficient supply of water must be located nearby.
- Damage to containers where batteries are stored and transported must be prevented.
- Keep away from fire, sparks and excessive heat.

3.10.5 5AC901.BUPS-01

3.10.5.1 General information

- Battery unit for UPS IF option 5AC901.IUPS-01
- Maintenance-free lead acid battery
- 2 Panasonic 12 V 2.2 Ah rechargeable batteries connected in series
- Rated voltage: 24 V
- Capacity: 2.2 Ah

The battery unit has a limited service life and should be replaced regularly (after the specified service life at the latest).

Warning!

The battery unit 5AC901.BUPS-01 must only be operated with the UPS IF option 5AC901.IUPS-01!

3.10.5.2 Order data

Model number	Short description	Figure
	Uninterruptible power supplies	
5AC901.BUPS-01	Battery unit 2.2 Ah; for UPS 5AC901.IUPS-01	
	Required accessories	
	Uninterruptible power supplies	
5CAUPS.0005-01	UPS cable 0.5 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0010-01	UPS cable 1 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0030-01	UPS cable 3 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	

Table 125: 5AC901.BUPS-01 - Order data

3.10.5.3 Technical data

Product ID	5AC901.BUPS-01
General information	
Battery	
Type	Panasonic 12V 2.2 Ah; two rechargeable batteries connected in series
Service life	Up to 5 years ¹⁾
Design	Maintenance-free lead acid battery
Temperature sensor	NTC resistance
Maintenance interval during storage	6 month interval between charges
Certification	
CE	Yes
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ²⁾
GOST-R	Yes
Charge duration when battery low	Typ. 5 hours
Electrical characteristics	
Nominal voltage	24 V
Capacity	2.2 Ah
Fuse	Yes
Battery charging data	
Charging current ³⁾	Typ. 0.88 A
Environmental conditions	
Temperature	
Operation	0 to 40°C ⁴⁾
Storage	-15 to 40°C
Transport	-15 to 40°C
Relative humidity	
Operation	25 to 85%, non-condensing
Storage	25 to 85%, non-condensing
Transport	25 to 85%, non-condensing
Altitude	
Operation	Max. 3000 m

Table 126: 5AC901.BUPS-01 - Technical data

Product ID	5AC901.BUPS-01
Mechanical characteristics	
Dimensions	
Width	188 mm
Height	78 mm
Depth	115 mm
Weight	Approx. 2550 g

Table 126: 5AC901.BUPS-01 - Technical data

- 1) Depends on the ambient temperature and charge/discharge cycles.
- 2) Yes, although applies only if all components installed within the complete system have this certification
- 3) Maximum charging current.
- 4) Battery backing is no longer provided if the temperature falls below the minimum temperature or rises above the maximum temperature. Charging also no longer takes place since this could lead to battery damage.

3.10.5.4 Dimensions




Figure 48: 5AC901.BUPS-01 - Dimensions

3.10.5.5 Drilling template




Figure 49: 5AC901.BUPS-01 - Drilling template

3.10.5.6 Installation

For information about installation and connecting to the UPS IF option, see "Installing and connecting the UPS battery unit" on page 147.

3.10.5.7 Precautions for handling and use

Spills and leaks:

Any further spillage or leakage must be prevented. Smaller spills must be bonded with dry sand, dirt and vermiculite. The use of flammable materials is prohibited. If possible, neutralize acids with sodium bicarbonate, chalk, etc. Acid-resistant clothing, shoes, gloves and face protection must be worn. The disposal of unneutralized acid in the sewage system is prohibited!

Waste disposal:

Used batteries must be disposed of in an environmentally friendly recycling process.

Neutralized mud must be stored in closed containers and stored/disposed of in accordance with applicable regulations. After neutralization and testing, larger spills diluted with water must be disposed of in accordance with applicable regulations.

Handling and storage:

- Batteries must be kept in cool, dry and well ventilated rooms with impermeable surfaces and appropriate containment conditions in case of leakage.
- Batteries must be protected from adverse weather conditions and separated from incompatible materials during storage and transport.
- A sufficient supply of water must be located nearby.
- Damage to containers where batteries are stored and transported must be prevented.
- Keep away from fire, sparks and excessive heat.

3.10.6 5CAUPS.xxxx-01

3.10.6.1 General information

The UPS connection cable establishes the connection between the UPS interface option and the battery unit.

3.10.6.2 Order data

Model number	Short description	Figure
Uninterruptible power supplies		
5CAUPS.0005-01	UPS cable 0.5 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0010-01	UPS cable 1 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	
5CAUPS.0030-01	UPS cable 3 m; for 5AC901.IUPS-00 and 5AC901.IUPS-01 UPS	

Table 127: 5CAUPS.0005-01, 5CAUPS.0010-01, 5CAUPS.0030-01 - Order data

3.10.6.3 Technical data

Product ID	5CAUPS.0005-01	5CAUPS.0010-01	5CAUPS.0030-01
General information			
Certification			
CE		Yes	
cULus		Yes	
cULus HazLoc Class 1 Division 2		Yes ¹⁾	
GOST-R		Yes	
Cable structure			
Wire cross section		2x 0.5 mm ² (AWG 20) 2x 2.5 mm ² (AWG 13)	
Conductor resistance		At 0.5 mm ² max. 39 Ω/km At 2.5 mm ² max. 7.98 Ω/km ²⁾	
Outer sheathing			
Material		Thermoplastic PVC-based material	
Color		Window gray (similar to RAL 7040)	
Connector			
Type		Screw clamp, 4-pin ³⁾	
Electrical characteristics			
Operating voltage		Max. 30 VDC	
Peak operating voltage		Typ. 30 VDC	
Test voltage Wire/Wire		1500 V	
Current load		10 A at 20°C	
Environmental conditions			
Temperature			
Moving		-5 to 70°C	
Static		-30 to 70°C	
Mechanical characteristics			
Dimensions			
Length	0.5 m	1 m	3 m
Diameter		7 mm	
Flex radius			
Moving		10x wire cross section	
Fixed installation		5x wire cross section	
Weight	Approx. 55 g	Approx. 100 g	Approx. 250 g

Table 128: 5CAUPS.0005-01, 5CAUPS.0010-01, 5CAUPS.0030-01 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

2) At an ambient temperature of 20°C.

3) Tightening torque: min. 0.4 Nm; max. 0.5 Nm

Information:

The maximum length of the UPS connection cable depends on:

- Power
- Voltage drop
- Wire cross section
- Sensor lines

3.10.6.4 Installation

For information about connecting the cable to the battery unit, please see the section "Installing and connecting the UPS battery unit" on page 147.

3.11 Power supply

3.11.1 5AC902.PS00-00

3.11.1.1 General information

The AC power supply for the Panel PC can optionally be expanded to allow operation with 100~240 VAC.

3.11.1.2 Order data

Model number	Short description	Figure
	Power supply	
5AC902.PS00-00	PPC900 power supply 85-264 VAC	
	Required accessories	
	Terminal blocks	
0TB3103.8000	Connector, 230 VAC, 3-pin female, 4 mm ² screw clamp, protected against vibration by the screw flange	

Table 129: 5AC902.PS00-00 - Order data

3.11.1.3 Technical data

Product ID	5AC902.PS00-00
General information	
Power button	Yes
Certification	
cULus	Yes
cULus HazLoc Class 1 Division 2	Yes ¹⁾
GOST-R	Yes
Input	
Nominal input voltage	100 to 240 VAC
Frequency	45 to 65 Hz
Starting current	< 20 A (cold restart, 100% load and 100 VAC)
Power failure bypass	> 10 ms (100 VAC and 230 VAC)
Internal fuse	Yes
Output	
Nominal voltage	24 VDC ±10%
Output current 0 to 55°C	5.5 A ²⁾
Mechanical characteristics	
Housing	
Material	Sheet metal
Paint	Anthracite
Dimensions	
Width	73.5 mm
Height	225.5 mm
Depth	53.5 mm
Weight	580 g

Table 130: 5AC902.PS00-00 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification
 2) At an ambient temperature of 0 to 55°C and nominal voltage.

3.11.1.4 Installation

For information about installing the power supply, please refer to the section "Installing or replacing the AC power supply" on page 130.

Chapter 3 • Installation

1 Installation

Danger!

- All supply voltage must be disconnected before removing device covers or components or removing/installing accessories, hardware or cables.
- The power cable must be disconnected from the device and from the voltage supply.
- Before the device can be connected to the power supply and turned on, all covers, components, accessories, hardware and cables must be installed or attached.

1.1 Installation Panel PC 900

The Panel PC 900 is mounted in the cutout using retaining clips. The number of retaining clips depends on the display unit.

Installation notes

- Environmental conditions must be taken into consideration.
- When installed in an enclosed housing, enough space must be available for air to circulate sufficiently.
- This device must be mounted to a flat, clean and burr-free surface.
- This device is only certified for operation in closed rooms.
- This device must not be subjected to direct sunlight.
- Ventilation holes must not be covered.
- This device must be mounted in one of the approved orientations.
- The wall or control cabinet must be able to withstand four times the total weight of the device.
- The flex radius of connected cables (DVI, SDL, USB, etc.) must not be exceeded.
- This device must be mounted in a position that minimizes glare on the screen.
- This device must be mounted in a position and orientation that make viewing as easy as possible for the operator.

The thickness of the wall or cabinet plate must be between 1 mm and 6 mm.


A hex-head screwdriver is needed to tighten and loosen the screws on the retaining clips. The maximum torque for the retaining clips is 1 Nm.

Devices must be installed on flat, clean and burr-free surface; uneven areas can cause damage to the display when the screws are tightened or intrusion of dust and water.

Information:

Sufficient clearance must be available on the sides of the Panel PC 900 (A, B and C in der image below) to allow unrestricted operation and maintenance of the back of the PPC. This clearance depends on the configuration of the Panel PC 900 as well as how it affects operating and service personnel.

- The clearance indicated by the letter "A" is necessary to replace the fan kit and fan filter.
- The clearance indicated by the letter "B" is necessary to access the LED status indicators, the power and reset buttons, the CFast slot, the slide-in compact drive and the slide-in DVD drive.
- The clearance indicated by the letter "C" is necessary to connect and disconnect cables as well as to ensure that the maximum flex radius of cables is not exceeded.



Procedure

1. Check whether the included mounting screws are screwed into the retaining clips. If not, then the mounting screws must be screwed into the retaining clips with a hex-head screwdriver. The mounting screws must only be screwed in far enough that they no longer protrude above the retaining clip.




Figure 50: Prepare retaining clips

2. Insert the device into the front side of the smooth, flat installation cutout. The dimensions for the cutout can be found under "Installation diagrams" on page 22.

3. Install the retaining clips on the device. To do this, insert the clips into the openings on the sides of the device (indicated by orange circles). The number of retaining clips may vary depending on the display unit. The exact number can be found in Figure 7 "Panel PC 900 + power supply + bus units - Installation diagram" on page 22.




Figure 51: Inserting the retaining clips

4. Now fasten the retaining clips to the wall or control cabinet by alternately tightening the screws with a hex-head screwdriver. The tightening torque should be max. 1 Nm to provide an optimal seal.




Figure 52: Fasten retaining clips

1.2 Replacing the CPU board and system unit

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.

Information:

If a bus unit is mounted on the Panel PC it must first be removed.

3. Remove the 4 Torx screws (T20) and 2 Torx screws (T10) shown in the following image.




Figure 53: Removing the Torx screws on the system unit

4. Remove the system unit with the installed CPU board.




Figure 54: Removing the system unit and CPU board

5. A different system unit with a preinstalled CPU board can now be installed on the display unit. Installation takes place in reverse order. The max. tightening torque is 0.5 Nm for the T10 Torx screws and 1.2 Nm for the T20 Torx screws.

It is very important that the system unit is installed correctly. The connector for the display interface must be carefully connected to the female connector on the display unit.

6. If the Panel PC 900 is converted to an Automation Panel 9x3, then the mounting plate must also be removed. To do so, remove the 5 Torx screws (T20) indicated below.




Figure 55: Removing the Torx screws on the mounting plate

7. Remove the mounting plate from the display unit.




Figure 56: Removing the mounting plate

8. The mounting plate is installed by following this instructions in reverse; the max. tightening torque is 1.2 Nm. It is very important that the mounting plate is installed correctly.

1.3 Installing or replacing the AC power supply

1. The on/off switch must be set to position "0" (off). Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
3. Remove the Panel PC from the control cabinet. To do so, follow the steps in section "Installation Panel PC 900" on page 125 in reverse order.
4. Place the Panel PC on a clean, flat surface.
5. Remove the Torx screws (T20) indicated in the following image.




Figure 57: Removing the screws

6. The AC power supply can now be removed parallel to the Panel PC in the direction indicated by the arrows in the image below. Exercise caution to prevent damage to the power supply connector.




Figure 58: Replacing the AC power supply

7. If the AC power supply is being installed for the first time (i.e. not a replacement), then both mounting plates must be installed first. To do so, guide the mounting plates into each of the three slots at a slight angle. These mounting plates are included in the delivery of the AC power supply.




Figure 59: Installing the mounting plates

8. To install an AC power supply on the Panel PC, it must be aligned parallel to the Panel PC. Plug the power supply connector into the female connector on the Panel PC.
 9. Then the AC power supply can be fastened with the 4 Torx screws (T20) (max. tightening torque 1.2 Nm). It is important that it is aligned parallel to the housing. The power supply connector must click into place in the female connector on the Panel PC. There must not be any pressure or mechanical strain on the connector.




Figure 60: Installing the AC power supply

10. The Panel PC can now be installed back in the control cabinet, see section "Installation Panel PC 900" on page 125.

1.4 Replacing the main memory modules

Information:

The Panel PC has 2 slots for main memory modules. Only the following B&R main memory modules are permitted:

- 5MMDDR.1024-03, 5MMDDR.2048-03, 5MMDDR.4096-03, 5MMDDR.8192-03

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Discharge any electrostatic charge on the ground connection.
3. Remove the Panel PC from the control cabinet. To do so, follow the steps in section "Installation Panel PC 900" on page 125 in reverse order.
4. Place the Panel PC on a clean, flat surface.
5. Remove the Torx screws (T10) indicated in the following image.




Figure 61: Removing the Torx screws

6. Tilt the cover plate forward and remove it by sliding it upward.




Figure 62: Removing the cover plate

Information:

The lower main memory module can only be replaced after the top one has been removed.

7. The main memory modules can now be replaced. To do so, carefully press the fastening clamps outward and pull out the main memory module.

8. If inserting a new main memory module, align the notch on the connector side of the memory module with the notch above the slot. The main memory module can now be carefully pressed into the slot until the fastening clamps are engaged.





Figure 63: Replacing the main memory modules

Caution!

If only one main memory module is to be used, it must be installed in RAM slot 2.



9. The cover plate can now be replaced by following these steps in reverse order. The maximum tightening torque of the Torx screws (T10) is 0.5 Nm.

10. The Panel PC can now be installed back in the control cabinet, see section "Installation Panel PC 900" on page 125.

1.5 Installing the interface option

Information:

Please note that not every interface option can be installed in interface slots 1 and 2. For more information, see "IF option 1 slot" on page 52 and "IF option 2 slot" on page 52.

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.

Information:

If a bus unit is mounted on the Panel PC it must first be removed.

3. Remove the Torx screws (T10) indicated by ① in the following image. The Torx screws indicated by ② only need to be removed if an IF option is already mounted.




Figure 64: Removing the Torx screws from cover plate

4. Lift the cover plate up and away to remove it.




Figure 65: Removing the cover plate

5. Remove the cover plate by sliding it upwards and also remove the installed IF option.




Figure 66: Removing the Torx screws and slot cover

6. Insert the interface option in the slot and fasten it to the Panel PC (max. tightening torque 0.5 Nm) with 2 torx screws (T10).




Figure 67: Inserting and fastening the IF option

7. Replace the cover plate.




Figure 68: Replacing the cover plate

8. Secure the cover plate to the B&R industrial PC using the same Torx screws (T10) from before. The Torx screws indicated by ② only need to be tightened if an IF option is mounted (max. tightening torque 0.5 Nm).




Figure 69: Fastening the cover plate with the Torx screws

9. This option must be enabled in BIOS after the interface has been installed successfully. To do this, open BIOS when booting the system, load the default BIOS values and then save the settings. For additional information, see "Save & Exit" on page 216.

1.6 Installing and replacing the slide-in compact drive

Information:

The slide-in compact drive can only be replaced without removing the PPC from the control cabinet if the wall is less than 5.5 mm thick. Steps 3, 4 and 11 are only necessary if the Panel PC is removed from the cabinet.

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
3. Remove the Panel PC from the control cabinet. To do so, follow the steps in section "Installation Panel PC 900" on page 125 in reverse order.
4. Place the Panel PC on a clean, flat surface.
5. Remove the Torx screws (T10) indicated in the following image.




Figure 70: Removing the Torx screws

6. Tilt the cover plate forward and remove it by sliding it upward.




Figure 71: Removing the cover plate

7. Free the plastic removal strip fastened to the side of the slide-in compact drive.




Figure 72: Freeing the removal strip on the slide-in compact drive

8. Pull firmly on the removal strip to remove the slide-in compact drive.




Figure 73: Removing the slide-in compact drive

9. When inserting a slide-in compact drive, be sure to align it with the guide rails. Tuck the removal strip back between the drive and the frame (as it was before it was pulled out).
10. The cover plate can now be replaced by following these steps in reverse order.
11. The Panel PC can now be installed back in the control cabinet, see section "Installation Panel PC 900" on page 125.

1.7 Replacing the fan kit

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
3. Press in the indicated latching mechanisms ① while pulling out the fan kit ② at the same time.




Figure 74: Pressing in the latching mechanism

4. A new fan kit can now be installed. Align the fan kit parallel to the Panel PC and press it in until it latches. Make sure the fan kit is inserted so that the connections match up.
5. If a fan kit is being installed for the first time (i.e. fan kit previously not used in device), then it must still be programmed. To do so, follow the instructions in the "Programming fan kit data" section.
If a fan kit has been removed from the device and is not being replaced, then its data must be deleted. To do so, follow the instructions in the "Deleting fan kit data" section.

Information:

If a fan kit has been replaced, then an incorrect serial number will be displayed. To display the correct serial number, the fan kit data must be deleted and reprogrammed.

6. After the fan kit has been programmed, the BIOS default values must be loaded and the settings saved. For additional information, see "Save & Exit" on page 216.

Programming fan kit data

Information:

If a fan kit is being installed for the first time (i.e. fan kit previously not used in device), then it must still be programmed.

1. Boot the B&R industrial PC and type the following on the command line:
`mtxcsvc i fanfset` - Checks whether the fan kit has already been programmed
2. If the fan kit has not yet been programmed, this can be done by typing in the following:
`mtxcsvc u fanfset "fn"` - The path of the file and filename must be specified in place of "fn".

Deleting fan kit data

Information:

If a fan kit has been removed from the device and is not being replaced, then its data must be deleted.

1. Boot the B&R industrial PC and type the following on the command line:
`mtxcsvc i fanfset` - Checks whether the fan kit has already been programmed
2. Since a fan kit was already installed, its data must be deleted. This is done by typing the following on the command line:
`mtxcsvc d fanfset` - Deletes the data of the previously installed fan kit

1.8 Replacing the fan filter

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
3. Press down the indicated latching mechanism ① while pulling out the filter cover ② at the same time.




Figure 75: Removing the filter cover

4. Insert the new filter cover into the fan kit by following these instructions in the reverse order.

1.9 Installing the bus unit

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
3. Remove the Panel PC from the control cabinet. To do so, follow the steps in section "Installation Panel PC 900" on page 125 in reverse order.
4. Place the Panel PC on a clean, flat surface.
5. Remove the 2 or 4 Torx screws (T10). Slide the cover plate forward to remove it.




Figure 76: Removing the Torx screws and side cover

6. Install the bus unit on the system unit using 4 Torx screws (T20) included in delivery (tightening torque approx. 1.2 Nm).




Figure 77: Installing the bus unit on the system unit

7. Install the side cover on the bus expansion using the 4 indicated Torx screws (T10) (2 already removed, 2 included in delivery); the tightening torque is approx. 0.5 Nm.




Figure 78: Replacing the side cover

8. The Panel PC can now be installed back in the control cabinet, see section "Installation Panel PC 900" on page 125.
9. Once installed, the bus unit must be enabled in BIOS. To do this, open BIOS when booting the system, load the default BIOS values and then save the settings. For additional information, see "Save & Exit" on page 216.

1.10 Installing PCI / PCIe cards

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
3. Remove the Panel PC from the control cabinet. To do so, follow the steps in section "Installation Panel PC 900" on page 125 in reverse order.
4. Place the Panel PC on a clean, flat surface.
5. Remove the Torx screws (T10) indicated in the following image. Slide the cover plate forward to remove it.




Figure 79: Removing the Torx screws and side cover

6. Remove the PCI slot cover from the bus unit. This is done by first removing the marked Torx screws (T10) and then removing the cover.




Figure 80: Removing the Torx screws and slot cover

7. Install the PCI or PCIe card in the bus unit. Be sure to insert the PCI or PCIe card in the black guide rail at the top of the bus unit. Fasten the PCI or PCIe card using the indicated Torx screws (T10) removed earlier; the max. tightening torque is 0.5 Nm.




Figure 81: Installing the PCI / PCIe card in the bus unit

8. Install the side cover on the bus unit using the 4 indicated Torx screws (T10); the max. tightening torque is 0.5 Nm.




Figure 82: Replacing the side cover

9. The Panel PC can now be installed back in the control cabinet, see section "Installation Panel PC 900" on page 125.

1.11 Installing a slide-in drive

1. Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
2. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
3. Remove the Panel PC from the control cabinet. To do so, follow the steps in section "Installation Panel PC 900" on page 125 in reverse order.
4. Place the Panel PC on a clean, flat surface.
5. Remove the Torx screws (T10) indicated in the following image. Slide the cover plate forward to remove it.




Figure 83: Removing the Torx screws and side cover

6. Remove the slide-in slot cover from the side cover. This is done by pressing in the 6 indicated snap arms and removing the slot cover.




Figure 84: Remove the slide-in slot cover from the side cover.

7. Install the slide-in drive in the bus unit. Be sure to insert the slide-in drive in the black guide rails at the top and bottom of the bus unit.




Figure 85: Installing the slide-in drive in the bus unit

8. Install the side cover on the bus unit using the 4 indicated Torx screws (T10); the max. tightening torque is 0.5 Nm.




Figure 86: Replacing the side cover

9. The Panel PC can now be installed back in the control cabinet, see section "Installation Panel PC 900" on page 125.

1.12 Installing and connecting the UPS battery unit

Warning!

Do not open the UPS battery unit!

1. Disconnect the power supply to the B&R Industrial PC.
2. Install the battery unit. Information about the drilling template can be found in the technical data of the respective UPS battery unit. Ensure that the distance between the battery unit and the B&R industrial PC allows them to be connected with the UPS cable (0.5 m, 1 m or 3 m). Installation requires 4 M5 screws, 4 washers and 1 screw lock (min. torque 1.3 Nm; screw depth as per applicable DIN regulations and specific application). These are not included in delivery.
3. Connect the UPS cable to the battery unit. When doing so, make sure to connect the red and black wires to the power supply (orange screw clamp). Be sure to use the right connection terminals (red wire for +; black wire for -)! Connect the white and brown wires to the temperature sensor (green screw clamp terminal block) (white wire for 1; brown wire for 2).




Figure 87: Connecting the UPS cable to the battery

4. Tighten the connected wires in the screw clamps with a screw driver (to a max. tightening torque of 0.4 Nm).
5. Loosen the two nuts (M3) on the cable clamp and feed the UPS cable through.
6. Fasten the UPS cable using the cable clamp. Tighten the previously removed nuts onto the cable clamp in alternating order (max. 0.35 Nm torque).
7. Connect the 4-pin screw clamp to the UPS IF option and tighten the two screws with a screwdriver (max. torque 0.4 Nm).

2 Connecting to the power mains

Danger!

- All supply voltage must be disconnected before removing device covers or components or removing/installing accessories, hardware or cables.
- The power cable must be disconnected from the device and from the voltage supply.
- Before the device can be connected to the power supply and turned on, all covers, components, accessories, hardware and cables must be installed or attached.

2.1 Installing the DC mains cable

Danger!

Supply voltage to the B&R Industrial PC must be disconnected completely. Before connecting the DC mains cable, it is important to make absolutely sure that it has been disconnected from the power source (e.g. power supply).

2.1.1 Wiring

The DC mains cable must be secured in the terminal block (power connector) as shown in the image. Wires with a cross section of 0.75 mm² to 1.5 mm² and wire end sleeves are to be used.

Installing the 0TB103.9 screw clamp terminal block

Insert the wires with the wire end sleeves into the terminal contacts ② as shown in the image and tighten the screw clamps ① with a screwdriver (max. torque of 0.4 Nm).

It is important to pay attention to the pin assignments of the power supply connector on the device!





Figure 88: Installing a screw clamp terminal block

Installing the 0TB103.91 cage clamp terminal block

Insert a screwdriver into the cage clamp terminal ① and fasten the wires with wire end sleeves in the terminal contacts ② as shown in the image below. Close the terminal contact by removing the screwdriver.

It is important to pay attention to the pin assignments of the power supply connector on the device!



2.2 Installing the AC mains cable

Danger!

Supply voltage to the B&R Industrial PC must be disconnected completely. Before connecting the AC mains cable, it is important to make absolutely sure that it has been disconnected from the power source (e.g. power supply).

2.2.1 Wiring

The AC mains cable must be secured in the terminal block (power connector) as shown in the image. Wires with a cross section of 0.75 mm² to 4 mm² and wire end sleeves are to be used.

Installing the 0TB3103.8000 screw clamp terminal block

Insert the wires with the wire end sleeves into the terminal contacts ② as shown in the image and tighten the screw clamps (located on the top of the screw clamp terminal block) with a screwdriver (max. torque 0.6 Nm).

It is important to pay attention to the pin assignments of the power supply connector on the device!




Figure 89: Installing a screw clamp terminal block

2.3 Connecting the power supply to a B&R device

Danger!

The supply voltage to the B&R device must be completely disconnected. Before connecting the mains cable, it is important to make absolutely sure that it has been disconnected from the power source (e.g. power supply).

1. Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
2. Connect the power supply connector to the B&R device and tighten the fastening screws (max. tightening torque 0.5 Nm).




Figure 90: Connecting the power supply connector to a B&R device.

2.4 Grounding concept functional ground

Functional ground is a current path of low impedance between electrical circuits and ground. It is used, for example, to improve immunity to disturbances and not necessarily as a protective measure. It therefore serves only to deflect disturbances, not to provide any kind of protection against electric shock.

The functional ground on the device has 2 connections:

- Supply voltage
- Ground connection

To guarantee safe conductance of electric disturbances, the following points should be observed:

- The device should be connected to the central grounding point in the control cabinet using the shortest route possible.
- A cable with a minimum cross section of 2.5 mm^2 per connection should be used. If a cable with wire end sleeves is connected to the 0TB103.9 or 0TB103.91 terminal block, then a cable with maximum 1.5 mm^2 per connection is possible.
- Note the line shielding concept; all connected data cables are used as shielded lines.

Functional ground is indicated on the B&R device with the following symbol: 




Figure 91: Panel PC 900 - Grounding concept

3 Cable connections

Flex radius specifications must be taken into account when installing or connecting cables.

Information:

The maximum torque for the locating screws is 0.5 Nm.




Figure 92: Flex radius - Cable connection

Information:

The specified flex radius can be found in the Automation Panel 800 or Automation Panel 900 user's manual, which can be downloaded as a PDF file from the B&R website at www.br-automation.com.

4 Switching on for the first time

4.1 General information before switching on

Checklist

The following items must be checked before the device is put into operation for the first time:

- Have the installation notes as specified in "Installation" on page 125 been observed?
- Have the permitted environmental conditions been taken into consideration for the device?
- If the power supply connected correctly and have the values been checked?
- Is the ground cable connected correctly to the ground connection?
- The device must be put into operation first before additional hardware (e.g. PCI card) is installed.

Caution!

Before the device is put into operation, it must first be acclimated to room temperature! It should not be immediately subjected to thermal radiation.

If transported at low temperatures or if there are large temperature fluctuations, the device must not be subjected to any type of moisture.

Requirements

The following requirements must be fulfilled before the device is switched on for the first time:

- The ground cable is connected.
- All connection cables are connected correctly.
- A USB keyboard and USB mouse are connected (optional).

4.2 Switching on the Panel PC

Procedure

1. Connect and switch on the voltage supply (e.g. power supply).
2. Switch on the device by pressing the power button (DC power supply) or the on/off switch on the optional power supply (AC voltage supply).
3. The device is booting and operating; the Power LED is lit.

5 Touch screen calibration

B&R touch screen devices are equipped with a B&R touch controller that supports hardware calibration. As a result, devices are pre-calibrated when delivered. This is an advantageous feature when replacing devices of the same model or type since it avoids having to recalibrate the new device. Nevertheless, calibrating the device is still recommended in order to achieve the best results and to better adapt the touch screen to the user's preferences.

5.1 Single-touch (analog resistive)

5.1.1 Windows 7 Professional / Ultimate

After installing Windows 7 on the device, the touch screen driver must be installed in order to operate the touch screen. The necessary driver is available in the Downloads section of the B&R website (www.br-automation.com).

5.1.2 Windows Embedded Standard 7 Embedded / Premium

A touch screen driver will be installed automatically if a touch controller is detected during the Windows Embedded Standard 7 installation.

The touch screen driver must be installed manually if a touch controller was not detected during the Windows Embedded Standard 7 setup or if a an Automation Panel 800/900/9x3 has been connected after setup. The necessary driver is available in the Downloads section of the B&R website (www.br-automation.com).

5.1.3 Windows XP Professional

After installing Windows XP Professional on the device, the touch screen driver must be installed in order to operate the touch screen. The necessary driver is available in the Downloads section of the B&R website (www.br-automation.com).

5.1.4 Windows Embedded Standard 2009

The required touch driver is automatically installed after starting Windows Embedded Standard 2009 for the first time (First Boot Agent) on a Panel PC or Power Panel.

Operating the touch screen on any other devices requires installing the touch driver manually. The necessary driver is available in the Downloads section of the B&R website (www.br-automation.com).

5.2 Multi-touch (PCT - Projected capacitive)

5.2.1 Windows 7 Professional / Ultimate

Microsoft multi-touch drivers are installed when Windows 7 is installed on the device. Once the installation of Windows 7 has completed, the device can be operated immediately.

5.2.2 Windows Embedded Standard 7 Premium

Microsoft multi-touch drivers are installed when Windows Embedded Standard 7 Premium is installed on the device. Once the installation of Windows Embedded Standard 7 Premium has completed, the device can be operated immediately.

6 Adjusting the display brightness

1. Open the Control Center in the Control Panel.
2. Select the Display tab.
3. Select a panel from the list. Only the local display (PP Link) and connected panels are shown in the list.
4. Set the desired brightness using the slider control.




Figure 93: Adjusting the display brightness

Information:

Changes to these settings are displayed online but are only noted by the system (and applied during the next restart) if the Control Center is closed with **OK**.

The configured brightness depends on the value configured in BIOS, i.e. until Windows is booted, the value set in BIOS is used. The value set in BIOS is only applied the first time the Control Center is opened.

7 Configuring a SATA RAID set using the internal RAID controller

The following software description applies to the internal RAID controller with QM77 chipset. The HM76 chipset does not provide RAID support.

Information:

B&R recommends using only drives of the same type in a SATA RAID set (hard disk with hard disk in a set, SSD with SSD in a set; CFast with CFast in a set).

Caution!

The maximum number of possible write cycles must be taken into consideration when setting up a RAID set with SSDs (with MLC technology).

In order to create a SATA RAID set and get into the "Configuration Utility", *SATA mode selection* must be set to *RAID* in the "Advanced - SATA configuration" menu.

The "Configuration Utility" in BIOS must be started in order to make the necessary settings. After POST, pressing <Ctrl+I> opens the RAID BIOS.

```

Intel(R) Rapid Storage Technology - Option ROM - 11.6.0.1624
Copyright(C) 2003-12 Intel Corporation. All Rights Reserved.

RAID Volumes:
ID Name      Level          Strip           Size  Status       Bootable
0  Mirror     RAID1(Mirror)  N/A             465.8GB Normal        Yes

Physical Devices:
ID Device    Model          Serial #        Size  Type/Status(Vol ID)
0   WDC       WD500LUCT-6   WD-WX21AB2X6150  465.7GB Member Disk(0)
2   WDC       WD500LUCT-6   WD-WX21AB2X6150  465.7GB Member Disk(0)

Press <CTRL-I> to enter Configuration Utility..

```

Figure 94: Configuration Utility - Boot

```

Intel(R) Rapid Storage Technology - Option ROM - 11.6.0.1624
Copyright(C) 2003-12 Intel Corporation. All Rights Reserved.

[ MAIN MENU ]
1. Create RAID Volume      4. Recovery Volume Options
2. Delete RAID Volume      5. Acceleration Options
3. Reset Disks to Non-RAID 6. Exit

[ DISK/VOLUME INFORMATION ]

RAID Volumes:
ID Name      Level          Strip           Size  Status       Bootable
0  Mirror     RAID1(Mirror)  N/A             465.8GB Normal        Yes

Physical Devices:
ID Device    Model          Serial #        Size  Type/Status(Vol ID)
0   WDC       WD500LUCT-6   WD-WX21AB2X6150  465.7GB Member Disk(0)
2   WDC       WD500LUCT-6   WD-WX21AB2P6063  465.7GB Member Disk(0)

[↑↓]-Select [ESC]-Exit [ENTER]-Select Menu

```

Figure 95: Configuration Utility - Overview

The following keys can be used once inside BIOS Setup:

Key	Function
Cursor ↑	Moves to the previous item
Cursor ↓	Moves to the next item
Enter	Selects an item or opens a submenu
ESC	Returns to the previous menu
Ctrl+E	Saves any changed settings and exits setup

Table 131: BIOS-relevant keys in the RAID Configuration Utility

7.1 Create RAID volume




Figure 96: Configuration Utility - Create RAID volume

Parameter	Function	Configuration options	Effect
Name	Option for entering the RAID name	Name with up to 16 characters	Assigns a name to the RAID volume
RAID level	Option for setting the RAID level	RAID0 (Stripes) RAID1 (Mirror) Recovery	Creates RAID0 Creates RAID1 Creates recovery RAID
Disks ¹⁾	Specifies the installed hard disks as either Master or Recovery	Master, Recovery	Defines the hard disks as Master or Recovery
Strip size ²⁾	Option for configuring the size of data blocks	4 KB, 8 KB, 16 KB, 32 KB, 64 KB, 128 KB	Configures the size of the data block
Capacity	Option for configuring the RAID capacity		Configures the memory size of the RAID
Sync ³⁾	Option for configuring RAID synchronization	N/A Continuous On request	Automatically synchronizes the RAID Manually synchronizes the RAID
Create volume	Creates the RAID volume	-	Creates the RAID volume

Table 132: Configuration Utility - Create RAID volume

- 1) This setting is only possible if *RAID level* is set to *Recovery*.
- 2) This setting is only possible if *RAID level* is set to *RAID0(Stripe)*.
- 3) This setting is only possible if *RAID level* is set to *Recovery*.

7.2 Delete RAID volume

The "Delete RAID volume" menu option can be used to format the RAID drive, making it non-RAID. The drive to be deleted must be selected and then deleted by pressing .

Information:

This option deletes all data on the drive, including the operating system.




Figure 97: Configuration Utility - Delete RAID volume

7.3 Reset disks to non-RAID

An existing RAID set can be deleted using the "Reset disks to Non-RAID" option. The RAID to be deleted must be selected and then deleted by pressing <SPACE> (<ENTER> to confirm).

Information:

Deleting a RAID set also deletes all of the data on the drive.




Figure 98: Configuration Utility - Reset disks to non-RAID

7.4 Recovery volume options

The "Recovery volume options" menu option can be used to enable/disable Recovery Disk and Master Disk.




Figure 99: Configuration Utility - Recovery volume options

Chapter 4 • Software

1 BIOS options

Information:

The following diagrams and BIOS menu items including descriptions refer to BIOS version 1.15. It is therefore possible that these diagrams and BIOS descriptions will not correspond with the BIOS version actually installed. In addition, the BIOS menu items provided depend on the system configuration.

1.1 General information

BIOS is an acronym for "Basic Input/Output System". It is the most basic standardized interface between the user and the system (hardware). The BIOS system used in this B&R Industrial PC was developed by American Megatrends Inc.

The BIOS Setup utility can be used to modify basic system configuration settings. These settings are stored in CMOS and EEPROM memory (as a backup).

CMOS data is buffered by a battery (if present) and continues to remain stored on the B&R Industrial PC even when the power is turned off (no 24 VDC supply).

1.2 BIOS Setup and boot procedure

BIOS is immediately activated when switching on the power supply or pressing the power button on the B&R Industrial PC. The system checks if the setup data from EEPROM memory is "OK". If the data is "OK", then it is transferred to CMOS. If the data is "Not OK", then the CMOS data is checked to see whether it is valid. An error message is output if the CMOS data contains errors, and the boot procedure can be continued by pressing <F1>. To prevent an error message from appearing at each restart, the BIOS Setup utility can be opened by pressing . The settings can then be re-saved.

BIOS reads the system configuration information, checks and configures the system with the Power-On Self-Test (POST).

When these "preliminaries" are finished, BIOS looks for an operating system on the available data storage devices (hard drive, floppy drive, etc.). BIOS then launches the operating system and hands over to it the control of system operations.

To enter BIOS Setup, the key must be pressed after the USB controller has been initialized as soon as the following message appears on the screen (during POST): "Press DEL to run SETUP".



Figure 100: Boot screen

1.2.1 BIOS Setup keys

The following keys are enabled during POST:

Information:

Key signals from USB keyboards will only be registered after the USB controller has been initialized.


Keys	Function
Del, F2	Opens the main BIOS Setup screen
F12	Network boot
F11	Opens the boot menu. This lists all bootable devices that are connected to the system. Selecting a device with cursor ↑, cursor ↓ and the pressing <ENTER> will boot from that device. 
<Pause>	Pauses POST. Pressing any other key resumes POST.

Table 133: BIOS-relevant keys for POST

The following keys can be used once inside BIOS Setup:

Key	Function
F1	Opens general help information
Cursor ↑	Moves to the previous item
Cursor ↓	Moves to the next item
Cursor ←	Moves to the previous item
Cursor →	Moves to the next item
+ -	Changes the setting for the selected function
Enter	Changes to the selected screen
Page ↑	Changes to the previous page
Page ↓	Changes to the next page
Pos 1	Jumps to the first BIOS menu item or object
End	Jumps to the last BIOS menu item or object
F2 / F3	Changes the colors of BIOS Setup
F7	Resets any changes
F9	Loads and configures CMOS default values for all BIOS settings
F10	Saves and exits
Esc	Exits a submenu

Table 134: BIOS-relevant keys

1.3 Main

The main BIOS Setup screen appears immediately after the button is pressed during startup.



Figure 101: Main

BIOS setting	Function	Configuration options	Effect
BIOS information			
Main BIOS version	Displays the BIOS version	None	-
OEM BIOS version	Displays the OEM BIOS version	None	-
Build date	Displays the date the BIOS was created	None	-
Board information			
Product revision	Displays the hardware revision of the CPU board	None	-
Serial number	Displays the serial number of the CPU board	None	-
Platform information	Displays information about the chipset, CPU board and main memory	Enter	Opens the submenu See "Platform information" on page 164
System date	The currently configured system date. This is buffered by the CMOS battery when the system is switched off.	Changes the system date	Sets the system date in the format Month:Day:Year (mm:dd:yyyy)
System time	The currently configured system time setting. This is buffered by the CMOS battery when the system is switched off.	Changes the system time	Sets the system time in the format Hour:Minute:Second (hh:mm:ss)

Table 135: Main - Configuration options

1.3.1 Platform information




Figure 102: Main - Platform information

BIOS setting	Function	Configuration options	Effect
Processor information			
Name	Displays the processor architecture	None	-
Brand string	Displays the processor type	None	-
Frequency	Displays the processor frequency	None	-
Processor ID	Displays the processor ID	None	-
Stepping	Displays the processor stepping version	None	-
Number of processors	Displays the number of processor cores/threads	None	-
Microcode revision	Displays the processor microcode revision	None	-
GT info	Displays GT information	None	-
IGFX VBIOS version	Displays the IGFX VBIOS version	None	-
Memory RC version	Displays the memory RC version	None	-
Total memory	Displays the system memory size	None	-
Memory frequency	Displays the RAM frequency	None	-
PCH information			
Name	Displays the platform controller hub	None	-
Intel PCH SKU name	Displays the chipset on the CPU board	None	-
Stepping	Displays the chipset stepping version	None	-
LAN PHY revision	Displays the LAN revision	None	-
ME FW version	Displays the Intel management engine firmware version	None	-
ME firmware SKU	Displays the Intel management stock-keeping unit version	None	-
SPI clock frequency			
DOFR support	Displays information about DOFR support	None	-
Read status clock frequency	Displays the read status clock frequency.	None	-
Write status clock frequency	Displays the write status clock frequency	None	-
Fast read status clock frequency	Displays the fast read status clock frequency	None	-

Table 136: Main - Platform information overview

1.4 Advanced




Figure 103: Advanced overview

BIOS setting	Function	Configuration options	Effect
Graphics configuration	Configures graphics settings	Enter	Opens the submenu See "Graphics configuration" on page 166
OEM features	Configures OEM features	Enter	Opens the submenu See "OEM features" on page 168
PCI configuration	Configures PCI devices	Enter	Opens the submenu See "PCI configuration" on page 187
PCI Express configuration	Configures PCI Express devices	Enter	Opens the submenu See "PCI Express configuration" on page 189
ACPI settings	Configures ACPI settings	Enter	Opens the submenu See "ACPI settings" on page 195
RTC wake settings	Configures the start time when switched off	Enter	Opens the submenu See "RTC wake settings" on page 196
CPU configuration	Configures CPU settings	Enter	Opens the submenu See "CPU configuration" on page 197
Chipset configuration	Configures chipset settings	Enter	Opens the submenu See "Chipset configuration" on page 200
SATA configuration	Configures SATA settings	Enter	Opens the submenu See "SATA configuration" on page 201
Memory configuration	Configures main memory settings	Enter	Opens the submenu See "Memory configuration" on page 204
USB configuration	Configures USB settings	Enter	Opens the submenu See "USB configuration" on page 207
Serial port console redirection	Configures the remote console	Enter	Opens the submenu See "Serial port console redirection" on page 211

Table 137: Advanced overview

1.4.1 Graphics configuration




Figure 104: Advanced - Graphics configuration

BIOS setting	Function	Configuration options	Effect
Primary display	Option for selecting the primary display device	Auto	Configures the display device automatically
		IGD	Uses the internal graphics chip on the CPU board as the display device
		PEG	Uses an external PCI Express graphics card connected to the x16 PEG port as the display device
		PCI	Uses the graphics chip of a connected graphics card as the display device
Internal graphics	Option for configuring the internal graphics chip	Auto	Enables the internal graphics chip
		Disabled	Disables the internal graphics chip
		Enabled	Enables the internal graphics chip
IGFX VBIOS version	Displays the IGFX BIOS version	None	-
GTT size	Option for setting the GTT size	1 MB	1 MB GTT
		2 MB	2 MB GTT
Aperture size	Option for configuring the maximum amount of RAM made available to the main memory when graphics memory is full	128 M	Reserves 128 MB
		256 M	Reserves 256 MB
		512 M	Reserves 512 MB
DVMT pre-allocated	Option for setting the fixed amount of memory used for the internal graphics controller	32 MB, 64 MB, 96 MB up to 1024 MB	Defines the fixed graphic memory as a value between 32 and 1024 MB
DVMT total gfx mem	Option for setting the amount of memory that can be used for the internal graphics controller. Memory over the permanently assigned graphics memory is assigned dynamically according to the DVMT 5.0 standard.	128 M	Allocates 128 MB of main memory
		256 M	Allocates 256 MB of main memory
		MAX	Allocates the entire main memory
Gfx low power mode	Option for setting the power saving function for the graphics controller	Enabled	Enables low power mode. The graphics controller does not operate at full speed.
		Disabled	Disables low power mode
Graphics performance analyzers	Option for enabling/disabling the Intel graphics performance analyzers	Enabled	Enables this function
		Disabled	Disables this function
Primary IGFX boot display	Option for defining the primary enabled display device during booting.	VBIOS default	Uses the default setting from IGFX BIOS
		CRT	Uses the CRT (cathode ray tube) channel
		LFP	Uses the LFP (local flat panel) channel
		EFP	Uses the EFP (external flat panel) channel

Table 138: Advanced - Graphics configuration options

BIOS setting	Function	Configuration options	Effect
	<p>Information:</p> <p>The numbering of EFP occurs dynamically depending on the DisplayPort interface (B/C/D).</p>	EFP2 EFP3	Uses the EFP2 (external flat panel 2) channel Uses the EFP3 (external flat panel 3) channel
Secondary IGFX boot display	<p>Option for defining the secondary enabled panel during POST</p> <p>Information:</p> <p>The numbering of EFP occurs dynamically depending on the DisplayPort interface (B/C/D).</p> <p>Information:</p> <p>After the BIOS boot screen, nothing more is shown on this display until the graphics driver is reloaded from the operating system.</p>	Disabled CRT LFP EFP EFP2 EFP3	Disables this function Only shows POST on one display Uses the CRT (cathode ray tube) channel Uses the LFP (local flat panel) channel Uses the EFP (external flat panel) channel Uses the EFP2 (external flat panel 2) channel Uses the EFP3 (external flat panel 3) channel
Active LFP configuration	<p>Option for selecting the active LFP (local flat panel) channel</p> <p>Information:</p> <p>This option has no effect on the Automation PC 910.</p>	No local flat panel Integrated LVDS	Does not use the LVDS channel Uses the integrated LVDS channel
Always try auto panel detect	This option first searches for EDID data in an external EEPROM to configure the LFP. If no EDID data is found, then the data selected under "Local flat panel type" is used.	No Yes	Disables this function Enables this function
Local flat panel type	This option can be used to set a predefined profile for the LVDS channel.	Auto VGA 1x18 (002h) VGA 1x18 (013h) SVGA 1x18 (01Ah) XGA 1x18 (006h) XGA 2x18 (007h) XGA 1x24 (008h) XGA 2x24 (012h) SXGA 2x24 (00Ah) SXGA 2x24 (018h) UXGA 2x24 (00Ch) Customized EDID 1 Customized EDID 2 Customized EDID 3	Automatic detection and configuration using the EDID data 640 x 480 640 x 480 800 x 600 1024 x 768 1024 x 768 1024 x 768 1024 x 768 1024 x 1024 1280 x 1024 1600 x 1200 User-defined profile User-defined profile User-defined profile
Display Port B interface	Option for selecting the display device that is connected to the DisplayPort interface	Disabled DisplayPort HDMI/DVI	Disables the DisplayPort interface Configures the DisplayPort interface as a DisplayPort interface Configures the DisplayPort interface as an HDMI/DVI interface
Display Port C interface	Option for selecting the display device that is connected to the monitor/panel option	Disabled DisplayPort HDMI/DVI	Disables the monitor/panel option Configures the monitor/panel option as a DisplayPort interface Configures the monitor/panel option as an HDMI/DVI interface
Display Port D interface	Option for selecting the display device that is connected to the monitor/panel interface	Disabled DisplayPort HDMI/DVI	Disables the monitor/panel interface Configures the monitor/panel interface as a DisplayPort interface Configures the monitor/panel interface as an HDMI/DVI interface
Display mode persistence	"Display mode persistence" means that the operating system can remember and restore past display configurations. For example, a dual DVI configuration is automatically restored when both DVI monitors are reconnected, even if only one of them was connected and enabled during a previous boot.	Disabled Enabled	Disables this function Enables this function

Table 138: Advanced - Graphics configuration options

1.4.2 OEM features




Figure 105: Advanced - OEM features

BIOS setting	Function	Configuration options	Effect
Main BIOS version	Displays the installed B&R BIOS version	None	-
OEM BIOS version		None	-
MTCX	Displays the installed MTCX version	None	-
ETH1 MAC address	Displays the assigned MAC address for the ETH1 interface	None	-
ETH2 MAC address	Displays the assigned MAC address for the ETH2 interface	None	-
Real-time environment	Configures settings for real-time operating systems such as ARwin	Disabled Enabled	Disables this function Disables hyper-threading, turbo mode and EIST. Also disables ASPM and the IRQ of root ports 2 and 3.
TI XIO2001 PCI bridge ¹⁾	Option for setting DMA access	Enabled Disabled	Optimizes DMA access Disables this function
Super I/O configuration	Configures special interface settings	Enter	Opens the submenu See "Super I/O configuration" on page 169
CPU board features	Displays device-specific information for the CPU board	Enter	Opens the submenu See "CPU board features" on page 170
System board features	Displays device-specific information for the system unit	Enter	Opens the submenu See "System board features" on page 171
Memory module features	Displays device-specific information for the main memory	Enter	Opens the submenu See "Memory module features" on page 174
Display board features	Displays device-specific information about the Panel PC display.	Enter	Opens the submenu See "Display board features" on page 175
Bus unit features	Displays device-specific information for the bus unit	Enter	Opens the submenu See "Bus unit features" on page 178
I/O board 1 features ²⁾	Displays device-specific information for interface option 1	Enter	Opens the submenu See "I/O board 1 features" on page 179
I/O board 2 features ²⁾	Displays device-specific information for interface option 2	Enter	Opens the submenu See "I/O board 2 features" on page 181
Fan unit features ³⁾	Displays device-specific information for the fan kit	Enter	Opens the submenu See "Fan unit features" on page 182

Table 139: Advanced - OEM features screen

BIOS setting	Function	Configuration options	Effect
Slide-in 1 features ⁴⁾	Displays device-specific information for slide-in drive 1	Enter	Opens the submenu See "Slide-in 1 features" on page 184
Panel control features	Displays device-specific information for the connected panel	Enter	Opens the submenu See "Panel control features" on page 186

Table 139: Advanced - OEM features screen

- 1) This option is only shown if a bus unit with a PCI slot is installed.
- 2) This option is only shown if the corresponding option is installed in the system unit.
- 3) This option is only shown if a fan kit is installed in the system unit.
- 4) This option is only shown if a slide-in drive is installed in the bus unit.

1.4.2.1 Super I/O configuration




Figure 106: Advanced - OEM features - Super I/O configuration

BIOS setting	Function	Configuration options	Effect
Serial port A	Settings for the COM1 serial interface	Enabled	Enables the interface
		Disabled	Disables the interface
Device settings	Displays the I/O address and interrupt of the COM1 interface	None	-
Serial port B	Settings for the COM2 serial interface	Enabled	Enables the interface
		Disabled	Disables the interface
Device settings	Displays the I/O address and interrupt for the COM2 serial interface in the system.	None	-
Serial port C	Setting for the onboard touch screen.	Enabled	Enables the interface
		Disabled	Disables the interface
Device settings	Displays the I/O address and the interrupt for the onboard touch screen.	None	-
Serial port D	Setting for the touch screen of a connected panel.	Enabled	Enables the interface
		Disabled	Disables the interface
Device settings	Displays the I/O address and the interrupt for the touch screen of a connected panel.	None	-
Serial port E ¹⁾	Setting for the RS232 IF option in IF option slot 1	Enabled	Enables the interface
		Disabled	Disables the interface
Device settings	Displays the I/O address and interrupt for the RS232 IF option in IF option slot 1	None	-
Serial port F ¹⁾	Setting for the RS232 IF option in IF option slot 2	Enabled	Enables the interface
		Disabled	Disables the interface
Device settings	Displays the I/O address and interrupt for the RS232 IF option in IF option slot 2	None	-

Table 140: Advanced - OEM features - Super I/O configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
CAN controller ¹⁾	Setting for the CAN IF option	Enabled	Enables the interface
		Disabled	Disables the interface
Device settings	Displays the I/O address and interrupt for the CAN IF option	None	-

Table 140: Advanced - OEM features - Super I/O configuration - Configuration options

1) This option is only shown if the corresponding IF option is installed in the system unit.

1.4.2.2 CPU board features




Figure 107: Advanced - OEM features - CPU board features

BIOS setting	Function	Configuration options	Effect
Device ID	Displays the device ID of the CPU board	None	-
Hardware revision	Displays the hardware revision of the CPU board	None	-
Product name	Displays the B&R model number	None	-
Temperature values	Displays current temperature values	Enter	Opens the submenu See "Temperature values" on page 171

Table 141: Advanced - OEM features - CPU board features

1.4.2.2.1 Temperature values




Figure 108: Advanced - OEM features - CPU board features - Temperature values

BIOS setting	Function	Configuration options	Effect
Sensor 1	Displays the current temperature of sensor 1 (CPU) in °C and °F	None	-

Table 142: Advanced - OEM features - CPU board features - Temperature values

1.4.2.3 System board features



Figure 109: Advanced - OEM features - System board features

BIOS setting	Function	Configuration options	Effect
Device ID	Displays the device ID of the CPU board	None	-
Compatibility ID	Displays the version of the device within the same B&R device ID. This ID is needed for Automation Runtime.	None	-
Vendor ID	Displays the vendor ID	None	-
Hardware revision	Displays the hardware revision of the CPU board	None	-
Serial number	Displays the B&R serial number	None	-
Product name	Displays the B&R model number	None	-
Parent device ID	Displays the manufacturer number	None	-
Parent compatibility ID	Displays the manufacturer ID	None	-
User serial ID	Displays the user serial ID. This 8-digit hexadecimal value can be freely specified by the user (e.g. to give the device a unique ID) and can only be changed using the "B&R Control Center" included with the ADI driver.	None	-
Statistical values	Displays statistical values	Enter	Opens the submenu See "Statistical values" on page 172
Temperature values	Displays current temperature values	Enter	Opens the submenu See "Temperature values" on page 173
Voltage control	Displays current battery properties	Enter	Opens the submenu See "Voltage values" on page 174

Table 143: Advanced - OEM features - System board features

1.4.2.3.1 Statistical values



Figure 110: Advanced - OEM features - System board features - Statistical values

BIOS setting	Function	Configuration options	Effect
Total hours	Displays the runtime in hours	None	-
Power on cycles	Displays the number of power-on cycles. Each restart increases the counter by one.	None	-

Table 144: Advanced - OEM features - System board features - Statistical values

1.4.2.3.2 Temperature values




Figure 111: Advanced - OEM features - System board features - Temperature values

BIOS setting	Function	Configuration options	Effect
Sensor 1	Displays the current temperature of sensor 1 (board) in °C and °F	None	-
Sensor 2	Displays the current temperature of sensor 2 (chipset) in °C and °F	None	-
Sensor 3	Displays the current temperature of sensor 3 (board power supply) in °C and °F	None	-
Sensor 4	Displays the current temperature of sensor 4 (CFast) in °C and °F	None	-

Table 145: Advanced - OEM features - System board features - Temperature values

1.4.2.3 Voltage values




Figure 112: Advanced - OEM features - System board features - Voltage values

BIOS setting	Function	Configuration options	Effect
Battery voltage	Displays the battery voltage in volts	None	-
Battery state	Displays the status of the battery	None	-

Table 146: Advanced - OEM features - System board features - Voltage values

1.4.2.4 Memory module features



Figure 113: Advanced - OEM features - Memory module features

BIOS setting	Function	Configuration options	Effect
Socket 1 module			
Serial number	Displays the B&R serial number	None	-
Product name	Displays the product number	None	-
Socket 2 module			
Serial number	Displays the B&R serial number	None	-
Product name	Displays the product number	None	-

Table 147: Advanced - OEM features - Memory module features

1.4.2.5 Display board features



Figure 114: Advanced - OEM features - Display board features

BIOS setting	Function	Configuration options	Effect
Device ID	Displays the device ID of the display unit	None	-
Compatibility ID	Displays the version of the device within the same B&R device ID. This ID is needed for Automation Runtime.	None	-
Vendor ID	Displays the vendor ID	None	-
Hardware revision	Displays the hardware revision of the display unit	None	-
Serial number	Displays the B&R serial number	None	-
Product name	Displays the B&R model number	None	-
Parent device ID	Displays the manufacturer number	None	-
Parent compatibility ID	Displays the manufacturer ID	None	-
Statistical values	Displays statistical values	Enter	Opens the submenu See "Statistical values" on page 176
Temperature values	Displays current temperature values	Enter	Opens the submenu See "Temperature values" on page 176
Panel #15	Displays the panel properties of the display unit	Enter	Opens the submenu See "Panel #15" on page 177

Table 148: Advanced - OEM features - Display board features

1.4.2.5.1 Statistical values




Figure 115: Advanced - OEM features - Display board features - Statistical values

BIOS setting	Function	Configuration options	Effect
Total hours	Displays the runtime in hours	None	-
Power on cycles	Displays the number of power-on cycles. Each restart increases the counter by one.	None	-

Table 149: Advanced - OEM features - Display board features - Statistical values

1.4.2.5.2 Temperature values




Figure 116: Advanced - OEM features - Display board features - Temperature values

BIOS setting	Function	Configuration options	Effect
Sensor 1	Displays the current temperature of sensor 1 (display unit) in °C and °F	None	-

Table 150: Advanced - OEM features - Display board features - Temperature values

1.4.2.5.3 Panel #15




Figure 117: Advanced - OEM features - Display board features - Panel #15

BIOS setting	Function	Configuration options	Effect
Version	Displays the firmware revision.	None	-
Brightness	Setting for the brightness of the display unit	0 to 100	Sets the brightness (in %) of the selected panel. Settings take effect immediately.
Fan speed	Displays the fan speed of the display unit	None	-
Keys/LEDs	Displays the available keys and LEDs for the display unit	None	-
Temperature	Displays the temperature of the display unit in °C and °F	None	-

Table 151: Advanced - OEM features - Display board features - Panel #15

1.4.2.6 Bus unit features



Figure 118: Advanced - OEM features - Bus unit features

BIOS setting	Function	Configuration options	Effect
Device ID	Displays the device ID of the bus unit	None	-
Compatibility ID	Displays the version of the device within the same B&R device ID. This ID is needed for Automation Runtime.	None	-
Vendor ID	Displays the vendor ID	None	-
Hardware revision	Displays the hardware revision of the bus unit	None	-
Serial number	Displays the B&R serial number	None	-
Product name	Displays the B&R model number	None	-
Parent device ID	Displays the manufacturer number	None	-
Parent compatibility ID	Displays the manufacturer ID	None	-
Statistical values	Displays statistical values	Enter	Opens the submenu See "Statistical values" on page 179

Table 152: Advanced - OEM features - Bus unit features

1.4.2.6.1 Statistical values




Figure 119: Advanced - OEM features - Bus unit features - Statistical values

BIOS setting	Function	Configuration options	Effect
Total hours	Displays the runtime in hours	None	-
Power on cycles	Displays the number of power-on cycles. Each restart increases the counter by one.	None	-

Table 153: Advanced - OEM features - Bus unit features - Statistical values

1.4.2.7 I/O board 1 features



Figure 120: Advanced - OEM features - I/O board 1 features

BIOS setting	Function	Configuration options	Effect
Device ID	Displays the device ID of IF option 1	None	-
Compatibility ID	Displays the version of the device within the same B&R device ID. This ID is needed for Automation Runtime.	None	-
Vendor ID	Displays the vendor ID	None	-
Hardware revision	Displays the hardware revision of IF option 1	None	-
Serial number	Displays the B&R serial number	None	-
Product name	Displays the B&R model number	None	-
Parent device ID	Displays the manufacturer number	None	-
Parent compatibility ID	Displays the manufacturer ID	None	-
Statistical values	Displays statistical values	Enter	Opens the submenu See "Statistical values" on page 180

Table 154: Advanced - OEM features - I/O board 1 features

1.4.2.7.1 Statistical values




Figure 121: Advanced - OEM features - I/O board 1 features - Statistical values

BIOS setting	Function	Configuration options	Effect
Total hours	Displays the runtime in hours	None	-
Power on cycles	Displays the number of power-on cycles. Each restart increases the counter by one.	None	-

Table 155: Advanced - OEM features - I/O board 1 features - Statistical values

1.4.2.8 I/O board 2 features



Figure 122: Advanced - OEM features - I/O board 2 features

BIOS setting	Function	Configuration options	Effect
Device ID	Displays the device ID of IF option 2	None	-
Compatibility ID	Displays the version of the device within the same B&R device ID. This ID is needed for Automation Runtime.	None	-
Vendor ID	Displays the vendor ID	None	-
Hardware revision	Displays the hardware revision of IF option 2	None	-
Serial number	Displays the B&R serial number	None	-
Product name	Displays the B&R model number	None	-
Parent device ID	Displays the manufacturer number	None	-
Parent compatibility ID	Displays the manufacturer ID	None	-
Statistical values	Displays statistical values	Enter	Opens the submenu See "Statistical values" on page 182

Table 156: Advanced - OEM features - I/O board 2 features

1.4.2.8.1 Statistical values



Figure 123: Advanced - OEM features - I/O board 2 features - Statistical values

BIOS setting	Function	Configuration options	Effect
Total hours	Displays the runtime in hours	None	-
Power on cycles	Displays the number of power-on cycles. Each restart increases the counter by one.	None	-

Table 157: Advanced - OEM features - I/O board 2 features - Statistical values

1.4.2.9 Fan unit features




Figure 124: Advanced - OEM features - Fan unit features

BIOS setting	Function	Configuration options	Effect
Device ID	Displays the device ID of the fan kit	None	-
Compatibility ID	Displays the version of the device within the same B&R device ID. This ID is needed for Automation Runtime.	None	-
Vendor ID	Displays the vendor ID	None	-
Hardware revision	Displays the hardware revision of the fan kit	None	-
Serial number	Displays the B&R serial number	None	-
Product name	Displays the B&R model number	None	-
Parent device ID	Displays the manufacturer number	None	-
Parent compatibility ID	Displays the manufacturer ID	None	-
Fan control	Option for setting the fan control	Auto Minimum 25% 50% 75% Maximum	Automatic fan control Sets the minimum revolution speed. If the temperature increases, however, the fan adjusts its speed automatically to prevent critical temperatures from being exceeded. Sets 25% of the maximum revolution speed Sets 50% of the maximum revolution speed Sets 75% of the maximum revolution speed Sets the maximum revolution speed
Statistical values	Displays statistical values	Enter	Opens the submenu See "Statistical values" on page 183
RPM values	Displays the speed (in RPM) of the individual fans in the fan kit	Enter	Opens the submenu See "RPM values" on page 184

Table 158: Advanced - OEM features - Fan unit features

1.4.2.9.1 Statistical values




Figure 125: Advanced - OEM features - Fan unit features - Statistical values

BIOS setting	Function	Configuration options	Effect
Total hours	Displays the runtime in hours	None	-
Power on cycles	Displays the number of power-on cycles. Each restart increases the counter by one.	None	-

Table 159: Advanced - OEM features - Fan unit features - Statistical values

1.4.2.9.2 RPM values




Figure 126: Advanced - OEM features - Fan unit features - RPM values

BIOS setting	Function	Configuration options	Effect
Fan 1	Displays the current speed of fan 1 in RPM	None	-
Fan 2	Displays the current speed of fan 2 in RPM	None	-
Fan 3	Displays the current speed of fan 3 in RPM	None	-
Fan 4	Displays the current speed of fan 4 in RPM	None	-

Table 160: Advanced - OEM features - Fan unit features - RPM values

1.4.2.10 Slide-in 1 features



Figure 127: Advanced - OEM Features - Slide-in 1 features

BIOS setting	Function	Configuration options	Effect
Device ID	Displays the device ID of the slide-in 1 drive	None	-
Compatibility ID	Displays the version of the device within the same B&R device ID. This ID is needed for Automation Runtime.	None	-
Vendor ID	Displays the vendor ID	None	-
Hardware revision	Displays the hardware revision of the slide-in drive	None	-
Serial number	Displays the B&R serial number	None	-
Product name	Displays the B&R model number	None	-
Parent device ID	Displays the manufacturer number	None	-
Parent compatibility ID	Displays the manufacturer ID	None	-
User serial ID	Displays the user serial ID. This 8-digit hexadecimal value can be freely specified by the user (e.g. to give the device a unique ID) and can only be changed using the "B&R Control Center" included with the ADI driver.	None	-
Temperature values	Displays current temperature values	Enter	Opens the submenu See "Temperature values" on page 185

Table 161: Advanced - OEM Features - Slide-in 1 features

1.4.2.10.1 Temperature values




Figure 128: Advanced - OEM features - Slide-in 1 features - Temperature values

BIOS setting	Function	Configuration options	Effect
Sensor 1	Displays the current temperature of sensor 1 (slide-in 1 drive) in °C and °F	None	-

Table 162: Advanced - OEM features - Slide-in 1 features - Temperature values

1.4.2.11 Panel control features




Figure 129: Advanced - OEM features - Panel control features

BIOS setting	Function	Configuration options	Effect
Panel #X	Displays the panel properties of the connected panel	Enter	Opens the submenu See "Panel #X" on page 186

Table 163: Advanced - OEM features - Panel control features

1.4.2.11.1 Panel #X




Figure 130: Advanced - OEM features - Panel control features - Panel #X

BIOS setting	Function	Configuration options	Effect
Version	Displays the firmware version of the SDR controller	None	-
Brightness	Setting for the brightness of the panel	0 to 100	Sets the brightness (in %) of the selected panel. Settings take effect immediately.
Fan speed	Displays the fan speed of the panel	None	-
Keys/LEDs	Displays the available keys and LEDs for the panel	None	-
Temperature	Displays the temperature of the panel in °C and °F	None	-

Table 164: Advanced - OEM features - Panel control features - Panel #X

1.4.3 PCI configuration



Figure 131: Advanced - PCI configuration

BIOS setting	Function	Configuration options	Effect
Above 4G decoding	Option for enabling/disabling 64-bit capable devices to decode them in the address space above 4 GB (only if the system supports 64-bit decoding)	Disabled	Disables this function
		Enabled	Enables this function
PCI latency timer	Option for controlling how long (in PCI ticks) one PCI bus card can continue to use the master after another PCI card has requested access	32 PCI bus clocks to 248 PCI bus clocks	Manually sets the value in PCI ticks
VGA palette snoop	Option for supporting graphics cards with 256 colors. This option should only be set to "Enabled" if colors are not displayed correctly.	Disabled	Disables this function
		Enabled	Enables this function
PERR# generation	Option for generating a PERR signal (parity error). This signal indicates a data parity error one cycle after PAR.	Disabled	Disables this function
		Enabled	Enables this function
SERR# generation	Option for generating a SERR signal (system error). This signal indicates a data error or other type of system error when executing a special cycle command.	Disabled	Disables this function
		Enabled	Enables this function
PIRQ routing & IRQ reservation	Configures PIRQ routing	Enter	Opens the submenu See "PIRQ routing & IRQ reservation" on page 188

Table 165: Advanced - PCI configuration - Configuration options

1.4.3.1 PIRQ routing & IRQ reservation




Figure 132: Advanced - PCI configuration - PIRQ routing & IRQ reservation

BIOS setting	Function	Configuration options	Effect
PIRQA	Option for configuring PIRQ A	Auto	Automatic assignment by BIOS and the operating system
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Manual assignment
PIRQB	Option for configuring PIRQ B	Auto	Automatic assignment by BIOS and the operating system
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Manual assignment
PIRC	Option for configuring PIRQ C	Auto	Automatic assignment by BIOS and the operating system
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Manual assignment
PIRQD	Option for configuring PIRQ D	Auto	Automatic assignment by BIOS and the operating system
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Manual assignment
PIRQE	Option for configuring PIRQ E	Auto	Automatic assignment by BIOS and the operating system
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Manual assignment
PIRF	Option for configuring PIRQ F	Auto	Automatic assignment by BIOS and the operating system
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Manual assignment
PIRG	Option for configuring PIRQ G	Auto	Automatic assignment by BIOS and the operating system
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Manual assignment
PIRH	Option for configuring PIRQ H	Auto	Automatic assignment by BIOS and the operating system
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Manual assignment
Reserve legacy interrupt 1	The interrupt reserved here is not made available to a PCI or PCI Express device.	None	No interrupt assigned
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Reserves IRQx
Reserve legacy interrupt 2	The interrupt reserved here is not made available to a PCI or PCI Express device.	None	No interrupt assigned
		IRQ3, IRQ4, IRQ5, IRQ6, IRQ10, IRQ11, IRQ14, IRQ15	Reserves IRQx

Table 166: Advanced - PCI configuration - PIRQ routing & IRQ reservation - Configuration options

1.4.4 PCI Express configuration




Figure 133: Advanced - PCI Express configuration

BIOS setting	Function	Configuration options	Effect
PCI Express settings	Configures PCI Express settings	Enter	Opens the submenu See "PCI Express settings" on page 190
PCI Express GEN 2 settings	Configures PCI Express GEN2 settings	Enter	Opens the submenu See "PCI Express GEN 2 settings" on page 191
PCI Express graphics (PEG) port	Configures PCI Express graphics settings	Enter	Opens the submenu See "PCI Express graphics (PEG) port" on page 192
PCI Express root port 0	Configures PCI Express settings on port 0	Enter	Opens the submenu See "PCI Express root port" on page 194
PCI Express root port 1	Configures PCI Express settings on port 1	Enter	Opens the submenu See "PCI Express root port" on page 194
PCI Express root port 2	Configures PCI Express settings on port 2	Enter	Opens the submenu See "PCI Express root port" on page 194
PCI Express root port 3	Configures PCI Express settings on port 3	Enter	Opens the submenu See "PCI Express root port" on page 194
PCI Express root port 4	Configures PCI Express settings on port 4	Enter	Opens the submenu See "PCI Express root port" on page 194
PCI Express root port 5	Configures PCI Express settings on port 5	Enter	Opens the submenu See "PCI Express root port" on page 194
PCI Express root port 6	Configures PCI Express settings on port 6	Enter	Opens the submenu See "PCI Express root port" on page 194

Table 167: Advanced - PCI Express configuration - Menu

1.4.4.1 PCI Express settings




Figure 134: Advanced - PCI Express configuration - PCI Express settings

BIOS setting	Function	Configuration options	Effect
Relaxed ordering	Option for enabling/disabling relaxed ordering	Disabled	Disables this function
		Enabled	Enables this function
Extended tag	Option for enabling/disabling the extended tag	Disabled	Disables this function Only 5 bits can be used.
		Enabled	Enables this function Devices with 8 bits in the requester transaction ID field can be used.
No snoop	Option for enabling/disabling the "No snoop" option	Disabled	Disables this function
		Enabled	Enables this function
Maximum payload	Option for setting the maximum surface packet size for data transfers	Auto	Automatically assigns the packet size
		128 bytes to 4096 bytes	Manual maps the packet size
Maximum read request	Option for setting the maximum read request	Auto	Automatic assignment
		128 bytes to 4096 bytes	Manual assignment
ASPM ¹⁾	Option for configuring a power saving function (L0s/L1) for PCIe slots if they do not require full power	Disabled	Disables the energy saving function
		Auto	Maximum energy savings. The energy saving function is set to L0 or L1.
		Force L0s	Enables L0 mode
Extended synth	Option for setting an extended synchronization pattern to improve system performance	Disabled	Disables this function
		Enabled	Enables this function
Link training retry	Option for defining the number of times the software should attempt to reroute a link if the previous training attempt was unsuccessful	Disabled	Disables this function
		2	2 link training attempts
		3	3 link training attempts
		5	5 link training attempts
Link training timeout (μS)	Option for defining how many microseconds the software waits before the link training bit in the link status register is queried	10 to 1000	Time setting in μs
Unpopulated links	Option for enabling/disabling PCIe slots where no devices are connected	Keep link on	Keeps PCIe slots where no devices are connected enabled
		Disable link	Disables PCIe slots where no devices are connected to save power

Table 168: Advanced - PCI Express configuration - PCI Express settings - Configuration options

1) ASPM = Active state power management.

1.4.4.2 PCI Express GEN 2 settings



Figure 135: Advanced - PCI Express configuration - PCI Express GEN 2 settings

BIOS setting	Function	Configuration options	Effect
Completion timeout	Option for allowing software to modify the completion timeout value if supported by device functions	Default	Timeout range: 50 µs - 50 ms
		Shorter	The software uses shorter timeout ranges than are supported by the hardware.
		Longer	The software uses longer timeout ranges than are supported by the hardware.
		Disabled	Disables this function
ARI forwarding	If supported by hardware and set to "Enabled", the downstream port disables its traditional "Device number" field being 0 enforcement when turning a Type1 configuration request into a Type0 configuration request, permitting access to extended functions in an ARI device immediately below the port.	Disabled	Disables this function
		Enabled	Enables this function
AtomicOp requester enable	Option for enabling/disabling the AtomicOp requester	Disabled	Disables this function
		Enabled	Enables this function AtomicOp queries are only initiated if the bus master enable bit is set in the command register.
AtomicOp egress blocking	Option for enabling/disabling AtomicOp egress blocking	Disabled	Disables this function
	If supported by hardware and set to "Enabled", outbound AtomicOp requests via egress ports will be locked.	Enabled	Enables this function Blocks outbound AtomicOp requests via the egress port
IDO request enable	If supported by hardware and set to "Enabled", this option permits setting the number of ID-based ordering (IDO) bit (Attribute[2]) requests to be initiated.	Disabled	Disables this function
		Enabled	Enables this function
IDO completion enable	If supported by hardware and set to "Enabled", this option permits setting the number of ID-based ordering (IDO) bit (Attribute[2]) requests to be initiated.	Disabled	Disables this function
		Enabled	Enables this function
LTR mechanism enable	If supported by hardware and set to "Enabled", this enables the Latency Tolerance Reporting (LTR) mechanism.	Disabled	Disables this function
		Enabled	Enables this function
End-End TLP prefix blocking	If supported by hardware and set to "Enabled", this function will block forwarding of TLPs containing End-End TLP prefixes.	Disabled	Disables this function
		Enabled	Enables this function
Target link speed	If supported by hardware and set to "Force to 2.5 GT/s" for downstream ports, this sets an upper limit on Link operational speed by redistricting the values advertised by the upstream component in its training sequences. When "Auto" is selected, hardware-initialized data will be used.	Auto	TBD
		Force to 2.5 GT/s	TBD
		Force to 5.0 GT/s	TBD

Table 169: Advanced - PCI Express configuration - PCI Express GEN 2 settings - Configuration options

BIOS setting	Function	Configuration options	Effect
Clock power management	If supported by hardware and set to "Enabled", the device is permitted to use the CLKREQ# signal for power management of the Link clock in accordance with the protocol defined in the appropriate form factor specification.	Disabled	Disables this function
		Enabled	Enables this function
Compliance SOS	If supported by hardware and set to "Enabled", this will force LTSSM to send SKP ordered sets between sequences when sending compliance patterns or modified compliance patterns.	Disabled	Disables this function
		Enabled	Enables this function
Hardware autonomous width	If supported by hardware and set to "Disabled", this will disable the hardware's ability to change link width except width size reduction for the purpose of correcting unstable link operation.	Disabled	Disables this function
		Enabled	Enables this function
Hardware autonomous speed	If supported by hardware and set to "Disabled", this will disable the hardware's ability to change link speed except speed size reduction for the purpose of correcting unstable link operation.	Disabled	Disables this function The PCIe device can no longer change the link speed except to correct unstable operation.
		Enabled	Enables this function

Table 169: Advanced - PCI Express configuration - PCI Express GEN 2 settings - Configuration options

1.4.4.3 PCI Express graphics (PEG) port



Figure 136: Advanced - PCI Express configuration - PCI Express graphics (PEG) port

BIOS setting	Function	Configuration options	Effect
PCI Express graphics (PEG) port	Option for configuring the PCI Express graphics port	Disabled	Disables internal PEG interface devices. Devices connected to the PEG port are not detected.
		Enabled	Enables internal PEG interface devices even if no device is detected on the PEG port
		Auto	Disables internal PEG interface devices if no device is detected on the PEG port
PEG root port configuration	Option for selecting the root port configuration on the 16 PCIe channels of the PEG port	1 x 16	Configuration with 1 x 16
		2 x 8	Configuration with 2 x 8
		1 x 8 + 2 x 4	Configuration with 1 x 8 and 2 x 4
PEG0	Displays the mode in which the device connected to the PEG0 port is being operated	None	-
PEG0 speed	Option for setting the maximum transfer rate of the PEG0 port	Auto	Selects the maximum transfer rate
		Gen1	Maximum transfer rate = 2.5 GT/s
		Gen2	Maximum transfer rate = 5 GT/s
		Gen3	Maximum transfer rate = 8 GT/s
PEG0 ASPM ¹⁾	Option for configuring a power saving function for the PEG0 port if it does not require full power	Disabled	Disables this function
		Auto	Automatic assignment by BIOS and the operating system
		ASPM L0s	Enables the L0 energy saving function

Table 170: Advanced - PCI Express configuration - PCI Express graphics (PEG) port - Configuration options

BIOS setting	Function	Configuration options	Effect
		ASPM L1	Enables the L1 energy saving function. Power consumption is lower than with L0, but the exit latency is higher.
		ASPM L0sL1	Automatic assignment of L0s or L1 power saving function by the PCIe device
ASPM L0s ²⁾	Option for configuring the L0 power saving function	Disabled	Disables this function
		Root port only	Enables the power saving function for the root port
		Endpoint only	Enables the power saving function for the endpoint port
		Both root and endpoint ports	Enables the power saving function for the root and endpoint ports
PEG1	Displays the mode in which the device connected to the PEG1 port is being operated.	None	-
PEG1 speed	Option for setting the maximum transfer rate for the PEG1 port	Auto	Selects the maximum transfer rate
		Gen1	Maximum transfer rate = 2.5 GT/s
		Gen2	Maximum transfer rate = 5 GT/s
		Gen3	Maximum transfer rate = 8 GT/s
PEG1 ASPM ¹⁾	Option for configuring a power saving function for the PEG1 port if it does not require full power	Disabled	Disables this function
		Auto	Automatic assignment by BIOS and the operating system
		ASPM L0s	Enables the L0 energy saving function
		ASPM L1	Enables the L1 energy saving function. Power consumption is lower than with L0, but the exit latency is higher.
		ASPM L0sL1	Automatic assignment of L0s or L1 power saving function by the PCIe device
ASPM L0s ³⁾	Option for configuring the L0 power saving function	Disabled	Disables this function
		Root port only	Enables the power saving function for the root port
		Endpoint only	Enables the power saving function for the endpoint port
		Both root and endpoint ports	Enables the power saving function for the root and endpoint ports
PEG2	Displays the mode in which the device connected to the PEG2 port is operated.	None	-
PEG2 speed	Option for setting the maximum transfer rate for the PEG2 port	Auto	Selects the maximum transfer rate
		Gen1	Maximum transfer rate = 2.5 GT/s
		Gen2	Maximum transfer rate = 5 GT/s
		Gen3	Maximum transfer rate = 8 GT/s
PEG2 ASPM ¹⁾	Option for configuring a power saving function for the PEG2 port if it does not require full power	Disabled	Disables this function
		Auto	Automatic assignment by BIOS and the operating system
		ASPM L0s	Enables the L0 energy saving function
		ASPM L1	Enables the L1 energy saving function. Power consumption is lower than with L0, but the exit latency is higher.
		ASPM L0sL1	Automatic assignment of L0s or L1 power saving function by the PCIe device
ASPM L0s ⁴⁾	Option for configuring the L0 power saving function	Disabled	Disables this function
		Root port only	Enables the power saving function for the root port
		Endpoint only	Enables the power saving function for the endpoint port
		Both root and endpoint ports	Enables the power saving function for the root and endpoint ports
Detect non-compliant device	Option for detecting incompatible PCI Express devices on the PEG port	Disabled	Disables this function
		Enabled	Enables this function Even incompatible PCI Express devices are detected on the PEG port.
De-emphasis control	Option for configuring de-emphasis on the PEG port	-6 dB	-6 dB de-emphasis
		-3.5 dB	-3.5 dB de-emphasis

Table 170: Advanced - PCI Express configuration - PCI Express graphics (PEG) port - Configuration options

1) ASPM = Active state power management.

2) This setting is only possible if PEG0 ASPM is set to ASPM L0s or ASPM L0sL1.

3) This setting is only possible if PEG1 ASPM is set to ASPM L0s or ASPM L0sL1.

4) This setting is only possible if PEG2 ASPM is set to ASPM L0s or ASPM L0sL1.

1.4.4.4 PCI Express root port

Warning!

Improper settings can cause instability or device problems. It is therefore strongly recommended that these settings only be changed by experienced users.




Figure 137: Advanced - PCI Express configuration - PCI Express root port

BIOS setting	Function	Configuration options	Effect
PCI Express root port x	Option for enabling/disabling the PCI Express root port	Enabled Disabled	Enables PCI Express root port 1 Disables PCI Express root port 1 and 2
ASPM	<i>Active state power management</i> Option for configuring a power saving function (L0s/L1) for PCIe devices if they do not require full power	Disabled L0s L1 L0sL1 Auto	Disables this function Enables the L0 energy saving function Enables the L1 energy saving function. Power consumption is lower than with L0, but the exit latency is higher. Automatic assignment of L0s or L1 power saving function by the PCIe device Automatic assignment by BIOS and the operating system
URR	<i>Unsupported Request (UR) reporting</i> Option for reporting unsupported requests. Logging of error messages received by the root port is controlled exclusively by the root control register.	Enabled Disabled	Enables this function Disables this function
FER	<i>Fatal error reporting</i> Option for reporting fatal errors. All of the functions of a multifunction device will be monitored. The report for the root port takes place internally inside the root complex.	Enabled Disabled	Enables this function Disables this function
NFER	<i>Non-fatal error reporting</i> Option for reporting non-fatal errors. All of the functions of a multifunction device will be monitored. The report for the root port takes place internally inside the root complex.	Enabled Disabled	Enables this function Disables this function
CER	<i>Correctable error reporting</i> Option for reporting non-fatal errors. All of the functions of a multifunction device will be monitored. The report for the root port takes place internally inside the root complex.	Enabled Disabled	Enables this function Disables this function
CTO	<i>PCI Express completion timer T0</i>	Enabled	Enables this function

Table 171: Advanced - PCI Express configuration - PCI Express root port - Configuration options

BIOS setting	Function	Configuration options	Effect
	Option for enabling/disabling the PCI Express completion timer Information: This setting should be set to "Enabled" if the system detected an ROB (processor reorder buffer) timeout.	Disabled	Disables this function
SEFE	<i>System error on fatal error</i> Option for generating a system error if a fatal error is registered by a device on the root port or by the root port itself	Enabled Disabled	Enables this function Disables this function
SENFE	<i>System error on non-fatal error</i> Option for generating a system error if a non-fatal error is registered by a device on the root port or by the root port itself	Enabled Disabled	Enables this function Disables this function
SECE	<i>System error on correctable error</i> Option for generating a system error if a correctable error is registered by a device on the root port or by the root port itself	Enabled Disabled	Enables this function Disables this function
PME SCI	Option for generating an SCI if power management is detected	Enabled Disabled	Enables this function Enables the root port to generate an SCI if power management is detected
Always enable port	Option for keeping the port enabled constantly	Enabled Disabled	Enables this function Disables this function
PCIe speed	Option for setting the PCI Express transfer rate	Auto Gen1 Gen2	Automatically sets the transfer rate Maximum transfer rate = 2.5 GT/s Maximum transfer rate = 5 GT/s
Assign INT to root port	Option for enabling/disabling the IRQ for the root port	Disabled Enabled	Disables this function Enables this function
Extra bus reserved	Option for reserving the extra bus to bridges behind this root bridge	0 to 7	
Reserved memory	Option for configuring reserved memory for this root bridge	0 to 20	
Prefetchable memory	Option for configuring prefetchable memory for this root bridge	1 to 20	
Reserved I/O	Option for configuring a reserved I/O range (4K/8K/12K/16K/20K) for this root bridge	4 to 20	

Table 171: Advanced - PCI Express configuration - PCI Express root port - Configuration options

1.4.5 ACPI settings




Figure 138: Advanced - ACPI settings

BIOS setting	Function	Configuration options	Effect
Enable hibernation	Option for enabling/disabling the hibernate function. This can put the operating system into the S4 state. This option may not have any effect on some operating systems.	Disabled	Disables this function
		Enabled	Enables this function
ACPI sleep state	Selects the ACPI status to be used when Suspend mode is enabled	Suspend disabled	Disables this function
		S1 only (CPU stop clock)	Sets S1 as Suspend mode. Only a few functions are disabled and are available again at the touch of a button.
		S3 only (Suspend to RAM)	Sets S3 as Suspend mode. The current state of the operating system is written to RAM, which is then the only component to receive power.
		Both S1 and S3 available for OS to choose from	Enables S1 and S3. The states can then be selected by the operating system.
Lock legacy resources	Option for configuring whether the operating system is permitted to configure legacy resources	Disabled	Disables this function
		Enabled	Enables this function
S3 video repost	Option for configuring whether the graphic ROM should be reposted after starting in the S3 status	Disabled	Disables this function
		Enabled	Enables this function
Critical trip point	Option for configuring a CPU temperature at which the operating system throttles the system	POR	Sets the critical trip point to 105°C
		87 C, 95 C, 103 C, 111 C, 119 C, 127 C	Temperature setting for the critical trip point. Configurable in increments of 5°C.

Table 172: Advanced - ACPI settings - Configuration options

1.4.6 RTC wake settings




Figure 139: Advanced - RTC wake settings

BIOS setting	Function	Configuration options	Effect
Wake system at fixed time	Option for setting the time (to the second) when the system should boot from a switched-off state (ACPI S5)	Disabled	Disables this function
		Enabled	Enables this function
Wake up hour	Option for setting the hour	0 to 23	Example: If set to 3, the system will start up at 3 AM. If set to 15, the system will start up at 3 PM.
Wake up minute	Option for setting the minute	0 to 59	Example: If set to 15, the system will start up at minute 15.
Wake up second	Option for setting the second	0 to 59	Example: If set to 32, the system will start up at second 32.

Table 173: Advanced - RTC wake settings - Configuration options

1.4.7 CPU configuration

Information:

The settings shown may vary depending on the CPU board being used.




Figure 140: Advanced - CPU configuration

BIOS setting	Function	Configuration options	Effect
CPU information	Displays CPU properties	Enter	Opens the submenu See "CPU information" on page 199
Hyper-threading	Option for enabling/disabling Intel hyper-threading technology	Disabled Enabled	Disables this function Enables this function Each processor core can execute multiple tasks (threads) at the same time. Intel hyper-threading technology increases processor throughput and improves the overall performance of multi-thread software.
Active processor cores	Option for configuring which processor cores are to be used	All 1	Uses all processor cores Only uses one processor core
Limit CPUID maximum	Option for limiting the CPUID value. This may be necessary for older operating systems.	Disabled Enabled	The processor returns the current maximum value when the CPUID value is requested. The processor limits the maximum CPUID value to 03h if necessary if the processor supports a higher value.
Execute disable bit	Option for enabling/disabling hardware support for prevention of data execution	Disabled Enabled	Disables this function Enables this function
Intel virtualization technology	Option for enabling/disabling a virtual machine	Disabled Enabled	Disables this function Allows a virtual machine to use the additional hardware capacity
Hardware prefetcher	Option for enabling/disabling the hardware prefetcher	Disabled Enabled	Disables this function Enables this function. Data is temporarily stored in cache memory to increase performance.

Table 174: Advanced - CPU configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
Adjacent cache line prefetch	Option for enabling/disabling the adjacent cache line prefetcher	Disabled	Disables this function
		Enabled	Enables this function. Loads the current and next line to cache in order to accelerate the read process
TCC ¹⁾ activation offset	Option for configuring the offset of the thermal control circuit (TCC) at temperatures below the TCC activation temperature	0 to 50	Sets the offset value
Primary plane current value	Option for configuring the maximum current on the primary plane at any single time	0 to 255	Setting from 0 to 255
Secondary plane current value	Option for configuring the maximum current on the secondary plane at any single time	0 to 255	Setting from 0 to 255
EIST	Option for enabling/disabling Intel® SpeedStep™ technology	Disabled	Disables Intel® SpeedStep™ technology
		Enabled	Enables Intel® SpeedStep™ technology
Turbo mode	Option for enabling/disabling Intel® Turbo Boost technology	Disabled	Disables Intel® Turbo Boost technology
		Enabled	Enables Intel® Turbo Boost technology
CPU C3 report	Option for enabling/disabling the CPU C3 (ACPI C2) report to the operating system	Disabled	Disables this function. No report is sent to the operating system.
		Enabled	Enables this function
CPU C6 report	Option for enabling/disabling the CPU C6 (ACPI C3) report to the operating system	Disabled	Disables this function. No report is sent to the operating system.
		Enabled	Enables this function
CPU C7 report	Option for enabling/disabling the CPU C7 (ACPI C3) report to the operating system	Disabled	Disables this function. No report is sent to the operating system.
		Enabled	Enables this function
Configurable TDP ²⁾	Option for configuring the TDP level	TDP NOMINAL	Value remains at the TDP level
		TDP DOWN	Value falls below the TDP level, with the CPU running at lower power
		TDP UP	Value rises above the TDP level, with the CPU running at higher power
		Disabled	Disables this function
Config TDP LOCK	Option for locking and configuring the TDP control register		Disables this function
		Enabled	Enables this function
Long duration power limit	Long duration power limit in watts	0 to 255	Setting from 0 to 255
Long duration maintained	Time period during which the "Long duration power" option is enabled	0 to 120	Setting from 0 to 120
Short duration power limit	Short duration power limit in watts	0 to 255	Setting from 0 to 255
ACPI T state	Option for enabling/disabling ACPI T state support.	Disabled	Disables this function
		Enabled	Enables this function

Table 174: Advanced - CPU configuration - Configuration options

1) TCC = Thermal control circuit

2) TDP = Thermal design power

1.4.7.1 CPU information

Information:

The settings shown may vary depending on the CPU board being used.




Figure 141: Advanced - CPU configuration - CPU information

BIOS setting	Function	Configuration options	Effect
CPU signature	Displays the CPU ID	None	-
Microcode patch	Displays the microcode patch ID	None	-
Max CPU speed	Displays the maximum processor frequency	None	-
Min CPU speed	Displays the minimum processor frequency	None	-
CPU speed	Displays the processor frequency	None	-
Processor cores	Displays the number of processor cores	None	-
Intel HT technology	Displays whether the processor supports HT technology	None	-
Intel VT-x technology	Displays whether the processor supports VT-x technology	None	-
Intel SMX technology	Displays whether the processor supports SMX technology	None	-
64-bit	Displays whether the processor supports Intel 64-bit architectures	None	-
L1 data cache	Displays the size of the L1 data cache	None	-
L1 code cache	Displays the size of the L1 code cache	None	-
L2 cache	Displays the size of the L2 cache	None	-
L3 cache	Displays the size of the L3 cache	None	-

Table 175: Advanced - CPU configuration - CPU information - Configuration options

1.4.8 Chipset configuration




Figure 142: Advanced - Chipset configuration

BIOS setting	Function	Configuration options	Effect
PCH LAN controller	Option for turning the onboard LAN controller (ETH1) on and off	Disabled	Disables the controller
		Enabled	Enables the controller
Wake on LAN	Option for switching on the system via the onboard LAN controller (ETH1)	Enabled	Enables this function. The LAN controller can switch on the system.
		Disabled	Disables this function. The LAN controller cannot switch on the system.
Azalia	Option for enabling/disabling the audio controller	Disabled	Disables the audio controller
		Enabled	Enables the audio controller
		Auto	Only enables the audio controller if a device is connected
Azalia PME	Option for enabling/disabling power management for the audio controller	Disabled	Disables this function
		Enabled	Enables this function
Azalia internal HDMI codec	Option for enabling/disabling the internal HDMI codec for Azalia	Disabled	Disables audio output
		Enabled	Enables audio output
High-precision timer	The HPET is a timer inside the PC. It is able to trigger an interrupt with a high degree of accuracy, which allows other programs to better synchronize a variety of applications.	Disabled	Disables this function
		Enabled	Enables this function. This function is recommended for multimedia applications.
CF9h global reset	Option for setting the restart on the CF9h reset register	Host only	Chipset only
		Host+ME	Chipset and management engine
PCI Express clock gating	Option for enabling/disabling PCI Express clock gating for each individual root port	Disabled	Disables this function
		Enabled	Enables this function
DMI link ASPM PCH side	Option for enabling/disabling active state power management (ASPM) for the DMI link on the PCH side	Disabled	Disables this function
		Enabled	Enables this function
PCIe USB glitch W/A	Option for enabling/disabling the PCIe USB glitch if a malfunctioning USB device is connected after the PCIe/PEG port	Disabled	Disables this function
		Enabled	Enables this function
SB CRID	Option for enabling/disabling the southbridge compatible revision ID	Disabled	Disables this function
		Enabled	Enables this function
NB CRID	Option for enabling/disabling the northbridge compatible revision ID	Disabled	Disables this function
		Enabled	Enables this function
DMI configuration			
DMI	Displays the DMI version / generation	None	-
DMI Vc1 control	Option for enabling/disabling DMI Vc1	Enabled	Enables this function
		Disabled	Disables this function

Table 176: Advanced - Chipset configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
DMI Vcp control	Option for enabling/disabling DMI Vcp	Enabled	Enables this function
		Disabled	Disables this function
DMI Vcm control	Option for enabling/disabling DMI Vcm.	Enabled	Enables this function
		Disabled	Disables this function
DMI link ASPM CPU side	Option for enabling/disabling active state power management (ASPM) for the DMI link on the CPU side	Disabled	Disables this function
		L0s	Enables the L0 energy saving function
		L1	Enables the L1 energy saving function. Power consumption is lower than with L0, but the exit latency is higher.
		L0sL1	Automatic assignment of L0s or L1 power saving function by the PCIe device
DMI extended synch control	Option for enabling/disabling DMI extended synchronization	Enabled	Enables this function
		Disabled	Disables this function
DMI Gen 2	Option for enabling/disabling DMI Gen 2	Auto	Disabled for IVB A0 MB/DT and IVB B0 MB, enabled for other CPUs
		Enabled	Enables this function
		Disabled	Disables this function

Table 176: Advanced - Chipset configuration - Configuration options

1.4.9 SATA configuration




Figure 143: Advanced - SATA configuration

BIOS setting	Function	Configuration options	Effect
SATA controller(s)	Option for configuring SATA support	Enabled	Provides support for SATA devices
		Disabled	No support for SATA devices
SATA mode selection	Option for configuring supported serial ATA connections	IDE	Uses the serial ATA hard drive as a parallel ATA physical drive It is not possible to configure the SATA port.
		AHCI	The AHCI setting enables the internal memory driver for SATA functions, which increases the storage performance for random read-write access by allowing the drive itself to determine the sequence of commands.

Table 177: Advanced - SATA configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
		RAID	RAID 0, 1, 5, 10 or Intel® Matrix Storage technology can be configured here with the serial ATA hard drive.
SATA test mode	Option for configuring the test function. This is only used for test measurements.	Enabled Disabled	Enables this function Disables this function
Aggressive LPM support	Aggressive Link Power Management (ALPM) is a power saving method for SATA drives.	Enabled Disabled	Enables this function Disables this function
SATA controller speed	Option for setting the maximum SATA transfer rate The transfer rate is also dependent on the maximum possible transfer rate of the drive.	Gen1 Gen2 Gen3	Maximum SATA transfer rate = 1.5 Gbit/s Maximum SATA transfer rate = 3.0 Gbit/s Maximum SATA transfer rate = 6.0 Gbit/s
Software feature mask configuration	Configuration of various drive settings	Enter	Opens the submenu See "Software feature mask configuration" on page 203
Alternate ID ¹⁾	Option for enabling/disabling a report of the alternate device ID	Enabled Disabled	Enables this function Disables this function
Serial ATA port 0	Displays the device connected to SATA port 0	None	-
Port 0	Option for enabling/disabling SATA port 0	Disabled Enabled	Disables SATA port 0 Enables SATA port 0
Hot plug	Option for configuring hot plugging for SATA port 0	Disabled Enabled	Hot plugging not enabled for SATA port 0 Hot plugging enabled for SATA port 0. Devices can be connected/disconnected during operation.
External SATA	Option for configuring the external SATA port	Disabled Enabled	Uses the port externally as eSATA Uses the port internally as SATA
Mechanical presence switch ²⁾	Option for enabling/disabling the report if this port has a mechanical presence switch	Disabled Enabled	Disables this function Enables this function
SATA device type	Identifies whether a solid state or hard disk drive is connected to the SATA port	Hard disk drive Solid-state drive	A hard disk is connected to the SATA port. A solid-state drive is connected to the SATA port.
Spin up device	Option for configuring an initialization sequence for the connected device during startup for the SATA port	Disabled Enabled	Disables this function Enables this function
Serial ATA port 1	Displays the device connected to SATA port 1	None	-
Port 1	Option for enabling/disabling SATA port 1	Disabled Enabled	Disables SATA port 1 Enables SATA port 1
Hot plug	Option for configuring hot plugging for SATA port 1	Disabled Enabled	Hot plugging not enabled for SATA port 1 Hot plugging enabled for SATA port 1. Devices can be connected/disconnected during operation.
External SATA	Option for configuring the external SATA port	Disabled Enabled	Uses the port externally as eSATA Uses the port internally as SATA
Mechanical presence switch ²⁾	Option for enabling/disabling the report if this port has a mechanical presence switch	Disabled Enabled	Disables this function Enables this function
SATA device type	Identifies whether a solid state or hard disk drive is connected to the SATA port	Hard disk drive Solid-state drive	A hard disk is connected to the SATA port. A solid-state drive is connected to the SATA port.
Spin up device	Option for configuring an initialization sequence for the connected device during startup for the SATA port	Disabled Enabled	Disables this function Enables this function
Serial ATA port 2	Displays the device connected to SATA port 2	None	-
Port 2	Option for enabling/disabling SATA port 2	Disabled Enabled	Disables SATA port 2 Enables SATA port 2
Hot plug	Option for configuring hot plugging for SATA port 2	Disabled Enabled	Hot plugging not enabled for SATA port 2 Hot plugging enabled for SATA port 2. Devices can be connected/disconnected during operation.
External SATA	Option for configuring the external SATA port	Disabled Enabled	Uses the port externally as eSATA Uses the port internally as SATA
Mechanical presence switch ²⁾	Option for enabling/disabling the report if this port has a mechanical presence switch	Disabled Enabled	Disables this function Enables this function
SATA device type	Identifies whether a solid state or hard disk drive is connected to the SATA port	Hard disk drive Solid-state drive	A hard disk is connected to the SATA port. A solid-state drive is connected to the SATA port.
Spin up device	Option for configuring an initialization sequence for the connected device during startup for the SATA port	Disabled Enabled	Disables this function Enables this function
Serial ATA port 3	Displays the device connected to SATA port 3	None	-
Port 3	Option for enabling/disabling SATA port 3	Disabled Enabled	Disables SATA port 3 Enables SATA port 3
Hot plug	Option for configuring hot plugging for SATA port 3	Disabled Enabled	Hot plugging not enabled for SATA port 3 Hot plugging enabled for SATA port 3. Devices can be connected/disconnected during operation.
External SATA	Option for configuring the external SATA port	Disabled Enabled	Uses the port externally as eSATA Uses the port internally as SATA

Table 177: Advanced - SATA configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
Mechanical presence switch ²⁾	Option for enabling/disabling the report if this port has a mechanical presence switch	Disabled	Disables this function
		Enabled	Enables this function
SATA device type	Identifies whether a solid state or hard disk drive is connected to the SATA port	Hard disk drive	A hard disk is connected to the SATA port.
		Solid-state drive	A solid-state drive is connected to the SATA port.
Spin up device	Option for configuring an initialization sequence for the connected device during startup for the SATA port	Disabled	Disables this function
		Enabled	Enables this function

Table 177: Advanced - SATA configuration - Configuration options

- 1) This setting is only possible if *SATA mode selection* is set to *RAID*.
 2) This setting is only possible if *Hot plug* is set to *Enabled*.

1.4.9.1 Software feature mask configuration




Figure 144: Advanced - SATA configuration - Software feature mask configuration

BIOS setting	Function	Configuration options	Effect
RAID0	Option for enabling/disabling a RAID0 system	Disabled	Disables this function
		Enabled	Enables this function
RAID1	Option for enabling/disabling a RAID1 system	Disabled	Disables this function
		Enabled	Enables this function
RAID10	Option for enabling/disabling a RAID10 system	Disabled	Disables this function
		Enabled	Enables this function
RAID5	Option for enabling/disabling a RAID5 system	Disabled	Disables this function
		Enabled	Enables this function
Intel Rapid Recovery technology	Option for enabling/disabling Intel® Rapid Recovery technology	Disabled	Disables this function
		Enabled	Enables this function
OROM UI and BANNER	Option for displaying the OROM UI	Disabled	Does not display the OROM UI or banner
		Enabled	Displays the OROM UI
HDD unlock	Option for enabling/disabling the HDD password unlock mechanism in the operating system	Disabled	Disables the HDD password unlock mechanism
		Enabled	Enables the HDD password unlock mechanism
LED locate	Option for displaying the LED/SGPIO when a drive is connected	Disabled	Disables this function
		Enabled	Enables an indicator for when a drive is connected
IRRT only on eSATA ¹⁾	Option for configuring Intel® Rapid Recovery technology	Disabled	Every RAID system can use internal and eSATA drives.
		Enabled	Only IRRT systems can use internal eSATA drives.

Table 178: Advanced - SATA configuration - Software feature mask configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
Smart Response technology	Option for enabling/disabling Intel® Smart Response technology	Disabled	Disables this function
		Enabled	Enables this function
OROM UI delay	Option for displaying the delay time for the OROM UI splash screen	2 seconds, 4 seconds, 6 seconds, 8 seconds	Setting in seconds

Table 178: Advanced - SATA configuration - Software feature mask configuration - Configuration options

1) IRRT = Intel Rapid Recovery technology

1.4.10 Memory configuration




Figure 145: Advanced - Memory configuration

BIOS setting	Function	Configuration options	Effect	
Memory information	Displays main memory properties	Enter	Opens the submenu See "Memory information" on page 205	
DIMM profile	Option for configuring the main memory timing profile	Default DIMM profile	Uses the default profile	
		Custom profile	Uses a user-defined profile	
		XMP Profile 1	Uses XMP profile 1	
		XMP Profile 2	Uses XMP profile 2	
Custom profile control ¹⁾	Configuration of the main memory timing profile	Enter	Opens the submenu See "Custom profile control" on page 206	
Memory frequency limiter ²⁾	Option for setting the maximum possible main memory frequency	Auto	Automatic configuration	
		1067, 1333, 1600, 1867, 2133, 2400, 2667	Manual configuration	
Information:				
If a fan kit is not installed in the device, then the main memory frequency is limited to 1067 MHz when set to "Auto".				
No fan memory frequency limiter	Option for automatically throttling down the main memory frequency when the system unit has no fan	Disabled	Disables this function	
		Enabled	Enables this function	
ECC support	Option for enabling/disabling main memory ECC support	Disabled	Disables this function	
		Enabled	Enables this function	
Max TOLUD ³⁾	Option for configuring the maximum "Top Of Low Usable DRAM"	Dynamic	Automatically adjusts the TOLUD based on the MMIO length of the graphics controller	
		1 GB, 1.25 GB, 1.5 GB, 1.75 GB, 2 GB, 2.25 GB, 2.5 GB, 2.75 GB, 3 GB, 3.25 GB	Manual setting of the TOLUD	
NMode support	Option for configuring NMode support	Auto	Sets automatically	
		1N mode	Sets 1N mode	
		2N mode	Sets 2N mode	

Table 179: Advanced - Memory configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
Memory scrambler	Option for enabling/disabling memory scrambler support	Enabled	Enables this function
		Disabled	Disables this function
Memory refresh rate	Option for configuring the RAM refresh rate	Disabled	Sets automatically
		x1	Manual setting
		x2	Manual setting
MRC fast boot	Option for enabling/disabling MRC fast booting	Enabled	Enables this function
		Disabled	Disables this function
Force cold reset	Option for enabling/disabling force cold resets	Enabled	Enables this function
		Disabled	Disables this function
DIMM exit mode	Option for configuring the DIMM exit mode	Auto	Sets automatically
		Slow exit	Enables slow exit mode
		Fast exit	Enables fast exit mode
Power down mode	Option for setting the power saving function for main memory	No power down	TBD
		APD	TBD
		PPD	TBD
		APD-PPD	TBD
Scrambler seed generation off	Option for enabling/disabling the scrambler seed generation off function	Enabled	Enables this function
		Disabled	Disables this function
Memory remap	Option for enabling/disabling memory remapping over 4 GB	Enabled	Enables this function
		Disabled	Disables this function
Memory alias check	Option for enabling/disabling the memory alias check function	Enabled	Enables this function
		Disabled	Disables this function
Channel A DIMM control	Option for configuring main memory channel A	Enable both DIMMS	Enables both channel A main memory modules
		Disable DIMM0	Disables channel A DIMM0 main memory
		Disable DIMM1	Disables channel A DIMM1 main memory
		Disable both DIMMS	Disables both channel A main memory modules
Channel B DIMM control	Option for configuring main memory channel B	Enable both DIMMS	Enables both channel B main memory modules
		Disable DIMM0	Disables channel B DIMM0 main memory
		Disable DIMM1	Disables channel B DIMM1 main memory
		Disable both DIMMS	Disables both channel B main memory modules

Table 179: Advanced - Memory configuration - Configuration options

- 1) This setting is only shown if *DIMM profile* is set to *Custom profile*.
- 2) This setting is only possible if *No fan memory frequency limiter* is set to *Disabled*.
- 3) TOLUD = Top of Low Usable DRAM

1.4.10.1 Memory information




Figure 146: Advanced - Memory configuration - Memory information

BIOS setting	Function	Configuration options	Effect
Memory RC version	Displays the main memory RC version	None	-
Memory frequency	Displays the main memory frequency	None	-
Total memory	Displays the total amount of main memory	None	-
DIMM#0	Displays the amount of main memory in DIMM slot 0	None	-
DIMM#1	Displays the amount of main memory in DIMM slot 1	None	-
DIMM#2	Displays the amount of main memory in DIMM slot 2	None	-
DIMM#3	Displays the amount of main memory in DIMM slot 3	None	-
CAS latency (tCL)	Displays the CAS latency	None	-
Minimum delay time			
CAS to RAS (tRCDmin)	Displays the delay time between CAS# and RAS#	None	-
Row precharge (tRPmin)	Displays the row precharge time	None	-
Active to precharge (tRASmin)	Displays the minimum active RAS# time	None	-
XMP Profile 1	Displays XMP profile 1	None	-
XMP Profile 2	Displays XMP profile 2	None	-

Table 180: Advanced - Memory configuration - Memory information

1.4.10.2 Custom profile control




Figure 147: Advanced - Memory configuration - Custom profile control

BIOS setting	Function	Configuration options	Effect
Memory frequency limiter	Sets the maximum main memory frequency in MHz	1067, 1333, 1600, 1867, 2133, 2400, 2667	
tCL	Sets the CAS latency	4 to 18	
tRCD	Sets the minimum "CAS to RAS" time	1 to 38	
tRP	Sets the minimum "Row precharge" time	1 to 38	
tRAS	Sets the minimum "Active to precharge" time	1 to 586	
tWR	Sets the minimum "Write recovery" time	1 to 38	
tRFC	Sets the minimum "Refresh recovery" time	1 to 9363	
tRRD	Sets the minimum "Row active to row active" time	1 to 38	

Table 181: Advanced - Memory configuration - Custom profile control - Configuration options

BIOS setting	Function	Configuration options	Effect
tWTR	Sets the minimum "Internal write to read command" time	1 to 38	
tRTP	Sets the minimum "Internal read to precharge command" time	1 to 38	
tFAW	Sets the minimum "Four active window" time	1 to 586	

Table 181: Advanced - Memory configuration - Custom profile control - Configuration options

1.4.11 USB configuration




Figure 148: Advanced - USB configuration

BIOS setting	Function	Configuration options	Effect
EHC1 (ports 0-5)	Sets USB EHCI controller 1 for USB ports #0 through #5 (USB1 through USB4 on the system unit, USB on the monitor/panel interface and the bus unit)	Enabled	Enables EHCI controller 1
		Disabled	Disables EHCI controller 1
EHC2 (ports 6-7)	Sets USB EHCI controller 1 for USB ports #6 through #7 (USB5 on the system unit and USB on the monitor/panel option)	Enabled	Enables EHCI controller 2
		Disabled	Disables EHCI controller 2
xHCI mode	Option for configuring the xHCI controller	Smart auto	The USB 3.0 ports are not handled as USB 3.0 until after the operating system has started. Before that, they are handled as USB 2.0 ports. If the APC910 is rebooted, then the USB 3.0 ports are handled as USB 3.0 during booting.
		Auto	During the BIOS boot procedure, USB 3.0 ports are handled as USB 2.0 ports. They are not handled as USB 3.0 ports until after the operating system has started and the USB 3.0 driver has been loaded.
		Enabled	Enables the xHCI controller so that USB 3.0 ports are always identified as such
		Disabled	Disables the xHCI controller. All USB 3.0 ports become USB 2.0 ports.
HS port #1 switchable	Option to switch HS port 1 between xHCI and EHCI	Disabled	Routes port 1 to EHCI and operates it as USB 2.0.
		Enabled	Routes port 1 to xHCI and enables the corresponding HS port
HS port #2 switchable	Option to switch HS port 2 between xHCI and EHCI	Disabled	Routes port 2 to EHCI and operates it as USB 2.0.
		Enabled	Routes port 2 to xHCI and enables the corresponding HS port

Table 182: Advanced - USB configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
HS port #3 switchable	Option to switch HS port 3 between xHCI and EHCI	Disabled	Routes port 3 to EHCI and operates it as USB 2.0.
		Enabled	Routes port 3 to xHCI and enables the corresponding HS port
HS port #4 switchable	Option to switch HS port 4 between xHCI and EHCI	Disabled	Routes port 4 to EHCI and operates it as USB 2.0.
		Enabled	Routes port 4 to xHCI and enables the corresponding HS port
Per port USB disable control	Option for enabling/disabling individual USB ports	Enter	Opens the submenu See "Per port USB disable control" on page 209
Legacy USB support	Option for configuring legacy USB support. USB ports do not function during startup. USB support is available again after the operating system has started. A USB keyboard is still recognized during POST.	Enabled	Enables this function
		Disabled	Disables this function
		Auto	Automatic enabling
Per port legacy USB support control	Option for enabling/disabling legacy support for individual USB ports	Enter	Opens the submenu See "Per port legacy USB support control" on page 210
USB 3.0 support	Option for enabling or disabling USB 3.0 mode	Enabled	Uses USB 3.0 for all USB 3.0 ports
		Disabled	Uses USB 2.0 or 1.1 for all USB ports
XHCI hand-off	Option for configuring support for operating systems without a fully automated XHCI function	Enabled	Enables USB 3.0 support
		Disabled	Disables this function With operating systems that do not have a fully automated XHCI function, USB devices are only operated with USB 2.0.
EHCI hand-off	Option for configuring support for operating systems without a fully automated EHCI function	Disabled	Disables this function With operating systems that do not have a fully automated EHCI function, USB devices are only operated with USB 1.1.
		Enabled	Enables USB 2.0 support
Device mass storage driver support	Option for enabling/disabling USB mass storage device support	Enabled	Enables this function
Device mass storage driver support	Option for enabling/disabling USB mass storage device support	Disabled	Disables this function
Device reset time-out	Option for configuring the time that POST waits for USB memory storage devices after the device start command is issued	10 sec, 20 sec, 30 sec, 40 sec	Value in seconds
USB transfer time-out	Option for configuring the timeout value for control, bulk and interrupt transfers	1 sec, 5 sec, 10 sec, 20 sec	Value in seconds
Device power-up delay	Option to set the maximum time to wait for a USB device to report to the host controller	Auto	Sets the maximum time automatically. For a root port, 100 ms is set; for a hub port, the data from the hub descriptor is used.
		Manual	Allows the maximum time to be entered manually using the "Device power-up delay in seconds" option
Device power-up delay in seconds ¹⁾	Option for setting the device power-up delay time manually	1 to 40	Value in seconds
Overcurrent protection	Option for configuring overcurrent protection for all USB ports	Disabled	Disables this function
		Enabled	Enables this function

Table 182: Advanced - USB configuration - Configuration options

1) This setting is only possible if *Device power-up delay* is set to *Manual*.

1.4.11.1 Per port USB disable control




Figure 149: Advanced - USB configuration - Per port USB disable control

BIOS setting	Function	Configuration options	Effect
USB port #0	Option for enabling/disabling the USB4 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB port #1	Option for enabling/disabling the USB2 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB port #2	Option for enabling/disabling the USB3 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB port #3	Option for enabling/disabling the USB1 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB port #4	Option for enabling/disabling the USB port on the bus unit	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB port #5	Option for enabling/disabling the USB port on the monitor/panel interface	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB port #6	Option for enabling/disabling the USB5 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB port #7	Option for enabling/disabling the USB port on the monitor/panel option	Disabled	Disables the USB port
		Enabled	Enables the USB port

Table 183: Advanced - USB configuration - Per port USB disable control - Configuration options

1.4.11.2 Per port legacy USB support control




Figure 150: Advanced - USB configuration - Per port legacy USB support control

BIOS setting	Function	Configuration options	Effect
USB0 port legacy support	Option for enabling/disabling legacy support for the USB4 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB1 port legacy support	Option for enabling/disabling legacy support for the USB2 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB2 port legacy support	Option for enabling/disabling legacy support for the USB3 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB3 port legacy support	Option for enabling/disabling legacy support for the USB1 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB4 port legacy support	Option for enabling/disabling legacy support for the USB port on the bus unit	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB5 port legacy support	Option for enabling/disabling legacy support for the USB port on the monitor/panel interface	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB6 port legacy support	Option for enabling/disabling legacy support for the USB5 port	Disabled	Disables the USB port
		Enabled	Enables the USB port
USB7 port legacy support	Option for enabling/disabling legacy support for the USB port on the monitor/panel option	Disabled	Disables the USB port
		Enabled	Enables the USB port

Table 184: Advanced - USB configuration - Per port legacy USB support control - Configuration options

1.4.12 Serial port console redirection




Figure 151: Advanced - Serial port console redirection

BIOS setting	Function	Configuration options	Effect
Console redirection	Option for enabling/disabling console redirection	Disabled	Disables this function
		Enabled	Enables this function
Console redirection settings	Configures the remote console	Enter	Opens the submenu See "Console redirection settings" on page 212

Table 185: Advanced - Serial port console redirection - Configuration options

- 1) This setting is only possible if *Device power-up delay* is set to *Manual*.

1.4.12.1 Console redirection settings




Figure 152: Advanced - Console redirection - Console redirection settings

BIOS setting	Function	Configuration options	Effect
Terminal type	Option for configuring keyboard input	VT100	Enables the VT100 convention (ASCII character set)
		VT100+	Enables the VT100+ convention (ASCII character set and support for color, function keys, etc)
		VT-UTF8	Enables the VT-UTF8 convention (uses UTF8 encoding to assign Unicode characters to one or more bytes)
		ANSI	Enables the ANSI convention (extended ASCII character set)
Baud rate	Option for setting the transfer rate of the serial interface (bits per second)	1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200	Enables a transfer rate of x bits
Data bits	Option for configuring the character length (data bits) to use for serial communication	7	Character length with 7 bits
		8	Character length with 8 bits
Parity	Option for configuring the parity bit to use for serial communication	None	Parity bit not used
		Even	Uses an even number of parity bits
		Odd	Uses an odd number of parity bits
		Mark	Parity bit always 1
		Space	Parity bit always 0
Stop bits	Option for configuring the stop bits to use for serial communication	1	Uses 1 bit as the stop bit
		2	Uses 2 bits as the stop bit
Flow control	Option for configuring the data flow control	None Hardware RTS/CTS	Disables data flow control Enables hardware handshake
VT-UTF8 combo key support	Option for enabling/disabling VT-UTF8 combo key support for ANSI and VT100 connections	Disabled	Disables this function
		Enabled	Enables this function
Recorder mode	Option for enabling/disabling recorder mode	Disabled	Disables this function
		Enabled	Enables this function When this setting is used, all control escape sequences are suppressed from the serial redirection output. This may lead to incorrectly formatted screen output but makes automatic storage of the serial console output easier.
Resolution 100x31	Option for enabling/disabling extended terminal resolution	Disabled	Disables this function
		Enabled	Enables this function
Legacy OS redirection resolution	Option for configuring the number of lines and columns for legacy OS redirection	80x24	Resolution of 80x24
		80x25	Resolution of 80x25
Putty keypad	TBD	VT100	TBD
		Linux	TBD
		XTERMR6	TBD
		SCO	TBD
		ESCN	TBD
		VT400	TBD

Table 186: Advanced - Console redirection - Console redirection settings - Configuration options

1.5 Boot




Figure 153: Boot

BIOS setting	Function	Configuration options	Effect
Boot device priority	Configures the boot order	Enter	Opens the submenu See "Boot device priority" on page 213
Boot configuration	Configures boot properties	Enter	Opens the submenu See "Boot configuration" on page 214

Table 187: Boot overview

1.5.1 Boot device priority




Figure 154: Boot - Boot device priority

BIOS setting	Function	Configuration options	Effect
Boot priority selection	Option for determining the method for how drives should be booted	Device based	Only lists devices that are recognized by the system. The order of devices in this list can be changed. Information: It is only possible to use either "Device based" or "Type based". Using both together is not permitted.
		Type based	The boot sequence of a device type list can be changed. It is also possible to add device types that are not connected to this list. Information: It is only possible to use either "Device based" or "Type based". Using both together is not permitted.
1st boot device 2nd boot device 3rd boot device 4th boot device 5th boot device 6th boot device 7th boot device 8th boot device	Option for selecting drives to be used for booting	Disabled, SATA 0 drive, SATA 1 drive, SATA 2 drive, SATA 3 drive, USB floppy, USB hard disk, USB CDROM, Onboard LAN, External LAN, Other BEV device	Specifies the desired boot sequence

Table 188: Boot - Boot device priority - Configuration options

1.5.2 Boot configuration




Figure 155: Boot - Boot configuration

BIOS setting	Function	Configuration options	Effect
PXE Option ROM launch policy	Option for booting from PXE Option ROM	Do not launch	Does not boot from PXE Option ROM
		UEFI ROM only	Boots from UEFI ROM
		Legacy ROM only	Boots from legacy ROM
Storage Option ROM launch policy	Option for booting from Storage Option ROM	Do not launch	Does not boot from Storage Option ROM
		UEFI ROM only	Boots from UEFI ROM
		Legacy ROM only	Boots from legacy ROM
Video Option ROM launch policy	Option for booting from Video Option ROM	Do not launch	Does not boot from Video Option ROM
		UEFI ROM only	Boots from UEFI ROM
		Legacy ROM only	Boots from legacy ROM

Table 189: Boot - Boot configuration - Configuration options

BIOS setting	Function	Configuration options	Effect
Option ROM messages	Option to display Option ROM messages during POST	Force BIOS	Displays Option ROM messages during POST
		Keep current	Does not display Option ROM messages during POST
Boot logo	Option for configuring the boot logo	Disabled	Does not display the boot logo
		Enabled	Displays the boot logo
		Auto	Displays the boot logo
Enter setup if no boot device	Option for configuring whether the setup screen is displayed when no bootable drive is connected	No	Does not display the setup screen
		Yes	Displays the setup screen
Setup prompt timeout	Option for configuring how long the setup activation key (key for entering BIOS) is displayed	1 to 65534	Displays the setup activation key for x seconds
		65535	Displays the setup activation key for an unlimited amount of time
Enable popup boot menu	Option for enabling/disabling the popup boot menu	Yes	Enables this function. Pressing "F11" during POST allows a boot device to be selected.
		No	Disables this function. It is not possible to select a boot device during POST. Devices will boot in their configured order.
Bootup NumLock state	Option for configuring the numeric keypad when booting the system	On	Enables the numeric keypad
		Off	Only enables the cursor (movement) functions of the numeric keypad
GateA20 active	Option for defining how memory above 1 MB is accessed	Upon request	GA20 can be disabled.
		Always	GA20 is not disabled.
INT19 trap response	Option for configuring the interrupt trap response for the ROM option	Immediate	Executes the interrupt trap response immediately
		Postponed	Executes the interrupt trap response during the legacy boot
Power loss control	Specifies whether the system should be on/off following power loss	Remain off	Keeps the APC910 turned off
		Turn on	Turns on the APC910
		Last state	Enables the previous state

Table 189: Boot - Boot configuration - Configuration options

1.6 Security




Figure 156: Security

BIOS setting	Function	Configuration options	Effect
Administrator password	Function for entering/changing the administrator password	Enter	Password entry

Table 190: Security menu - Configuration options

1.6.1 HDD user password




Figure 157: Security - HDD user password

BIOS setting	Function	Configuration options	Effect
User password	Function for entering/changing a user password.	Enter	Password entry

Table 191: Security - HDD user password - Configuration options

1.7 Save & Exit




Figure 158: Save & Exit

BIOS setting	Function	Configuration options	Effect
Save changes and exit	Selecting this option closes BIOS Setup. Any changes made are saved to CMOS after confirmation.	Yes / No	
Discard changes and exit	Selecting this option closes BIOS Setup without saving any changes made.	Yes / No	
Save changes and reset	Selecting this option closes BIOS Setup. Any changes made are saved to CMOS after confirmation, and the system is rebooted.	Yes / No	
Discard changes and reset	Selecting this option closes BIOS Setup without saving any changes made. The system is then rebooted.	Yes / No	
Save changes	Any changes made are saved to CMOS after confirmation.	Yes / No	
Discard changes	This option can be used to reset any settings that may have been made but have been forgotten in the meantime (provided they have not yet been saved).	Yes / No	
Restore defaults	This option restores BIOS default values.	Yes / No	

Table 192: Save & Exit menu - Configuration options

1.8 BIOS default settings

BIOS default settings may vary depending on how the complete system is configured.

If the function "Restore defaults" is selected in the main BIOS setup menu, or if "Save & Exit" is selected (or F9 is pressed) in the individual setup screens, the following BIOS settings are the optimized values that will be used.

1.8.1 Advanced

1.8.1.1 Graphics configuration

Setting/Option	Default profile	My setting
Primary display	Auto	
Internal graphics	Auto	
IGFX VBIOS version	-	
GTT size	2 MB	
Aperture size	256 M	
DVMT pre-allocated	64 M	
DVMT total gfx mem	256 M	
Gfx low power mode	Disabled	
Graphics performance analyzers	Disabled	
Primary IGFX boot display	LFP	
Secondary IGFX boot display	CRT	
Active LFP configuration	Integrated LVDS	
Always try auto panel detect	No	
Local flat panel type	Auto	
Display Port B interface	Disabled	
Display Port C interface	Disabled	
Display Port D interface	HDMI/DVI	
Display mode persistence	Disabled	

Table 193: Advanced - Graphics configuration - Overview of profile settings

1.8.1.2 OEM features

Setting/Option	Default profile	My setting
Main BIOS version	-	
OEM BIOS version	-	
MTCX	-	
ETH2 MAC address	-	
Real-time environment	Disabled	

Table 194: Advanced - OEM features - Overview of profile settings

1.8.1.2.1 Super I/O configuration

Setting/Option	Default profile	My setting
Serial port A	Enabled	
Device settings	-	
Serial port B	Enabled	
Device settings	-	
Serial port C	Enabled	
Device settings	-	
Serial port D	Disabled	
Device settings	-	
Serial port E	Enabled	
Device settings	-	
Serial port F	Enabled	
Device settings	-	

Table 195: Advanced - OEM features - Super I/O configuration - Overview of profile settings

1.8.1.3 PCI configuration

Setting/Option	Default profile	My setting
Above 4G decoding	Disabled	
PCI latency timer	32 PCI bus clocks	
VGA palette snoop	Disabled	
PERR# generation	Disabled	
SERR# generation	Disabled	
PIRQ routing & IRQ reservation		

Table 196: Advanced - PCI configuration - Overview of profile settings

Setting/Option	Default profile	My setting
PIRQA	Auto	
PIRQB	Auto	
PIRC	Auto	
PIRQD	Auto	
PIRQE	Auto	
PIRF	Auto	
PIRG	Auto	
PIRH	Auto	
Reserve legacy interrupt 1	None	
Reserve legacy interrupt 2	None	

Table 196: Advanced - PCI configuration - Overview of profile settings

1.8.1.4 PCI Express configuration

1.8.1.4.1 PCI Express settings

Setting/Option	Default profile	My setting
Relaxed ordering	Disabled	
Extended tag	Disabled	
No snoop	Enabled	
Maximum payload	Auto	
Maximum read request	Auto	
ASPM	Disabled	
Extended synch	Disabled	
Link training retry	5	
Link training timeout (μS)	100	
Unpopulated links	Keep link on	

Table 197: Advanced - PCI Express configuration - PCI Express settings - Overview of profile settings

1.8.1.4.2 PCI Express GEN 2 settings

Setting/Option	Default profile	My setting
Completion timeout	Default	
ARI forwarding	Disabled	
AtomicOp requester enable	Disabled	
AtomicOp egress blocking	Disabled	
IDO request enable	Disabled	
IDO completion enable	Disabled	
LTR mechanism enable	Disabled	
End-End TLP prefix blocking	Disabled	
Target link speed	Auto	
Clock power management	Disabled	
Compliance SOS	Disabled	
Hardware autonomous width	Enabled	
Hardware autonomous speed	Enabled	

Table 198: Advanced - PCI Express configuration - PCI Express GEN 2 settings - Overview of profile settings

1.8.1.4.3 PCI Express graphics (PEG) port

Setting/Option	Default profile	My setting
PCI Express graphics (PEG) port	Disabled	

Table 199: Advanced - PCI Express configuration - PCI Express graphics (PEG) port - Overview of profile settings

1.8.1.4.4 PCI Express root port

Setting/Option	Default profile	My setting
PCI Express root port x	Enabled	
ASPM	Auto	
URR	Disabled	
FER	Disabled	
NFER	Disabled	
CER	Disabled	
CT0	Disabled	
SEFE	Disabled	
SENFE	Disabled	
SECE	Disabled	
PME SCI	Enabled	
Always enable port	Disabled	

Table 200: Advanced - PCI Express configuration - PCI Express root port - Overview of profile settings

Setting/Option	Default profile	My setting
PCIe speed	Auto	
Assign INT to root port	Enabled	
Extra bus reserved	0	
Reserved memory	10	
Prefetchable memory	10	
Reserved I/O	4	

Table 200: Advanced - PCI Express configuration - PCI Express root port - Overview of profile settings

1.8.1.5 ACPI settings

Setting/Option	Default profile	My setting
Enable hibernation	Enabled	
ACPI sleep state	Both S1 and S3 available for OS to choose from	
Lock legacy resources	Disabled	
S3 video repost	Disabled	
Critical trip point	111 C	

Table 201: Advanced - ACPI settings - Overview of profile settings

1.8.1.6 RTC wake settings

Setting/Option	Default profile	My setting
Wake system at fixed time	Disabled	

Table 202: Advanced - RTC wake settings - Overview of profile settings

1.8.1.7 CPU configuration

Setting/Option	Default profile	My setting
Hyper-threading	Enabled	
Active processor cores	All	
Limit CPUID maximum	Disabled	
Execute disable bit	Enabled	
Intel virtualization technology	Disabled	
Hardware prefetcher	Enabled	
Adjacent cache line prefetch	Enabled	
TCC activation offset	0	
Primary plane current value	0	
Secondary plane current value	0	
EIST	Enabled	
Turbo mode	Enabled	
CPU C3 report	Disabled	
CPU C6 report	Disabled	
CPU C7 report	Disabled	
Configurable TDP	TDP NOMINAL	
Config TDP LOCK	Disabled	
Long duration power limit	0	
Long duration maintained	1	
Short duration power limit	0	
ACPI T state	Disabled	

Table 203: Advanced - CPU configuration - Overview of profile settings

1.8.1.8 Chipset configuration

Setting/Option	Default profile	My setting
PCH LAN controller	Enabled	
Wake on LAN	Enabled	
Azalia	Auto	
Azalia PME	Disabled	
Azalia internal HDMI codec	Disabled	
High-precision timer	Enabled	
CF9h global reset	Host only	
PCI Express clock gating	Disabled	
DMI link ASPM PCH side	Disabled	
PCIe USB glitch W/A	Disabled	
SB CRID	Disabled	
NB CRID	Disabled	
DMI	-	

Table 204: Advanced - Chipset configuration - Overview of profile settings

Setting/Option	Default profile	My setting
DMI Vc1 control	Enabled	
DMI Vcp control	Enabled	
DMI Vcm control	Enabled	
DMI link ASPM CPU side	Disabled	
DMI extended synch control	Disabled	
DMI Gen 2	Auto	

Table 204: Advanced - Chipset configuration - Overview of profile settings

1.8.1.9 SATA configuration

Setting/Option	Default profile	My setting
SATA controller(s)	Enabled	
SATA mode selection	AHCI	
SATA test mode	Disabled	
Aggressive LPM support	Disabled	
SATA controller speed	Gen3	
Alternate ID	Disabled	
Serial ATA port 0	-	
Port 0	Enabled	
Hot plug	Disabled	
External SATA	Disabled	
SATA device type	Hard disk drive	
Spin up device	Disabled	
Serial ATA port 1	-	
Port 1	Enabled	
Hot plug	Disabled	
External SATA	Disabled	
SATA device type	Hard disk drive	
Spin up device	Disabled	
Serial ATA port 2	-	
Port 2	Enabled	
Hot plug	Disabled	
External SATA	Disabled	
Spin up device	Disabled	
Serial ATA port 3	-	
Port 3	Enabled	
Hot plug	Disabled	
External SATA	Disabled	
Spin up device	Disabled	

Table 205: Advanced - SATA configuration - Overview of profile settings

1.8.1.10 Memory configuration

Setting/Option	Default profile	My setting
DIMM profile	Default DIMM profile	
No fan memory frequency limiter	Enabled	
ECC support	Disabled	
Max TOLUD	Dynamic	
NMode support	Auto	
Memory scrambler	Enabled	
Memory refresh rate	Disabled	
MRC fast boot	Enabled	
Force cold reset	Enabled	
DIMM exit mode	Fast exit	
Power down mode	PPD	
Scrambler seed generation off	Disabled	
Memory remap	Enabled	
Memory alias check	Disabled	
Channel A DIMM control	Enable both DIMMS	
Channel B DIMM control	Enable both DIMMS	

Table 206: Advanced - Memory configuration - Overview of profile settings

1.8.1.11 USB configuration

Setting/Option	Default profile	My setting
EHC1 (ports 0-5)	Enabled	
EHC2 (ports 6-7)	Enabled	
xHCI mode	Auto	
HS port #1 switchable	Enabled	
HS port #2 switchable	Enabled	
HS port #3 switchable	Enabled	
HS port #4 switchable	Enabled	
Legacy USB support	Enabled	
USB 3.0 support	Enabled	
XHCI hand-off	Enabled	
EHCI hand-off	Disabled	
USB mass storage driver support	Enabled	
Device reset time-out	20 sec	
USB transfer time-out	20 sec	
Device power-up delay	Auto	
Overcurrent protection	Disabled	
Per port USB disable control		
USB port #0	Enabled	
USB port #1	Enabled	
USB port #2	Enabled	
USB port #3	Enabled	
USB port #4	Enabled	
USB port #5	Enabled	
USB port #6	Enabled	
USB port #7	Enabled	
Per port legacy USB support control		
USB0 port legacy support	Enabled	
USB1 port legacy support	Enabled	
USB2 port legacy support	Enabled	
USB3 port legacy support	Enabled	
USB4 port legacy support	Enabled	
USB5 port legacy support	Enabled	
USB6 port legacy support	Enabled	
USB7 port legacy support	Enabled	

Table 207: Advanced - USB configuration - Overview of profile settings

1.8.1.12 Serial port console redirection

Setting/Option	Default profile	My setting
Console redirection	Disabled	

Table 208: Advanced - Serial port console redirection - Overview of profile settings

1.8.2 Boot

1.8.2.1 Boot device priority

Setting/Option	Default profile	My setting
Boot priority selection	Type based	
1st boot device	SATA 0 drive	
2nd boot device	SATA 1 drive	
3rd boot device	SATA 2 drive	
4th boot device	SATA 3 drive	
5th boot device	USB hard disk	
6th boot device	USB CDROM	
7th boot device	Onboard LAN	
8th boot device	Other BEV device	

Table 209: Boot - Boot device priority - Overview of profile settings

1.8.2.2 Boot configuration

Setting/Option	Default profile	My setting
PXE Option ROM launch policy	Do not launch	
Storage Option ROM launch policy	Legacy ROM only	
Video Option ROM launch policy	Legacy ROM only	
Option ROM messages	Force BIOS	

Table 210: Boot - Boot configuration - Overview of profile settings

Setting/Option	Default profile	My setting
Boot logo	Auto	
Enter setup if no boot device	No	
Setup prompt timeout	1	
Enable popup boot menu	Yes	
Bootup NumLock state	On	
GateA20 active	Upon request	
INT19 trap response	Immediate	
Power loss control	Turn on	

Table 210: Boot - Boot configuration - Overview of profile settings

1.9 Allocation of resources

1.9.1 RAM address assignment

RAM address	Address in hexadecimal	Resource
(TOM - xxxx) – TOM ¹⁾	N.A.	ACPI reclaim, PCI memory range, video
1024 kB – (TOM - xxxx)	100000 - N.A.	Extended memory
869 kB – 1024 kB	0E0000h - 0FFFFFh	Runtime BIOS
768 kB – 896 kB	0C0000h - 0DFFFFh	Expansion area
640 kB – 768 kB	0A0000h - 0BFFFFh	Video memory and BIOS
639 kB – 640 kB	09FC00h - 09FFFFh	Extended BIOS data
0 – 639 kB	000000h - 09FC00h	Conventional memory

Table 211: RAM address assignment

1) TOM = Top of memory: max. installed DRAM.

1.9.2 I/O address assignment

I/O address	Resource
0000h - 00FFh	Motherboard resources
0170h - 0177h	Secondary IDE channel
01F0h - 01F7h	Primary IDE channel
0228h - 022Fh	COMF (I/O board 2)
02E8h - 02EFh	COME (I/O board 1)
02F8h - 02FFh	COMB (COM2)
0376h - 0376h	Secondary IDE channel command port
0377h - 0377h	Secondary IDE channel status port
0384h - 0385h	CAN controller
03B0h - 03DFh	Video system
03E8h - 03EFh	COMC (SDL onboard)
03F6h - 03F6h	Primary IDE channel command port
03F7h - 03F7h	Primary IDE channel status port
03F8h - 03FFh	COMA (COM1)
0400h - 047Fh	Motherboard resources
0500h - 057Fh	Motherboard resources
0CF8h - 0CFBh	PCI config address register
0CFCh - 0CFFh	PCI config data register
0D00h - FFFFh	PCI / PCI Express bus
4100h - 417Fh	MTCX
FF00h - FF07h	IDE bus master register

Table 212: I/O address assignment

1.9.3 Interrupt assignments in PIC mode

IRQ	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	NONE
System timer	•																
Keyboard		•															
IRQ cascade			•														
COMA (COM1)				○	•	○	○	○			○	○	○				
COMB (COM2)					•	○	○	○	○								
ACPI ¹⁾										•							
Real-time clock									•								
Coprocessor (FPU)												•					
Primary IDE channel													•				
Secondary IDE channel														•			
B&R	COMC (SDL onboard)				○	○	○	○	○		○	•	○				
	COME (IF Option 1 / I/O board 1)				○	○	○	○	○		•	○	○				
	COMF (IF Option 2 / I/O board 2)				○	○	○	○	●		○	○	○				
	CAN				○	○	○	○	○		●	○	○				

Table 213: IRQ interrupt assignments in PIC mode

1) Advanced Configuration and Power Interface.

- ... Default setting
- ... Optional setting

1.9.4 Interrupt assignments in APIC mode

A total of 23 IRQs are available in APIC (Advanced Programmable Interrupt Controller) mode. Enabling this option is only effective if done before the Windows operating system is installed.

IRQ	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	NONE
System timer	•																								
Keyboard		•																							
IRQ cascade			•																						
COMA (COM1)				○	●	○	○	○				○	○	○											
COMB (COM2)					●	○	○	○	○																
ACPI ¹⁾										●															
Real-time clock									●																
Coprocessor (FPU)												●													
Primary IDE channel													●												
Secondary IDE channel														●											
B&R	COMC (SDL onboard)				○	○	○	○	○			○	●	○											
	COME (IF Option 1 / I/O board 1)				○	○	○	○	○			●	○	○											
	COMF (IF Option 2 / I/O board 2)				○	○	○	○	●			○	○	○											
	CAN				○	○	○	○	○			●	○	○											
PIRQ A ²⁾																	●								
PIRQ B ³⁾																		●							
PIRQ C ⁴⁾																			●						
PIRQ D ⁵⁾																				●					
PIRQ E ⁶⁾																					●				
PIRQ F ⁷⁾																						●			
PIRQ G ⁸⁾																							●		
PIRQ H ⁹⁾																								●	

Table 214: IRQ interrupt assignments in APIC mode

1) Advanced Configuration and Power Interface.

2) PIRQ A: For PCIe; PEG 0/1/2, PCI Express root port 0, VGA controller, PCI Express root port 4 (ETH2)

3) PIRQ B: For PCIe; PCI Express root port 1, PCI Express root port 5

4) PIRQ C: For PCIe; PCI Express root port 2, SRAM

5) PIRQ D: For PCIe; PCI Express root port 3, PCIe to PCI bridge

6) PIRQ E: For PCIe; onboard gigabit LAN controller (ETH1)

7) PIRQ F: For PCIe; EHCI host controller 2, serial ATA controller 1, serial ATA controller 2

8) PIRQ G: For PCIe; Intel High Definition Audio controller, SMBus controller

9) PIRQ H: For PCIe; EHCI host controller 1, XHCI host controller

● ... Default setting

○ ... Optional setting




Figure 159: PCI and PCIe routing with enabled APIC for QM77/HM76 CPU boards

2 Upgrade information

Warning!

The BIOS and firmware on B&R devices must be kept current. New versions can be downloaded from the B&R website (www.br-automation.com).

2.1 BIOS upgrade

An upgrade may be necessary in order to accomplish the following:

- Updating implemented functions or adding newly implemented functions or components to BIOS Setup (information about changes can be found in the Readme file for the BIOS upgrade).

2.1.1 Important information

Information:

Customized BIOS settings are deleted when upgrading BIOS.

Before starting an upgrade, it helps to determine the various software versions.

2.1.1.1 Which BIOS version and firmware are already installed?

This information can be found on the following BIOS Setup screen:

- After switching on the PPC900, BIOS Setup can be accessed by pressing .
- From the "Advanced" menu in BIOS, select "OEM features".




Figure 160: Software version

2.1.2 Procedure with MS-DOS

1. Download the .zip file from the B&R website (www.br-automation.com).
2. Create bootable media.

Information:

In MS-DOS, Win95 and Win98, a blank HD disk can be made bootable by typing "sys a:" or "format a: / s" on the command line.

Information about creating a bootable diskette in Windows XP can be found on page 230.

Information on creating a USB flash drive for a B&R upgrade can be found on page 232.

Information on creating a storage device for a B&R upgrade can be found on page 233.

3. Copy the contents of the .zip file to the bootable media. If the B&R upgrade was already added when creating the bootable media with the B&R Embedded OS Installer, then this step is not necessary.
4. Connect the bootable media to the B&R device and reboot.
5. The following boot menu will be shown after startup:

- ```
1. Upgrade AMI BIOS for APC910/PPC900 (QM77 or HM76)
2. Exit
```

*Item 1:*

BIOS is automatically upgraded (default after 5 seconds).

*Item 2:*

Returns to the shell (MS-DOS)

### Information:

If a button is not pressed within 5 seconds, then item 1 is automatically carried out to update the industrial PC.

6. The system must be rebooted after a successful upgrade.
7. Reboot and press <Del> to enter BIOS Setup and load the setup defaults, then select "Save changes and exit".

## 2.2 Firmware upgrade

The "Firmware upgrade (MTCX, AP830)" software makes it possible to update the firmware for multiple controllers (MTCX, AP830) according to the PPC900 system variant.

The latest firmware upgrade is available in the Downloads section of the B&R website ([www.br-automation.com](http://www.br-automation.com)).

### 2.2.1 Procedure

1. Download the .zip file from the B&R website ([www.br-automation.com](http://www.br-automation.com)).
2. Open the **Control Center** in the Control Panel.
3. Select the **Versions** tab.
4. Under System unit, click on **Update** for **MTCX**. This brings up the "Open" dialog box.
5. Enter the name of the firmware file or select the file under **Filename**.
6. Click on **Open**. This brings up the "Open" dialog box.

The transfer can be canceled by clicking on **Cancel**. **Cancel** is disabled when writing to flash memory.

#### Warning!

**Do not press any panel keys while the firmware is being transferred! This can disrupt the procedure.**

Deleting the data in flash memory can take several seconds depending on the memory block being used. The progress indicator is not updated during this time.

#### Information:

**Power to the PC must be shut off and turned back on for the new firmware to take effect and for the updated version to be displayed. The user is prompted to do this when closing the Control Center.**

#### Information:

**For more information about saving and updating firmware, please refer to the help documentation for the Control Center.**

## 2.3 Creating an MS-DOS boot diskette in Windows XP

1. Insert a blank 1.44 MB HD diskette into the disk drive.
2. Open Windows Explorer.
3. Right-click on the 3½ floppy diskette icon and select "Format".




Figure 161: Creating a bootable diskette in Windows XP - Step 1

4. Select the "**Create an MS-DOS startup disk**" option, click on "**Start**" and acknowledge the warning message with "**OK**".



Figure 162: Creating a bootable diskette in Windows XP - Step 2



Figure 163: Creating a bootable diskette in Windows XP - Step 3

After creating the startup disk, some of the files must be deleted because of the size of the update.

To do this, all files (hidden system files, etc.) must be visible on the diskette.

In Explorer, go to the "Tools" menu, select "Folder options..." and open the "view" tab - now deactivate the option "hide protected operating system files (recommended)" (activated as default) and deactivate the option "show hidden files and folders".

| before       |       |                    |                  | after        |        |                    |                    |
|--------------|-------|--------------------|------------------|--------------|--------|--------------------|--------------------|
| Name         | Size  | Type               | Date Modified    | Name         | Size   | Type               | Date Modified      |
| DISPLAY.SYS  | 17 KB | System file        | 6/8/2000 5:00 PM | AUTOEXEC.BAT | 0 KB   | MS-DOS Batch File  | 3/22/2006 10:08 AM |
| EGA2.CPI     | 58 KB | CPI File           | 6/8/2000 5:00 PM | COMMAND.COM  | 91 KB  | MS-DOS Application | 6/8/2000 5:00 PM   |
| EGA3.CPI     | 58 KB | CPI File           | 6/8/2000 5:00 PM | CONFIG.SYS   | 0 KB   | System file        | 3/22/2006 10:08 AM |
| EGA.CPI      | 58 KB | CPI File           | 6/8/2000 5:00 PM | DISPLAY.SYS  | 17 KB  | System file        | 6/8/2000 5:00 PM   |
| KEYB.COM     | 22 KB | MS-DOS Application | 6/8/2000 5:00 PM | EGA2.CPI     | 58 KB  | CPI File           | 6/8/2000 5:00 PM   |
| KEYBOARD.SYS | 34 KB | System file        | 6/8/2000 5:00 PM | EGA3.CPI     | 58 KB  | CPI File           | 6/8/2000 5:00 PM   |
| KEYBRD2.SYS  | 32 KB | System file        | 6/8/2000 5:00 PM | EGA.CPI      | 58 KB  | CPI File           | 6/8/2000 5:00 PM   |
| KEYBRD3.SYS  | 31 KB | System file        | 6/8/2000 5:00 PM | IO.SYS       | 114 KB | System file        | 5/15/2001 6:57 PM  |
| KEYBRD4.SYS  | 13 KB | System file        | 6/8/2000 5:00 PM | KEYB.COM     | 22 KB  | MS-DOS Application | 6/8/2000 5:00 PM   |
| MODE.COM     | 29 KB | MS-DOS Application | 6/8/2000 5:00 PM | KEYBOARD.SYS | 34 KB  | System file        | 6/8/2000 5:00 PM   |
|              |       |                    |                  | KEYBRD2.SYS  | 32 KB  | System file        | 6/8/2000 5:00 PM   |
|              |       |                    |                  | KEYBRD3.SYS  | 31 KB  | System file        | 6/8/2000 5:00 PM   |
|              |       |                    |                  | KEYBRD4.SYS  | 13 KB  | System file        | 6/8/2000 5:00 PM   |
|              |       |                    |                  | MODE.COM     | 29 KB  | MS-DOS Application | 6/8/2000 5:00 PM   |
|              |       |                    |                  | MSDOS.SYS    | 1 KB   | System file        | 4/7/2001 1:40 PM   |

Figure 164: Creating a bootable diskette in Windows XP - Step 4

| Name         | Size   | Type               | Date Modified      |
|--------------|--------|--------------------|--------------------|
| AUTOEXEC.BAT | 0 KB   | MS-DOS Batch File  | 3/22/2006 10:08 AM |
| COMMAND.COM  | 91 KB  | MS-DOS Application | 6/8/2000 5:00 PM   |
| CONFIG.SYS   | 0 KB   | System file        | 3/22/2006 10:08 AM |
| DISPLAY.SYS  | 17 KB  | System file        | 6/8/2000 5:00 PM   |
| EGA2.CPI     | 58 KB  | CPI File           | 6/8/2000 5:00 PM   |
| EGA3.CPI     | 58 KB  | CPI File           | 6/8/2000 5:00 PM   |
| EGA.CPI      | 58 KB  | CPI File           | 6/8/2000 5:00 PM   |
| IO.SYS       | 114 KB | System file        | 5/15/2001 6:57 PM  |
| KEYB.COM     | 22 KB  | MS-DOS Application | 6/8/2000 5:00 PM   |
| KEYBOARD.SYS | 34 KB  | System file        | 6/8/2000 5:00 PM   |
| KEYBRD2.SYS  | 32 KB  | System file        | 6/8/2000 5:00 PM   |
| KEYBRD3.SYS  | 31 KB  | System file        | 6/8/2000 5:00 PM   |
| KEYBRD4.SYS  | 13 KB  | System file        | 6/8/2000 5:00 PM   |
| MODE.COM     | 29 KB  | MS-DOS Application | 6/8/2000 5:00 PM   |
| MSDOS.SYS    | 1 KB   | System file        | 4/7/2001 1:40 PM   |

Figure 165: Creating a bootable diskette in Windows XP - Step 5

Now all files (selected) except Command.com, IO.sys and MSDOS.sys can be deleted.

## 2.4 Creating a bootable USB flash drive for B&R upgrade files

When used in connection with a B&R Industrial PC, it is possible to upgrade (e.g. upgrade BIOS) from one of the USB flash drives available from B&R. To do this, the USB flash drive must be prepared accordingly. This is done with the B&R Embedded OS Installer, which can be downloaded at no cost from the B&R website ([www.br-automation.com](http://www.br-automation.com)).

### 2.4.1 Requirements

The following is required to create a bootable USB flash drive:

- B&R USB flash drive
- B&R Industrial PC
- USB media drive
- B&R Embedded OS Installer (V3.00 or higher)

### 2.4.2 Procedure

1. Connect the USB flash drive to the PC.
2. If the drive list is not refreshed automatically, the list can be updated using the command **Drives > Refresh**.
3. Select the desired USB flash drive in the drive list.
4. Change to the **Action** tab and select **Install a B&R update to a USB flash drive** as the type of action.
5. Enter the path to the MS-DOS operating system files. If the files are part of a .zip archive, then click on the button **From .zip file**. If the files are stored in a directory on the hard drive, then click on the button **From folder**.
6. In the **B&R upgrade** text box, it is also possible to enter the path to the .zip file for the B&R upgrade disk and select the file.
7. Click on the **Start action** button in the toolbar.




Figure 166: Creating a USB flash drive for B&R upgrade files

### 2.4.3 How to access MS-DOS

Information on creating an MS-DOS boot diskette can be found in section see "Creating an MS-DOS boot diskette in Windows XP" on page 230. The files from the diskette are then copied to the hard drive.

## 2.5 Creating a bootable mass storage device for B&R upgrade files

When used in connection with a B&R Industrial PC, it is possible to upgrade (e.g. upgrade BIOS) from a mass storage device (e.g. CFast card) available from B&R. To do this, the mass storage device must be prepared accordingly. This is done with the B&R Embedded OS Installer, which can be downloaded at no cost from the B&R website ([www.br-automation.com](http://www.br-automation.com)).

### 2.5.1 Requirements

The following is required to create a bootable mass storage device:

- B&R mass storage device (e.g. CFast card)
- PC with CFast slot
- B&R Embedded OS Installer (V3.00 or higher)

### 2.5.2 Procedure

1. Connect the storage device to the PC.
2. If the drive list is not refreshed automatically, the list can be updated using the command **Drives > Refresh**.
3. Select the desired mass storage device from the list of drives.
4. Change to the **Action** tab and select **Install a B&R update to a mass storage device** as the type of action.
5. Enter the path to the MS-DOS operating system files. If the files are part of a .zip archive, then click on the button **From .zip file**. If the files are stored in a directory on the hard drive, then click on the button **From folder**.
6. In the **B&R upgrade** text box, it is also possible to enter the path to the .zip file for the B&R upgrade disk and select the file.
7. Click on the **Start action** button in the toolbar.




Figure 167: Creating a mass storage device for B&R upgrade files

### 2.5.3 How to access MS-DOS

Information on creating an MS-DOS boot diskette can be found in section "Creating an MS-DOS boot diskette in Windows XP" on page 230. The files from the diskette are then copied to the hard drive.

## 3 Windows 7

### 3.1 General information

Windows® 7 offers a wealth of innovative features and performance improvements. The 64-bit variants can also exploit the full power of current PC architectures. Faster switching to power saving mode, quicker restores, less memory usage and high-speed detection of USB devices are just a few of the advantages provided by Windows® 7. Both English and German are available in Windows® 7 Professional, while Windows® 7 Ultimate supports up to 35 different languages (up to 36 languages in Service Pack 1). Product activation is not necessary on B&R PCs, which is a huge advantage for simple logistical procedures relating to machine automation.

All of the Windows® operating systems offered by B&R are from the Microsoft Embedded division. This guarantees much longer availability, especially compared to products offered on the consumer market.

### 3.2 Order data

| Model number                    | Short description                                                                                             | Figure                                                                                       |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| Windows 7 Professional/Ultimate |                                                                                                               |                                                                                              |
| 5SWWI7.1100-GER                 | Microsoft OEM Windows 7 Professional 32-bit, Service Pack 1, DVD, German. Only available with a new device.   |  Windows 7 |
| 5SWWI7.1100-ENG                 | Microsoft OEM Windows 7 Professional 32-bit, Service Pack 1, DVD, English. Only available with a new device.  |                                                                                              |
| 5SWWI7.1200-GER                 | Microsoft OEM Windows 7 Professional 64-bit, Service Pack 1, DVD, German. Only available with a new device.   |                                                                                              |
| 5SWWI7.1200-ENG                 | Microsoft OEM Windows 7 Professional 64-bit, Service Pack 1, DVD, English. Only available with a new device.  |                                                                                              |
| 5SWWI7.1300-MUL                 | Microsoft OEM Windows 7 Ultimate 32-bit, Service Pack 1, DVD, multilingual. Only available with a new device. |                                                                                              |
| 5SWWI7.1400-MUL                 | Microsoft OEM Windows 7 Ultimate 64-bit, Service Pack 1, DVD, multilingual. Only available with a new device. |                                                                                              |

Table 215: 5SWWI7.1100-GER, 5SWWI7.1100-ENG, 5SWWI7.1200-GER, 5SWWI7.1200-ENG, 5SWWI7.1300-MUL, 5SWWI7.1400-MUL - Order data

### 3.3 Overview

| Model number    | Edition      | Target system                                                     | Chipset                                       | Service Pack | Architectures | Language     | Preinstalled | Minimum hard disk space required | Minimum RAM required |
|-----------------|--------------|-------------------------------------------------------------------|-----------------------------------------------|--------------|---------------|--------------|--------------|----------------------------------|----------------------|
| 5SWWI7.1100-GER | Professional | APC510<br>APC511<br>APC810<br>APC910<br>PPC800<br>PPC900<br>PP500 | 945GME<br>GM45<br>QM77/HM76<br>NM10<br>US15W  | SP1          | 32-bit        | German       | Optional     | 16 GB                            | 1 GB                 |
| 5SWWI7.1100-ENG | Professional | APC510<br>APC511<br>APC810<br>APC910<br>PPC800<br>PPC900<br>PP500 | 945GME<br>GM45<br>QM77/HM76<br>NM10<br>US15W  | SP1          | 32-bit        | English      | Optional     | 16 GB                            | 1 GB                 |
| 5SWWI7.1200-GER | Professional | APC810<br>APC910<br>PPC800<br>PPC900                              | 945GME Intel® Core™2 Duo<br>GM45<br>QM77/HM76 | SP1          | 64-bit        | German       | Optional     | 20 GB                            | 2 GB                 |
| 5SWWI7.1200-ENG | Professional | APC810<br>APC910<br>PPC800<br>PPC900                              | 945GME Intel® Core™2 Duo<br>GM45<br>QM77/HM76 | SP1          | 64-bit        | English      | Optional     | 20 GB                            | 2 GB                 |
| 5SWWI7.1300-MUL | Ultimate     | APC510<br>APC511<br>APC810<br>APC910<br>PPC800<br>PPC900<br>PP500 | 945GME<br>GM45<br>QM77/HM76<br>NM10<br>US15W  | SP1          | 32-bit        | Multilingual | Optional     | 16 GB <sup>1)</sup>              | 1 GB                 |
| 5SWWI7.1400-MUL | Ultimate     | APC810<br>APC910<br>PPC800<br>PPC900                              | 945GME Intel® Core™2 Duo<br>GM45<br>QM77/HM76 | SP1          | 64-bit        | Multilingual | Optional     | 20 GB <sup>1)</sup>              | 2 GB                 |

Table 216: Windows 7 - Overview

1) The memory used by additional language packs is not taken into account in the minimum size of the disk.

### 3.4 Installation

Upon request, B&R can preinstall the required Windows 7 version on the desired mass storage device (e.g. CompactFlash card, etc.). All of the drivers required for operation (graphics, network, etc.) are also installed in this process.

### 3.5 Drivers

Current drivers for all approved operating systems are available in the Downloads section of the B&R website [www.br-automation.com](http://www.br-automation.com).

#### Information:

**Required drivers can only be downloaded from the B&R website, not from manufacturer websites.**

### 3.6 Special considerations, limitations

- Windows 7 does not contain a Beep.sys file, which means that an audible signal is no longer sounded (e.g. when pressing a key).
- There is currently no support for the Windows 7 system rating (although this does not apply to PP500, APC510, APC511, APC910 or PPC800 devices with an NM10 chipset).

## 4 Windows Embedded Standard 7

### 4.1 General information

The successor to Windows® XP Embedded is Windows® Embedded Standard 7. As with previous versions, this embedded operating system offers full system support for B&R Industrial PCs. In addition to brand new features that are also included in Windows® 7 Professional, Windows® Embedded Standard 7 includes embedded components such as Enhanced Write Filter, File-Based Write Filter, Registry Filter and USB Boot. Windows® Embedded Standard 7 is available in two different versions. The main difference between them has to do with multilingual support. Windows® Embedded Standard 7 is only available in a single language, whereas Windows® Embedded Standard 7 Premium supports the installation of several languages simultaneously.

With Windows® Embedded Standard 7, Microsoft has made substantial improvements in the area of security. The AppLocker program, available in the premium version, can prevent the execution of unknown or potentially undesired applications that are being installed over a network or from drives that are directly connected. A tiered approach allows the differentiation between scripts (.ps1, .bat, .cmd, .vbs and .js), installation files (.msi, .msp) and libraries (.dll, .ocx). AppLocker can also be configured to record undesired activity and display it in the Event Viewer. Windows® Embedded Standard 7 is available in both a 32-bit and 64-bit version.<sup>4)</sup> This ensures that even the most demanding applications have the level of support they need.

### 4.2 Order data

| Model number    | Short description                                                                                             | Figure |
|-----------------|---------------------------------------------------------------------------------------------------------------|--------|
|                 | <b>Windows Embedded Standard 7</b>                                                                            |        |
| 5SWWI7.1541-ENG | Windows Embedded Standard 7 SP1 - 32-bit - English - For PPC900 with QM77/HM76 chipset - License              |        |
| 5SWWI7.1641-ENG | Windows Embedded Standard 7 SP1 - 64-bit - English - For PPC900 with QM77/HM76 chipset - License              |        |
| 5SWWI7.1741-MUL | Windows Embedded Standard 7 Premium SP1 - 32-bit - Multilingual - For PPC900 with QM77/HM76 chipset - License |        |
| 5SWWI7.1841-MUL | Windows Embedded Standard 7 Premium SP1 - 64-bit - Multilingual - For PPC900 with QM77/HM76 chipset - License |        |
|                 | <b>Required accessories</b>                                                                                   |        |
|                 | <b>CFast cards</b>                                                                                            |        |
| 5CFAST.016G-00  | CFast card, 16 GB                                                                                             |        |
| 5CFAST.032G-00  | CFast card, 32 GB                                                                                             |        |
|                 | <b>Optional accessories</b>                                                                                   |        |
|                 | <b>Windows Embedded Standard 7</b>                                                                            |        |
| 5SWWI7.1900-MUL | Microsoft OEM Windows Embedded Standard 7 32-bit, Service Pack 1, Language Pack DVD                           |        |
| 5SWWI7.2000-MUL | Microsoft OEM Windows Embedded Standard 7 64-bit, Service Pack 1, Language Pack DVD                           |        |

Table 217: 5SWWI7.1541-ENG, 5SWWI7.1641-ENG, 5SWWI7.1741-MUL, 5SWWI7.1841-MUL - Order data

### 4.3 Overview

| Model number    | Edition  | Target system | Chipset      | Service Pack | Architectures | Language     | Preinstalled | Minimum disk size   | Minimum RAM required |
|-----------------|----------|---------------|--------------|--------------|---------------|--------------|--------------|---------------------|----------------------|
| 5SWWI7.1541-ENG | Embedded | PPC900        | QM77<br>HM76 | SP1          | 32-bit        | English      | Optional     | 16 GB               | 1 GB                 |
| 5SWWI7.1641-ENG | Embedded | PPC900        | QM77<br>HM76 | SP1          | 64-bit        | English      | Optional     | 16 GB               | 2 GB                 |
| 5SWWI7.1741-MUL | Premium  | PPC900        | QM77<br>HM76 | SP1          | 32-bit        | Multilingual | Optional     | 16 GB <sup>1)</sup> | 1 GB                 |
| 5SWWI7.1841-MUL | Premium  | PPC900        | QM77<br>HM76 | SP1          | 64-bit        | Multilingual | Optional     | 16 GB <sup>1)</sup> | 2 GB                 |

1) The memory used by additional language packs is not taken into account in the minimum size of the disk.

### 4.4 Features with WES7 (Windows Embedded Standard 7)

The following list of features shows the most important device functions included in Windows Embedded Standard 7.

| Function                       | Windows Embedded Standard 7 | Windows Embedded Standard 7 Premium |
|--------------------------------|-----------------------------|-------------------------------------|
| Enhanced Write Filter (EWF)    | ✓                           | ✓                                   |
| File-Based Write Filter (FBWF) | ✓                           | ✓                                   |
| Administrator accounts         | ✓                           | ✓                                   |
| User accounts                  | Configurable                | Configurable                        |

Table 218: Device functions in Windows Embedded Standard 7

<sup>4)</sup> 64-bit versions are not supported by all systems

| Function                                            | Windows Embedded Standard 7 | Windows Embedded Standard 7 Premium |
|-----------------------------------------------------|-----------------------------|-------------------------------------|
| Windows Explorer shell                              | ✓                           | ✓                                   |
| Registry filter                                     | ✓                           | ✓                                   |
| Internet Explorer 8.0                               | ✓                           | ✓                                   |
| Internet Information Service (IIS) 7.0              | ✓                           | ✓                                   |
| Anti-malware (Windows Defender)                     | -                           | ✓                                   |
| Add-ons (Snipping Tool, Sticky Notes)               | -                           | ✓                                   |
| Windows Firewall                                    | ✓                           | ✓                                   |
| .NET Framework 3.5                                  | ✓                           | ✓                                   |
| 32-bit and 64-bit                                   | ✓                           | ✓                                   |
| Remote Desktop Protocol 7.0                         | ✓                           | ✓                                   |
| File Compression Utility                            | ✓                           | ✓                                   |
| Windows Installer Service                           | ✓                           | ✓                                   |
| Windows XP Mode                                     | -                           | -                                   |
| Media Player 12                                     | ✓                           | ✓                                   |
| DirectX                                             | ✓                           | ✓                                   |
| Multilingual user interface packs in the same image | -                           | ✓                                   |
| International components and language services      | ✓                           | ✓                                   |
| Language pack setup                                 | ✓                           | ✓                                   |
| Windows Update                                      | Configurable                | Configurable                        |
| Windows PowerShell 2.0                              | ✓                           | ✓                                   |
| BitLocker                                           | -                           | ✓                                   |
| AppLocker                                           | -                           | ✓                                   |
| Tablet PC support                                   | -                           | ✓                                   |
| Windows Touch                                       | -                           | ✓                                   |
| Boot from USB flash drive                           | ✓                           | ✓                                   |
| Accessories                                         | ✓                           | ✓                                   |
| Page file                                           | Configurable                | Configurable                        |
| Number of fonts                                     | 134                         | 134                                 |

Table 218: Device functions in Windows Embedded Standard 7

## 4.5 Installation

Upon request, B&R can preinstall Windows Embedded Standard 7 on a suitable CompactFlash card (32-bit: at least 8 GB necessary, 64-bit: at least 16 GB necessary). The system is then automatically configured when it is switched on for the first time. This procedure takes approximately 30 minutes, with the device being rebooted a number of times.

### Information:

If the EWF should be used, all mass storage devices should be disconnected from the system during installation oder SYSPREP (except for the boot drive). It is also possible to disable additional mass storage devices in BIOS.

## 4.6 Drivers

All drivers required for operation are preinstalled along with the operating system. If an older version of the driver is still being used, the latest version can be downloaded and installed from the B&R website ([www.br-automation.com](http://www.br-automation.com)). It is important that Enhanced Write Filter (EWF) is disabled for this.

### 4.6.1 Touch screen driver

A touch screen driver will be installed automatically if a touch controller is detected during the Windows Embedded Standard 7 installation. If a touch controller is not detected during Windows Embedded Standard 7 installation, or if an Automation Panel 800/900 is connected later on, then the touch screen driver needs to be installed manually or the additional touch screen interface must be selected in the touch screen settings in the Windows Control Panel. The driver is available in the Downloads section of the B&R website ([www.br-automation.com](http://www.br-automation.com)). It is important that both the Enhanced Write Filter (EWF) and the File Based Write Filter (FBWF) are disabled for this.

### Information:

Required drivers can only be downloaded from the B&R website, not from manufacturer websites.

## 5 Windows XP Professional

### 5.1 General information

#### Information:

**After April 8th, 2014 Microsoft will no longer be providing any security updates, hotfixes, support (free or paid) nor technical resources for Windows XP.**

### 5.2 Order data

| Model number    | Short description                                                                                         | Figure                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| 5SWWXP.0600-ENG | Microsoft OEM Windows XP Professional Service Pack 3, CD, English. Only available with a new device.      |                                                                                    |
| 5SWWXP.0600-GER | Microsoft OEM Windows XP Professional Service Pack 3, CD, German. Only available with a new device.       |                                                                                    |
| 5SWWXP.0600-MUL | Microsoft OEM Windows XP Professional Service Pack 3, CD, multilingual. Only available with a new device. |  |

Table 219: 5SWWXP.0600-ENG, 5SWWXP.0600-GER, 5SWWXP.0600-MUL - Order data

### 5.3 Overview

| Model number    | Edition      | Target system                                                                                             | Chipset                                      | Service Pack | Language     | Preinstalled | Minimum hard disk space required | Minimum RAM required |
|-----------------|--------------|-----------------------------------------------------------------------------------------------------------|----------------------------------------------|--------------|--------------|--------------|----------------------------------|----------------------|
| 5SWWXP.0600-ENG | Professional | APC510<br>APC511<br>APC620<br>APC810<br>APC820<br>APC910<br>PPC700<br>PPC725<br>PPC800<br>PPC900<br>PP500 | 945GME<br>GM45<br>QM77/HM76<br>NM10<br>US15W | SP3          | English      | Optional     | ≤2.1 GB                          | 128 MB               |
| 5SWWXP.0600-GER | Professional | APC510<br>APC511<br>APC620<br>APC810<br>APC820<br>APC910<br>PPC700<br>PPC725<br>PPC800<br>PPC900<br>PP500 | 945GME<br>GM45<br>QM77/HM76<br>NM10<br>US15W | SP3          | German       | Optional     | ≤2.1 GB                          | 128 MB               |
| 5SWWXP.0600-MUL | Professional | APC510<br>APC511<br>APC620<br>APC810<br>APC820<br>APC910<br>PPC700<br>PPC725<br>PPC800<br>PPC900<br>PP500 | 945GME<br>GM45<br>QM77/HM76<br>NM10<br>US15W | SP3          | Multilingual | Optional     | ≤2.1 GB                          | 128 MB               |

### 5.4 Installation

Upon request, B&R can preinstall the required Windows XP Professional version on the desired mass storage device (e.g. CompactFlash card, etc.). All of the drivers required for operation (graphics, network, etc.) are also installed in this process.

### 5.5 Drivers

Current drivers for all approved operating systems are available in the Downloads section of the B&R website [www.br-automation.com](http://www.br-automation.com).

## Information:

Required drivers can only be downloaded from the B&R website, not from manufacturer websites.

## 6 Windows Embedded Standard 2009

### 6.1 General information

Windows® Embedded Standard 2009 is the modular version of Windows® XP Professional. It is used if XP applications should be executed with a minimal operating system size. Together with CompactFlash memory, Windows® Embedded Standard 2009 makes it possible to use the Microsoft desktop operating system in harsh environmental conditions. In addition to the familiar features included in Windows® XP Professional, Windows® Embedded Standard 2009 has been improved with regard to dependability by adding a write filter for individual memory partitions. By protecting individual partitions such as the boot partition, the PC system can be started without problems even after an unexpected power failure. B&R offers complete images for industrial PCs, Power Panel and Mobile Panel devices to make the transition to Windows® Embedded Standard 2009 as easy as possible. In addition to Windows® Embedded Standard 2009, the standard Windows® XP Professional operating system is also available in English, German and a multilingual version.

Windows® Embedded Standard 2009 is based on the same binary files as Windows® XP Professional with Service Pack 3 and is optimally tailored to the hardware being used. In other words, only the functions and modules required by the respective device are included. Windows® Embedded Standard 2009 is also based on the same reliable code as Windows® XP Professional with SP3. It provides industry with leading reliability, security and performance improvements as well as the latest technology for web browsing and extensive device support.

### 6.2 Order data

| Model number    | Short description                                                            | Figure |
|-----------------|------------------------------------------------------------------------------|--------|
|                 | <b>Windows Embedded Standard 2009</b>                                        |        |
| 5SWWXP.0741-ENG | Windows Embedded Standard 2009 - English - For PPC900 with QM77/HM76 chipset |        |
|                 | <b>Required accessories</b>                                                  |        |
|                 | <b>CFast cards</b>                                                           |        |
| 5CFAST.016G-00  | CFast card, 16 GB                                                            |        |
| 5CFAST.032G-00  | CFast card, 32 GB                                                            |        |
| 5CFAST.2048-00  | CFast card, 2 GB                                                             |        |
| 5CFAST.4096-00  | CFast card, 4 GB                                                             |        |
| 5CFAST.8192-00  | CFast card, 8 GB                                                             |        |

Table 220: 5SWWXP.0741-ENG - Order data

### 6.3 Overview

| Model number    | Target sys-tem | Chipset      | Language | Preinstalled | Minimum disk size | Minimum RAM required |
|-----------------|----------------|--------------|----------|--------------|-------------------|----------------------|
| 5SWWXP.0741-ENG | PPC900         | QM77<br>HM76 | English  | Yes          | 2 GB              | 256 MB               |

### 6.4 Features with WES2009 (Windows Embedded Standard 2009)

The following list of features shows the most important device functions included in Windows Embedded Standard 2009.

| Function                           | Present      |
|------------------------------------|--------------|
| Enhanced Write Filter (EWF)        | ✓            |
| File-Based Write Filter (FBWF)     | ✓            |
| Page file                          | Configurable |
| Administrator accounts             | ✓            |
| User accounts                      | Configurable |
| Explorer shell                     | ✓            |
| Registry filter                    | ✓            |
| Internet Explorer 8.0              | ✓            |
| Internet information service (IIS) | -            |
| Terminal service                   | ✓            |
| Windows Firewall                   | ✓            |
| MSN Explorer                       | -            |
| Outlook Express                    | -            |
| Administrative Tools               | ✓            |
| Remote Desktop                     | ✓            |
| Remote Assistance                  | -            |
| .NET Framework                     | -            |
| ASP.NET                            | -            |
| OpenGL support                     | ✓            |

Table 221: Device functions in Windows Embedded Standard 2009

| Function                             | Present |
|--------------------------------------|---------|
| Local network bridge                 | ✓       |
| Codepages / User locales / Keyboards | ✓       |
| Disk Management Service              | ✓       |
| Windows Installer Service            | ✓       |
| Class Installer                      | ✓       |
| CoDevice Installer                   | ✓       |
| Media Player 6.4                     | ✓       |
| DirectX 9.0c                         | ✓       |
| Accessories                          | ✓       |
| Number of fonts                      | 89      |

Table 221: Device functions in Windows Embedded Standard 2009

## 6.5 Installation

Upon request, Windows Embedded Standard 2009 can be preinstalled by B&R on a suitable CompactFlash card (min. 1 GB). The system is then automatically configured when it is switched on for the first time. This procedure takes approximately 10 minutes, with the device being rebooted a number of times.

## 6.6 Drivers

All drivers required for operation are preinstalled along with the operating system. If an older version of the driver is still being used, the latest version can be downloaded and installed from the B&R website ([www.br-automation.com](http://www.br-automation.com)). It is important that Enhanced Write Filter (EWF) is disabled for this.

# Chapter 5 • Standards and certifications

## 1 Standards and guidelines

### 1.1 CE mark



This mark certifies that all harmonized EN standards for the applicable directives have been met for B&R products.

### 1.2 EMC directive

These devices meet the requirements of EC directive "2004/108/EC Electromagnetic compatibility" and are designed for the following areas:

|                   |                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------|
| EN 61131-2:2007   | Programmable logic controllers - Part 2: Equipment requirements and tests                                         |
| EN 61000-6-2:2005 | Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity for industrial environments          |
| EN 61000-6-4:2007 | Electromagnetic compatibility (EMC) - Part 6-4: Generic standards - Emission standard for industrial environments |

### 1.3 Low voltage directive

These devices satisfy the requirements of EC directive "2006/95/EC Low voltage directive" and are designed for the following areas:

|                           |                                                                                       |
|---------------------------|---------------------------------------------------------------------------------------|
| EN 61131-2:2007           | Programmable logic controllers - Part 2: Equipment requirements and tests             |
| EN 60204-1:2006 + A1:2009 | Safety of machinery - Electrical equipment of machines - Part 1: General requirements |

## 2 Certifications

### Danger!

**A complete system can only receive certification if ALL of the individual components it includes have the applicable certifications. If an individual component is being used that DOES NOT have an applicable certification, then the complete system will NOT RECEIVE certification.**

B&R products and services comply with applicable standards. This includes international standards from organizations such as ISO, IEC and CENELEC, as well as national standards from organizations such as UL, CSA, FCC, VDE, ÖVE, etc. We are committed to ensuring the reliability of our products in an industrial environment.

Unless otherwise specified, the following certifications apply:

### 2.1 UL certification



Products with this label have been certified by Underwriters Laboratories and are listed as "Industrial Control Equipment". This mark is valid for the USA and Canada and simplifies the certification of your machines and systems in these areas.

Underwriters Laboratories (UL) in accordance with the UL508 standard - 17th Edition Canadian (CSA) standard in accordance with C22.2 No. 142-M1987

### 2.2 UL Haz. Loc. Certifications



Products with this label have been certified by Underwriters Laboratories and are listed as "Industrial Control Equipment for Use in Hazardous Locations". This mark is valid for the USA and Canada and simplifies the certification of your machines and systems in these areas.

Underwriters Laboratories (UL) in accordance with standard ANSI/ISA 12.12.01:2013 Canadian (CSA) standard in accordance with C22.2 No. 213-M1987

Ind. Cont. Eq.  
for Haz.Locs.  
Cl. I, Div. 2,  
Groups ABCD  
2P61 (T3C)

### 2.3 GOST-R



Products with this mark have been certified by an accredited certification body and have been approved for import to the Russian Federation.

# Chapter 6 • Accessories

The following accessories have successfully completed functional testing at B&R and are approved for use with this device. Nevertheless, it is important to observe any limitations that may apply to the complete system when operated with other individual components. When operating the complete system, the specifications for the individual components must be adhered to.

All components listed in this manual have been subjected to extensive system and compatibility testing and are approved for use. B&R can make no guarantee regarding the functionality of non-approved accessories.

## 1 Power connectors

### 1.1 0TB103.9x

#### 1.1.1 General information

The single-row 3-pin terminal block 0TB103 is used to connect the supply voltage.

#### 1.1.2 Order data

| Model number           | Short description                                                                                                  | Figure                                                                               |
|------------------------|--------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Terminal blocks</b> |                                                                                                                    |                                                                                      |
| 0TB103.9               | Connector, 24 VDC, 3-pin female, 3.31 mm <sup>2</sup> screw clamp, protected against vibration by the screw flange |                                                                                      |
| 0TB103.91              | Connector, 24 VDC, 3-pin female, 3.31 mm <sup>2</sup> cage clamp, protected against vibration by the screw flange  |  |

Table 222: 0TB103.9, 0TB103.91 - Order data

#### 1.1.3 Technical data

#### Information:

**The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.**

| Product ID                             | 0TB103.9                                                                          | 0TB103.91                    |
|----------------------------------------|-----------------------------------------------------------------------------------|------------------------------|
| <b>General information</b>             |                                                                                   |                              |
| Certification                          |                                                                                   |                              |
| CE                                     | Yes                                                                               |                              |
| cULus                                  | Yes                                                                               |                              |
| cULus HazLoc Class 1 Division 2        | Yes <sup>1)</sup>                                                                 |                              |
| GL                                     | Yes <sup>1)</sup>                                                                 |                              |
| <b>Terminal block</b>                  |                                                                                   |                              |
| Note                                   | Protected against vibration by the screw flange<br>Nominal values according to UL |                              |
| Number of pins                         | 3 (female)                                                                        |                              |
| Type of terminal clamp                 | Screw clamps                                                                      | Cage clamps <sup>3)</sup>    |
| Cable type                             | Only copper wires (no aluminum wires!)                                            |                              |
| Distance between contacts              | 5.08 mm                                                                           |                              |
| Connection cross section               |                                                                                   |                              |
| AWG wire                               | 26 to 14 AWG                                                                      | 26 to 12 AWG                 |
| Wire end sleeves with plastic covering | 0.20 to 1.50 mm <sup>2</sup>                                                      |                              |
| Solid wires                            | 0.20 to 2.50 mm <sup>2</sup>                                                      |                              |
| Fine strand wires                      | 0.20 to 1.50 mm <sup>2</sup>                                                      | 0.20 to 2.50 mm <sup>2</sup> |
| With wire end sleeves                  | 0.20 to 1.50 mm <sup>2</sup>                                                      |                              |
| Fastening torque                       | 0.4 Nm                                                                            | -                            |

Table 223: 0TB103.9, 0TB103.91 - Technical data

| Product ID                        | 0TB103.9       | 0TB103.91 |
|-----------------------------------|----------------|-----------|
| <b>Electrical characteristics</b> |                |           |
| Nominal voltage                   | 300 V          |           |
| Nominal current <sup>2)</sup>     | 10 A / contact |           |
| Contact resistance                | ≤5 mΩ          |           |

Table 223: 0TB103.9, 0TB103.91 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification  
 2) The limit data for each I/O module must be taken into consideration.  
 3) Cage clamp terminal blocks cannot be used side-by-side.

## 1.2 0TB3103.8000

### 1.2.1 General information

This single row 3-pin terminal block is used to connect the supply voltage.

### 1.2.2 Order data

| Model number | Short description                                                                                                | Figure                                                                              |
|--------------|------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 0TB3103.8000 | Connector, 230 VAC, 3-pin female, 4 mm <sup>2</sup> screw clamp, protected against vibration by the screw flange |  |

Table 224: 0TB3103.8000 - Order data

### 1.2.3 Technical data

| Product ID                             | 0TB3103.8000                                    |
|----------------------------------------|-------------------------------------------------|
| <b>General information</b>             |                                                 |
| Certification                          |                                                 |
| CE                                     | Yes                                             |
| cULus                                  | Yes                                             |
| cULus HazLoc Class 1 Division 2        | Yes <sup>1)</sup>                               |
| <b>Terminal block</b>                  |                                                 |
| Note                                   | Protected against vibration by the screw flange |
| Number of pins                         | 3 (male)                                        |
| Type of terminal clamp                 | Screw clamps                                    |
| Distance between contacts              | 7.62 mm                                         |
| Connection cross section               |                                                 |
| AWG wire                               | 24 to 10 AWG                                    |
| Wire end sleeves with plastic covering | 0.25 to 4 mm <sup>2</sup>                       |
| Flexible                               | 0.2 to 4 mm <sup>2</sup>                        |
| Inflexible                             | 0.2 to 4 mm <sup>2</sup>                        |
| Fastening torque                       | Min. 0.5 Nm / max. 0.6 Nm                       |
| <b>Electrical characteristics</b>      |                                                 |
| Nominal voltage                        | 400 V                                           |
| Nominal current                        | 20 A                                            |

Table 225: 0TB3103.8000 - Technical data

- 1) Yes, although applies only if all components installed within the complete system have this certification

## 2 Replacement CMOS batteries

### 2.1 0AC201.91 / 4A0006.00-000

#### 2.1.1 General information

This lithium battery is needed to back BIOS CMOS data and the real-time clock (RTC).

The battery is subject to wear and must be replaced when the battery power is insufficient ("Bad" status).

#### 2.1.2 Order data

| Model number  | Short description                                                                                                                                                                                                                                                                                                                                                 | Figure |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| 0AC201.91     | Batteries<br>Lithium batteries 4 pcs., 3 V / 950 mAh button cell We hereby state that the lithium cells contained in this shipment qualify as "partly regulated". Handle with care. If the package is damaged, inspect the cells, repack intact cells and protect the cells against short circuit. For emergency information, call RENATA SA at + 41 61 319 28 27 |        |
| 4A0006.00-000 | Lithium battery, 3 V / 950 mAh, button cell                                                                                                                                                                                                                                                                                                                       |        |

Table 226: 0AC201.91, 4A0006.00-000 - Order data

#### 2.1.3 Technical data

#### Warning!

**The battery must be replaced by a Type CR2477N Renata battery only. The use of another battery may present a risk of fire or explosion.**

**The battery may explode if handled improperly. Do not recharge, disassemble or dispose of in fire.**

#### Information:

**The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.**

| Product ID                        | 0AC201.91              | 4A0006.00-000 |
|-----------------------------------|------------------------|---------------|
| <b>General information</b>        |                        |               |
| Storage time                      | Max. 3 years at 30°C   |               |
| Certification                     |                        |               |
| CE                                | Yes                    |               |
| cULus                             | Yes                    |               |
| <b>Electrical characteristics</b> |                        |               |
| Capacity                          | 950 mAh                |               |
| Self-discharging                  | <1% per year (at 23°C) |               |
| Voltage range                     | 3 V                    |               |
| <b>Environmental conditions</b>   |                        |               |
| Temperature Storage               | -20 to 60°C            |               |
| Relative humidity Operation       | 0 to 95%               |               |
| Storage                           | 0 to 95%               |               |
| Transport                         | 0 to 95%               |               |

Table 227: 0AC201.91, 4A0006.00-000 - Technical data

## 3 CFast cards

### 3.1 5CFAST.xxxx-00

#### 3.1.1 General information

CFast cards are based on SLC (single-level cell) technology and are SATA 2.6 compatible. Their dimensions are identical to CompactFlash cards.

#### 3.1.2 Order data

| Model number   | Short description  | Figure                                                                             |
|----------------|--------------------|------------------------------------------------------------------------------------|
|                | <b>CFast cards</b> |                                                                                    |
| 5CFAST.2048-00 | CFast card, 2 GB   |                                                                                    |
| 5CFAST.4096-00 | CFast card, 4 GB   |                                                                                    |
| 5CFAST.8192-00 | CFast card, 8 GB   |                                                                                    |
| 5CFAST.016G-00 | CFast card, 16 GB  |                                                                                    |
| 5CFAST.032G-00 | CFast card, 32 GB  |  |

Table 228: 5CFAST.2048-00, 5CFAST.4096-00, 5CFAST.8192-00, 5CFAST.016G-00, 5CFAST.032G-00 - Order data

#### 3.1.3 Technical data

##### Information:

The following characteristics, features and limit values only apply to this accessory and can deviate from those specified for the complete system. The data specifications for the complete system take precedence over those of individual components.

| Product ID                      | 5CFAST.2048-00                                                    | 5CFAST.4096-00 | 5CFAST.8192-00                                                | 5CFAST.016G-00 | 5CFAST.032G-00 |
|---------------------------------|-------------------------------------------------------------------|----------------|---------------------------------------------------------------|----------------|----------------|
| <b>General information</b>      |                                                                   |                |                                                               |                |                |
| Capacity                        | 2 GB                                                              | 4 GB           | 8 GB                                                          | 16 GB          | 32 GB          |
| Data retention                  |                                                                   |                | 10 years                                                      |                |                |
| Data reliability                |                                                                   |                | < 1 unrecoverable error in 10 <sup>14</sup> bit read accesses |                |                |
| Lifetime monitoring             |                                                                   |                | Yes                                                           |                |                |
| MTBF                            |                                                                   |                | >2,500,000 hours (at 25°C)                                    |                |                |
| Maintenance                     |                                                                   |                | None                                                          |                |                |
| Supported operating modes       | SATA 2.6, max. PIO Mode 4, Multiword DMA Mode 2, Ultra DMA Mode 6 |                |                                                               |                |                |
| <b>Continuous reading</b>       |                                                                   |                |                                                               |                |                |
| Typical                         |                                                                   |                |                                                               |                |                |
| With 128 kB block size          | 56 MB/s                                                           | 107 MB/s       | 116 MB/s                                                      | 116 MB/s       | 116 MB/s       |
| With 4 kB block size            | 23 MB/s                                                           | 26 MB/s        | 29 MB/s                                                       | 29 MB/s        | 29 MB/s        |
| Maximum                         |                                                                   |                |                                                               |                |                |
| With 128 kB block size          | 60 MB/s                                                           | 110 MB/s       | 120 MB/s                                                      | 120 MB/s       | 120 MB/s       |
| With 4 kB block size            | 25 MB/s                                                           | 30 MB/s        | 35 MB/s                                                       | 35 MB/s        | 35 MB/s        |
| <b>Continuous writing</b>       |                                                                   |                |                                                               |                |                |
| Typical                         |                                                                   |                |                                                               |                |                |
| With 128 kB block size          | 24 MB/s                                                           | 49 MB/s        | 93 MB/s                                                       | 93 MB/s        | 93 MB/s        |
| With 4 kB block size            | 17 MB/s                                                           | 19 MB/s        | 21 MB/s                                                       | 21 MB/s        | 21 MB/s        |
| Maximum                         |                                                                   |                |                                                               |                |                |
| With 128 kB block size          | 30 MB/s                                                           | 55 MB/s        | 100 MB/s                                                      | 100 MB/s       | 100 MB/s       |
| With 4 kB block size            | 20 MB/s                                                           | 25 MB/s        | 25 MB/s                                                       | 25 MB/s        | 25 MB/s        |
| <b>Certification</b>            |                                                                   |                |                                                               |                |                |
| CE                              |                                                                   |                | Yes                                                           |                |                |
| cULus                           |                                                                   |                | Yes                                                           |                |                |
| cULus HazLoc Class 1 Division 2 |                                                                   |                | Yes <sup>1)</sup>                                             |                |                |
| GOST-R                          |                                                                   |                | Yes                                                           |                |                |
| GL                              |                                                                   |                | Yes <sup>1)</sup>                                             |                |                |
| <b>Endurance</b>                |                                                                   |                |                                                               |                |                |
| SLC flash                       |                                                                   |                | Yes                                                           |                |                |
| Wear leveling                   |                                                                   |                | Static                                                        |                |                |
| S.M.A.R.T. support              |                                                                   |                | Yes                                                           |                |                |
| <b>Support</b>                  |                                                                   |                |                                                               |                |                |
| Hardware                        | APC910, PPC900                                                    |                |                                                               |                |                |

Table 229: 5CFAST.2048-00, 5CFAST.4096-00, 5CFAST.8192-00, 5CFAST.016G-00, 5CFAST.032G-00 - Technical data

| Product ID                          | 5CFAST.2048-00 | 5CFAST.4096-00                                          | 5CFAST.8192-00           | 5CFAST.016G-00 | 5CFAST.032G-00 |
|-------------------------------------|----------------|---------------------------------------------------------|--------------------------|----------------|----------------|
| Operating systems                   |                |                                                         |                          |                |                |
| Windows 7 32-bit                    | No             | No                                                      | No                       | Yes            | Yes            |
| Windows 7 64-bit                    | No             | No                                                      | No                       | No             | Yes            |
| Windows Embedded Standard 7, 32-bit | No             | No                                                      | No                       | Yes            | Yes            |
| Windows Embedded Standard 7, 64-bit | No             | No                                                      | No                       | Yes            | Yes            |
| Windows XP Professional             | No             | Yes                                                     | Yes                      | Yes            | Yes            |
| Windows Embedded Standard 2009      |                |                                                         | Yes                      |                |                |
| Software                            |                |                                                         |                          |                |                |
| PVI Transfer                        |                | ≥V4.0.0.8 (part of PVI Development Setup ≥ V3.0.2.3014) |                          |                |                |
| B&R Embedded OS Installer           | ≥V3.10         | ≥V3.10                                                  | ≥V3.10                   | ≥V3.20         | ≥V3.21         |
| <b>Environmental conditions</b>     |                |                                                         |                          |                |                |
| Temperature                         |                |                                                         |                          |                |                |
| Operation                           |                |                                                         | 0 to 70°C                |                |                |
| Storage                             |                |                                                         | -50 to 100°C             |                |                |
| Transport                           |                |                                                         | -50 to 100°C             |                |                |
| Relative humidity                   |                |                                                         |                          |                |                |
| Operation                           |                |                                                         | Max. 85% at 70°C         |                |                |
| Storage                             |                |                                                         | Max. 85% at 70°C         |                |                |
| Transport                           |                |                                                         | Max. 85% at 70°C         |                |                |
| Vibration                           |                |                                                         |                          |                |                |
| Operation                           |                |                                                         | 20 g peak, 10 to 2000 Hz |                |                |
| Storage                             |                |                                                         | 20 g peak, 10 to 2000 Hz |                |                |
| Transport                           |                |                                                         | 20 g peak, 10 to 2000 Hz |                |                |
| Shock                               |                |                                                         |                          |                |                |
| Operation                           |                |                                                         | 1.5 kg peak, 0.5 ms      |                |                |
| Storage                             |                |                                                         | 1.5 kg peak, 0.5 ms      |                |                |
| Transport                           |                |                                                         | 1.5 kg peak, 0.5 ms      |                |                |
| Altitude                            |                |                                                         |                          | TBD            |                |
| Operation                           |                |                                                         |                          |                |                |
| <b>Mechanical characteristics</b>   |                |                                                         |                          |                |                |
| Dimensions                          |                |                                                         |                          |                |                |
| Width                               |                |                                                         | 42.8 ±0.10 mm            |                |                |
| Length                              |                |                                                         | 36.4 ±0.10 mm            |                |                |
| Depth                               |                |                                                         | 3.6 ±0.10 mm             |                |                |
| Weight                              |                |                                                         | 10 g                     |                |                |

Table 229: 5CFAST.2048-00, 5CFAST.4096-00, 5CFAST.8192-00, 5CFAST.016G-00, 5CFAST.032G-00 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

### 3.1.4 Dimensions




Figure 168: CFast card - Dimensions

### 3.1.5 Temperature humidity diagram




Figure 169: 5CFAST.xxxx-00 - Temperature humidity diagram

## 4 USB flash drives

### 4.1 5MMUSB.xxxx-01

#### 4.1.1 General information

USB flash drives are storage media that are easy to replace. Because of their fast data transfer (USB 2.0), USB flash drives are ideal for use as portable data storage. Without requiring additional drivers ("hot plugging", except in the case of Windows 98SE), the USB flash drive can immediately act as an additional drive where data can be read or written.

#### Information:

**Due to the vast quantity of USB flash drives available on the market as well as their short product life cycle, we reserve the right to supply alternative products at any time. The following measures may therefore be necessary in order to boot from these flash drives as well:**

- The flash drive must be reformatted or in some cases even repartitioned (set active partition).
- The flash drive must be the first bootable device in the BIOS boot order; alternatively, the IDE controllers can be disabled in BIOS. This can be avoided in most cases if the "fdisk /mbr" command is additionally executed on the USB flash drive.

#### 4.1.2 Order data

| Model number           | Short description                 | Figure                                                                              |
|------------------------|-----------------------------------|-------------------------------------------------------------------------------------|
| <b>USB accessories</b> |                                   |                                                                                     |
| 5MMUSB.2048-01         | USB 2.0 flash drive, 2048 MB, B&R |                                                                                     |
| 5MMUSB.4096-01         | USB 2.0 flash drive, 4096 MB, B&R |  |

Table 230: 5MMUSB.2048-01, 5MMUSB.4096-01 - Order data

#### 4.1.3 Technical data

| Product ID                        | 5MMUSB.2048-01                                                          | 5MMUSB.4096-01 |
|-----------------------------------|-------------------------------------------------------------------------|----------------|
| <b>General information</b>        |                                                                         |                |
| Capacity                          | 2 GB                                                                    | 4 GB           |
| Data retention                    | >10 years                                                               |                |
| LEDs                              | 1 LED (green) <sup>1)</sup>                                             |                |
| MTBF                              | >3,000,000 hours                                                        |                |
| Type                              | USB 1.1, USB 2.0                                                        |                |
| Maintenance                       | None                                                                    |                |
| Default file system               | FAT16                                                                   | FAT32          |
| Certification                     |                                                                         |                |
| CE                                | Yes                                                                     |                |
| GOST-R                            | Yes                                                                     |                |
| <b>Interfaces</b>                 |                                                                         |                |
| USB                               |                                                                         |                |
| Type                              | USB 1.1, USB 2.0                                                        |                |
| Connection                        | To any USB Type A interface                                             |                |
| Transfer rate                     | Low speed (1.5 Mbit/s), full speed (12 Mbit/s), high speed (480 Mbit/s) |                |
| Sequential reading                | Full speed max. 1 MB/s,<br>High speed max. 32 MB/s                      |                |
| Sequential writing                | Full speed max. 0.9 MB/s,<br>High speed max. 23 MB/s                    |                |
| <b>Support</b>                    |                                                                         |                |
| Operating systems                 |                                                                         |                |
| Windows 7                         | Yes                                                                     |                |
| Windows XP Professional           | Yes                                                                     |                |
| Windows XP Embedded               | Yes                                                                     |                |
| Windows ME                        | Yes                                                                     |                |
| Windows 2000                      | Yes                                                                     |                |
| Windows CE 5.0                    | Yes                                                                     |                |
| Windows CE 4.2                    | Yes                                                                     |                |
| <b>Electrical characteristics</b> |                                                                         |                |
| Power consumption                 | Max. 500 µA sleep mode, max. 120 mA read/write                          |                |

Table 231: 5MMUSB.2048-01, 5MMUSB.4096-01 - Technical data

| Product ID                        | 5MMUSB.2048-01             | 5MMUSB.4096-01 |
|-----------------------------------|----------------------------|----------------|
| <b>Environmental conditions</b>   |                            |                |
| Temperature                       |                            |                |
| Operation                         | 0 to 70°C                  |                |
| Storage                           | -50 to 100°C               |                |
| Transport                         | -50 to 100°C               |                |
| Relative humidity                 |                            |                |
| Operation                         | 85%, non-condensing        |                |
| Storage                           | 85%, non-condensing        |                |
| Transport                         | 85%, non-condensing        |                |
| Vibration                         |                            |                |
| Operation                         | 20 to 2000 Hz: 20 g (peak) |                |
| Storage                           | 20 to 2000 Hz: 20 g (peak) |                |
| Transport                         | 20 to 2000 Hz: 20 g (peak) |                |
| Shock                             |                            |                |
| Operation                         | Max. 1500 g (peak)         |                |
| Storage                           | Max. 1500 g (peak)         |                |
| Transport                         | Max. 1500 g (peak)         |                |
| Altitude                          |                            |                |
| Operation                         | Max. 3048 m                |                |
| Storage                           | Max. 12192 m               |                |
| Transport                         | Max. 12192 m               |                |
| <b>Mechanical characteristics</b> |                            |                |
| Dimensions                        |                            |                |
| Width                             | 17.97 mm                   |                |
| Length                            | 67.85 mm                   |                |
| Height                            | 8.35 mm                    |                |

Table 231: 5MMUSB.2048-01, 5MMUSB.4096-01 - Technical data

1) Indicates data being transferred (sending and receiving).

#### 4.1.4 Temperature humidity diagram




Figure 170: 5MMUSB.xxxx-01 - Temperature humidity diagram

## 5 Cables

### 5.1 DVI cables

#### 5.1.1 5CADVI.0xxx-00

##### 5.1.1.1 General information

5CADVI.0xxx-00 DVI cables are designed for use in inflexible applications.

##### Caution!

**Power must be turned off before plugging in and unplugging cables.**

##### 5.1.1.2 Order data

| Model number   | Short description  | Figure                                                                             |
|----------------|--------------------|------------------------------------------------------------------------------------|
|                | DVI cable          |                                                                                    |
| 5CADVI.0018-00 | DVI-D cable, 1.8 m |                                                                                    |
| 5CADVI.0050-00 | DVI-D cable, 5 m   |                                                                                    |
| 5CADVI.0100-00 | DVI-D cable, 10 m  |  |

Table 232: 5CADVI.0018-00, 5CADVI.0050-00, 5CADVI.0100-00 - Order data

##### 5.1.1.3 Technical data

| Product ID                        | 5CADVI.0018-00                                                                | 5CADVI.0050-00                                              | 5CADVI.0100-00 |
|-----------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------|----------------|
| <b>General information</b>        |                                                                               |                                                             |                |
| Certification                     |                                                                               |                                                             |                |
| CE                                |                                                                               | Yes                                                         |                |
| cULus                             |                                                                               | Yes                                                         |                |
| GOST-R                            |                                                                               | Yes                                                         |                |
| GL                                |                                                                               | Yes <sup>1)</sup>                                           |                |
| <b>Cable structure</b>            |                                                                               |                                                             |                |
| Wire cross section                |                                                                               | AWG 28                                                      |                |
| Shielding                         |                                                                               | Individual cable pairs and entire cable                     |                |
| Cable shielding                   |                                                                               | Tinned copper mesh, optical coverage >86%                   |                |
| Outer sheathing                   |                                                                               |                                                             |                |
| Material                          |                                                                               | PVC                                                         |                |
| Color                             |                                                                               | Beige                                                       |                |
| Labeling                          |                                                                               | AWM STYLE 20276 80°C 30V VW1 DVI DIGITAL SINGLE LINK DER AN |                |
| <b>Connector</b>                  |                                                                               |                                                             |                |
| Type                              |                                                                               | 2x DVI-D (18+1), male                                       |                |
| Connection cycles                 |                                                                               | 100                                                         |                |
| Locating screw tightening torque  |                                                                               | Max. 0.5 Nm                                                 |                |
| <b>Electrical characteristics</b> |                                                                               |                                                             |                |
| Conductor resistance              |                                                                               | Max. 237 Ω/km                                               |                |
| Insulation resistance             |                                                                               | Min. 100 MΩ/km                                              |                |
| <b>Mechanical characteristics</b> |                                                                               |                                                             |                |
| Dimensions                        |                                                                               |                                                             |                |
| Length                            | 1.8 m ±50 mm                                                                  | 5 m ±80 mm                                                  | 10 m ±100 mm   |
| Diameter                          |                                                                               | Max. 8.5 mm                                                 |                |
| Flex radius                       | ≥5x cable diameter (connector - ferrite bead and ferrite bead - ferrite bead) |                                                             |                |
| Weight                            | Approx. 260 g                                                                 | Approx. 460 g                                               | Approx. 790 g  |

Table 233: 5CADVI.0018-00, 5CADVI.0050-00, 5CADVI.0100-00 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

### 5.1.1.4 Flex radius specifications




Figure 171: Flex radius specifications

### 5.1.1.5 Dimensions




Figure 172: 5CADVI.0xxx-00 - Dimensions

### 5.1.1.6 Cable pinout

#### Warning!

If you choose to build a suitable cable yourself, it should be wired according to these specifications. If a self-built cable is used, B&R cannot guarantee that it will function properly. All cables provided by B&R are guaranteed to function properly.




Figure 173: 5CADVI.0xxx-00 - Pinout

## 5.2 SDL cables

### 5.2.1 5CASDL.0xxx-00

#### 5.2.1.1 General information

5CASDL.0xxx-00 SDL cables are designed for use in inflexible applications. SDL flex cables 5CASDL.0xxx-03 are required for flexible applications (e.g. swing arm systems).

#### Caution!

**Power must be turned off before plugging in and unplugging cables.**

#### 5.2.1.2 Order data

| Model number   | Short description | Figure |
|----------------|-------------------|--------|
| 5CASDL.0018-00 | SDL cable, 1.8 m  |        |
| 5CASDL.0050-00 | SDL cable, 5 m    |        |
| 5CASDL.0100-00 | SDL cable, 10 m   |        |
| 5CASDL.0150-00 | SDL cable, 15 m   |        |
| 5CASDL.0200-00 | SDL cable, 20 m   |        |
| 5CASDL.0250-00 | SDL cable, 25 m   |        |
| 5CASDL.0300-00 | SDL cable, 30 m   |        |

Table 234: 5CASDL.0018-00, 5CASDL.0050-00, 5CASDL.0100-00, 5CASDL.0150-00,  
5CASDL.0200-00, 5CASDL.0250-00, 5CASDL.0300-00 - Order data

#### 5.2.1.3 Technical data

| Product ID                        | 5CASDL.0018-00                                                                                                            | 5CASDL.0050-00 | 5CASDL.0100-00 | 5CASDL.0150-00                                               | 5CASDL.0200-00  | 5CASDL.0250-00 | 5CASDL.0300-00                                                    |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------|----------------|----------------|--------------------------------------------------------------|-----------------|----------------|-------------------------------------------------------------------|
| <b>General information</b>        |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| Certification                     |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| CE                                |                                                                                                                           |                |                | Yes                                                          |                 |                |                                                                   |
| cULus                             |                                                                                                                           |                |                | Yes                                                          |                 |                |                                                                   |
| GOST-R                            |                                                                                                                           |                |                | Yes                                                          |                 |                |                                                                   |
| GL                                |                                                                                                                           |                |                | Yes <sup>1)</sup>                                            |                 |                |                                                                   |
| <b>Cable structure</b>            |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| Wire cross section                | AWG 28                                                                                                                    |                |                | AWG 24                                                       |                 |                |                                                                   |
| Shielding                         |                                                                                                                           |                |                | Individual cable pairs and entire cable                      |                 |                |                                                                   |
| Cable shielding                   |                                                                                                                           |                |                | Tinned copper mesh, optical coverage >85%                    |                 |                |                                                                   |
| Outer sheathing                   |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| Material                          |                                                                                                                           |                |                | PVC                                                          |                 |                |                                                                   |
| Color                             |                                                                                                                           |                |                | Black                                                        |                 |                |                                                                   |
| Labeling                          |                                                                                                                           |                |                | E74020-C (UL) AWM STYLE 20176 80°C 30V VW-1 DVI DIGITAL LINK |                 |                |                                                                   |
| <b>Connector</b>                  |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| Type                              |                                                                                                                           |                |                | 2x DVI-D (24+1), male                                        |                 |                |                                                                   |
| Connection cycles                 |                                                                                                                           |                |                | 100                                                          |                 |                |                                                                   |
| Contacts                          |                                                                                                                           |                |                | Gold-plated                                                  |                 |                |                                                                   |
| Mechanical protection             |                                                                                                                           |                |                | Metal cover with crimped stress relief                       |                 |                |                                                                   |
| Locating screw tightening torque  |                                                                                                                           |                |                | Max. 0.5 Nm                                                  |                 |                |                                                                   |
| <b>Electrical characteristics</b> |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| Conductor resistance              |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| AWG 24                            | -                                                                                                                         |                |                | ≤93 Ω/km                                                     |                 |                |                                                                   |
| AWG 28                            | ≤237 Ω/km                                                                                                                 |                |                | -                                                            |                 |                |                                                                   |
| Insulation resistance             |                                                                                                                           |                |                | Min. 10 MΩ/km                                                |                 |                |                                                                   |
| <b>Mechanical characteristics</b> |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| Dimensions                        |                                                                                                                           |                |                |                                                              |                 |                |                                                                   |
| Length                            | 1.8 m ±30 mm                                                                                                              |                | 5 m ±30 mm     |                                                              | 10 m ±50 mm     |                | 15 m ±100 mm   20 m ±100 mm   25 m ±100 mm   30 m ±100 mm         |
| Diameter                          | Typ. 8.6 ±0.2 mm                                                                                                          |                |                |                                                              | Typ. 11 ±0.2 mm |                |                                                                   |
|                                   | Max. 9 mm                                                                                                                 |                |                |                                                              | Max. 11.5 mm    |                |                                                                   |
| Flex radius                       | ≥5x cable diameter (connector - ferrite bead and ferrite bead - ferrite bead)                                             |                |                |                                                              |                 |                |                                                                   |
| Flexibility                       | Limited flexibility; valid for ferrite bead - ferrite bead (tested 100 cycles with 5x cable diameter, 20 cycles / minute) |                |                |                                                              |                 |                |                                                                   |
| Weight                            | Approx. 300 g                                                                                                             |                | Approx. 580 g  |                                                              | Approx. 1500 g  |                | Approx. 2250 g   Approx. 2880 g   Approx. 4800 g   Approx. 5520 g |

Table 235: 5CASDL.0018-00, 5CASDL.0050-00, 5CASDL.0100-00, 5CASDL.0150-00,  
5CASDL.0200-00, 5CASDL.0250-00, 5CASDL.0300-00 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

### 5.2.1.4 Flex radius specifications




Figure 174: Flex radius specifications

### 5.2.1.5 Dimensions




Figure 175: 5CSDL.0xx-00- Dimensions

### 5.2.1.6 Cable pinout

#### Warning!

If you choose to build a suitable cable yourself, it should be wired according to these specifications. If a self-built cable is used, B&R cannot guarantee that it will function properly. All cables provided by B&R are guaranteed to function properly.




Figure 176: 5CASDL.0xxx-00 - Pinout

## 5.3 SDL cables with 45° male connector

### 5.3.1 5CASDL.0xxx-01

#### 5.3.1.1 General information

5CASDL.0xxx-01 SDL cables with a 45° connector are designed for use in inflexible applications.

#### Caution!

**Power must be turned off before plugging in and unplugging cables.**

#### 5.3.1.2 Order data

| Model number   | Short description                        | Figure                                                                              |
|----------------|------------------------------------------|-------------------------------------------------------------------------------------|
|                | <b>SDL cable - 45° connector</b>         |                                                                                     |
| 5CASDL.0018-01 | SDL cable with 45° male connector, 1.8 m |                                                                                     |
| 5CASDL.0050-01 | SDL cable with 45° male connector, 5 m   |                                                                                     |
| 5CASDL.0100-01 | SDL cable with 45° male connector, 10 m  |                                                                                     |
| 5CASDL.0150-01 | SDL cable with 45° male connector, 15 m  |  |

Table 236: 5CASDL.0018-01, 5CASDL.0050-01, 5CASDL.0100-01, 5CASDL.0150-01 - Order data

#### 5.3.1.3 Technical data

| Product ID                        | 5CASDL.0018-01                                                                                                            | 5CASDL.0050-01                                                                | 5CASDL.0100-01 | 5CASDL.0150-01 |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|----------------|----------------|
| <b>General information</b>        |                                                                                                                           |                                                                               |                |                |
| Certification                     |                                                                                                                           |                                                                               |                |                |
| CE                                |                                                                                                                           | Yes                                                                           |                |                |
| cULus                             |                                                                                                                           | Yes                                                                           |                |                |
| GOST-R                            |                                                                                                                           | Yes                                                                           |                |                |
| GL                                |                                                                                                                           | Yes <sup>1)</sup>                                                             |                |                |
| <b>Cable structure</b>            |                                                                                                                           |                                                                               |                |                |
| Wire cross section                | AWG 28                                                                                                                    |                                                                               | AWG 24         |                |
| Shielding                         |                                                                                                                           | Individual cable pairs and entire cable                                       |                |                |
| Cable shielding                   |                                                                                                                           | Tinned copper mesh, optical coverage >85%                                     |                |                |
| Outer sheathing                   |                                                                                                                           |                                                                               |                |                |
| Material                          |                                                                                                                           | PVC                                                                           |                |                |
| Color                             |                                                                                                                           | Black                                                                         |                |                |
| <b>Connector</b>                  |                                                                                                                           |                                                                               |                |                |
| Type                              |                                                                                                                           | 2x DVI-D (24+1), male                                                         |                |                |
| Connection cycles                 |                                                                                                                           | 100                                                                           |                |                |
| Contacts                          |                                                                                                                           | Gold-plated                                                                   |                |                |
| Mechanical protection             |                                                                                                                           | Metal cover with crimped stress relief                                        |                |                |
| Locating screw tightening torque  |                                                                                                                           | Max. 0.5 Nm                                                                   |                |                |
| <b>Electrical characteristics</b> |                                                                                                                           |                                                                               |                |                |
| Conductor resistance              |                                                                                                                           |                                                                               |                |                |
| AWG 24                            | -                                                                                                                         |                                                                               | ≤93 Ω/km       |                |
| AWG 28                            | ≤237 Ω/km                                                                                                                 |                                                                               | -              |                |
| Insulation resistance             |                                                                                                                           | Min. 10 MΩ/km                                                                 |                |                |
| <b>Mechanical characteristics</b> |                                                                                                                           |                                                                               |                |                |
| Dimensions                        |                                                                                                                           |                                                                               |                |                |
| Length                            | 1.8 m ±30 mm                                                                                                              | 5 m ±50 mm                                                                    | 10 m ±100 mm   | 15 m ±100 mm   |
| Diameter                          | Max. 9 mm                                                                                                                 |                                                                               | Max. 11.5 mm   |                |
| Flex radius                       |                                                                                                                           | ≥5x cable diameter (connector - ferrite bead and ferrite bead - ferrite bead) |                |                |
| Fixed installation                |                                                                                                                           |                                                                               |                |                |
| Flexibility                       | Limited flexibility; valid for ferrite bead - ferrite bead (tested 100 cycles with 5x cable diameter, 20 cycles / minute) |                                                                               |                |                |
| Weight                            | Approx. 300 g                                                                                                             | Approx. 590 g                                                                 | Approx. 2800 g | Approx. 2860 g |

Table 237: 5CASDL.0018-01, 5CASDL.0050-01, 5CASDL.0100-01, 5CASDL.0150-01 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

### 5.3.1.4 Flex radius specifications




Figure 177: Flex radius specifications

### 5.3.1.5 Dimensions




Figure 178: 5CSDL.0xx-01 - Dimensions

## 5.3.1.6 Cable pinout

**Warning!**

If you choose to build a suitable cable yourself, it should be wired according to these specifications.  
**If a self-built cable is used, B&R cannot guarantee that it will function properly. All cables provided by B&R are guaranteed to function properly.**




Figure 179: 5CASDL.0xxx-01 - Pinout

## 5.4 SDL flex cables

### 5.4.1 5CASDL.0xxx-03

#### 5.4.1.1 General information

5CASDL.0xxx-03 SDL flex cables are designed for use in both inflexible and flexible applications (e.g. support arm systems).

#### Caution!

**Power must be turned off before plugging in and unplugging cables.**

#### 5.4.1.2 Order data

| Model number   | Short description     | Figure |
|----------------|-----------------------|--------|
|                | <b>SDL flex cable</b> |        |
| 5CASDL.0018-03 | SDL flex cable, 1.8 m |        |
| 5CASDL.0050-03 | SDL flex cable, 5 m   |        |
| 5CASDL.0100-03 | SDL flex cable, 10 m  |        |
| 5CASDL.0150-03 | SDL flex cable, 15 m  |        |
| 5CASDL.0200-03 | SDL flex cable, 20 m  |        |
| 5CASDL.0250-03 | SDL flex cable, 25 m  |        |
| 5CASDL.0300-03 | SDL flex cable, 30 m  |        |

Table 238: 5CASDL.0018-03, 5CASDL.0050-03, 5CASDL.0100-03, 5CASDL.0150-03, 5CASDL.0200-03, 5CASDL.0250-03, 5CASDL.0300-03 - Order data

#### 5.4.1.3 Technical data

| Product ID                        | 5CASDL.<br>0018-03 | 5CASDL.<br>0050-03 | 5CASDL.<br>0100-03 | 5CASDL.<br>0150-03                                   | 5CASDL.<br>0200-03 | 5CASDL.<br>0250-03 | 5CASDL.<br>0300-03 |
|-----------------------------------|--------------------|--------------------|--------------------|------------------------------------------------------|--------------------|--------------------|--------------------|
| <b>General information</b>        |                    |                    |                    |                                                      |                    |                    |                    |
| Certification                     |                    |                    |                    |                                                      |                    |                    |                    |
| CE                                |                    |                    |                    | Yes                                                  |                    |                    |                    |
| cULus                             |                    |                    |                    | Yes                                                  |                    |                    |                    |
| GOST-R                            |                    |                    |                    | Yes                                                  |                    |                    |                    |
| GL                                |                    |                    |                    | Yes <sup>1)</sup>                                    |                    |                    |                    |
| <b>Cable structure</b>            |                    |                    |                    |                                                      |                    |                    |                    |
| Wire cross section                |                    |                    |                    | AWG 24 (control wires)<br>AWG 26 (DVI, USB, data)    |                    |                    |                    |
| Properties                        |                    |                    |                    | Silicone- and halogen-free                           |                    |                    |                    |
| Shielding                         |                    |                    |                    | Individual cable pairs and entire cable              |                    |                    |                    |
| Cable shielding                   |                    |                    |                    | Aluminum-clad foil + tinned copper mesh              |                    |                    |                    |
| Outer sheathing                   |                    |                    |                    |                                                      |                    |                    |                    |
| Material                          |                    |                    |                    | Special TMPU - semi gloss                            |                    |                    |                    |
| Color                             |                    |                    |                    | Black                                                |                    |                    |                    |
| Labeling                          |                    |                    |                    | (B&R) SDL Cable (UL) AWM 20236 80°C 30V E 63216      |                    |                    |                    |
| <b>Connector</b>                  |                    |                    |                    |                                                      |                    |                    |                    |
| Type                              |                    |                    |                    | 2x DVI-D (24+1), male                                |                    |                    |                    |
| Connection cycles                 |                    |                    |                    | Min. 200                                             |                    |                    |                    |
| Contacts                          |                    |                    |                    | Gold-plated                                          |                    |                    |                    |
| Mechanical protection             |                    |                    |                    | Metal cover with crimped stress relief               |                    |                    |                    |
| Locating screw tightening torque  |                    |                    |                    | Max. 0.5 Nm                                          |                    |                    |                    |
| <b>Electrical characteristics</b> |                    |                    |                    |                                                      |                    |                    |                    |
| Operating voltage                 |                    |                    |                    | ≤30 V                                                |                    |                    |                    |
| Test voltage                      |                    |                    |                    |                                                      |                    |                    |                    |
| Wire/Wire                         |                    |                    |                    | 1 kV                                                 |                    |                    |                    |
| Wire/Shield                       |                    |                    |                    | 0.5 kV                                               |                    |                    |                    |
| Wave impedance                    |                    |                    |                    | 100 ±10 Ω                                            |                    |                    |                    |
| Conductor resistance              |                    |                    |                    |                                                      |                    |                    |                    |
| AWG 24                            |                    |                    |                    | ≤95 Ω/km                                             |                    |                    |                    |
| AWG 26                            |                    |                    |                    | ≤145 Ω/km                                            |                    |                    |                    |
| Insulation resistance             |                    |                    |                    | >200 MΩ/km                                           |                    |                    |                    |
| <b>Operating conditions</b>       |                    |                    |                    |                                                      |                    |                    |                    |
| Approbation                       |                    |                    |                    | UL AWM 20236 80°C 30 V                               |                    |                    |                    |
| Flame resistant                   |                    |                    |                    | In accordance with UL758 (cable vertical flame test) |                    |                    |                    |
| Oil and hydrolysis resistance     |                    |                    |                    | In accordance with VDE 0282-10                       |                    |                    |                    |

Table 239: 5CASDL.0018-03, 5CASDL.0050-03, 5CASDL.0100-03, 5CASDL.0150-03, 5CASDL.0200-03, 5CASDL.0250-03, 5CASDL.0300-03 - Technical data

| Product ID                        | 5CASDL.<br>0018-03                                                                                                | 5CASDL.<br>0050-03 | 5CASDL.<br>0100-03 | 5CASDL.<br>0150-03                                     | 5CASDL.<br>0200-03 | 5CASDL.<br>0250-03 | 5CASDL.<br>0300-03 |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------|--------------------|--------------------|--------------------------------------------------------|--------------------|--------------------|--------------------|
| <b>Environmental conditions</b>   |                                                                                                                   |                    |                    |                                                        |                    |                    |                    |
| Temperature                       |                                                                                                                   |                    |                    | -20 to 80°C                                            |                    |                    |                    |
| Storage                           |                                                                                                                   |                    |                    | -20 to 80°C                                            |                    |                    |                    |
| Fixed installation                |                                                                                                                   |                    |                    | -5 to 60°C                                             |                    |                    |                    |
| Flexible installation             |                                                                                                                   |                    |                    |                                                        |                    |                    |                    |
| <b>Mechanical characteristics</b> |                                                                                                                   |                    |                    |                                                        |                    |                    |                    |
| Dimensions                        |                                                                                                                   |                    |                    |                                                        |                    |                    |                    |
| Length                            | 1.8 m ±20 mm                                                                                                      | 5 m ±45 mm         | 10 m ±90 mm        | 15 m ±135 mm                                           | 20 m ±180 mm       | 25 m ±225 mm       | 30 m ±270 mm       |
| Diameter                          |                                                                                                                   |                    |                    | Max. 12 mm                                             |                    |                    |                    |
| Flex radius                       |                                                                                                                   |                    |                    |                                                        |                    |                    |                    |
| Fixed installation                |                                                                                                                   |                    |                    | ≥6x cable diameter (connector - ferrite bead)          |                    |                    |                    |
| Flexible installation             |                                                                                                                   |                    |                    | ≥10x cable diameter (from ferrite bead - ferrite bead) |                    |                    |                    |
|                                   |                                                                                                                   |                    |                    | ≥15x cable diameter (from ferrite bead - ferrite bead) |                    |                    |                    |
| Flexibility                       | Flexible; valid for ferrite bead - ferrite bead (tested 300,000 cycles with 15x cable diameter, 4800 cycles/hour) |                    |                    |                                                        |                    |                    |                    |
| Drag chain data                   |                                                                                                                   |                    |                    |                                                        |                    |                    |                    |
| Flex cycles                       |                                                                                                                   |                    |                    | 300,000                                                |                    |                    |                    |
| Velocity                          |                                                                                                                   |                    |                    | 4800 cycles/hour                                       |                    |                    |                    |
| Flex radius                       |                                                                                                                   |                    |                    | 180 mm; 15x cable diameter                             |                    |                    |                    |
| Hub                               |                                                                                                                   |                    |                    | 460 mm                                                 |                    |                    |                    |
| Weight                            | Approx. 460 g                                                                                                     | Approx. 1020 g     | Approx. 1940 g     | Approx. 2840 g                                         | Approx. 3740 g     | Approx. 4560 g     | Approx. 5590 g     |
| Tension                           |                                                                                                                   |                    |                    |                                                        |                    |                    |                    |
| During operation                  |                                                                                                                   |                    |                    | ≤50 N                                                  |                    |                    |                    |
| During installation               |                                                                                                                   |                    |                    | ≤400 N                                                 |                    |                    |                    |

Table 239: 5CASDL.0018-03, 5CASDL.0050-03, 5CASDL.0100-03, 5CASDL.0150-03, 5CASDL.0200-03, 5CASDL.0250-03, 5CASDL.0300-03 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

#### 5.4.1.4 Flex radius specifications




Figure 180: Flex radius specifications

#### 5.4.1.5 Dimensions




Figure 181: 5CASDL.0xx-03 - Dimensions

### 5.4.1.6 Structure

| Element       | Assignment      | Cross section |                                                                                       |
|---------------|-----------------|---------------|---------------------------------------------------------------------------------------|
| DVI           | TMDS data 0     | 26 AWG        | TMDS data 1                                                                           |
|               | TMDS data 1     | 26 AWG        | TMDS data 0                                                                           |
|               | TMDS data 2     | 26 AWG        | Control wires<br>- DDC clock<br>- DDC data<br>- +5 V<br>- Ground<br>- Hot Plug detect |
|               | TMDS cycle      | 26 AWG        |                                                                                       |
| USB           | XUSB0           | 26 AWG        |                                                                                       |
|               | XUSB1           | 26 AWG        |                                                                                       |
| Data          | SDL             | 26 AWG        |                                                                                       |
| Control wires | DDC cycle       | 24 AWG        |                                                                                       |
|               | DDC data        | 24 AWG        |                                                                                       |
|               | +5 V            | 24 AWG        |                                                                                       |
|               | Mass            | 24 AWG        |                                                                                       |
|               | Hot plug detect | 24 AWG        |                                                                                       |




Table 240: 5CASDL.0xxx-03 SDL flex cables - Structure

### 5.4.1.7 Cable pinout

#### Warning!

If you choose to build a suitable cable yourself, it should be wired according to these specifications.  
If a self-built cable is used, B&R cannot guarantee that it will function properly. All cables provided by B&R are guaranteed to function properly.




Figure 182: 5CASDL.0xxx-03 - Pinout

## 5.5 SDL flex cables with extender

### 5.5.1 5CASDL.0xx0-13

#### 5.5.1.1 General information

5CASDL.0xx0-13 SDL flex cables with an extender are designed for use in both inflexible and flexible applications (e.g. support arm systems).

#### Caution!

**Power must be turned off before plugging in and unplugging cables.**

#### 5.5.1.2 Order data

| Model number   | Short description                  | Figure                                                                             |
|----------------|------------------------------------|------------------------------------------------------------------------------------|
| 5CASDL.0300-13 | SDL flex cable with extender, 30 m |                                                                                    |
| 5CASDL.0400-13 | SDL flex cable with extender, 40 m |                                                                                    |
| 5CASDL.0430-13 | SDL flex cable with extender, 43 m |  |

Table 241: 5CASDL.0300-13, 5CASDL.0400-13, 5CASDL.0430-13 - Order data

#### 5.5.1.3 Technical data

| Product ID                        | 5CASDL.0300-13 | 5CASDL.0400-13                                       | 5CASDL.0430-13 |
|-----------------------------------|----------------|------------------------------------------------------|----------------|
| <b>General information</b>        |                |                                                      |                |
| Certification                     |                |                                                      |                |
| CE                                |                | Yes                                                  |                |
| cULus                             |                | Yes                                                  |                |
| GOST-R                            |                | Yes                                                  |                |
| GL                                |                | Yes <sup>1)</sup>                                    |                |
| <b>Cable structure</b>            |                |                                                      |                |
| Wire cross section                |                | AWG 24 (control wires)<br>AWG 26 (DVI, USB, data)    |                |
| Properties                        |                | Silicone- and halogen-free                           |                |
| Shielding                         |                | Individual cable pairs and entire cable              |                |
| Cable shielding                   |                | Aluminum-clad foil + tinned copper mesh              |                |
| Outer sheathing                   |                |                                                      |                |
| Material                          |                | Special TMPU - semi gloss                            |                |
| Color                             |                | Black                                                |                |
| Labeling                          |                | (B&R) SDL cable (UL) AWM 20236 80°C 30V E63216       |                |
| <b>Connector</b>                  |                |                                                      |                |
| Type                              |                | 2x DVI-D (24+1), male                                |                |
| Connection cycles                 |                | Min. 200                                             |                |
| Contacts                          |                | Gold-plated                                          |                |
| Mechanical protection             |                | Metal cover with crimped stress relief               |                |
| Locating screw tightening torque  |                | Max. 0.5 Nm                                          |                |
| <b>Electrical characteristics</b> |                |                                                      |                |
| Operating voltage                 |                | ≤30 V                                                |                |
| Test voltage                      |                |                                                      |                |
| Wire/Wire                         |                | 1 kV                                                 |                |
| Wire/Shield                       |                | 0.5 kV                                               |                |
| Wave impedance                    |                | 100 ±10 Ω                                            |                |
| Conductor resistance              |                |                                                      |                |
| AWG 24                            |                | ≤95 Ω/km                                             |                |
| AWG 26                            |                | ≤145 Ω/km                                            |                |
| Insulation resistance             |                | >200 MΩ/km                                           |                |
| <b>Operating conditions</b>       |                |                                                      |                |
| Approbation                       |                | UL AWM 20236 80°C 30 V                               |                |
| Flame resistant                   |                | In accordance with UL758 (cable vertical flame test) |                |
| Oil and hydrolysis resistance     |                | In accordance with VDE 0282-10                       |                |
| <b>Environmental conditions</b>   |                |                                                      |                |
| Temperature                       |                |                                                      |                |
| Storage                           |                | -20 to 60°C                                          |                |
| Fixed installation                |                | -20 to 60°C                                          |                |
| Flexible installation             |                | -5 to 60°C                                           |                |

Table 242: 5CASDL.0300-13, 5CASDL.0400-13, 5CASDL.0430-13 - Technical data

| Product ID                        | 5CSDL.0300-13  | 5CSDL.0400-13                                                                                                                                                     | 5CSDL.0430-13  |
|-----------------------------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>Mechanical characteristics</b> |                |                                                                                                                                                                   |                |
| Dimensions                        |                |                                                                                                                                                                   |                |
| Length                            | 30 m ±280 mm   | 40 m ±380 mm                                                                                                                                                      | 43 m ±410 mm   |
| Diameter                          |                | Max. 12 mm                                                                                                                                                        |                |
| Extender box                      |                |                                                                                                                                                                   |                |
| Width                             |                | 35 mm                                                                                                                                                             |                |
| Length                            |                | 125 mm                                                                                                                                                            |                |
| Height                            |                | 18.5 mm                                                                                                                                                           |                |
| Flex radius                       |                |                                                                                                                                                                   |                |
| Fixed installation                |                | ≥6x cable diameter (connector - ferrite bead)<br>≥10x cable diameter (from ferrite bead - ferrite bead)<br>≥15x cable diameter (from ferrite bead - ferrite bead) |                |
| Flexible installation             |                |                                                                                                                                                                   |                |
| Flexibility                       |                | Flexible; valid for ferrite bead - ferrite bead (tested<br>300,000 cycles with 15x cable diameter, 4800 cycles/hour)                                              |                |
| Drag chain data                   |                |                                                                                                                                                                   |                |
| Flex cycles                       |                | 300,000                                                                                                                                                           |                |
| Velocity                          |                | 4800 cycles/hour                                                                                                                                                  |                |
| Flex radius                       |                | 180 mm; 15x cable diameter                                                                                                                                        |                |
| Hub                               |                | 460 mm                                                                                                                                                            |                |
| Weight                            | Approx. 5430 g | Approx. 7200 g                                                                                                                                                    | Approx. 7790 g |
| Tension                           |                |                                                                                                                                                                   |                |
| During operation                  |                | ≤50 N                                                                                                                                                             |                |
| During installation               |                | ≤400 N                                                                                                                                                            |                |

Table 242: 5CSDL.0300-13, 5CSDL.0400-13, 5CSDL.0430-13 - Technical data

1) Yes, although applies only if all components installed within the complete system have this certification

### 5.5.1.4 Flex radius specifications




Figure 183: Flex radius specification with extender

### 5.5.1.5 Dimensions




Figure 184: 5CSDL.0xx0-13 - Dimensions

## 5.5.1.6 Cable pinout

**Warning!**

If you choose to build a suitable cable yourself, it should be wired according to these specifications.  
**If a self-built cable is used, B&R cannot guarantee that it will function properly. All cables provided by B&R are guaranteed to function properly.**




Figure 185: 5CASDL.0xx0-13 - Pinout

### 5.5.1.7 Cable connection

SDL flex cables with an extender must be connected between the B&R Industrial PC and the Automation Panel display unit in the correct direction. The proper signal direction is indicated on the extender.




Figure 186: Example of the signal direction for an SDL flex cable with extender

## 5.6 USB cables

### 5.6.1 5CAUSB.00xx-00

#### 5.6.1.1 General information

USB cables are designed to achieve USB 2.0 transfer speeds.

#### 5.6.1.2 Order data

| Model number   | Short description                               | Figure |
|----------------|-------------------------------------------------|--------|
|                | <b>USB cable</b>                                |        |
| 5CAUSB.0018-00 | USB 2.0 connection cable type A - type B, 1.8 m |        |
| 5CAUSB.0050-00 | USB 2.0 connection cable type A - type B, 5 m   |        |

Table 243: 5CAUSB.0018-00, 5CAUSB.0050-00 - Order data

#### 5.6.1.3 Technical data

| Product ID                        | 5CAUSB.0018-00                      | 5CAUSB.0050-00 |
|-----------------------------------|-------------------------------------|----------------|
| <b>General information</b>        |                                     |                |
| Certification                     |                                     |                |
| CE                                | Yes                                 |                |
| cULus                             | Yes                                 |                |
| GOST-R                            | Yes                                 |                |
| <b>Cable structure</b>            |                                     |                |
| Wire cross section                | AWG 24, 28                          |                |
| Shielding                         | Entire cable                        |                |
| Outer sheathing<br>Color          | Beige                               |                |
| <b>Connector</b>                  |                                     |                |
| Type                              | USB type A male and USB type B male |                |
| <b>Mechanical characteristics</b> |                                     |                |
| Dimensions                        |                                     |                |
| Length                            | 1.8 m ±30 mm                        | 5 m ±50 mm     |
| Diameter                          | Max. 5 mm                           |                |
| Flex radius                       | Min. 100 mm                         |                |

Table 244: 5CAUSB.0018-00, 5CAUSB.0050-00 - Technical data

#### 5.6.1.4 Cable pinout

### Warning!

If you choose to build a suitable cable yourself, it should be wired according to these specifications.

If a self-built cable is used, B&R cannot guarantee that it will function properly. All cables provided by B&R are guaranteed to function properly.




Figure 187: 5CAUSB.00xx-00 USB cables - Pinout

## 5.7 RS232 cables

### 5.7.1 9A0014.xx

#### 5.7.1.1 General information

RS232 cables are used as extension cables between two RS232 interfaces.

#### 5.7.1.2 Order data

| Model number | Short description                                                                     | Figure                                                                              |
|--------------|---------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|              | <b>RS232 cable</b>                                                                    |                                                                                     |
| 9A0014.02    | RS232 extension cable for remote operation of a display unit with touch screen, 1.8 m |                                                                                     |
| 9A0014.05    | RS232 extension cable for remote operation of a display unit with touch screen, 5 m   |                                                                                     |
| 9A0014.10    | RS232 extension cable for remote operation of a display unit with touch screen, 10 m  |  |

Table 245: 9A0014.02, 9A0014.05, 9A0014.10 - Order data

#### 5.7.1.3 Technical data

| Product ID                        | 9A0014.02                        | 9A0014.05    | 9A0014.10    |
|-----------------------------------|----------------------------------|--------------|--------------|
| <b>General information</b>        |                                  |              |              |
| Certification                     |                                  |              |              |
| CE                                |                                  | Yes          |              |
| GOST-R                            | -                                |              | Yes          |
| <b>Cable structure</b>            |                                  |              |              |
| Wire cross section                |                                  | AWG 26       |              |
| Shielding                         |                                  | Entire cable |              |
| Outer sheathing                   |                                  |              |              |
| Color                             |                                  | Beige        |              |
| <b>Connector</b>                  |                                  |              |              |
| Type                              | 9-pin male/female DSUB connector |              |              |
| Locating screw tightening torque  | Max. 0.5 Nm                      |              |              |
| <b>Mechanical characteristics</b> |                                  |              |              |
| Dimensions                        |                                  |              |              |
| Length                            | 1.8 m ±50 mm                     | 5 m ±80 mm   | 10 m ±100 mm |
| Diameter                          |                                  | Max. 5 mm    |              |
| Flex radius                       | Min. 70 mm                       |              |              |

Table 246: 9A0014.02, 9A0014.05, 9A0014.10 - Technical data

### 5.7.1.4 Cable pinout

#### Warning!

If you choose to build a suitable cable yourself, it should be wired according to these specifications. If a self-built cable is used, B&R cannot guarantee that it will function properly. All cables provided by B&R are guaranteed to function properly.




Figure 188: 9A0014.xx RS232 cables - Pinout

# Chapter 7 • Maintenance and service

This chapter describes service/maintenance work that can be carried out by a qualified end user.

## 1 Changing the battery

The lithium battery buffers the internal real-time clock (RTC) and CMOS data.

### Information:

- The product design allows the battery to be changed with the B&R device switched either on or off. In some countries, safety regulations do not allow batteries to be changed while the module is switched on.
- Any BIOS settings that have been made will remain when the battery is changed with the power turned off (stored in non-volatile EEPROM). The date and time must be reset later since this data is lost when the battery is changed.
- The battery should only be changed by qualified personnel.

### Warning!


**The battery must be replaced by a Type CR2477N Renata battery only. The use of another battery may present a risk of fire or explosion.**

**The battery may explode if handled improperly. Do not recharge, disassemble or dispose of in fire.**

The following replacement lithium batteries are available: 4A0006.00-000 (1 pc.) and 0AC201.91 (4 pcs.).

### 1.1 Procedure

- Disconnect the power supply to the B&R industrial PC (unplug the power cable!). Isolate from all potential sources of electrical power!
- Touch the housing or ground connection in order to discharge any electrostatic charge from your body.
- Pull the battery holder out of the Panel PC ① and remove the battery ②.



Chapter 7  
Maintenance  
and service

Figure 189: Pull out battery holder and remove battery

- The battery should not be held by its edges. Insulated tweezers may also be used to insert the battery.




Figure 190: Battery handling

- Insert the new battery with the correct polarity.
- Insert battery holder into the Panel PC.
- Reconnect the power supply to the B&R Industrial PC (plug in the power cable).
- Check the date and time in BIOS and correct them if necessary.

## Warning!

Lithium batteries are considered hazardous waste. Used batteries should be disposed of in accordance with applicable local regulations.

## 2 Replacing a CFast card

### Caution!

**Power must be turned off before replacing CFast cards.**

The CFast card can be replaced quickly and easily using the ejector (see image).




Figure 191: Replacing a CFast card

## 3 Cleaning

### Danger!

**This device can only be cleaned when switched off in order to prevent unintended functions from being triggered when handling the touch screen or pressing keys.**

This device should be cleaned with a moist cloth. The cloth should be moistened with water and detergent, a screen cleaning agent or alcohol (ethanol). The cleaning agent should be applied to the cloth beforehand, not sprayed directly on the device! Aggressive solvents, chemicals, scouring agents, pressurized air or steam jets should never be used.

### Information:

**Displays with a touch screen should be cleaned regularly.**

## 4 Tips for extending the service life of the display

### 4.1 Backlight

The service life of the backlight is specified by its "half-brightness time". For example, a specified operating time of 50,000 hours means that the display would still retain 50% of its brightness after this time.

#### 4.1.1 How can the service life of the backlight be extended?

- By setting the display brightness to the lowest value that is still comfortable for the eyes
- By using dark images
- By reducing the brightness by 50%, which can result in an approximately 50% increase in the half-brightness time

### 4.2 Screen burn-in

Screen burn-in refers to the "burning in" of a static image on a display after being displayed for a prolonged period of time. Nevertheless, static images are not the only cause of screen burn-in. Screen burn-in is also referred to as burn-in effect, image retention, memory effect, memory sticking or ghost image.

There are basically two types:

- Area type: This type of screen burn-in is indicated by a dark gray image. The effect will disappear if the display is switched off for a long period of time.
- Line type: This type of screen burn-in can cause lasting damage.

#### 4.2.1 What causes screen burn-in?

- Static images
- No screensaver
- Sharp transitions in contrast (e.g. black/white)
- High ambient temperatures
- Operation outside of specifications

#### 4.2.2 How can screen burn-in be avoided?

- By constantly changing between static and dynamic images
- By avoiding excessive brightness differences between foreground and background elements
- By using colors with similar brightness
- By using complementary colors in follow-up images
- By using a screensaver

## 5 Pixel errors

### Information:

Displays may contain defective pixels (dead/stuck pixels) that result from the manufacturing process. These flaws are not grounds for claiming reclamation or warranty.

# Appendix A

---


## 1 Abbreviations

| Abbreviation | Stands for      | Description                                                                                                                                                       |
|--------------|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NC           | Normally closed | A normally closed relay contact                                                                                                                                   |
|              | Not connected   | Used in pinout descriptions if a terminal or pin is not connected to a module                                                                                     |
| ND           | Not defined     | In data tables, this stands for a value that has not been defined. This may be because a cable manufacturer does not provide certain technical data, for example. |
| NO           | Normally open   | A N.O. relay contact                                                                                                                                              |
| TBD          | To be defined   | Used in technical data tables when certain information is not yet available. The value will be provided later.                                                    |

Table 247: Abbreviations used in this user's manual

## 2 Viewing angles

Viewing angle specifications (R, L, U, D) for the display types are listed in the technical data for each device.



|            |                                                                     |     |
|------------|---------------------------------------------------------------------|-----|
| Figure 1:  | Panel PC 900 - Base system configuration.....                       | 18  |
| Figure 2:  | Panel PC 900 - Accessory configuration.....                         | 19  |
| Figure 3:  | Panel PC 900 without bus unit.....                                  | 20  |
| Figure 4:  | Panel PC 900 with 1-slot bus unit.....                              | 20  |
| Figure 5:  | Panel PC 900 with 2-slot bus unit.....                              | 20  |
| Figure 6:  | Panel PC 900 + power supply + bus units - Dimensions.....           | 21  |
| Figure 7:  | Panel PC 900 + power supply + bus units - Installation diagram..... | 22  |
| Figure 8:  | Panel PC 900 - Spacing for air circulation.....                     | 23  |
| Figure 9:  | Panel PC 900 - Mounting orientation.....                            | 24  |
| Figure 10: | Panel PC 900 - Temperature sensor positions.....                    | 30  |
| Figure 11: | Block diagram - Panel PC 900.....                                   | 36  |
| Figure 12: | Device interfaces - Overview (bottom).....                          | 37  |
| Figure 13: | Device interfaces - Overview (side).....                            | 38  |
| Figure 14: | Ground connection.....                                              | 39  |
| Figure 15: | Standard half-size 32-bit PCI card - Dimensions.....                | 53  |
| Figure 16: | Standard half-size PCIe card - Dimensions.....                      | 53  |
| Figure 17: | 5AP23.1215-00 - Dimensions.....                                     | 55  |
| Figure 18: | 5AP923.1215-00 - Temperature humidity diagram.....                  | 55  |
| Figure 19: | 5AP23.1505-00 - Dimensions.....                                     | 57  |
| Figure 20: | 5AP923.1505-00 - Temperature humidity diagram.....                  | 57  |
| Figure 21: | 5AP23.1906-00 - Dimensions.....                                     | 59  |
| Figure 22: | 5AP923.1906-00 - Temperature humidity diagram.....                  | 59  |
| Figure 23: | 5AP933.156B-00 - Dimensions.....                                    | 61  |
| Figure 24: | 5AP933.156B-00 - Temperature humidity diagram.....                  | 61  |
| Figure 25: | 5AP933.185B-00 - Dimensions.....                                    | 63  |
| Figure 26: | 5AP933.185B-00 - Temperature humidity diagram.....                  | 63  |
| Figure 27: | 5AP933.215C-00 - Dimensions.....                                    | 65  |
| Figure 28: | 5AP933.215C-00 - Temperature humidity diagram.....                  | 65  |
| Figure 29: | 5AP933.240C-00 - Dimensions.....                                    | 67  |
| Figure 30: | 5AP933.240C-00 - Temperature humidity diagram.....                  | 67  |
| Figure 31: | 1-slot bus units.....                                               | 77  |
| Figure 32: | 2-slot bus units.....                                               | 77  |
| Figure 33: | 5AC901.CHDD-01 - Temperature humidity diagram.....                  | 82  |
| Figure 34: | 5AC901.CSSD-03 - Temperature humidity diagram.....                  | 84  |
| Figure 35: | 5AC901.CSSD-04 Rev. ≤ C0 - Temperature humidity diagram.....        | 86  |
| Figure 36: | 5AC901.CSSD-04 Rev. ≥ D0 - Temperature humidity diagram.....        | 87  |
| Figure 37: | 5AC901.CSSD-05 - Temperature humidity diagram.....                  | 89  |
| Figure 38: | 5MMSSD.0060-01 - Temperature humidity diagram.....                  | 91  |
| Figure 39: | 5MMSSD.0128-01 - Temperature humidity diagram Rev. ≤ C0.....        | 93  |
| Figure 40: | 5MMSSD.0128-01 - Temperature humidity diagram Rev. ≥ D0.....        | 94  |
| Figure 41: | 5MMSSD.0256-00 - Temperature humidity diagram.....                  | 96  |
| Figure 42: | 5AC901.SDVW-00 - Temperature humidity diagram.....                  | 99  |
| Figure 43: | RS232/422/485 interface - Operation in RS485 mode.....              | 103 |
| Figure 44: | 5AC901.I485-00 - Terminating resistor.....                          | 104 |
| Figure 45: | 5AC901.ICAN-00 - Terminating resistor.....                          | 106 |
| Figure 46: | 5AC901.BUPS-00 - Dimensions.....                                    | 117 |
| Figure 47: | 5AC901.BUPS-00 - Drilling template.....                             | 118 |
| Figure 48: | 5AC901.BUPS-01 - Dimensions.....                                    | 120 |
| Figure 49: | 5AC901.BUPS-01 - Drilling template.....                             | 121 |
| Figure 50: | Prepare retaining clips.....                                        | 126 |
| Figure 51: | Inserting the retaining clips.....                                  | 127 |
| Figure 52: | Fasten retaining clips.....                                         | 127 |
| Figure 53: | Removing the Torx screws on the system unit.....                    | 128 |
| Figure 54: | Removing the system unit and CPU board.....                         | 128 |
| Figure 55: | Removing the Torx screws on the mounting plate.....                 | 129 |
| Figure 56: | Removing the mounting plate.....                                    | 129 |
| Figure 57: | Removing the screws.....                                            | 130 |

|             |                                                                           |     |
|-------------|---------------------------------------------------------------------------|-----|
| Figure 58:  | Replacing the AC power supply.....                                        | 130 |
| Figure 59:  | Installing the mounting plates.....                                       | 131 |
| Figure 60:  | Installing the AC power supply.....                                       | 131 |
| Figure 61:  | Removing the Torx screws.....                                             | 132 |
| Figure 62:  | Removing the cover plate.....                                             | 132 |
| Figure 63:  | Replacing the main memory modules.....                                    | 133 |
| Figure 64:  | Removing the Torx screws from cover plate.....                            | 134 |
| Figure 65:  | Removing the cover plate.....                                             | 134 |
| Figure 66:  | Removing the Torx screws and slot cover.....                              | 135 |
| Figure 67:  | Inserting and fastening the IF option.....                                | 135 |
| Figure 68:  | Replacing the cover plate.....                                            | 136 |
| Figure 69:  | Fastening the cover plate with the Torx screws.....                       | 136 |
| Figure 70:  | Removing the Torx screws.....                                             | 137 |
| Figure 71:  | Removing the cover plate.....                                             | 137 |
| Figure 72:  | Freeing the removal strip on the slide-in compact drive.....              | 137 |
| Figure 73:  | Removing the slide-in compact drive.....                                  | 138 |
| Figure 74:  | Pressing in the latching mechanism.....                                   | 139 |
| Figure 75:  | Removing the filter cover.....                                            | 140 |
| Figure 76:  | Removing the Torx screws and side cover.....                              | 141 |
| Figure 77:  | Installing the bus unit on the system unit.....                           | 141 |
| Figure 78:  | Replacing the side cover.....                                             | 142 |
| Figure 79:  | Removing the Torx screws and side cover.....                              | 143 |
| Figure 80:  | Removing the Torx screws and slot cover.....                              | 143 |
| Figure 81:  | Installing the PCI / PCIe card in the bus unit.....                       | 144 |
| Figure 82:  | Replacing the side cover.....                                             | 144 |
| Figure 83:  | Removing the Torx screws and side cover.....                              | 145 |
| Figure 84:  | Remove the slide-in slot cover from the side cover.....                   | 145 |
| Figure 85:  | Installing the slide-in drive in the bus unit.....                        | 146 |
| Figure 86:  | Replacing the side cover.....                                             | 146 |
| Figure 87:  | Connecting the UPS cable to the battery.....                              | 147 |
| Figure 88:  | Installing a screw clamp terminal block.....                              | 148 |
| Figure 89:  | Installing a screw clamp terminal block.....                              | 149 |
| Figure 90:  | Connecting the power supply connector to a B&R device.....                | 150 |
| Figure 91:  | Symbol for functional ground.....                                         | 151 |
| Figure 92:  | Panel PC 900 - Grounding concept.....                                     | 151 |
| Figure 93:  | Flex radius - Cable connection.....                                       | 152 |
| Figure 94:  | Adjusting the display brightness.....                                     | 155 |
| Figure 95:  | Configuration Utility - Boot.....                                         | 156 |
| Figure 96:  | Configuration Utility - Overview.....                                     | 156 |
| Figure 97:  | Configuration Utility - Create RAID volume.....                           | 157 |
| Figure 98:  | Configuration Utility - Delete RAID volume.....                           | 158 |
| Figure 99:  | Configuration Utility - Reset disks to non-RAID.....                      | 159 |
| Figure 100: | Configuration Utility - Recovery volume options.....                      | 160 |
| Figure 101: | Boot screen.....                                                          | 161 |
| Figure 102: | Main.....                                                                 | 163 |
| Figure 103: | Main - Platform information.....                                          | 164 |
| Figure 104: | Advanced overview.....                                                    | 165 |
| Figure 105: | Advanced - Graphics configuration.....                                    | 166 |
| Figure 106: | Advanced - OEM features.....                                              | 168 |
| Figure 107: | Advanced - OEM features - Super I/O configuration.....                    | 169 |
| Figure 108: | Advanced - OEM features - CPU board features.....                         | 170 |
| Figure 109: | Advanced - OEM features - CPU board features - Temperature values.....    | 171 |
| Figure 110: | Advanced - OEM features - System board features.....                      | 171 |
| Figure 111: | Advanced - OEM features - System board features - Statistical values..... | 172 |
| Figure 112: | Advanced - OEM features - System board features - Temperature values..... | 173 |
| Figure 113: | Advanced - OEM features - System board features - Voltage values.....     | 174 |
| Figure 114: | Advanced - OEM features - Memory module features.....                     | 174 |

|             |                                                                             |     |
|-------------|-----------------------------------------------------------------------------|-----|
| Figure 115: | Advanced - OEM features - Display board features.....                       | 175 |
| Figure 116: | Advanced - OEM features - Display board features - Statistical values.....  | 176 |
| Figure 117: | Advanced - OEM features - Display board features - Temperature values.....  | 176 |
| Figure 118: | Advanced - OEM features - Display board features - Panel #15.....           | 177 |
| Figure 119: | Advanced - OEM features - Bus unit features.....                            | 178 |
| Figure 120: | Advanced - OEM features - Bus unit features - Statistical values.....       | 179 |
| Figure 121: | Advanced - OEM features - I/O board 1 features.....                         | 179 |
| Figure 122: | Advanced - OEM features - I/O board 1 features - Statistical values.....    | 180 |
| Figure 123: | Advanced - OEM features - I/O board 2 features.....                         | 181 |
| Figure 124: | Advanced - OEM features - I/O board 2 features - Statistical values.....    | 182 |
| Figure 125: | Advanced - OEM features - Fan unit features.....                            | 182 |
| Figure 126: | Advanced - OEM features - Fan unit features - Statistical values.....       | 183 |
| Figure 127: | Advanced - OEM features - Fan unit features - RPM values.....               | 184 |
| Figure 128: | Advanced - OEM Features - Slide-in 1 features.....                          | 184 |
| Figure 129: | Advanced - OEM features - Slide-in 1 features - Temperature values.....     | 185 |
| Figure 130: | Advanced - OEM features - Panel control features.....                       | 186 |
| Figure 131: | Advanced - OEM features - Panel control features - Panel #X.....            | 186 |
| Figure 132: | Advanced - PCI configuration.....                                           | 187 |
| Figure 133: | Advanced - PCI configuration - PIRQ routing & IRQ reservation.....          | 188 |
| Figure 134: | Advanced - PCI Express configuration.....                                   | 189 |
| Figure 135: | Advanced - PCI Express configuration - PCI Express settings.....            | 190 |
| Figure 136: | Advanced - PCI Express configuration - PCI Express GEN 2 settings.....      | 191 |
| Figure 137: | Advanced - PCI Express configuration - PCI Express graphics (PEG) port..... | 192 |
| Figure 138: | Advanced - PCI Express configuration - PCI Express root port.....           | 194 |
| Figure 139: | Advanced - ACPI settings.....                                               | 195 |
| Figure 140: | Advanced - RTC wake settings.....                                           | 196 |
| Figure 141: | Advanced - CPU configuration.....                                           | 197 |
| Figure 142: | Advanced - CPU configuration - CPU information.....                         | 199 |
| Figure 143: | Advanced - Chipset configuration.....                                       | 200 |
| Figure 144: | Advanced - SATA configuration.....                                          | 201 |
| Figure 145: | Advanced - SATA configuration - Software feature mask configuration.....    | 203 |
| Figure 146: | Advanced - Memory configuration.....                                        | 204 |
| Figure 147: | Advanced - Memory configuration - Memory information.....                   | 205 |
| Figure 148: | Advanced - Memory configuration - Custom profile control.....               | 206 |
| Figure 149: | Advanced - USB configuration.....                                           | 207 |
| Figure 150: | Advanced - USB configuration - Per port USB disable control.....            | 209 |
| Figure 151: | Advanced - USB configuration - Per port legacy USB support control.....     | 210 |
| Figure 152: | Advanced - Serial port console redirection.....                             | 211 |
| Figure 153: | Advanced - Console redirection - Console redirection settings.....          | 212 |
| Figure 154: | Boot.....                                                                   | 213 |
| Figure 155: | Boot - Boot device priority.....                                            | 213 |
| Figure 156: | Boot - Boot configuration .....                                             | 214 |
| Figure 157: | Security.....                                                               | 215 |
| Figure 158: | Security - HDD user password.....                                           | 216 |
| Figure 159: | Save & Exit.....                                                            | 216 |
| Figure 160: | PCI and PCIe routing with enabled APIC for QM77/HM76 CPU boards.....        | 226 |
| Figure 161: | Software version.....                                                       | 227 |
| Figure 162: | Creating a bootable diskette in Windows XP - Step 1.....                    | 230 |
| Figure 163: | Creating a bootable diskette in Windows XP - Step 2.....                    | 230 |
| Figure 164: | Creating a bootable diskette in Windows XP - Step 3.....                    | 230 |
| Figure 165: | Creating a bootable diskette in Windows XP - Step 4.....                    | 231 |
| Figure 166: | Creating a bootable diskette in Windows XP - Step 5.....                    | 231 |
| Figure 167: | Creating a USB flash drive for B&R upgrade files.....                       | 232 |
| Figure 168: | Creating a mass storage device for B&R upgrade files.....                   | 233 |
| Figure 169: | CFast card - Dimensions.....                                                | 248 |
| Figure 170: | 5CFAST.xxxx-00 - Temperature humidity diagram.....                          | 249 |
| Figure 171: | 5MMUSB.xxxx-01 - Temperature humidity diagram.....                          | 251 |

## Figure index

|             |                                                                          |     |
|-------------|--------------------------------------------------------------------------|-----|
| Figure 172: | Flex radius specifications.....                                          | 253 |
| Figure 173: | 5CADVI.0xxx-00 - Dimensions.....                                         | 253 |
| Figure 174: | 5CADVI.0xxx-00 - Pinout.....                                             | 254 |
| Figure 175: | Flex radius specifications.....                                          | 256 |
| Figure 176: | 5CASDL.0xxx-00- Dimensions.....                                          | 256 |
| Figure 177: | 5CASDL.0xxx-00 - Pinout.....                                             | 257 |
| Figure 178: | Flex radius specifications.....                                          | 259 |
| Figure 179: | 5CASDL.0xxx-01 - Dimensions.....                                         | 259 |
| Figure 180: | 5CASDL.0xxx-01 - Pinout.....                                             | 260 |
| Figure 181: | Flex radius specifications.....                                          | 262 |
| Figure 182: | 5CASDL.0xxx-03 - Dimensions.....                                         | 262 |
| Figure 183: | 5CASDL.0xxx-03 - Pinout.....                                             | 263 |
| Figure 184: | Flex radius specification with extender.....                             | 265 |
| Figure 185: | 5CASDL.0xx0-13 - Dimensions.....                                         | 265 |
| Figure 186: | 5CASDL.0xx0-13 - Pinout.....                                             | 266 |
| Figure 187: | Example of the signal direction for an SDL flex cable with extender..... | 267 |
| Figure 188: | 5CAUSB.00xx-00 USB cables - Pinout.....                                  | 268 |
| Figure 189: | 9A0014.xx RS232 cables - Pinout .....                                    | 270 |
| Figure 190: | Pull out battery holder and remove battery.....                          | 271 |
| Figure 191: | Battery handling.....                                                    | 272 |
| Figure 192: | Replacing a CFast card.....                                              | 273 |

|           |                                                                                     |    |
|-----------|-------------------------------------------------------------------------------------|----|
| Table 1:  | Manual history.....                                                                 | 9  |
| Table 2:  | Environmentally friendly separation of materials.....                               | 12 |
| Table 3:  | Description of the safety notices used in this documentation.....                   | 13 |
| Table 4:  | Range of nominal sizes.....                                                         | 13 |
| Table 5:  | Display unit - Dimensions.....                                                      | 21 |
| Table 6:  | CPU boards, system units, bus units and power supply - Dimensions.....              | 21 |
| Table 7:  | Display units - Installation diagrams.....                                          | 22 |
| Table 8:  | Mounting orientations with and without a fan kit.....                               | 24 |
| Table 9:  | Mounting orientation when operated with individual components with limitations..... | 24 |
| Table 10: | Display units - Weight.....                                                         | 25 |
| Table 11: | CPU boards, system units, bus units and power supply - Weight.....                  | 25 |
| Table 12: | Ambient temperature with a fan kit.....                                             | 27 |
| Table 13: | Ambient temperature without a fan kit.....                                          | 28 |
| Table 14: | Ambient temperature in storage / transport.....                                     | 29 |
| Table 15: | Temperature sensor locations.....                                                   | 30 |
| Table 16: | Temperature sensor locations.....                                                   | 30 |
| Table 17: | Display units - Humidity.....                                                       | 31 |
| Table 18: | CPU boards, system units, bus units and power supply - Humidity.....                | 31 |
| Table 19: | Vibration.....                                                                      | 32 |
| Table 20: | Shock.....                                                                          | 32 |
| Table 21: | +24 VDC supply voltage connection.....                                              | 33 |
| Table 22: | Supply voltage connection - VAC power supply.....                                   | 33 |
| Table 23: | CPU board - Power calculation.....                                                  | 34 |
| Table 24: | Display units - Power calculation.....                                              | 35 |
| Table 25: | Interface options - Power calculation.....                                          | 35 |
| Table 26: | +24 VDC supply voltage connection.....                                              | 39 |
| Table 27: | Supply voltage connection - VAC power supply.....                                   | 40 |
| Table 28: | On/Off switch.....                                                                  | 40 |
| Table 29: | COM1 - Pinout.....                                                                  | 41 |
| Table 30: | COM2 - Pinout.....                                                                  | 41 |
| Table 31: | Monitor/Panel interface - RGB, DVI, SDL.....                                        | 42 |
| Table 32: | DVI interface - Pinout.....                                                         | 42 |
| Table 33: | Cable lengths and resolutions for SDL transmission.....                             | 43 |
| Table 34: | Cable lengths and resolutions for DVI transmission.....                             | 43 |
| Table 35: | Ethernet interface (ETH1).....                                                      | 44 |
| Table 36: | Ethernet interface (ETH2).....                                                      | 44 |
| Table 37: | USB1, USB2, USB3 and USB4 interfaces.....                                           | 45 |
| Table 38: | CFast slot.....                                                                     | 46 |
| Table 39: | Audio.....                                                                          | 46 |
| Table 40: | Data - LED status indicators.....                                                   | 47 |
| Table 41: | Power button.....                                                                   | 48 |
| Table 42: | Reset button.....                                                                   | 48 |
| Table 43: | Battery.....                                                                        | 49 |
| Table 44: | Battery status.....                                                                 | 49 |
| Table 45: | Slide-in compact slot.....                                                          | 50 |
| Table 46: | Slide-in slot.....                                                                  | 50 |
| Table 47: | Main memory slot.....                                                               | 51 |
| Table 48: | IF option 1 slot.....                                                               | 52 |
| Table 49: | IF option 2 slot.....                                                               | 52 |
| Table 50: | 5AP923.1215-00 - Order data.....                                                    | 54 |
| Table 51: | 5AP923.1215-00 - Technical data.....                                                | 54 |
| Table 52: | 5AP923.1505-00 - Order data.....                                                    | 56 |
| Table 53: | 5AP923.1505-00 - Technical data.....                                                | 56 |
| Table 54: | 5AP923.1906-00 - Order data.....                                                    | 58 |
| Table 55: | 5AP923.1906-00 - Technical data.....                                                | 58 |
| Table 56: | 5AP933.156B-00 - Order data.....                                                    | 60 |
| Table 57: | 5AP933.156B-00 - Technical data.....                                                | 60 |

|            |                                                                                                                                         |     |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------|-----|
| Table 58:  | 5AP933.185B-00 - Order data.....                                                                                                        | 62  |
| Table 59:  | 5AP933.185B-00 - Technical data.....                                                                                                    | 62  |
| Table 60:  | 5AP933.215C-00 - Order data.....                                                                                                        | 64  |
| Table 61:  | 5AP933.215C-00 - Technical data.....                                                                                                    | 64  |
| Table 62:  | 5AP933.240C-00 - Order data.....                                                                                                        | 66  |
| Table 63:  | 5AP933.240C-00 - Technical data.....                                                                                                    | 66  |
| Table 64:  | 5PC901.TS77-00, 5PC901.TS77-01, 5PC901.TS77-02, 5PC901.TS77-03, 5PC901.TS77-04,<br>5PC901.TS77-05, 5PC901.TS77-06 - Order data.....     | 68  |
| Table 65:  | 5PC901.TS77-00, 5PC901.TS77-01, 5PC901.TS77-02, 5PC901.TS77-03, 5PC901.TS77-04,<br>5PC901.TS77-05, 5PC901.TS77-06 - Technical data..... | 68  |
| Table 66:  | 5PC901.TS77-07, 5PC901.TS77-08, 5PC901.TS77-09, 5PC901.TS77-10 - Order data.....                                                        | 71  |
| Table 67:  | 5PC901.TS77-07, 5PC901.TS77-08, 5PC901.TS77-09, 5PC901.TS77-10 - Technical data.....                                                    | 71  |
| Table 68:  | 5PC911.SX00-00 - Order data.....                                                                                                        | 74  |
| Table 69:  | 5PC911.SX00-00 - Technical data.....                                                                                                    | 74  |
| Table 70:  | 5PC911.SX00-01 - Order data.....                                                                                                        | 75  |
| Table 71:  | 5PC911.SX00-01 - Technical data.....                                                                                                    | 75  |
| Table 72:  | 5MMDDR.1024-03, 5MMDDR.2048-03, 5MMDDR.4096-03, 5MMDDR.8192-03 - Order data...                                                          | 76  |
| Table 73:  | 5MMDDR.1024-03, 5MMDDR.2048-03, 5MMDDR.4096-03, 5MMDDR.8192-03 - Technical da-<br>ta.....                                               | 76  |
| Table 74:  | 5AC902.BX01-00, 5AC902.BX01-01, 5AC902.BX02-00, 5AC902.BX02-01 - Order data.....                                                        | 78  |
| Table 75:  | 5AC902.BX01-00, 5AC902.BX01-01, 5AC902.BX02-00, 5AC902.BX02-01 - Technical data....                                                     | 78  |
| Table 76:  | 5AC902.FA00-00 - Order data.....                                                                                                        | 79  |
| Table 77:  | 5AC902.FA00-00 - Technical data.....                                                                                                    | 79  |
| Table 78:  | 5AC902.FA0X-00 - Order data.....                                                                                                        | 80  |
| Table 79:  | 5AC902.FA0X-00 - Technical data.....                                                                                                    | 80  |
| Table 80:  | 5AC901.CHDD-01 - Order data.....                                                                                                        | 81  |
| Table 81:  | 5AC901.CHDD-01 - Technical data.....                                                                                                    | 81  |
| Table 82:  | 5AC901.CSSD-03 - Order data.....                                                                                                        | 83  |
| Table 83:  | 5AC901.CSSD-03 - Technical data.....                                                                                                    | 83  |
| Table 84:  | 5AC901.CSSD-04 - Order data.....                                                                                                        | 85  |
| Table 85:  | 5AC901.CSSD-04, 5AC901.CSSD-04, 5AC901.CSSD-04 - Technical data.....                                                                    | 85  |
| Table 86:  | 5AC901.CSSD-05 - Order data.....                                                                                                        | 88  |
| Table 87:  | 5AC901.CSSD-05 - Technical data.....                                                                                                    | 88  |
| Table 88:  | 5MMSSD.0060-01 - Order data.....                                                                                                        | 90  |
| Table 89:  | 5MMSSD.0060-01 - Technical data.....                                                                                                    | 90  |
| Table 90:  | 5MMSSD.0128-01 - Order data.....                                                                                                        | 92  |
| Table 91:  | 5MMSSD.0128-01, 5MMSSD.0128-01 - Technical data.....                                                                                    | 92  |
| Table 92:  | 5MMSSD.0256-00 - Order data.....                                                                                                        | 95  |
| Table 93:  | 5MMSSD.0256-00 - Technical data.....                                                                                                    | 95  |
| Table 94:  | 5AC901.CCFA-00 - Order data.....                                                                                                        | 97  |
| Table 95:  | 5AC901.CCFA-00 - Technical data.....                                                                                                    | 97  |
| Table 96:  | 5AC901.SDVW-00 - Order data.....                                                                                                        | 98  |
| Table 97:  | 5AC901.SDVW-00 - Technical data.....                                                                                                    | 98  |
| Table 98:  | 5AC901.SSCA-00 - Order data.....                                                                                                        | 100 |
| Table 99:  | 5AC901.SSCA-00 - Technical data.....                                                                                                    | 100 |
| Table 100: | 5AC901.I485-00 - Order data.....                                                                                                        | 101 |
| Table 101: | 5AC901.I485-00 - Technical data.....                                                                                                    | 101 |
| Table 102: | COM - Pinout.....                                                                                                                       | 102 |
| Table 103: | RS232 - Bus length and transfer rate.....                                                                                               | 102 |
| Table 104: | RS232 - Cable requirements.....                                                                                                         | 102 |
| Table 105: | RS422 - Bus length and transfer rate.....                                                                                               | 103 |
| Table 106: | RS422 - Cable requirements.....                                                                                                         | 103 |
| Table 107: | RS485 - Bus length and transfer rate.....                                                                                               | 103 |
| Table 108: | RS485 - Cable requirements.....                                                                                                         | 103 |
| Table 109: | 5AC901.ICAN-00 - Order data.....                                                                                                        | 105 |
| Table 110: | 5AC901.ICAN-00 - Technical data.....                                                                                                    | 105 |
| Table 111: | 5AC901.ICAN-00 - CAN pinout.....                                                                                                        | 106 |
| Table 112: | 5AC901.ISRM-00 - Order data.....                                                                                                        | 107 |

|            |                                                                                             |     |
|------------|---------------------------------------------------------------------------------------------|-----|
| Table 113: | 5AC901.ISRM-00 - Technical data.....                                                        | 107 |
| Table 114: | 5AC901.IHDA-00 - Order data.....                                                            | 109 |
| Table 115: | 5AC901.IHDA-00 - Technical data.....                                                        | 109 |
| Table 116: | MIC, Line IN, Line OUT.....                                                                 | 110 |
| Table 117: | 5AC901.IUPS-00 - Order data.....                                                            | 112 |
| Table 118: | 5AC901.IUPS-00 - Technical data.....                                                        | 112 |
| Table 119: | 5AC901.IUPS-00 / -01 - Pinout.....                                                          | 113 |
| Table 120: | 5AC901.IUPS-01 - Order data.....                                                            | 114 |
| Table 121: | 5AC901.IUPS-01 - Technical data.....                                                        | 114 |
| Table 122: | 5AC901.IUPS-00 / -01 - Pinout.....                                                          | 115 |
| Table 123: | 5AC901.BUPS-00 - Order data.....                                                            | 116 |
| Table 124: | 5AC901.BUPS-00 - Technical data.....                                                        | 116 |
| Table 125: | 5AC901.BUPS-01 - Order data.....                                                            | 119 |
| Table 126: | 5AC901.BUPS-01 - Technical data.....                                                        | 119 |
| Table 127: | 5CAUPS.0005-01, 5CAUPS.0010-01, 5CAUPS.0030-01 - Order data.....                            | 122 |
| Table 128: | 5CAUPS.0005-01, 5CAUPS.0010-01, 5CAUPS.0030-01 - Technical data.....                        | 122 |
| Table 129: | 5AC902.PS00-00 - Order data.....                                                            | 124 |
| Table 130: | 5AC902.PS00-00 - Technical data.....                                                        | 124 |
| Table 131: | BIOS-relevant keys in the RAID Configuration Utility.....                                   | 157 |
| Table 132: | Configuration Utility - Create RAID volume.....                                             | 157 |
| Table 133: | BIOS-relevant keys for POST.....                                                            | 162 |
| Table 134: | BIOS-relevant keys.....                                                                     | 162 |
| Table 135: | Main - Configuration options.....                                                           | 163 |
| Table 136: | Main - Platform information overview.....                                                   | 164 |
| Table 137: | Advanced overview.....                                                                      | 165 |
| Table 138: | Advanced - Graphics configuration options.....                                              | 166 |
| Table 139: | Advanced - OEM features screen.....                                                         | 168 |
| Table 140: | Advanced - OEM features - Super I/O configuration - Configuration options.....              | 169 |
| Table 141: | Advanced - OEM features - CPU board features.....                                           | 170 |
| Table 142: | Advanced - OEM features - CPU board features - Temperature values.....                      | 171 |
| Table 143: | Advanced - OEM features - System board features.....                                        | 172 |
| Table 144: | Advanced - OEM features - System board features - Statistical values.....                   | 172 |
| Table 145: | Advanced - OEM features - System board features - Temperature values.....                   | 173 |
| Table 146: | Advanced - OEM features - System board features - Voltage values.....                       | 174 |
| Table 147: | Advanced - OEM features - Memory module features.....                                       | 175 |
| Table 148: | Advanced - OEM features - Display board features.....                                       | 175 |
| Table 149: | Advanced - OEM features - Display board features - Statistical values.....                  | 176 |
| Table 150: | Advanced - OEM features - Display board features - Temperature values.....                  | 177 |
| Table 151: | Advanced - OEM features - Display board features - Panel #15.....                           | 177 |
| Table 152: | Advanced - OEM features - Bus unit features.....                                            | 178 |
| Table 153: | Advanced - OEM features - Bus unit features - Statistical values.....                       | 179 |
| Table 154: | Advanced - OEM features - I/O board 1 features.....                                         | 180 |
| Table 155: | Advanced - OEM features - I/O board 1 features - Statistical values.....                    | 180 |
| Table 156: | Advanced - OEM features - I/O board 2 features.....                                         | 181 |
| Table 157: | Advanced - OEM features - I/O board 2 features - Statistical values.....                    | 182 |
| Table 158: | Advanced - OEM features - Fan unit features.....                                            | 183 |
| Table 159: | Advanced - OEM features - Fan unit features - Statistical values.....                       | 183 |
| Table 160: | Advanced - OEM features - Fan unit features - RPM values.....                               | 184 |
| Table 161: | Advanced - OEM Features - Slide-in 1 features.....                                          | 185 |
| Table 162: | Advanced - OEM features - Slide-in 1 features - Temperature values.....                     | 185 |
| Table 163: | Advanced - OEM features - Panel control features.....                                       | 186 |
| Table 164: | Advanced - OEM features - Panel control features - Panel #X.....                            | 187 |
| Table 165: | Advanced - PCI configuration - Configuration options.....                                   | 187 |
| Table 166: | Advanced - PCI configuration - PIRQ routing & IRQ reservation - Configuration options.....  | 188 |
| Table 167: | Advanced - PCI Express configuration - Menu.....                                            | 189 |
| Table 168: | Advanced - PCI Express configuration - PCI Express settings - Configuration options.....    | 190 |
| Table 169: | Advanced - PCI Express configuration - PCI Express GEN 2 settings - Configuration options.. | 191 |

|            |                                                                                                                           |     |
|------------|---------------------------------------------------------------------------------------------------------------------------|-----|
| Table 170: | Advanced - PCI Express configuration - PCI Express graphics (PEG) port - Configuration options.....                       | 192 |
| Table 171: | Advanced - PCI Express configuration - PCI Express root port - Configuration options.....                                 | 194 |
| Table 172: | Advanced - ACPI settings - Configuration options.....                                                                     | 196 |
| Table 173: | Advanced - RTC wake settings - Configuration options.....                                                                 | 196 |
| Table 174: | Advanced - CPU configuration - Configuration options.....                                                                 | 197 |
| Table 175: | Advanced - CPU configuration - CPU information - Configuration options.....                                               | 199 |
| Table 176: | Advanced - Chipset configuration - Configuration options.....                                                             | 200 |
| Table 177: | Advanced - SATA configuration - Configuration options.....                                                                | 201 |
| Table 178: | Advanced - SATA configuration - Software feature mask configuration - Configuration options.                              | 203 |
| Table 179: | Advanced - Memory configuration - Configuration options.....                                                              | 204 |
| Table 180: | Advanced - Memory configuration - Memory information.....                                                                 | 206 |
| Table 181: | Advanced - Memory configuration - Custom profile control - Configuration options.....                                     | 206 |
| Table 182: | Advanced - USB configuration - Configuration options.....                                                                 | 207 |
| Table 183: | Advanced - USB configuration - Per port USB disable control - Configuration options.....                                  | 209 |
| Table 184: | Advanced - USB configuration - Per port legacy USB support control - Configuration options..                              | 210 |
| Table 185: | Advanced - Serial port console redirection - Configuration options.....                                                   | 211 |
| Table 186: | Advanced - Console redirection - Console redirection settings - Configuration options.....                                | 212 |
| Table 187: | Boot overview.....                                                                                                        | 213 |
| Table 188: | Boot - Boot device priority - Configuration options.....                                                                  | 214 |
| Table 189: | Boot - Boot configuration - Configuration options.....                                                                    | 214 |
| Table 190: | Security menu - Configuration options.....                                                                                | 215 |
| Table 191: | Security - HDD user password - Configuration options.....                                                                 | 216 |
| Table 192: | Save & Exit menu - Configuration options.....                                                                             | 217 |
| Table 193: | Advanced - Graphics configuration - Overview of profile settings.....                                                     | 218 |
| Table 194: | Advanced - OEM features - Overview of profile settings.....                                                               | 218 |
| Table 195: | Advanced - OEM features - Super I/O configuration - Overview of profile settings.....                                     | 218 |
| Table 196: | Advanced - PCI configuration - Overview of profile settings.....                                                          | 218 |
| Table 197: | Advanced - PCI Express configuration - PCI Express settings - Overview of profile settings...                             | 219 |
| Table 198: | Advanced - PCI Express configuration - PCI Express GEN 2 settings - Overview of profile settings.....                     | 219 |
| Table 199: | Advanced - PCI Express configuration - PCI Express graphics (PEG) port - Overview of profile settings.....                | 219 |
| Table 200: | Advanced - PCI Express configuration - PCI Express root port - Overview of profile settings...                            | 219 |
| Table 201: | Advanced - ACPI settings - Overview of profile settings.....                                                              | 220 |
| Table 202: | Advanced - RTC wake settings - Overview of profile settings.....                                                          | 220 |
| Table 203: | Advanced - CPU configuration - Overview of profile settings.....                                                          | 220 |
| Table 204: | Advanced - Chipset configuration - Overview of profile settings.....                                                      | 220 |
| Table 205: | Advanced - SATA configuration - Overview of profile settings.....                                                         | 221 |
| Table 206: | Advanced - Memory configuration - Overview of profile settings.....                                                       | 221 |
| Table 207: | Advanced - USB configuration - Overview of profile settings.....                                                          | 222 |
| Table 208: | Advanced - Serial port console redirection - Overview of profile settings.....                                            | 222 |
| Table 209: | Boot - Boot device priority - Overview of profile settings.....                                                           | 222 |
| Table 210: | Boot - Boot configuration - Overview of profile settings.....                                                             | 222 |
| Table 211: | RAM address assignment.....                                                                                               | 224 |
| Table 212: | I/O address assignment.....                                                                                               | 224 |
| Table 213: | IRQ interrupt assignments in PIC mode.....                                                                                | 224 |
| Table 214: | IRQ interrupt assignments in APIC mode.....                                                                               | 225 |
| Table 215: | 5SWWI7.1100-GER, 5SWWI7.1100-ENG, 5SWWI7.1200-GER, 5SWWI7.1200-ENG,<br>5SWWI7.1300-MUL, 5SWWI7.1400-MUL - Order data..... | 234 |
| Table 216: | 5SWWI7.1541-ENG, 5SWWI7.1641-ENG, 5SWWI7.1741-MUL, 5SWWI7.1841-MUL - Order data.....                                      | 236 |
| Table 217: | Device functions in Windows Embedded Standard 7.....                                                                      | 236 |
| Table 218: | 5SWWPX.0600-ENG, 5SWWPX.0600-GER, 5SWWPX.0600-MUL - Order data.....                                                       | 238 |
| Table 219: | 5SWWPX.0741-ENG - Order data.....                                                                                         | 240 |
| Table 220: | Device functions in Windows Embedded Standard 2009.....                                                                   | 240 |
| Table 221: | OTB103.9, OTB103.91 - Order data.....                                                                                     | 244 |
| Table 222: | OTB103.9, OTB103.91 - Technical data.....                                                                                 | 244 |

|            |                                                                                                                                      |     |
|------------|--------------------------------------------------------------------------------------------------------------------------------------|-----|
| Table 223: | 0TB3103.8000 - Order data.....                                                                                                       | 245 |
| Table 224: | 0TB3103.8000 - Technical data.....                                                                                                   | 245 |
| Table 225: | 0AC201.91, 4A0006.00-000 - Order data.....                                                                                           | 246 |
| Table 226: | 0AC201.91, 4A0006.00-000 - Technical data.....                                                                                       | 246 |
| Table 227: | 5CFAST.2048-00, 5CFAST.4096-00, 5CFAST.8192-00, 5CFAST.016G-00, 5CFAST.032G-00 - Order data.....                                     | 247 |
| Table 228: | 5CFAST.2048-00, 5CFAST.4096-00, 5CFAST.8192-00, 5CFAST.016G-00, 5CFAST.032G-00 - Technical data.....                                 | 247 |
| Table 229: | 5MMUSB.2048-01, 5MMUSB.4096-01 - Order data.....                                                                                     | 250 |
| Table 230: | 5MMUSB.2048-01, 5MMUSB.4096-01 - Technical data.....                                                                                 | 250 |
| Table 231: | 5CADVI.0018-00, 5CADVI.0050-00, 5CADVI.0100-00 - Order data.....                                                                     | 252 |
| Table 232: | 5CADVI.0018-00, 5CADVI.0050-00, 5CADVI.0100-00 - Technical data.....                                                                 | 252 |
| Table 233: | 5CASDL.0018-00, 5CASDL.0050-00, 5CASDL.0100-00, 5CASDL.0150-00, 5CASDL.0200-00, 5CASDL.0250-00, 5CASDL.0300-00 - Order data.....     | 255 |
| Table 234: | 5CASDL.0018-00, 5CASDL.0050-00, 5CASDL.0100-00, 5CASDL.0150-00, 5CASDL.0200-00, 5CASDL.0250-00, 5CASDL.0300-00 - Technical data..... | 255 |
| Table 235: | 5CASDL.0018-01, 5CASDL.0050-01, 5CASDL.0100-01, 5CASDL.0150-01 - Order data.....                                                     | 258 |
| Table 236: | 5CASDL.0018-01, 5CASDL.0050-01, 5CASDL.0100-01, 5CASDL.0150-01 - Technical data..                                                    | 258 |
| Table 237: | 5CASDL.0018-03, 5CASDL.0050-03, 5CASDL.0100-03, 5CASDL.0150-03, 5CASDL.0200-03, 5CASDL.0250-03, 5CASDL.0300-03 - Order data.....     | 261 |
| Table 238: | 5CASDL.0018-03, 5CASDL.0050-03, 5CASDL.0100-03, 5CASDL.0150-03, 5CASDL.0200-03, 5CASDL.0250-03, 5CASDL.0300-03 - Technical data..... | 261 |
| Table 239: | 5CASDL.0xxx-03 SDL flex cables - Structure.....                                                                                      | 263 |
| Table 240: | 5CASDL.0300-13, 5CASDL.0400-13, 5CASDL.0430-13 - Order data.....                                                                     | 264 |
| Table 241: | 5CASDL.0300-13, 5CASDL.0400-13, 5CASDL.0430-13 - Technical data.....                                                                 | 264 |
| Table 242: | 5CAUSB.0018-00, 5CAUSB.0050-00 - Order data.....                                                                                     | 268 |
| Table 243: | 5CAUSB.0018-00, 5CAUSB.0050-00 - Technical data.....                                                                                 | 268 |
| Table 244: | 9A0014.02, 9A0014.05, 9A0014.10 - Order data.....                                                                                    | 269 |
| Table 245: | 9A0014.02, 9A0014.05, 9A0014.10 - Technical data.....                                                                                | 269 |
| Table 246: | Abbreviations used in this user's manual.....                                                                                        | 276 |

## Model number index

|                     |     |
|---------------------|-----|
| 0AC201.91.....      | 246 |
| 0TB103.9.....       | 244 |
| 0TB103.91.....      | 244 |
| 0TB3103.8000.....   | 245 |
| 4A0006.00-000.....  | 246 |
| 5AC901.BUPS-00..... | 116 |
| 5AC901.BUPS-01..... | 119 |
| 5AC901.CCFA-00..... | 97  |
| 5AC901.CHDD-01..... | 81  |
| 5AC901.CSSD-03..... | 83  |
| 5AC901.CSSD-04..... | 85  |
| 5AC901.CSSD-05..... | 88  |
| 5AC901.I485-00..... | 101 |
| 5AC901.ICAN-00..... | 105 |
| 5AC901.IHDA-00..... | 109 |
| 5AC901.ISRM-00..... | 107 |
| 5AC901.IUPS-00..... | 112 |
| 5AC901.IUPS-01..... | 114 |
| 5AC901.SDVW-00..... | 98  |
| 5AC901.SSCA-00..... | 100 |
| 5AC902.BX01-00..... | 78  |
| 5AC902.BX01-01..... | 78  |
| 5AC902.BX02-00..... | 78  |
| 5AC902.BX02-01..... | 78  |
| 5AC902.FA00-00..... | 79  |
| 5AC902.FA0X-00..... | 80  |
| 5AC902.PS00-00..... | 124 |
| 5AP923.1215-00..... | 54  |
| 5AP923.1505-00..... | 56  |
| 5AP923.1906-00..... | 58  |
| 5AP933.156B-00..... | 60  |
| 5AP933.185B-00..... | 62  |
| 5AP933.215C-00..... | 64  |
| 5AP933.240C-00..... | 66  |
| 5CADVI.0018-00..... | 252 |
| 5CADVI.0050-00..... | 252 |
| 5CADVI.0100-00..... | 252 |
| 5CASDL.0018-00..... | 255 |
| 5CASDL.0018-01..... | 258 |
| 5CASDL.0018-03..... | 261 |
| 5CASDL.0050-00..... | 255 |
| 5CASDL.0050-01..... | 258 |
| 5CASDL.0050-03..... | 261 |
| 5CASDL.0100-00..... | 255 |
| 5CASDL.0100-01..... | 258 |
| 5CASDL.0100-03..... | 261 |
| 5CASDL.0150-00..... | 255 |
| 5CASDL.0150-01..... | 258 |
| 5CASDL.0150-03..... | 261 |
| 5CASDL.0200-00..... | 255 |
| 5CASDL.0200-03..... | 261 |
| 5CASDL.0250-00..... | 255 |
| 5CASDL.0250-03..... | 261 |
| 5CASDL.0300-00..... | 255 |
| 5CASDL.0300-03..... | 261 |
| 5CASDL.0300-13..... | 264 |
| 5CASDL.0400-13..... | 264 |
| 5CASDL.0430-13..... | 264 |
| 5CAUPS.0005-01..... | 122 |
| 5CAUPS.0010-01..... | 122 |
| 5CAUPS.0030-01..... | 122 |
| 5CAUSB.0018-00..... | 268 |

|                      |     |
|----------------------|-----|
| 5CAUSB.0050-00.....  | 268 |
| 5CFAST.016G-00.....  | 247 |
| 5CFAST.032G-00.....  | 247 |
| 5CFAST.2048-00.....  | 247 |
| 5CFAST.4096-00.....  | 247 |
| 5CFAST.8192-00.....  | 247 |
| 5MMDDR.1024-03.....  | 76  |
| 5MMDDR.2048-03.....  | 76  |
| 5MMDDR.4096-03.....  | 76  |
| 5MMDDR.8192-03.....  | 76  |
| 5MMSSD.0060-01.....  | 90  |
| 5MMSSD.0128-01.....  | 92  |
| 5MMSSD.0256-00.....  | 95  |
| 5MMUSB.2048-01.....  | 250 |
| 5MMUSB.4096-01.....  | 250 |
| 5PC901.TS77-00.....  | 68  |
| 5PC901.TS77-01.....  | 68  |
| 5PC901.TS77-02.....  | 68  |
| 5PC901.TS77-03.....  | 68  |
| 5PC901.TS77-04.....  | 68  |
| 5PC901.TS77-05.....  | 68  |
| 5PC901.TS77-06.....  | 68  |
| 5PC901.TS77-07.....  | 71  |
| 5PC901.TS77-08.....  | 71  |
| 5PC901.TS77-09.....  | 71  |
| 5PC901.TS77-10.....  | 71  |
| 5PC911.SX00-00.....  | 74  |
| 5PC911.SX00-01.....  | 75  |
| 5SWWI7.1100-ENG..... | 234 |
| 5SWWI7.1100-GER..... | 234 |
| 5SWWI7.1200-ENG..... | 234 |
| 5SWWI7.1200-GER..... | 234 |
| 5SWWI7.1300-MUL..... | 234 |
| 5SWWI7.1400-MUL..... | 234 |
| 5SWWI7.1541-ENG..... | 236 |
| 5SWWI7.1641-ENG..... | 236 |
| 5SWWI7.1741-MUL..... | 236 |
| 5SWWI7.1841-MUL..... | 236 |
| 5SWWXP.0600-ENG..... | 238 |
| 5SWWXP.0600-GER..... | 238 |
| 5SWWXP.0600-MUL..... | 238 |
| 5SWWXP.0741-ENG..... | 240 |
| 9A0014.02.....       | 269 |
| 9A0014.05.....       | 269 |
| 9A0014.10.....       | 269 |

**A**

|                                       |          |
|---------------------------------------|----------|
| Accessories.....                      | 244      |
| AC mains cable.....                   | 149      |
| ACPI.....                             | 224, 225 |
| ADI Control Center.....               | 111      |
| Adjusting the display brightness..... | 155      |
| Allocation of resources.....          | 224      |
| Audio.....                            | 46       |

**B**

|                       |          |
|-----------------------|----------|
| Backlight.....        | 275      |
| Battery.....          | 49       |
| Battery unit.....     | 111, 116 |
| BIOS                  |          |
| Advanced.....         | 165      |
| Boot.....             | 213      |
| default settings..... | 218      |
| Main.....             | 163      |
| Save & Exit.....      | 216      |
| Security.....         | 215      |
| BIOS Setup keys.....  | 162      |
| BIOS upgrade.....     | 227      |
| Blink code.....       | 47       |
| buffer lifespan.....  | 49       |

**C**

|                                         |            |
|-----------------------------------------|------------|
| Cable connections.....                  | 152        |
| Cables.....                             | 252        |
| DVI cables.....                         | 252        |
| SDL cables.....                         | 255        |
| SDL cables with 45° male connector..... | 258        |
| SDL flex cables.....                    | 261        |
| SDL flex cables with extender.....      | 264        |
| USB cables.....                         | 268        |
| CAN interfaces.....                     | 106        |
| CAN master interface.....               | 105        |
| CE mark.....                            | 242        |
| Certifications.....                     | 243        |
| certifications                          |            |
| GOST-R.....                             | 243        |
| Certifications                          |            |
| UL.....                                 | 243        |
| UL Haz. Loc.....                        | 243        |
| CFast slot.....                         | 46         |
| Changing the battery.....               | 271        |
| Chipset.....                            | 68, 71     |
| Cleaning.....                           | 274        |
| COM.....                                | 102        |
| COM1.....                               | 41         |
| COM2.....                               | 41         |
| Complete system.....                    | 21         |
| Configuration.....                      | 18         |
| Connecting the battery unit.....        | 147        |
| CPU board.....                          | 17, 68, 71 |
| Create RAID volume.....                 | 157        |

**D**

|                                  |        |
|----------------------------------|--------|
| DC mains cable.....              | 148    |
| dead/stuck pixels.....           | 275    |
| defective pixels.....            | 275    |
| deflect disturbances.....        | 151    |
| Delete RAID volume.....          | 158    |
| Device interfaces and slots..... | 37     |
| Dimensions                       |        |
| 5AC901.BUPS-00.....              | 117    |
| 5AC901.BUPS-01.....              | 120    |
| Dimension standards.....         | 13     |
| Display brightness.....          | 155    |
| Display unit.....                | 16     |
| Display units.....               | 54     |
| Disposal.....                    | 12, 12 |
| Drilling template                |        |
| 5AC901.BUPS-00.....              | 118    |
| 5AC901.BUPS-01.....              | 121    |
| Drives.....                      | 81     |
| dual-channel memory.....         | 76     |
| DVI cables.....                  | 252    |
| DVI resolution.....              | 43     |

**E**

|                                              |        |
|----------------------------------------------|--------|
| Electrical characteristics.....              | 33     |
| Electromagnetic compatibility.....           | 242    |
| EMC directive.....                           | 242    |
| Environmental characteristics.....           | 26     |
| ESD.....                                     | 10     |
| Electrical components with a housing.....    | 10     |
| Electrical components without a housing..... | 10     |
| Individual components.....                   | 10     |
| Packaging.....                               | 10     |
| ETH1.....                                    | 44     |
| ETH2.....                                    | 44     |
| Ethernet 1.....                              | 44     |
| Ethernet 2.....                              | 44     |
| Ethernet controller.....                     | 44, 44 |

**F**

|                                 |     |
|---------------------------------|-----|
| Fan control.....                | 30  |
| Fan kit.....                    | 79  |
| Fan kits.....                   | 79  |
| fan speed.....                  | 30  |
| Firmware upgrade.....           | 229 |
| Flex radius.....                | 152 |
| Flex radius specifications..... | 152 |
| Functional ground.....          | 151 |

**G**

|                              |         |
|------------------------------|---------|
| General tolerance.....       | 13      |
| GOST-R.....                  | 243     |
| Gosudarstwenny standard..... | 243     |
| ground connection.....       | 39, 151 |
| Grounding.....               | 39, 151 |
| Guidelines.....              | 13      |

**H**

|                   |     |
|-------------------|-----|
| HDA.....          | 109 |
| HDD LED.....      | 47  |
| heat sink.....    | 17  |
| HM76 chipset..... | 71  |

**I**

|                                                          |          |
|----------------------------------------------------------|----------|
| I/O address assignment.....                              | 224      |
| IF option.....                                           | 101      |
| IF option 1 slot.....                                    | 52       |
| IF option 2 slot.....                                    | 52       |
| immunity to disturbances.....                            | 151      |
| Installation                                             |          |
| AC power supply.....                                     | 130      |
| battery unit.....                                        | 147      |
| Bus unit.....                                            | 141      |
| CPU board and system unit.....                           | 128      |
| Fan filter.....                                          | 140      |
| Fan kit.....                                             | 139      |
| Interface option.....                                    | 134      |
| Main memory.....                                         | 132      |
| Panel PC 900.....                                        | 125      |
| PCI / PCIe cards.....                                    | 143      |
| Slide-in compact drive.....                              | 137      |
| Slide-in drive.....                                      | 145      |
| Installation notes.....                                  | 125      |
| Installing and replacing the slide-in compact drive..... | 137      |
| Installing a slide-in drive.....                         | 145      |
| Installing or replacing the AC power supply.....         | 130      |
| Installing PCI / PCIe cards.....                         | 143      |
| Installing the AC mains cable.....                       | 149      |
| Installing the battery unit.....                         | 147      |
| Installing the bus unit.....                             | 141      |
| Installing the DC mains cable.....                       | 148      |
| Installing the interface option.....                     | 134      |
| Installing the power supply.....                         | 130      |
| Interface option.....                                    | 101      |
| Interfaces.....                                          | 37       |
| +24 VDC power supply.....                                | 33, 39   |
| CFast slot.....                                          | 46       |
| Ethernet 1.....                                          | 44       |
| Ethernet 2.....                                          | 44       |
| Grounding.....                                           | 39       |
| Monitor/Panel interface.....                             | 42       |
| Supply voltage VAC.....                                  | 33, 40   |
| USB.....                                                 | 45       |
| Internal RAID controller.....                            | 156      |
| Interrupt assignments.....                               | 224, 225 |

**L**

|                            |     |
|----------------------------|-----|
| LED.....                   | 47  |
| LEDs.....                  | 47  |
| LED status indicator.....  | 47  |
| Line IN.....               | 46  |
| Line OUT.....              | 46  |
| Link LED.....              | 47  |
| Low voltage directive..... | 242 |

**M**

|                                 |        |
|---------------------------------|--------|
| Main memory.....                | 51, 76 |
| Mechanical characteristics..... | 21     |
| MIC.....                        | 46     |
| MIC, Line IN, Line OUT.....     | 110    |
| Monitor/Panel interface.....    | 42     |
| Multi-touch.....                | 154    |

**O**

|                                     |     |
|-------------------------------------|-----|
| Operating system                    |     |
| Windows 7.....                      | 234 |
| Windows Embedded Standard 2009..... | 240 |
| Windows Embedded Standard 7.....    | 236 |
| Windows XP Professional.....        | 238 |

**P**

|                                                    |        |
|----------------------------------------------------|--------|
| Panel PC                                           |        |
| Ambient temperature for storage and transport..... | 29     |
| Block diagram.....                                 | 36     |
| Dimensions.....                                    | 21     |
| Fan control.....                                   | 30     |
| Humidity.....                                      | 31     |
| Installation diagrams.....                         | 22     |
| Maximum ambient temperature during operation.....  | 27     |
| Minimum ambient temperature during operation.....  | 29     |
| Mounting orientations.....                         | 24     |
| Power calculation.....                             | 34     |
| Protection.....                                    | 32     |
| Shock.....                                         | 32     |
| Spacing for air circulation.....                   | 23     |
| Temperature.....                                   | 26     |
| Temperature sensors.....                           | 30     |
| Vibration.....                                     | 32     |
| Weight specifications.....                         | 25     |
| Power button.....                                  | 48     |
| Power connectors.....                              | 244    |
| Power LED.....                                     | 47     |
| Power mains connection                             |        |
| AC mains cable.....                                | 149    |
| DC mains cable.....                                | 148    |
| power supply.....                                  | 33, 39 |
| Proper ESD handling.....                           | 10     |

**Q**

|                   |    |
|-------------------|----|
| QM77 chipset..... | 68 |
|-------------------|----|

**R**

|                                              |     |
|----------------------------------------------|-----|
| RAID set.....                                | 156 |
| RAM address assignment.....                  | 224 |
| real-time clock.....                         | 49  |
| Recovery volume options.....                 | 160 |
| Relative humidity.....                       | 31  |
| Replacing a CFast card.....                  | 273 |
| Replacing the CPU board and system unit..... | 128 |
| Replacing the fan filter.....                | 140 |

|                                                 |             |
|-------------------------------------------------|-------------|
| Replacing the fan kit.....                      | 139         |
| Replacing the main memory modules.....          | 132         |
| Reset button.....                               | 48          |
| Reset disks to non-RAID.....                    | 159         |
| RS232                                           |             |
| Bus length.....                                 | 102         |
| Cable type.....                                 | 102         |
| RS232/422/485 interface.....                    | 101         |
| RS232 cables.....                               | 269         |
| RS422                                           |             |
| Bus length.....                                 | 102         |
| Cable type.....                                 | 103         |
| RS485                                           |             |
| Bus length.....                                 | 103         |
| Cable type.....                                 | 103         |
| RS485 interface.....                            | 103         |
| Run LED.....                                    | 47          |
| <b>S</b>                                        |             |
| S.M.A.R.T.....                                  | 29          |
| Safety guidelines.....                          | 10          |
| Intended use.....                               | 10          |
| Policies and procedures.....                    | 10          |
| Safety notices                                  |             |
| Environmental conditions.....                   | 11          |
| Environmentally friendly disposal.....          | 12          |
| Installation.....                               | 11          |
| Operation.....                                  | 11          |
| Protection against electrostatic discharge..... | 10          |
| Separation of materials.....                    | 12          |
| Transport and storage.....                      | 11          |
| SATA RAID set.....                              | 156         |
| Screen burn-in.....                             | 275, 275    |
| SDL cables.....                                 | 255         |
| SDL cables with 45° male connector.....         | 258         |
| SDL flex cables.....                            | 261         |
| SDL flex cables with extender.....              | 264         |
| SDL resolution.....                             | 43          |
| serial interface.....                           | 41, 41, 102 |
| service life of the display.....                | 275         |
| Single-touch.....                               | 154         |
| Slide-in compact slot.....                      | 50          |
| Slide-in slot.....                              | 50          |
| Slots.....                                      | 37          |
| Standards and guidelines.....                   | 242         |
| Startup temperature of fans.....                | 30          |
| Status LEDs.....                                | 47          |
| Structure.....                                  | 18          |
| Supply voltage.....                             | 33, 40, 151 |
| Switching on for the first time.....            | 153         |
| system unit.....                                | 17          |
| System units.....                               | 74          |
| <b>T</b>                                        |             |
| Temperature monitoring.....                     | 29          |
| Temperature sensor locations.....               | 30          |
| Temperature specifications.....                 | 26          |
| Touch screen calibration.....                   | 154         |

**U**

|                                   |          |
|-----------------------------------|----------|
| UL certification.....             | 243      |
| UL Haz. Loc. Certifications.....  | 243      |
| Uninterruptible power supply..... | 111      |
| Upgrade                           |          |
| BIOS.....                         | 227      |
| Firmware.....                     | 229      |
| Upgrade information.....          | 227      |
| UPS.....                          | 111, 111 |
| UPS connection cable.....         | 111, 122 |
| UPS IF option.....                | 111      |
| UPS interface.....                | 113, 115 |
| USB 3.0.....                      | 45       |
| USB cables.....                   | 268      |
| USB flash drive.....              | 250      |
| USB interfaces.....               | 45       |

**V**

|                     |     |
|---------------------|-----|
| Video signal.....   | 42  |
| Viewing angles..... | 276 |

**W**

|                                     |          |
|-------------------------------------|----------|
| WES2009.....                        | 240      |
| WES7.....                           | 236      |
| Windows 7.....                      | 234      |
| Windows Embedded Standard 2009..... | 240      |
| Windows Embedded Standard 7.....    | 236      |
| Windows XP Professional.....        | 238      |
| Wiring.....                         | 148, 149 |