

X20BB62

1 General information

1.1 Other applicable documents

For additional and supplementary information, see the following documents.

Other applicable documents

Document name	Title
MAX20	X20 System user's manual
MAEMV	Installation / EMC guide

1.2 Order data


Order number	Short description	Figure
	System modules for Compact-S PLCs	
X20BB62	X20 Compact-S bus base, for Compact-S PLC and Compact-S PLC power supply module, base for integrated RS232 interface, slot for X20 interface module, X20 connection, X20 end cover plates (left and right) X20AC0SL1/X20AC0SR1 included	

Table 1: X20BB62 - Order data

1.3 Module description

The bus module is the base for all X20CP048x Compact-S controllers in the X20 family. It is equipped with 1 slot for X20 interface modules.

The left and right end cover plates are included in delivery.

- Base for X20 Compact-S controllers
- 1 slot for X20 interface modules
- RS232 connection

Information:

Compact-S controllers must be inserted into the slot on the far right.

2 Technical description

2.1 Technical data

Order number	X20BB62
Short description	
Bus module	X20 Compact-S PLC base - backplane for Compact-S PLC and Compact-S PLC power supply module and X20 interface module
Interfaces	1x RS232 connection
General information	
B&R ID code	0xEB08
Power consumption	
Bus	0.94 W
Internal I/O	-
Additional power dissipation caused by actuators (resistive) [W]	-
Certifications	
CE	Yes
UKCA	Yes
UL	cULus E115267 Industrial control equipment
DNV	Temperature: B (0 to 55°C) Humidity: B (up to 100%) Vibration: B (4 g) EMC: B (bridge and open deck)
LR	ENV1
ABS	Yes
BV	EC33B Temperature: 5 - 55°C Vibration: 4 g EMC: Bridge and open deck
EAC	Yes
I/O power supply	
Nominal voltage	24 VDC
Permissible contact load	10 A
Electrical properties	
Electrical isolation	Bus not isolated from RS232
Operating conditions	
Mounting orientation	
Horizontal	Yes
Vertical	Yes
Installation elevation above sea level	
0 to 2000 m	No limitation
>2000 m	Reduction of ambient temperature by 0.5°C per 100 m
Degree of protection per EN 60529	IP20
Ambient conditions	
Temperature	
Operation	
Horizontal mounting orientation	-25 to 60°C
Vertical mounting orientation	-25 to 50°C
Derating	-
Storage	-40 to 85°C
Transport	-40 to 85°C
Relative humidity	
Operation	5 to 95%, non-condensing
Storage	5 to 95%, non-condensing
Transport	5 to 95%, non-condensing
Mechanical properties	
Note	Left and right X20 end cover plates included in delivery
Pitch	62.5 ^{+0.2} mm

Table 2: X20BB62 - Technical data

2.2 Voltage routing

