# X20(c)IF1082-2

### 1 General information

The interface module can be used to expand the X20 CPU for specific applications. It is equipped with an POW-ERLINK interface.

The interface has two RJ45 sockets. Both connections lead to an integrated hub. This makes it easy to create daisy-chain connections using POWERLINK.

- POWERLINK for real-time Ethernet communication
- · Integrated hub for efficient cabling
- · Configurable ring redundancy
- · Poll response chaining
- Dynamic Node Allocation (DNA)

### 2 Coated modules

Coated modules are X20 modules with a protective coating for the electronics component. This coating protects X20c modules from condensation and corrosive gases.

The modules' electronics are fully compatible with the corresponding X20 modules.

For simplification purposes, only images and module IDs of uncoated modules are used in this data sheet.

The coating has been certified according to the following standards:

- Condensation: BMW GS 95011-4, 2x 1 cycle
- Corrosive gas: EN 60068-2-60, method 4, exposure 21 days







### 3 Order data

Model number	Short description	Figure
	X20 interface module communication	
X20IF1082-2	X20 interface module, 1 POWERLINK interface, managing or controlled node, integrated 2-port hub, ring redundancy function PRC function	
X20clF1082-2	X20 interface module, coated, 1 POWERLINK interface, managing or controlled node, integrated 2-port hub, ring redundancy function PRC function	

Table 1: X20IF1082-2, X20cIF1082-2 - Order data

#### **Optional accessories**

Model number	Short description
Woder Humber	Short description
X20CA0E61.xxxxx	POWERLINK/Ethernet connection cable, RJ45 to RJ45, 0.2 to 20 m
X20CA0E61.xxxx	POWERLINK/Ethernet connection cable, RJ45 to RJ45, 20 m and longer


## 4 Technical data

Model number	X20IF1082-2	X20clF1082-2		
Short description				
Communication module	1x POWERLINK (V1/V2) m	nanaging or controlled node		
General information				
B&R ID code	0xA7A3 0xE236			
Status indicators	Module status	s, bus function		
Diagnostics				
Module status	Yes, using status	LED and software		
Bus function	Yes, using status	LED and software		
Power consumption	2	W		
Additional power dissipation caused by actuators		-		
(resistive) [W]				
Certifications				
CE		es		
KC	Yes	-		
EAC		es		
UL		E115267		
		trol equipment		
HazLoc		s 244665 crol equipment		
		ous locations		
		, Groups ABCD, T5		
ATEX		nA nC IIA T5 Gc		
	IP20, Ta (see X2	20 user's manual)		
		TEX 0083X		
DNV GL		E B (0 - 55°C)		
		(up to 100%)		
		n: <b>B</b> (4 g) and open deck)		
LR				
KR	ENV1 Yes			
Interfaces	.,,			
Fieldbus	POWERLINK (V1/V2) ma	anaging or controlled node		
Туре	Type 4 1)			
Variant		I RJ45 (hub)		
Line length	Max. 100 m between 2 stations (segment length)			
Transfer rate	100 Mbit/s			
Transfer				
Physical layer	100BA	ASE-TX		
Half-duplex		es		
Full-duplex		lo		
Autonegotiation		es		
Auto-MDI/MDIX		es		
Hub propagation delay	0.96 t	to 1 µs		
Controller		INK MAC		
Electrical properties				
Electrical isolation	PLC isolated from PO	PLC isolated from POWERLINK (X1 and X2)		
Operating conditions				
Mounting orientation				
Horizontal	Y	es		
Vertical	Y	es		
Installation elevation above sea level				
0 to 2000 m	No lim	itations		
>2000 m	Reduction of ambient temperature by 0.5°C per 100 m			
Degree of protection per EN 60529	<u> </u>	20		
Ambient conditions				
Temperature				
Operation				
Horizontal mounting orientation	-25 to 60°C			
Vertical mounting orientation	-25 to 50°C			
Derating	-			
Storage	-40 to 85°C			
Transport	-40 to 85°C			
Relative humidity				
Operation	5 to 95%, non-condensing	Up to 100%, condensing		
Storage		n-condensing		
_	5 to 95%, non-condensing			
Transport				
Transport  Mechanical properties				

Table 2: X20IF1082-2, X20cIF1082-2 - Technical data

<sup>1)</sup> See Automation Help under "Communication / POWERLINK / General information / Hardware - IF/LS" for more information.

### 5 LED status indicators



### 5.1 LED "S/E" (LED "Status/Error")

This LED is a green/red dual LED and indicates the state of the POWERLINK interface. The LED states have a different meaning depending on the operating mode of the POWERLINK interface.

#### 5.1.1 Ethernet mode

In this mode, the interface is operated as an Ethernet interface.

LED "S/E"		
Green	Red	Description
On	Off	The interface is operated as an Ethernet interface.

Table: LED "S/E": Interface in Ethernet mode

#### 5.1.2 POWERLINK V1 mode

LED "S/E"	D "S/E"		
Green	Red	d Status of the POWERLINK node	
On	Off	The POWERLINK node is running with no errors.	
Off	On	A system error occurred. The type of error can be read using the PLC logbook. An irreparable problem has occurred. The system can no longer properly carry out its tasks. This state can only be changed by resetting the module.	
Blinking alt	ernately	The POWERLINK managing node has failed. This error code can only occur when operated as a controlled node. This means that the set node number lies within the range 0x01 - 0xFD.	
Off	Blinking	System stop. The red blinking LED indicates an error code (see "System stop error codes" on page 5).	
Off	Off	The interface is either not active or one of the following states or errors is present:	
		The device is switched off.	
		The device is in the startup phase.	
		The interface or device is not configured correctly in Automation Studio.	
		The interface or device is defective.	

Table 3: LED "S/E": POWERLINK V1 mode

### 5.1.3 POWERLINK V2 mode

#### **Error message**





Table: LED "S/E" - Error message (interface in POWERLINK mode)

### Interface status

LED "S/E"			
Green	Red	Description Description	
Off	Off	Mode: NOT_ACTIVE The interface is either in mode NOT ACTIVE or one of the following modes or errors is present:	
		The device is switched off.	
		The device is in the startup phase.	
		The interface or device is not configured correctly in Automation Studio.	
		The interface or device is defective.	
		Managing node (MN)	
		The network is monitored for POWERLINK frames. If a frame is not received within the configured time window (timeout), the interface immediately enters mode PRE_OPERATIONAL_1.	
		If POWERLINK communication is detected before the time has elapsed, however, the MN is not started.	
		Controlled node (CN)	
		The network is monitored for POWERLINK frames. If a frame is not received within the configured time window (timeout), the interface immediately enters mode BASIC_ETHERNET. If POWERLINK communication is detected before this time expires, however, the interface immediately enters mode PRE_OPERATIONAL_1.	
Flickering	Off	Mode: BASIC_ETHERNET	
(approx. 10 Hz)		The interface is in mode BASIC_ETHERNET. The interface is operated in Ethernet mode.	
		Managing node (MN) This mode can only be exited by resetting the controller.	
		Controlled node (CN)	
Single flash	Off	If POWERLINK communication is detected during this mode, the interface enters mode PRE_OPERATIONAL_1.  Mode: PRE_OPERATIONAL_1	
(approx. 1 Hz)	Oii	The interface is in mode PRE_OPERATIONAL_1.	
		Managing node (MN)	
		The MN is in "reduced cycle" operation. The CNs are configured in this mode.  Cyclic communication is not yet taking place.	
		Controlled node (CN)	
		The CN can be configured by the MN in this mode. The CN waits until it receives an SoC frame and then switches to mode	
	On	PRE_OPERATIONAL_2.  Controlled node (CN)	
	OII	If the red LED lights up in this mode, this means that the MN has failed.	
Double flash	Off	Mode: PRE_OPERATIONAL_2	
(approx. 1 Hz)		The interface is in mode PRE_OPERATIONAL_2.	
		Managing node (MN)	
		The MN starts cyclic communication (cyclic input data is not yet evaluated).  The CNs are configured in this mode.	
		The Gras are configured in this mode.	
		Controlled node (CN) The CN can be configured by the MN in this mode. A command then switches the mode to READY_TO_OPERATE.	
	On	Controlled node (CN)	
		If the red LED lights up in this mode, this means that the MN has failed.	
Triple flash (approx. 1 Hz)	Off	Mode: READY_TO_OPERATE The interface is in mode READY_TO_OPERATE.	
		Managing node (MN) Cyclic and asynchronous communication. Received PDO data is ignored.	
		Controlled node (CN)	
		The configuration of the CN is completed. Normal cyclic and asynchronous communication. The transmitted PDO data corresponds to the PDO mapping. However, cyclic data is not yet evaluated.	
	On	Controlled node (CN)  If the red LED lights up in this mode, this means that the MN has failed.	
On	Off	Mode: OPERATIONAL The interface is in mode OPERATIONAL. PDO mapping is active and cyclic data is evaluated.	
Blinking	Off Mode: STOPPED		
(approx. 2.5 Hz)		The interface is in mode STOPPED.	
2.0112)		Managing node (MN) This mode does not occur for the MN.	
		Controlled node (CN)  Output data is not being output, and no input data is being provided. This mode can only be reached and exited by a corre-	
		sponding command from the MN.	

Table: LED "S/E" - Interface state (interface in POWERLINK mode)


#### **Blink times**



### 5.1.4 System stop error codes


A system stop error can occur due to incorrect configuration or defective hardware.

The error code is indicated by LED "S/E" blinking red. The blinking signal of the error code consists of 4 switch-on phases with short (150 ms) or long (600 ms) duration. The error code is repeated every 2 seconds.



Error	Error description	
RAM error	The device is defective and must be replaced.	
Hardware error	The device or a system component is defective and must be replaced.	

## 6 Operating and connection elements



### 7 POWERLINK node number



The node number for the POWERLINK station is set using the two number switches. The node number can also be directly configured using Automation Studio.

#### 7.1 POWERLINK V1

Switch position	Description
0x00	Operation as managing node.
0x01 - 0xFD	Node number of the POWERLINK node. Operation as controlled node.
0xFE - 0xFF	Reserved, switch position not permitted

#### 7.2 POWERLINK V2


Switch position	Description
0x00 Reserved, switch position not permitted.	
0x01 - 0xEF	Node number of the POWERLINK node. Operation as a controlled node (CN).
0xF0	Operation as a managing node (MN).
0xF1 - 0xFF	Reserved, switch position not permitted.

### 7.3 Ethernet mode

In this mode, the interface is operated as an Ethernet interface. The INA2000 node number is set using the B&R Automation Studio software.

### 8 Ethernet interface

For information about wiring X20 modules with an Ethernet interface, see section "Mechanical and electrical configuration - Wiring guidelines for X20 modules with Ethernet cables" of the X20 user's manual.



Interface	Pinout		
	Pin	Ethernet	
	1	RXD	Receive data
	2	RXD\	Receive data\
	3	TXD	Transmit data
	4	Termination	
	5	Termination	
<u> </u>	6	TXD\	Transmit data\
RJ45 shielded	7	Termination	
	8	Termination	

### 9 Firmware

The module comes with preinstalled firmware. The firmware is part of Automation Studio. The module is automatically brought up to this level.

To update the firmware contained in Automation Studio, a hardware upgrade must be performed (see "Project management / Workspace / Upgrades" in Automation Help).